



PART NUMBER STRUCTURE CHART

CATALOG NUMBER	----- SYSTEM NUMBER -----															EXAMPLES
	MANDATORY (9 digits)									OPTIONS (if applicable - 6 digits)						
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
Series				Rating/Sequence				Std. Pack Qty.	Pkg. Type Code		Suffix/Free Form					
2070001	0	2	0	7	0	0	0	1	Z							T1, T2, T3, T4, T5, T6 "P" always follows B" Cust. Specific pack.
23001.5	0	2	3	0	0	1	.	5	D	R	T	1				
313001	0	3	1	3	0	0	1	.	V	B	P					
SLC003	0	S	L	C	0	0	3	.	H	X	R					Indicator fuse
FLNR030	F	L	N	R	0	3	0	.	T							
FLSR100ID	F	L	S	R	1	0	0	.	V	X	I	D				
LLNRK200	L	N	R	K	2	0	0	.	X							Drip-proof seal
JTD.800	0	J	T	D	.	8	0	0	T							
LEB0AA	0	L	E	B	0	0	A	A	X							
571007	0	5	7	1	0	0	0	7	L	X	P					

STANDARD PACK QUANTITIES

X=1	F=200	W=3000
V=5	G=250	Y=4000
T=10	U=500	N=5000
S=20	M=1000	K=10000
L=50	D=1500	J=12000
H=100	P=2000	Z=Misc.
	E=2500	

PACKAGE TYPE CODES

A=Ammo packed
B=Bubble packed
C=Chip packed
R=Reeled
X=Filler

SUFFIX/FREE FORM CODES

Used to add options or descriptions, such as:
ID=Indicating fuse
P=Drip-proof seal
L=RoHS Compliant
P=Lead-Free

TAPED & REELED SUFFIXES

SUFFIX	SPACING	QTY per REEL
MRT1	2.062in (52.4mm)	1000
MRT2	2.50 in (63.5mm)	1000
MRT3	2.874in (73mm)	1000
NRT1	2.062in (52.4mm)	5000
NRT2	2.50 in (63.5mm)	5000
NRT3	2.874in (73mm)	5000