



- This series will be discontinued in 2002, and combine with PS series.

[illegible]

α	(L<20) 1.5
	(L≥20) 2.0

1 2 3 4 5 6 7 8 9 10 11 12

U P R 1 A 3 3 1 M P H []

Case size Code (φD)

Configuration (DH)

Configuration (EH)

Capacitance tolerance (±20%)

Rated Capacitance (330μF)

Rated voltage (10V)

Series name (PH)

Series name (HH)

Type (12.5 ~ 18)

Type (20)

Type (RH)

φD	Code
5	DH
6.3	EH
8 • 10	PH
12.5 ~ 18	HH
20	RH

■ Dimension table in next page.

■ Standard ratings

V(Code) Cap.(μF) Item		6.3(0J)			10(1A)			16(1C)			25(1E)		
Code	Item	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple
4.7	4R7										5×11	5.00	24
10	100							5×11	2.80	35	5×11	2.80	39
22	220	5×11	2.40	34	5×11	2.40	45	5×11	2.40	55	5×11	2.40	60
33	330	5×11	2.30	50	5×11	2.30	60	5×11	2.30	70	5×11	2.20	75
47	470	5×11	2.10	65	5×11	2.10	75	5×11	1.80	85	5×11	1.60	90
100	101	5×11	1.90	100	5×11	1.80	110	6.3×11	0.80	135	6.3×11	0.62	145
220	221	6.3×11	0.67	165	6.3×11	0.58	180	8×11.5	0.36	235	8×11.5	0.35	250
330	331	6.3×11	0.48	200	8×11.5	0.36	255	8×11.5	0.32	285	10×12.5	0.22	355
470	471	8×11.5	0.31	280	8×11.5	0.26	305	10×12.5	0.20	395	10×16	0.16	470
1000	102	10×12.5	0.22	470	10×16	0.14	570	10×20	0.12	700	12.5×20	0.10	855
2200	222	12.5×20	0.096	930	12.5×20	0.090	1010	12.5×25	0.067	1150	16×25	0.053	1230
3300	332	12.5×20	0.090	1100	12.5×25	0.074	1220	16×25	0.052	1350	16×31.5	0.045	1450
4700	472	16×25	0.061	1320	16×25	0.054	1410	16×31.5	0.045	1560	●18×35.5	0.040	1660
6800	682	16×25	0.056	1490	16×31.5	0.046	1610	●18×35.5	0.040	1750	20×40	0.030	2070
10000	103	16×31.5	0.051	1830	●18×35.5	0.038	1980	△18×40	0.035	2170			
15000	153	●18×35.5	0.039	2280	△18×40	0.033	2470						
22000	223	20×40	0.030	2860									

V(Code) Cap.(μF) Item		35(1V)			50(1H)			63(1J)			100(2A)		
Code	Item	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple	Case size	Impedance	Rated ripple
0.47	R47				5×11	47.0	7				5×11	43.0	10
1	010				5×11	22.0	12				5×11	20.0	15
2.2	2R2				5×11	10.0	18				5×11	9.80	22
3.3	3R3				5×11	6.70	25				5×11	6.60	29
4.7	4R7	5×11	5.00	27	5×11	4.70	30	5×11	4.70	34	5×11	4.60	37
10	100	5×11	2.80	44	5×11	2.20	50	5×11	2.10	55	6.3×11	1.80	65
22	220	5×11	2.30	65	5×11	1.90	75	6.3×11	0.98	90	8×11.5	0.68	115
33	330	5×11	1.90	85	6.3×11	0.84	105	6.3×11	0.71	110	10×12.5	0.46	160
47	470	6.3×11	1.00	115	6.3×11	0.80	125	8×11.5	0.65	155	10×16	0.37	210
100	101	8×11.5	0.50	190	8×11.5	0.45	210	10×12.5	0.31	260	12.5×20	0.18	385
220	221	10×12.5	0.24	325	10×16	0.21	400	10×20	0.20	465	16×25	0.10	590
330	331	10×16	0.20	440	10×20	0.19	535	12.5×20	0.12	650	16×25	0.090	720
470	471	10×20	0.12	580	12.5×20	0.10	730	12.5×25	0.081	800	16×31.5	0.076	875
1000	102	12.5×25	0.067	995	16×25	0.053	1110	16×31.5	0.049	1200	△18×40	0.047	1320
2200	222	16×31.5	0.044	1450	●18×35.5	0.037	1530	△18×40	0.032	1840			
3300	332	●18×35.5	0.038	1660	20×40	0.028	1950						
4700	472	△18×40	0.033	2030									

Case size : D × L(mm) MAX. Impedance : (Ω) at 20°C 100kHz Rated ripple : (mA) at 105°C 120Hz

V		160		200		250		315		350		400		450	
Cap.(μF)	Code	2 C		2 D		2 E		2 F		2 V		2 G		2 W	
0.47	R47	6.3×11	12	6.3×11	12	6.3×11	12	8×11.5	11	8×11.5	11				
1	010	6.3×11	17	6.3×11	17	6.3×11	17	8×11.5	16	10×12.5	17	10×12.5	16	10×12.5	18
2.2	2R2	6.3×11	25	6.3×11	25	8×11.5	29	10×12.5	28	10×16	31	10×16	27	10×20	29
3.3	3R3	8×11.5	36	8×11.5	36	10×12.5	42	10×12.5	34	10×16	38	10×20	36	12.5×20	41
4.7	4R7	8×11.5	43	10×12.5	50	10×12.5	50	10×16	45	10×20	49	10×20	43	12.5×20	49
10	100	10×12.5	70	10×16	80	10×20	88	10×20	72	12.5×20	82	12.5×25	72	16×25	75
22	220	10×20	130	10×20	140	12.5×25	155	12.5×25	120	16×25	130	16×25	110	16×31.5	115
33	330	12.5×20	180	12.5×25	190	12.5×25	190	16×25	155	16×31.5	160	16×31.5	140	●18×35.5	145
47	470	12.5×25	220	12.5×25	220	16×25	230	16×35.5	190	●18×35.5	200	●18×35.5	170	20×40	175
100	101	16×25	330	16×31.5	335	●18×35.5	340	△18×40	285	20×40	290				
220	221	●18×35.5	500	△18×40	515	20×40	525							Case size	Rated ripple

Rated Ripple(mA rms) at 105°C 120Hz

Size 20 × 31 is available for capacitors marked. "●"
 Size 20 × 35 is available for capacitors marked. "△"
 In this case, [6] will be put at 12th digit of type numbering system.

■ Frequency coefficient of rated ripple current

V	Cap.(μF)	Frequency	50Hz	120Hz	300Hz	1kHz	10kHz ~
6.3 ~ 100	~ 47		0.75	1.00	1.35	1.57	2.00
	100 ~ 470		0.80	1.00	1.23	1.34	1.50
	1000 ~ 22000		0.85	1.00	1.10	1.13	1.15
160 ~ 450	0.47 ~ 220		0.80	1.00	1.25	1.40	1.60