

NX2016AB

For OA / AV

■ Features

A small surface-mount type crystal unit, especially suited for small-sizing requirements.

- Ultra compact and thin. (2.0 × 1.6 × 0.35 mm typ., Max. H:0.4 mm)
- Highly reliable.
- Ideal for ultra compact TV tuners.
- Lead-free. Meets the requirements for re-flow profiling using lead-free solder.



Pb Free

RoHS Compliant
Directive 2002/95/EC

■ Specifications

Item	Model	NX2016AB
Frequency Range		24 to 80 MHz
Overtone Order		Fundamental
Frequency Tolerance (25 ±3 °C)		±20 × 10 ⁻⁶
Temperature Characteristics (with reference to +25 °C)		±20 × 10 ⁻⁶
Operating Temperature Range		-30 to +75 °C
Storage Temperature Range		-40 to +85 °C
Equivalent Series Resistance		Refer to *1
Drive Level		10 µW (Max. 200 µW)
Load Capacitance		8 pF

The above specifications are standard for this NDK product.

Custom-made specifications such as load capacitance and temperature characteristics are also available.

Please contact NDK sales with your enquiries.


■ How to Specify an Order

When ordering our products, specify them with an "Ordering Code" that consists of the following :

Model name - Frequency (Max : 9 digits) M - Number for specifying an order Example NX2016AB-26.000M-STD-CSZ-2

If you have any queries concerning our standard frequencies and numbers for specifying orders, please contact our sales representatives or visit our homepage (<http://www.ndk.com/>).

■ Dimensions



*1 Equivalent Series Resistance

Frequency Range (MHz)	Equivalent Series Resistance max. [Ω]
24 to 26	80
26 to 40	60
40 to 80	50