

Description

The IS31AP4913 evaluation board is a fully assembled and tested PCB. The IS31AP4913 is a high quality stereo headphone driver with 3D-surround and bass enhancement capability. It also features removal of the output DC-blocking capacitors for a reduction in system component count and end cost. 3D-surround and bass-enhancement are controlled via RC network.

Features

- Supply voltage range from 2.7V to 5.5V
- Low output noise (8 μ V)
- High SNR (102dB)
- -92dB PSRR
- No output DC-blocking capacitors
- Pulse Count Control serial interface
- Available in QFN-20(3mm x 3mm) package

Quick start



Figure 1 Photo of IS31AP4913 Evaluation Board

Recommended Equipment

- 5.0V, 2A power supply
- Audio source (i.e. MP3 player, Notebook PC, etc.)
- Headphone (32 Ω)

Absolute Maximum Ratings

- \leq 5.5V power supply

Caution: Do not exceed the conditions listed above; otherwise, the board risks permanent damage.

Procedure

The evaluation board allows verification of IS31AP4913 device operation.

Caution: Do not turn on the power supply until all connections are completed.

1. Connect headphone (32 Ω) to the connector (headphone input jack).
2. Connect the ground terminal of the power supply to the GND and the positive terminal to the VCC.
3. Alternatively, connect DC power to connector (DC IN).
4. Connect the audio sources to the INR terminal (right channel) and INL terminal (left channel); or connect audio source directly to connector (AUDIO- IN).
5. Turn on the power supply, and pay attention to the supply current. Be cautious: currents above 200mA are large enough to cause board damage.
6. Turn on the audio source.

Ordering Information

| Part No. | Temperature Range | IC Package |
|---------------------|-----------------------------|-------------------|
| IS31AP4913-QFLS2-EB | -40°C to +85°C (Industrial) | QFN-20, Lead-free |

Table 1. Ordering Information

For pricing, delivery, and ordering information, please contact ISSI at analog_mkt@issi.com or (408) 969-6600

Performance Description*

The IS31AP4913 evaluation board has six buttons to switch between the different modes. The operating mode is indicated by an LED illuminated above the appropriate buttons. The (1-4) modes are performed by IS31AP4913.

1. (Default mode) normal: basic operating mode
2. 3D mode: enable 3D enhance function.
3. Bass mode: enable bass enhance function.
4. 3D&Bass: enable 3D and bass enhance function.
5. 2111: use the output DC-blocking capacitors headphone amplifier (HWD2111) drive headphone
6. DIR: use the input audio source direct drive headphone.

**Note: IS31AP4913 headphone driver provides solely audio function capability on the evaluation board.*

Software Support

Please refer to the integrated program.

**Note: Please refer to the datasheet to get more information about IS11AP4913*




Figure 2: IS31AP4913 Application Circuit

Bill of Materials

| No. | Name | Symbol | Description | Manufacturer PN |
|-----|-------------|--------|------------------------------|------------------|
| 1 | USB Control | U1 | Controller | LPC936 |
| 2 | HP Amp | U2 | CSMSC Headphone Driver | CSMSC HWD2111 |
| 3 | LDO | U3 | Low-Drop Out Regulator | EUTECH |
| 4 | HP Driver | U4 | ISSI Stereo Headphone Driver | IS31AP4913-QFLS2 |
| 5 | Relay | S1 | Panasonic | |
| 6 | Resistors | R1~R23 | Refer to Figure 2 | |
| 6 | Capacitors | C1~C23 | Refer to Figure 2 | |

Table 2: Bill of Materials; Refer to Figure 2 for additional information.




Figure 3: Board Component Placement Guide - Top Layer




Figure 4: Board PCB Layout- Top Layer




Figure 5: Board Component Placement Guide -Bottom Layer




Figure 6: Board PCB Layout-Bottom Layer

Copyright © 2011 Integrated Silicon Solution, Inc. All rights reserved. ISSI reserves the right to make changes to this specification and its products at any time without notice. ISSI assumes no liability arising out of the application or use of any information, products or services described herein. Customers are advised to obtain the latest version of this device specification before relying on any published information and before placing orders for products.

Integrated Silicon Solution, Inc. does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless Integrated Silicon Solution, Inc. receives written assurance to its satisfaction, that:

- a.) the risk of injury or damage has been minimized;
- b.) the user assume all such risks; and
- c.) potential liability of Integrated Silicon Solution, Inc is adequately protected under the circumstances.