



SELV IP30 

 (for Blank type only)

 18 (for E type only)

■ Features

- 230VAC only or Full range (up to 295VAC) models available
- Built-in active PFC function
- Constant current design
- Protections:Short circuit
- Cooling by free air convection
- Fully isolated plastic case
- Class II power unit, no FG
- Class 2 power unit(for PLM-25-500/700/1050)
- No load power consumption <0.5W
- High reliability,low cost
- 2 years warranty

■ Applications


- Indoor LED lighting
- LED office lighting
- LED commercial lighting
- LED decorative lighting

■ Description

PLM-25 is a 25W economical AC/DC LED power supply series. Incorporating a built-in active PFC design, PLM-25 provides a high Power Factor value greater than 0.9. In addition, with the low no load power consumption below 0.5W, and the setup time less than 500ms, PLM-25 is complied with the ErP regulation required by European Union for lighting fixtures.

PLM-25 is a class II (without FG pin) power unit housed with the UL 94V-0 rated flame retardant plastic case. The I/O terminals are designed with screw-less clamp style terminal block that greatly simplifies the wiring installation. Two types of models with different input voltage range are offered: PLM-25 series, which operates from 110~295VAC, and PLM-25E series, which operates from 180~295VAC. These two series are both constant current output design, supplying models with the current of 350mA, 500mA, 700mA and 1050mA, respectively.

■ Model Encoding





25W Single Output LED Power Supply


PLM-25 series

SPECIFICATION

MODEL	PLM-25□-350	PLM-25□-500	PLM-25□-700	PLM-25□-1050	
OUTPUT	CONSTANT CURRENT REGION Note.5	42 ~ 72V	30 ~ 50V	21 ~ 36V	
	RATED CURRENT	0.35A	0.5A	0.7A	
	NO LOAD OUTPUT VOLTAGE(max.)	80V	56V	42V	
	RATED POWER	25.2W	25W	25.2W	
	RIPPLE & NOISE (max.) Note.2	Blank type 7.2Vp-p E type 9Vp-p	5.0Vp-p 7.5Vp-p	3.6Vp-p 5.4Vp-p	
	CURRENT ACCURACY Note.3	±5.0%			
	SETUP TIME	Blank type: 500ms / 115VAC, 230VAC at full load; E type: 500ms / 230VAC at full load			
INPUT	VOLTAGE RANGE Note.4	Blank type: 110 ~ 295VAC 156 ~ 417VDC; E type: 180 ~ 295VAC 254 ~ 417VDC			
	FREQUENCY RANGE	47 ~ 63Hz			
	POWER FACTOR	Blank type	PF > 0.97/115VAC, PF > 0.95/230VAC, PF > 0.9/277VAC (at full load) (Please refer to "Power Factor Characteristic" curve)		
		E type	PF > 0.95/230VAC, PF > 0.9/277VAC (at full load) (Please refer to "Power Factor Characteristic" curve)		
	TOTAL HARMONIC DISTORTION	Blank type	THD < 20% when output loading ≥ 60% at 115VAC/230VAC input and output loading ≥ 75% at 277VAC input		
		E type	THD < 20% when output loading ≥ 60% at 230VAC input and output loading ≥ 75% at 277VAC input		
	EFFICIENCY (Typ.)	Blank type	87%	86%	86%
		E type	86%	85%	85%
	AC CURRENT	Blank type: 0.3A/115VAC 0.15A/230VAC 0.12A/277VAC; E type: 0.15A/230VAC 0.12A/277VAC			
	INRUSH CURRENT(Typ.)	COLD START 15A (twidth=50μs measured at 50% Ipeak) at 230VAC			
PROTECTION	MAX. No. of PSUs on 16A CIRCUIT BREAKER	80 units (circuit breaker of type B) / 80 units (circuit breaker of type C) at 230VAC			
	LEAKAGE CURRENT	0.25mA / 240VAC			
ENVIRONMENT	SHORT CIRCUIT	Hiccup mode, recovers automatically after fault condition is removed.			
SAFETY & EMC	WORKING TEMP.	-30 ~ +45°C			
	WORKING HUMIDITY	20 ~ 90% RH non-condensing			
	STORAGE TEMP., HUMIDITY	-40 ~ +80°C, 10 ~ 95% RH			
	TEMP. COEFFICIENT	±0.06%/°C (0 ~ 50°C)			
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes			
OTHERS	SAFETY STANDARDS	UL8750, CSA C22.2 No. 250.13-12 (for Blank type only); ENEC EN61347-1, EN61347-2-13, EN62384, GB19510.14, GB19510.1 (for E type only), IP30 approved			
	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC			
	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms/500VDC / 25°C / 70%RH			
	EMC EMISSION	Compliance to EN55015, GB17743, GB17625.1 (for E type only), EN61000-3-2 Class C (≥ 60% load); EN61000-3-3			
	EMC IMMUNITY	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11; EN61547, light industry level, criteria B (surge 2KV)			
NOTE	MTBF	808.162Khrs min. MIL-HDBK-217F (25°C)			
	DIMENSION	145*38*22mm (L*W*H)			
	PACKING	0.126Kg; 60pcs/8.6 Kg/0.48CUFT			

■ Mechanical Specification

Case No.PLM-25 Unit:mm



 Terminal Pin No. Assignment (TB1) :
 SWITCHLAB MWX201-75002EB(GRAY)

Pin No.	Assignment
1	AC/L
2	AC/N


 Terminal Pin No. Assignment (TB2) :
 SWITCHLAB MWX201-75002B(BLUE)

Pin No.	Assignment
1	+V
2	-V


■ Block Diagram







■ Derating Curve



■ Static Characteristics



■ Power Factor Characteristic
Constant Current Mode

Constant Current Mode

■ EFFICIENCY vs LOAD (500mA Model)

■ AC input voltage drop vs. output current characteristics

AC input drop	10%	8%	5%	3%
Io drop	<16%	<12%	<8%	<7%

NOTE: Output current will return to the rated value within 50ms