

MLH Series

All Metal Pressure Sensors



DESCRIPTION

MLH Series pressure sensors combine Application Specific Integrated Circuit (ASIC) technology with a media isolated, metal diaphragm design. This digitally compensated sensor offers value and performance, making it the ideal pressure sensing solution for demanding applications. Fully temperature compensated, calibrated and amplified, the MLH is available in 50 psi to 8,000 psi pressure ranges.

MLH sensors deliver $\pm 0.25\%$ full scale accuracy Best Fit Straight Line (BFSL) and as low as 2% total error over a temperature range of $-40\text{ }^{\circ}\text{C}$ to $125\text{ }^{\circ}\text{C}$ [$-40\text{ }^{\circ}\text{F}$ to $257\text{ }^{\circ}\text{F}$]. Industry standard connectors and process ports are offered for enhanced reliability and user flexibility.

FEATURES

- All metal wetted parts for use in wide variety of fluid applications
- No internal elastomeric seals mean no o-ring compatibility issues
- Amplified outputs eliminate cost of external amplifiers
- Input reverse voltage and output short circuit protections guard against mis-wiring
- Less than 2 ms response time provides accurate, high speed measurement
- Rated IP65 or better for protection from harsh environments

The MLH has seven standard output options:

- A. 0.5 Vdc to 4.5 Vdc ratiometric output from 5 Vdc excitation
- B. 4 mA to 20 mA current from 9.5 Vdc to 30 Vdc excitation
- C. 1.0 Vdc to 6.0 Vdc regulated output from 8 Vdc to 30 Vdc excitation
- D. 0.25 Vdc to 10.25 Vdc regulated output from 14 Vdc to 30 Vdc excitation
- E. 0.5 Vdc to 4.5 Vdc regulated output from 7 Vdc to 30 Vdc excitation
- F. 0 mV to 50 mV from 5 Vdc excitation
- G. 1 Vdc to 5 Vdc output from 8 Vdc to 30 Vdc excitation

POTENTIAL APPLICATIONS

- Compressors
- Refrigeration and HVAC/R
- General industrial
- General hydraulics
- Multiple transportation applications including braking and alternate fuels
- Medical

MLH Series

Table 1. Pressure Range Specifications¹ (At 25 °C [77 °F] and at rated excitation unless otherwise specified.)

psi												
Pressure	50	100	150	200	250	300	500	1000	2000	3000	5000	8000
Proof pressure	150	300	450	600	750	900	1500	2000	4000	6000	7500	12000
Burst pressure	500	1000	1500	2000	2500	3000	5000	10000	20000	30000	30000	30000
bar												
Pressure	6	10	16	25	40	60	100	160	250	350	500	550
Proof pressure	18	30	48	75	80	120	200	320	500	700	750	825
Burst pressure	60	100	160	250	400	600	1000	1600	2068	2068	2068	2068

Note:

1. Comparable metric units follow same proof and burst specifications.

Table 2. Physical and Environmental Specifications

Parameter	Characteristic
Material in contact with media	stainless steel 300 series and Haynes 214 alloy, Hastelloy C22 sensor available (contact factory)
Housing material	black plastic – Amodel AS-4133 HS – PPA
Weight	57.0 g [2.0 oz] (typical for Packard MetriPak and 1/8 NPT port)
Shock	100 g peak [11 ms]
Vibration	MIL-STD-810C, Figure 514.2-5, Curve AK, Table 514.2-V, Random Vibration Test [overall g rms = 20.7 min.]
Compensated, operating and storage temperature range	-40 °C to 125 °C [-40 °F to 257 °F]

Table 3. Electrical Specifications (At 25 °C [77 °F] and at rated excitation unless otherwise specified.)

Parameter	Ratiometric (A) ¹	Current (B)	Regulated (C)	Regulated (D)	Regulated (E)	mV (F)	Regulated (G)
Zero output	0.5 Vdc	4.0 mA	1.0 Vdc	0.25 Vdc	0.5 Vdc	0 ±2.5 mV	1.0 Vdc
Full scale span (FSS)	4.0 Vdc (0.5 to 4.5 Vdc)	16 mA (4 to 20 mA)	5.0 Vdc (1.0 to 6.0 Vdc)	10.0 Vdc (0.25 to 10.25 Vdc)	4.0 Vdc (0.5 to 4.5 Vdc)	50 mV (0 to 50 mV)	4.0 Vdc (1.0 to 5.0 Vdc)
Excitation	5 Vdc (6.0 Vdc max.)	9.5 Vdc to 30.0 Vdc	8.0 Vdc to 30.0 Vdc	14.0 Vdc to 30.0 Vdc	7.0 Vdc to 30.0 Vdc	5.0 Vdc (6.0 Vdc max.)	8.0 Vdc to 30.0 Vdc
Supply current	4.0 mA typical (8 mA max.)	N/A	5.0 mA typical (17 mA max.)	5.0 mA typical (17 mA max.)	5.0 mA typical (17 mA max.)	8.0 mA typical (17 mA max.)	5.0 mA typical (17 mA max.)
Source (nominal)	1.0 mA	N/A	1.0 mA	1.0 mA	1.0 mA	N/A	1.0 mA
Sink (nominal)	1.0 mA at zero output	N/A	1.0 mA at zero output	1.0 mA at zero output	1.0 mA at zero output	N/A	1.0 mA at zero output
Supply rejection ratio	90 db	90 db	90 db	90 db	90 db	N/A	90 db
Output impedance	25 Ω max.	N/A	25 Ω max.	25 Ω max.	25 Ω max.	2000 Ω	25 Ω max.

Note:

1. Maintains ratiometricity at 5 ±0.25 Vdc excitation. Product can tolerate 6 Vdc excitation without damage.

All Metal Pressure Sensors

Table 4. Performance Specifications (At 25 °C [77 °F] and at rated excitation unless otherwise specified.)

Parameter	Characteristic
Response time	<2 ms
Accuracy ¹ :	
≥100 psi	±0.25% FSS
<100 psi	±0.50% FSS
Total error band ² :	
Gage:	
<300 psig	±3% FSS
≥300 psig	±2% FSS
Seal gage:	
≥300 psis	±2% FSS
Seal gage <u>without</u> L, M, P termination:	
100 psis to 299 psis (-40 °C to 85 °C [-40 °F to 185 °F])	±3% FSS
100 psis to 299 psis (>85 °C to 125 °C [>185 °F to 257 °F])	±10% FSS
≥300 psis (-40 °C to 125 °C [-40 °F to 257 °F])	±2% FSS
Seal gage <u>with</u> L, M, P termination:	
100 psis to 299 psis (-40 °C to 65 °C [-40 °F to 149 °F])	±10% FSS
100 psis to 299 psis (>65 °C to 125 °C [>149 °F to 257 °F])	±15% FSS
≥300 psis (-40 °C to 65 °C [-40 °F to 149 °F])	±5% FSS
≥300 psis (>65 °C to 125 °C [>149 °F to 257 °F])	±15% FSS


Notes:

- Includes pressure non-linearity (BFSL), pressure hysteresis and non-repeatability. Thermal errors are not included.
- Includes zero error, span error, thermal effect on zero, thermal effect on span, thermal hysteresis, pressure-non-linearity, pressure hysteresis and non-repeatability.

Figure 1. Nomenclature and Order Guide¹

Series ——— MLH 500 P S B 06 B ——— Output Pressure Range <table border="1"> <thead> <tr> <th>PSI</th> <th>BAR</th> </tr> </thead> <tbody> <tr><td>050</td><td>006</td></tr> <tr><td>100</td><td>010</td></tr> <tr><td>150</td><td>016</td></tr> <tr><td>200</td><td>025</td></tr> <tr><td>250</td><td>040</td></tr> <tr><td>300</td><td>050</td></tr> <tr><td>006</td><td>100</td></tr> <tr><td>010</td><td>160</td></tr> <tr><td>016</td><td>250</td></tr> <tr><td>025</td><td>350</td></tr> <tr><td>040</td><td>500</td></tr> <tr><td>050</td><td>550</td></tr> </tbody> </table> Unit P = psi B = bar Reference G = Gage (psi) S = Sealed Gage (psi)⁵ Electrical Termination B = Packard MetriPak 150 C = Hirschman (mates with G4W1F) D = M12 x 1 (Brad Harrison micro) G = DIN 43650-C, 8 mm-male H = Amp Superseal 1.5² L = Cable (1 meter) M = Cable (3 meter) P = Flying Leads (20 AWG – 6 in) T = Deutsch DTM04-3P (integral) (Mating connectors are not supplied.) Pressure Connection 01 = 1/4-18 NPT 02 = M12 x 1.5 (ISO 6149)⁴ 03 = M14 x 1.5 (ISO 6149)⁴ 04 = 3/8-24 UNF (SAE-3 O-Ring Boss)⁴ 05 = M18 x 1.5 (ISO 6149)⁴ 06 = 1/8 in-27 NPT 07 = 1/2 in-20 UNF (SAE-5 O-Ring Boss)⁴ 08 = M10 x 1 (ISO 6149)⁴ 09 = 1/4 in SAE Female Schrader (7/16-20 UNF-2B Internal Thread) 10 = 7/16-20 UNF (SAE-4 O-Ring Boss)⁴ 11 = 1/2 in NPT 12 = 9/16-18 UNF (SAE-6 O-Ring Boss)⁴ 13 = PT 1/4-19 BSP Tapered Thread 14 = G 1/4-19 (DIN 3852-2)⁴ 15 = G 1/8 with O Ring Groove⁴ 16 = M16 x 1.5 (ISO 6149)⁴ 17 = G 1/4 with O-Ring Groove⁴ 18 = G 1/8 (DIN 3852-2)⁴ 19 = PT 1/8-28 BSP Tapered Thread 20 = M20 x 1.5 (ISO 6149)⁴ 21 = 1/2-20 (SAE J514)⁴	PSI	BAR	050	006	100	010	150	016	200	025	250	040	300	050	006	100	010	160	016	250	025	350	040	500	050	550	Notes: - Not all combinations are available. Minimum quantity orders apply. Additional pressure ranges, port styles and special calibration versions are available. Contact your local sales representative for assistance. - Available with "A" output only. - Available with "L," "M" or "P" electrical terminations only. - Supplied with O-ring. - Sealed gage devices are not available for ranges below 100 psi.
PSI	BAR																										
050	006																										
100	010																										
150	016																										
200	025																										
250	040																										
300	050																										
006	100																										
010	160																										
016	250																										
025	350																										
040	500																										
050	550																										

Figure 2. Mounting Dimensions (For reference only. mm/(in).)



⚠ WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

⚠ WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

SALES AND SERVICE

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office or:

E-mail: info.sc@honeywell.com

Internet: www.honeywell.com/sensing

Phone and Fax:

Asia Pacific	+65 6355-2828
	+65 6445-3033 Fax
Europe	+44 (0) 1698 481481
	+44 (0) 1698 481676 Fax
Latin America	+1-305-805-8188
	+1-305-883-8257 Fax
USA/Canada	+1-800-537-6945
	+1-815-235-6847
	+1-815-235-6545 Fax

Sensing and Control

Honeywell

1985 Douglas Drive North

Golden Valley, MN 55422

www.honeywell.com/sensing

008118-5-EN IL50 GLO Printed in USA

January 2009

Copyright © 2009. Honeywell International Inc. All rights reserved.

Honeywell