

# General Specifications

## Electrical Capacity (Resistive Load)

Power Level (silver): 0.1A maximum @ 30V AC/DC

## Other Ratings

Contact Resistance:	50 milliohms maximum
Insulation Resistance:	100 megohms minimum @ 500V DC
Dielectric Strength:	500V AC minimum for 1 minute minimum
Mechanical Life:	100,000 operations minimum
Electrical Life:	50,000 operations minimum
Nominal Operating Force:	3.43N
Contact Timing:	Nonshorting (break before make)
Travel:	Pretravel .087" (2.2mm); Overtravel .031" (0.8mm); Total Travel .118" (3.0mm)

## Materials & Finishes

Housing:	Glass fiber reinforced polyamide
Base:	Glass fiber reinforced polyamide
Movable Contact:	Phosphor bronze with silver plating
Stationary Contacts:	Phosphor bronze with silver plating
Common Terminal:	Phosphor bronze with silver plating
End Terminals:	Phosphor bronze with silver plating
Lamp Terminals:	Phosphor bronze with silver plating

## Environmental Data

Operating Temperature Range:	-25°C through +50°C (-13°F through +122°F) for Illuminated -25°C through +70°C (-13°F through +158°F) for Nonilluminated
Humidity:	90 ~ 95% humidity for 96 hours @ 40°C (104°F)
Vibration:	10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock:	50G (490m/s <sup>2</sup> ) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

## Installation

Mounting Torque:	0.49Nm (4.34 lb•in) maximum for round mounting nut
Cap Installation Force:	9.8N (2.2 lbf) maximum downward force on cap
Soldering Time & Temperature:	Manual Soldering: See Profile A in Supplement section.

## Standards & Certifications

UL:	<b>File No. E44145 - Recognized only when ordered with marking on switch.</b> Add "/U" or "/CUL" before first dash in part number to order UL recognized switch. All models recognized at 0.1A @ 30V AC/DC.
-----	---

# Distinctive Characteristics

Full face and spot illumination available. Front panel relamping.

Choice of super bright LEDs in white, green, and blue in addition to bright red, amber, and green LEDs.

Compact front panel design with 9mm square or round bezel options.

Rear panel threaded mounting. Behind panel depth of less than one inch. 8mm body diameter fits common size panel cutout.

Latchdown feature gives indication of circuit status. Audible and tactile feedback with smooth and responsive operation.

Dual, sliding contacts with self-cleaning action provide contact stability, high reliability, and increased operating life.

Solder lug terminals have spacing of .100" (2.54mm) for choice of mounting.


Longer normally closed terminal facilitates wiring and soldering.

Molded-in terminals lock out flux, dust, and other contaminants.


Matching indicators available.



Actual Size



### TYPICAL SWITCH ORDERING EXAMPLE



#### IMPORTANT:

Switches are supplied without UL & cULus marking unless specified. **UL & cULus recognized only when ordered with marking on the switch.** Specific models, ratings, & ordering instructions are noted on the General Specifications page.



#### DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

**HB15SKW01-6G-JB**




POLES & CIRCUITS							
		Plunger Position ( ) = Momentary		Connected Terminals		Throw & Switch/Lamp Schematics	
Pole	Model	Normal	Down	Normal	Down	Notes: Switch is marked with NO, NC, C, L. LED circuit is isolated and requires external power source.	
SP	HB15 *HB16	ON ON	(ON) ON	1-3	1-2	SPDT	

\* When in latchdown position for the alternate circuit, cap position is .051" (1.3mm) above the built-in bezel.

- Toggle
- Rockers
- Pushbuttons
- Pushbutton
- Programmable
- Keylocks
- Rotaries
- Slides
- Tactiles
- Tilt
- Touch
- Indicators
- Accessories
- Supplement

## SHAPES & PANEL CUTOUT

**S** .354" (9.0mm) Square



The bezel is an integral part of the switch body.


**C** .354" (9.0mm) Round



The bezel is an integral part of the switch body.

## Panel Cutout & Mounting

Recommended Panel Thickness:  
.020 ~ .197" (0.5 ~ 5.0mm)



Overtightening the mounting nut AT073 may damage the switch housing.

## HOUSING

**K** Housing available in black only.

## CONTACT MATERIALS, RATINGS, & TERMINALS


**W01**

Silver Contacts

Power Level

0.1A maximum @ 30V AC/DC

### Solder Lug



### PCB Mounting

Solder lug terminals are spaced .100" x .200" (2.54mm x 5.08mm). This enables PCB mounting which can be accomplished by elongating PC board holes to .080" (2.03mm).

### LED COLORS & SPECIFICATIONS

The electrical specifications shown are determined at a basic temperature of 25°C. LED circuit is isolated and requires external power source. Single element LED is colored in OFF state. If the source voltage exceeds the rated voltage, a ballast resistor is required. The resistor value can be calculated by using the formula in the Supplement section.

Bright AT633	 Note for Super Bright: 	Bright			Super Bright			Unit
		5C	5D	5F	6B	6F	6G	
Super Bright	(+)-O-  O(-)	Color	Red	Amber	Green	White	Green	Blue
AT624G Blue	Maximum Forward Current	$I_{FM}$	30	30	30	30	30	30
AT629B White	Typical Forward Current	$I_F$	20	20	20	20	20	20
AT630F Green	Forward Voltage	$V_F$	1.95	2.0	2.1	3.6	3.3	3.3
T-1 Bi-pin	Maximum Reverse Voltage	$V_{RM}$	5	5	5	5	7	7
	Current Reduction Rate Above 25°C	$\Delta I_F$	0.42	0.42	0.42	0.50	0.40	0.40
	Ambient Temperature Range		-25° ~ +50°C			-25° ~ +50°C		

**No Code**

No Lamp


### CAP TYPES & COLORS


Color Codes:	A Black	B White	C Red	D Amber	E Yellow	F Green	G Blue	J Clear
--------------	---------	---------	-------	---------	----------	---------	--------	---------

**Cap Colors Available:**
**AB** Black Cap with Translucent White Window for LED Display

**Colored Cap for Bright LEDs**

 Square only  
 Material: Polycarbonate  
 Finish: Matte

**AT4052**  
 Spot Illuminated

**Lens/Diffuser Colors Available:**
**CB** Red/White

**AT4166**  
 Square

**DB** Amber/White

**AT4167**  
 Round

**FB** Green/White

Material: Polycarbonate

Finish: Glossy



Transparent Colored Lens




Translucent White Diffuser



Colored LED AT633

**JB** Clear Lens/White Diffuser

 Material: Polycarbonate  
 Finish: Glossy

**White Cap for Bright & Super Bright LEDs**
**AT4031**  
 Square

**AT4032**  
 Round


Transparent Clear Lens



Translucent White Diffuser



Colored LEDs AT624, AT629, AT630, or AT633

**Cap Colors Available:**
**A** Black (Square Only)

**C**

Red

**F**

Green

**B** White

**E**



Yellow

**G**

Blue



Material: Polycarbonate

Finish: Glossy

**Nonilluminated Caps**
**AT4035**  
 Square

**AT4036**  
 Round


## TYPICAL SWITCH DIMENSIONS

## Single Pole





## Square



HB15SKW01-5C-CB

## Single Pole



## Round




HB16CKW01-5C-CB

## ASSEMBLY INSTRUCTIONS


## Cap Removal

1. Have cap in extended position (not latchdown) for alternate action models.
2. Use the grip slots on the sides of the cap and pull it out of the switch.



## LED Polarity &amp; Orientation in Lamp Socket


For AT624, AT629, AT630: Insert the LED with the D flat opposite the black dot molded inside the switch lamp socket. For AT633: Insert the LED with the Black Dot on the terminal to the right.



Super Bright LEDs AT624, AT629, & AT630 are electrostatic sensitive.

## Cap Replacement

1. Match the prongs on the cap base with the projections in the switch, at the same time aligning the spring clips on the cap with the indentations in the switch.
2. Press firmly in place.



## AT111 Lamping Tool

Lamping Tool AT111 may be used to remove and replace LED.



## AT110 Socket Wrench

Socket Wrench AT110 may be used to tighten the mounting nut.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## NKK Switches:

[HB15CKW01](#) [HB16CKW01](#) [HB16SKW01-B](#) [HB15SKW01-C](#) [HB15CKW01-G](#) [HB15SKW01-A](#) [HB16SKW01-A](#)  
[HB15SKW01-B](#) [HB15CKW01-B](#) [HB16SKW01-C](#) [HB15CKW01-C](#) [HB16CKW01-C](#) [HB15SKW01-E](#) [HB16SKW01-E](#)  
[HB15CKW01-E](#) [HB15CKW01-F](#) [HB16CKW01-F](#) [HB15SKW01-G](#) [HB16CKW01-G](#) [HB15CKW01-A/1](#) [HB15SKW01-F](#)  
[HB16CKW01-E](#)