

Diode Plug



Dimensions

Terminal width (+ assembly tolerance 0.2)	mm (in.)
Insulation stripping length	mm (in.)

Connection data

Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	

VDE rated data

Diode current	
Diode reverse voltage	
Cross-section	

Ordering data

DLS 2 = Diode plug
for lateral disconnection
DQS 2 = Diode plug
for cross-connection

DLS 2
for SAKR-D




SAKR-D



DLS 2
for SAKR-D




SAKR-D




WSD 2.5



WTR 2.5 D
with diode plug
with test sockets



WTR 2.5 D



Type	Part No.
DLS 2	0321060000
without components	
DLS 2	0547660000
with wire link	
DLS 2	0630160000
with diode	
1 N 4007	
DLS 2	0547760000
with diode	
1 N 4007	
SAKR-D, TS 32	0263660000
with DLS 2	
054776	
SAKR-D, TS 32	0413060000
with DLS 2	
without components	
SAKR-D, TS 32	0413160000
with test sockets	
and DLS 2 without components	
Special design	
SAKR-D, TS 32	0606560000
with test socket	
and 2 antiparallel diodes	
1 N 4007, without DLS 2	
SAKR-D, TS 32	0412960000
SAKR-D, TS 32	0546460000
with test sockets	

Type	Part No.
DLS 2	0321060000
without components	
DLS 2	0547660000
with wire link	
DLS 2	0630160000
with diode	
1 N 4007	
DLS 2	0547760000
with diode	
1 N 4007	
SAKR-D, TS 35	0299560000
with DLS 2	
054776	
SAKR-D, TS 35	0185760000
with DLS 2	
without components	
SAKR-D, TS 35	1175360000
with test sockets	
and DLS 2 without components	
Special design	
SAKR-D, TS 35	1175460000
with test socket	
and 2 antiparallel diodes	
1 N 4007, without DLS 2	
SAKR-D, TS 35	0299960000

Type	Part No.
WSD 2.5	1058760000
without components	
WSD 2.5	1058660000
with wire link	
WSD 2.5	1058560000
with diode	
1 N 4007	
WSD 2.5	1058460000
with diode	
1 N 4007	
WTR 2.5 D	1013500000
with WSD 2.5	
105856	
WTR 2.5 D	1013600000
with WSD 2.5	
105846	
WTR 2.5 D	1013700000
with WSD 2.5	
105866	
WTR 2.5 D	1013200000
with test sockets	
and WSD 2.5	
105856	
WTR 2.5 D	1013300000
with test sockets	
and WSD 2.5	
105846	
WTR 2.5 D	1013400000
with test sockets	
and WSD 2.5	
105866	

Type	Part No.
WTR 2.5 D	8017050000
with diode 1 N 4007	
WTR 2.5 D	8016820000
with diode 1 N 4007	
WTR 2.5 D	on request
with 2 antiparallel diodes 1 N 4007	
WTR 2.5 D	1014600000
with test sockets and Diode 1 N 4007	
WTR 2.5 D	1014700000
with test sockets and Diode 1 N 4007	
WTR 2.5 D	1014800000
with test sockets and 2 antiparallel diodes 1 N 4007	

Maximum values for built-in components: Length 23 mm (.91 in.), diameter 3.5 mm (.18 in.), output 0.5 Watt, limit temperature 100°C