


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION, 19
© COPYRIGHT 19 BY AMP INCORPORATED, HARRISBURG, PA. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENTS AND/OR PATENTS PENDING.

REVISIONS					
P	F	ZONE	LTR	DESCRIPTION	DATE
✓	✓		V	REDRAWN & REVISED PER ECN R-1451	9-30-85
✓	✓		W	OBSOLETE -3 PER R-2760	3-4-87
✓	✓		Y	REV PER ECN DF-5920	11-25-92
			Z	REV PER 0630-269-03	5-03



- 1. REELED FOR USE WITH STANDARD APPLICATORS.
- 2. REELED FOR USE WITH HEAVY DUTY MINI-APPLICATORS.
- 3. PLATED WITH .000100 MIN SILVER PER QQ-S-365.
- 4. PLATED WITH .000015 MIN GOLD PER MIL-G-45204 IN THE LOCALIZED GOLD PLATE AREA, GOLD FLASH ON THE REMAINDER, OVER .000030 MIN NICKEL PER QQ-N-290.
- 5. PLATED WITH .000030 MIN GOLD PER MIL-G-45204 IN THE LOCALIZED GOLD PLATE AREA, GOLD FLASH ON THE REMAINDER, OVER .000030 MIN NICKEL PER QQ-N-290.
- 6. PLATED WITH .000050 MIN 93-7% TIN-LEAD ALLOY OVER .000030 MIN NICKEL PER QQ-N-290.
- 7. WIRE RANGE = 10 AWG.
- 8. INSULATION RANGE = .190-.220 DIA.
- 9. PLATED TIN (NO LEAD), .000050 MIN THK PER ASTM-B-545 OVER NICKEL .000030 MIN THK PER QQ-N-290.

BLACK	NATURAL	BLACK	BLACK	BLACK
1-66253-0	66253-8	66253-7	66253-6	66253-5
66253-9	66253-4	66253-2	66253-1	66253-1
66259-5	66259-4	66259-3	66259-2	66259-1
66259-5	66259-4	66259-3	66259-2	66259-1

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ON: DECIMALS ± .010 ANGLES ± .010	CONTRACT NO DR <i>Rick Rolabaugh</i> 9-27-85 CHK <i>Larry G. Lawner</i> 10-1-85 APPD <i>B. L. Bolash</i> 10-1-85 APPD <i>Kevin E. Smith</i> 10-3-85	AMP INCORPORATED Harrisburg, Pa. 17105			
MATERIAL SEE CALLOUT	FINISH SEE DASH NO	NAME MALE TYPE XII CONTACT LOOSE PIECE ASS'Y			
DSGN APPD		SIZE C	FSCM NO 00779	DRAWING NO 66259	
OTHER APPD		SCALE NTS		SHEET	