

SN54AS866, SN74AS866A 8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

- Package Options Include Plastic Small Outline Packages, Both Plastic and Ceramic Chip Carriers, and Standard Plastic and Ceramic DIPs
- Input and Output Latches with Active-High Enables
- Fast Compare to Zero
- Arithmetic and Logical Comparison
- Open-Collector P = Q Output

description

These Advanced Schottky devices are capable of performing high-speed arithmetic or logical comparisons on two 8-bit binary or two's complement words. Three fully decoded decisions about words P and Q are externally available at the outputs. These devices are fully expandable to any word length by connecting the totem pole P>Q and P<Q outputs of each stage to the P>Q and P<Q inputs of the next higher-order stage. The cascading paths are implemented with only a two-gate-level delay to reduce overall comparison times for long words. The open-collector P=Q output may be wire-ANDed together.


Both input words P and Q plus all three outputs (P>Q, P<Q, and P = Q) are equipped with latches to provide the designer with temporary data storage for avoiding race conditions. The enable circuitry is implemented with minimal delay times to enhance performance when the devices are cascaded for longer word lengths. Each latch is transparent when the appropriate latch enable, PLE, QLE, or OLE is high.

The enable inputs PLE and QLE and data inputs P and Q utilize pnp input transistors to reduce the low-level input current requirement to typically -0.25 mA, which minimizes loading effects.


The Q register may be cleared to zero for a fast comparison of the P word to zero.

The SN54AS866 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74AS866A is characterized for operation from 0°C to 70°C .

SN54AS866 . . . JD PACKAGE
SN74AS866A . . . N PACKAGE
(TOP VIEW)



SN54AS866 . . . FK PACKAGE
SN74AS866A . . . FN PACKAGE
(TOP VIEW)




SN54AS866, SN74AS866A

8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

logic symbol†




† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

SN54AS866, SN74AS866A 8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

logic diagram (positive logic)



SN54AS866, SN74AS866A

8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

FUNCTION TABLE

COMPARISON	L/\bar{A}	DATA INPUTS P0–P7, Q0–Q7	INPUTS		OUTPUTS		
			P>Q	P<Q	P>Q	P<Q	P=Q
Logical	H	P>Q	X	X	H	L	L
Logical	H	P<Q	X	X	L	H	L
Logical	H	P=Q	L	L	L	L	H
Logical	H	P=Q	L	H	L	H	L
Logical	H	P=Q	H	L	H	L	L
Logical	H	P=Q	H	H	H	H	L
Arithmetic	L	P AG Q	X	X	H	L	L
Arithmetic	L	Q AG P	X	X	L	H	L
Arithmetic	L	P=Q	L	L	L	L	H
Arithmetic	L	P=Q	L	H	L	H	L
Arithmetic	L	P=Q	H	L	H	L	L
Arithmetic	L	P=Q	H	H	H	H	L

AG = arithmetically greater than

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage	7 V
Off-state output voltage, P = Q output	7 V
Operating free-air temperature range: SN54AS866	–55°C to 125°C
SN74AS866A	0°C to 70°C
Storage temperature range	–65°C to 150°C

recommended operating conditions

	SN54AS866			SN74AS866A			UNIT
	MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC} Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH} High-level input voltage	2			2			V
V_{IL} Low-level input voltage			0.8			0.8	V
I_{OH} High-level output current, all outputs except P=Q			–2			–2	mA
V_{OH} High-level output voltage, P=Q output			5.5			5.5	V
I_{OL} Low-level output current			20			20	mA
t_{su} Setup time to PLE, OLE, OLE↓	2			2			ns
t_h Hold time after PLE, QLE, OLE↓	4			4			
t_A Operating free-air temperature	–55		125	0	70		°C

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54AS866, SN74AS866A

8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54AS866			SN74AS866A			UNIT
				MIN	TYP†	MAX	MIN	TYP†	MAX	
V _{IK}		V _{CC} = 4.5 V, I _I = −18 mA		−1.2			−1.2			V
V _{OH}	P>Q, P<Q	V _{CC} = 4.5 V to 5.5 V, I _{OH} = −2 mA		V _{CC} −2			V _{CC} −2			
I _{OH}	P=Q only	V _{CC} = 4.5 V, V _{OH} = 5.5 V		0.25			0.25			mA
V _{OL}		V _{CC} = 4.5 V, I _{OL} = 20 mA		0.35 0.5			0.35 0.5			V
I _I		V _{CC} = 5.5 V, V _I = 7 V		0.1			0.1			mA
I _{IH}	L/A, OLE	V _{CC} = 5.5 V, V _I = 2.7 V		40			40			μA
	20			20						
I _{IL}	L/A, OLE, P>Q _{in} , P<Q _{in}	V _{CC} = 5.5 V, V _I = 0.4 V		−4			−4			mA
	−2			−2						
	−0.25 −1			−0.25						
I _O ‡		V _{CC} = 5.5 V, V _O = 2.25 V		−20 −112			−20 −112			mA
I _{CC}		V _{CC} = 5.5 V, See Note 1		160 240			160 240			mA

NOTE 1: I_{CC} is measured with all inputs high except L/A, which is low.

switching characteristics (see Note 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 500 Ω, T _A = MIN to MAX§						UNIT
			SN54AS866			SN74AS866A			
			MIN	TYP†	MAX	MIN	TYP†	MAX	
t _{PLH}	L/ \bar{A}	P<Q, P>Q	1	8.5	14	1	8.5	19	ns
t _{PHL}			1	7.5	14	1	7	13	
t _{PLH}	P<Q, P>Q		1	5	10	1	5	8	ns
t _{PHL}			1	5.5	10	1	5.5	8	
t _{PLH}	Any P or Q Data Input		1	13.5	21	1	13.5	17.5	ns
t _{PHL}			1	10	17	1	10	15	
t _{PLH}	CLRQ		1	16	21	1	16	20	ns
t _{PHL}			1	12	17	1	12	16	

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 280 Ω, T _A = MIN to MAX§						UNIT
			SN54AS866			SN74AS866A			
			MIN	TYP†	MAX	MIN	TYP†	MAX	
t _{PLH}	P<Q,	P=Q	1	6.5	12	1	6.5	16	ns
t _{PHL}	P>Q		1	8	14	1	8	14	
t _{PLH}	Any P or Q Data Input	P=Q	1	10	15	1	10	17	ns
t _{PHL}			1	9	14	1	9	14	
t _{PLH}	CLRQ	P=Q	1	12	17	1	12	24	ns
t _{PHL}			1	13	18	1	13	21	

† All typical values are at $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$.

‡ The output conditions have been chosen to produce a current that closely approximates one-half of the true short-circuit, I_{OS} .

§ For conditions shown MIN or MAX, use the appropriate value specified under recommended operating conditions.

NOTE 2: Load circuit and voltage waveforms are shown in Section 1 of the *ALS/AS Logic Data Book*, 1986.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

SN54AS866, SN74AS866A

8-BIT MAGNITUDE COMPARATORS

SDAS183A – DECEMBER 1982 – REVISED JUNE 1990

TYPICAL APPLICATION DATA

This sequence of comparisons illustrates how the $\overline{\text{CLRQ}}$ function can be used to perform dual comparisons of the varying P terms (P0, P1, etc.). When $\overline{\text{CLRQ}}$ is high, the P term is compared to the Q term. When $\overline{\text{CLRQ}}$ is taken low, the P term is compared to zero. This or similar sequences can enhance performance and reduce package count to perform value range checks.




Figure 1. Magnitude Comparisons Combined With Quick Comparisons to Zero (Range Verifications)

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.