






10 9 8 7 6 5 4 3 2 1



注記:
NOTES:
△ 3極 ~ 12極 : $\varnothing 0.8^{+0.05}$
3CKTS ~ 12CKTS : $\varnothing 0.8^{+0.05}$
13極 ~ 20極 : $\varnothing 0.85^{+0.05}$
13CKTS ~ 20CKTS : $\varnothing 0.85^{+0.05}$
△ キンクは 全ピン交互に設ける。
SET KINK ALTERNATELY TO ALL CIRCUITS.

35.9	32	39-27-0174	5550-17A	17
29.9	26	39-27-0144	5550-14A	14
19.9	10	39-27-0064	5550-06A	6
7.9	4	39-27-0034	5550-03A	3
(B)	A	EDP NO.	ENG.NO.	極数 CKT.

REVISED EC NO: J2008-3104 DRAWN: NAKAMURA CHKD: HARUYAMA APPR: NUKITA B	DESCRIPTION REV	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		10 UNDER	± 0.2	DRAWN BY S. MATSUZAKI	DATE '95/9/6	TITLE 2.0 B/B DIP				
		10 OVER 30 UNDER	± 0.25	CHECKED BY Y. M	DATE '95/9/6					
		30 OVER	± 0.3	APPROVED BY M. FUKUSHIMA	DATE '95/9/6	MOLEX INCORPORATED				
		ANGULAR ± 3 °		MATERIAL NO.						
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-5550-001			1 OF 1	
				SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					