



Features

- Carbon element
- Plain or knurled shaft option
- Metal bushing
- Metal shaft
- Rear solder lugs
- Audio or linear taper options
- Variety of resistance values



- Detent at "no-load" position
- RoHS compliant*

PDB241-GNL Series - "No-Load" Guitar Potentiometer

Electrical Characteristics

Taper.....Audio, linear
Standard Resistance..... 10K to 1M ohms
Standard Resistance Tolerance..... $\pm 20\%$


Environmental Characteristics

Operating Temperature
.....-10 °C to +70 °C
Power Rating.....0.25 watt
Maximum Operating Voltage.....250 V
Rotational Noise.....150 mV max.

Mechanical Characteristics

Mechanical Angle.....300 ° $\pm 5^\circ$
Rotational Torque.....50 to 150 gf-cm
Stop Strength.....8 kg-cm min.
Rotational Life.....15,000 cycles min.
Detent Position.....300 °
Detent Torque.....100-300 gf-cm
Soldering Condition
Manual Soldering
.....300 °C within 3 seconds
Wave Soldering
.....260 °C within 3 seconds
Hardware.....Two flat washers
and two mounting nuts supplied
per potentiometer


Derating Curve




Standard Resistance Table

Resistance (Ohms)	Resistance Code
10,000	103
25,000	253
50,000	503
100,000	104
250,000	254
300,000	304
500,000	504
1,000,000	105

Product Dimensions



Circuit



How To Order

PDB24 1 - GNL 01 - 504 A2

Model _____
Number of Units _____
1 = Single
Guitar Pot Designator _____
Configuration _____
01 = Knurled Shaft (18-Tooth) / Solder Lugs
02 = Plain Shaft / Solder Lugs
03 = Knurled Shaft (18-Tooth, Long) / Solder Lugs
04 = Plain Shaft (Long) / Solder Lugs
11 = Knurled Shaft (24-Tooth) / Solder Lugs
13 = Knurled Shaft (24-Tooth, Long) / Solder Lugs
Resistance Code (See Table) _____
Resistance Taper (See Taper Charts) _____

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.



The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.

PDB241-GNL Series - “No-Load” Guitar Potentiometer

BOURNS®

Taper Chart



Inquire for availability of other tapers.