



- | | | | | | | |
|------------------|---|--|--|--|--|---------|
| | KNOCKOUT | 0.86-1.04 [.034-.041] | TIN  | TIN  | 6-50865-7 | |
| | OPEN | | GOLD  | GOLD  | 6-50865-6 | |
| | | | GOLD  | GOLD  | 1-50865-2 | |
| | | | | | 1-50865-1 | |
| SUPSD BY 50865-5 | | | | | 1-50865-0 | |
| OBSOLETE | CLOSED | | 0.86-1.04 [.034-.041] | TIN  | TIN  | 50865-8 |
| OBSOLETE | KNOCKOUT | | | | | 50865-7 |
| | OPEN | | | | | 50865-6 |
| | CLOSED | | | | | 50865-5 |
| OBSOLETE | OPEN | | | GOLD  | GOLD  | 50865-4 |
| OBSOLETE | | | | TIN  | | 50865-3 |
| | | | | GOLD  | | 50865-2 |
| | TIN  | | | 50865-1 | | |
| OBSOLETE | KNOCKOUT | | | GOLD  | | 50865 |
| | CLOSED | | | | | |
| NOTES | BOTTOM TYPE | RECOMMENDED PIN DIA.  | EYELET | SPRING | PART NO | |
| | | | FINISH | | | |

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY		4-5-91		 TE Connectivity			
DIMENSIONS: mm [INCHES]		CHK —		APVD —				NAME MINIATURE SPRING SOCKET ASSEMBLY SERIES 4 —	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC —		APPLICATION SPEC —					
		0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± 0.20 [.008] 4 PLC ± — ANGLES ± —		SIZE A2		CAGE CODE 00779	DRAWING NO C-50865		RESTRICTED TO —
MATERIAL 		FINISH —		WEIGHT —		SCALE 1:1			SHEET 1 OF 1
CUSTOMER DRAWING									