Part numbers

FL1E Base Modules



Part Numbers		Rated Voltage	Input Signal	Input Type	Output Type	With Clock
With LCD Display	FL1E-H12RCE	12/24V DC	DC	PNP	Relay	Yes
	FL1E-H12SND	24V DC	DC		Transistor Source	_
	FL1E-H12RCA	24V AC/DC	AC/DC	NPN/PNP	Relay	Yes
	FL1E-H12RCC	100-240V AC/DC	AG/DG	PNP		
Without	FL1E-B12RCE	12/24V DC	DC	PNP		Yes
LCD Display	FL1E-B12RCA	24V AC/DC	A.C./D.C	NPN/PNP	Relay	Yes
	FL1E-B12RCC	100-240V AC/DC	AC/DC	PNP		

Text Message Display



Part Number	Rated Voltage	Description
FL1E-RD1	12 VDC, 24 VAC/DC	FL1E SmartRelay Text Display

Communication Modules



Part Numbers	Module	Input Power	Total I/O
FL1B-CL1C12	LonWorks [®] Communication Module	24V AC/DC	Input: 16 points Analog Input: 8 points Output: 12 points
FL1B-CAS2	AS-Interface Communication Module	30V DC	Input: 4 points Output: 4 points

^{*}LonWorks $^{\circledR}$ is a registered trademark of Echelon

I/O Expansion Modules



Part Numbers	Module	Rated Voltage	Input Type	Output Type	Total I/O
FL1B-M08B2R2		12/24V DC	PNP	Relay	8 (4 in/4 Out)
FL1B-M08B1S2	Combination I/O	24V DC		Transistor	
FL1B-M08C2R2		100-240V AC/DC		Relay	
FL1B-M08D2R2		24V AC/DC	NPN/PNP		
FL1B-J2B2	Analog Input	12/24V DC	0-10V, 4-20mA	_	2 (2 in/0 Out)
FL1D-K2B2	Analog Output	24V DC	_	0-10V	2 (0 in/2 Out)

Starter Kits & Accessories



Part Numbers		Description		
Starter Kits	SMARTSTART-BAC-E	FL1E-B12RCC, WindLGC software and programming cable		
	SMARTSTART-BDC-E	FL1E-B12RCE, WindLGC software, programming cable, and simulator switch		
	SMARTSTART-HAC-E	FL1E-H12RCC, WindLGC software and programming cable		
	SMARTSTART-HDC-E	FL1E-H12RCE, WindLGC software, programming cable, and simulator switch		
Accessories	FL9Y-LP1CDW	WindLGC 6.0 programming software		
	FL1A-PC1	SmartRelay Serial programming cable		
	FL1E-PC2	SmartRelay USB programming cable (direct)		
	FL1E-PM4	FL1E SmartRelay memory cartridge		
	FL1E-PB1	FL1E SmartRelay battery cartridge		
	FL1E-PG1	FL1E SmartRelay memory and battery combination cartridge		
	FC4A-USB	Serial to USB converter		
	FL9Y-B1090-0	FL1E SmartRelay user's manual		
	FL1B-Y1371-SW8	8-pt simulator switch, used with 12-24VDC, 24VDC base module only		