



For more Information
please call

1-800-Belden1



General Description:

Belden's .050" pitch gray ribbon cable was designed for general purpose electronic interconnect applications. The cable provides reliable mass-termination to standard IDC connectors.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 10 | 26 | 7x34 | TC - Tinned Copper |

Total Number of Conductors: 10

Conductor Spacing Center to Center: .050

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|--------------------------|---------------------|
| PVC - Polyvinyl Chloride | 0.254 |

Insulation Resistance: >10,000 Megaohms

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Overall Cable

Overall Nominal Thickness: .039

Overall Nominal Width: .50

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +105°C

Bulk Cable Weight: 23.811 Kg/Km

Min. Bend Radius/Minor Axis: 12.700 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating: AWM 2651

CSA Specification: AWM I A

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: VW-1

CSA Flame Test: FT1

Plenum/Non-Plenum

Plenum (Y/N): No

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Description | Impedance (Ohm) |
|-------------|-----------------|
| (GS) | 135 |
| (GSG) | 90 |

Nom. Inductance:

| Description | Inductance (µH/m) |
|---------------|-------------------|
| @ 1 MHz (GS) | 0.75463 |
| @ 1 MHz (GSG) | 0.49215 |

Nom. Capacitance Conductor to Conductor:

| Description | Capacitance (pF/m) |
|---------------|--------------------|
| @ 1 kHz (GSG) | 75.463 |
| @ 1 MHz (GS) | 36.091 |
| @ 1 MHz (GSG) | 59.058 |

Nominal Velocity of Propagation:

| Description | VP (%) |
|-------------|--------|
| | 67.6 |

Nominal Delay:

| Delay (ns/m) |
|-------------------|
| 1.48 NS/FT. (GSG) |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/km) |
|-----------------------|
| 43 OHMS/1000 FT. MAX. |

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100m) |
|-------------|-----------------------|
| 10 | 12.7959 |
| 20 | 20.9984 |
| 30 | 28.5447 |
| 40 | 42.653 |
| 50 | 55.4489 |
| 60 | 65.9481 |
| 70 | 73.8225 |
| 80 | 78.4159 |
| 90 | 82.3531 |
| 100 | 86.6184 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Current |
|-------------------------------|
| 1.5 Amps per conductor @ 20°C |

Dielectric Withstand Voltage: 2,000 V RMS

Typical Unbalanced Crosstalk:

| Description | Pulse Rise Time (NS) (MHz) | Near End % (MHz) | Far End % (MHz) |
|------------------------|----------------------------|------------------|-----------------|
| 10 ft. sample length 3 | | 5.2 | 6.2 |
| 10 ft. sample length 5 | | 4.2 | 5 |
| 10 ft. sample length 7 | | 3.3 | 3.8 |

Notes (Overall)

Notes: GS=Ground-Signal Mode; GSG=Ground-Signal-Ground Mode

Polarity Identification (Overall)

Polarity Identification: BLUE POLARITY STRIPE ON #1 CONDUCTOR

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|--------|-------------|-------|-------|-----------------------|
| 9L26010 008H100 | 100 FT | 1.800 LB | GRAY | | 10 #26 STR PVC RIBBON |
| 9L26010 008H300 | 300 FT | 6.300 LB | GRAY | | 10 #26 STR PVC RIBBON |

METRIC MEASUREMENT VERSION

9L26010 Flat - Gray Ribbon 9L260XX Series

Revision Number: 2 Revision Date: 10-02-2012

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.