


## Features

- High Current Capability
- Surge Overload Rating to 150A Peak
- High Case Dielectric Strength of 1500V
- Ideal for Printed Circuit Board Application
- UL Listed Under Recognized Component Index, File Number E94661

## Mechanical Data

- Case: PBPC-8
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Marked on Body
- Mounting: Through Hole for #6 Screw
- Mounting Torque: 5.0 Inch-pounds Maximum
- Ordering Information: See Page 2
- Marking: Type Number
- Weight: 3.8 grams (approximate)



PBPC-8		
Dim	Min	Max
A	18.54	19.56
B	6.35	7.60
C	22.20	—
D	1.27 Ø Typical	
E	5.33	7.37
G	3.60 Ø	4.00 Ø
H	12.70 Typical	
J	2.38 X 45° Typical	
All Dimensions in mm		

## Maximum Ratings and Electrical Characteristics

@ T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

Characteristic	Symbol	PBPC 1001	PBPC 1002	PBPC 1003	PBPC 1004	PBPC 1005	PBPC 1006	PBPC 1007	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>								
Working Peak Reverse Voltage	V <sub>RWM</sub>	50	100	200	400	600	800	1000	V
DC Blocking Voltage	V <sub>R</sub>								
RMS Reverse Voltage	V <sub>R(RMS)</sub>	35	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1) @ T <sub>C</sub> = 50°C	I <sub>O</sub>				10				A
(Note 2) @ T <sub>C</sub> = 50°C					8.0				
Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load	I <sub>FSM</sub>				150				A
Forward Voltage (per element) @ I <sub>F</sub> = 5.0A	V <sub>FM</sub>				1.1				V
Peak Reverse Current @ T <sub>C</sub> = 25°C	I <sub>R</sub>				10				µA
at Rated DC Blocking Voltage (per element) @ T <sub>C</sub> = 100°C					1.0				mA
I <sup>2</sup> t Rating for Fusing (t < 8.3ms) (Note 3)	I <sup>2</sup> t				64				A <sup>2</sup> s
Typical Total Capacitance, per element (Note 4)	C <sub>T</sub>				110				pF
Typical Thermal Resistance Junction to Case (per element)	R <sub>θJC</sub>				7.5				°C/W
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>STG</sub>				-65 to +125				°C

- Notes:
1. Mounted on metal chassis.
  2. Mounted on PC board FR-4 material.
  3. Non-repetitive, for t > 1.0ms and < 8.3ms.
  4. Per element, measured at 1.0 MHz and applied reverse voltage of 4.0V DC.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics, per element




Fig. 3 Typical Reverse Characteristics




Fig. 4 Typical Reverse Characteristics, per element

## Ordering Information (Note 5)

Device	Packaging	Shipping
PBPC1001	PBPC-8	150/Box
PBPC1002	PBPC-8	150/Box
PBPC1003	PBPC-8	150/Box
PBPC1004	PBPC-8	150/Box
PBPC1005	PBPC-8	150/Box
PBPC1006	PBPC-8	150/Box
PBPC1007	PBPC-8	150/Box

Notes: 5. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02008.pdf>.

#### **IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

#### **LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2010, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)