

TECHNICAL DATA
DATA SHEET 175, REV. B

HERMETIC AXIAL LEAD/MELF RECTIFIER

DESCRIPTION: A 600 VOLT, 1.0 AMP, 250 NANOSECOND AXIAL LEAD MELF RECTIFIER

MAXIMUM RATINGS

All ratings are at $T_A = 25^\circ\text{C}$ unless otherwise specified.

RATING	CONDITIONS	MIN.	TYP.	MAX.	UNIT
Peak Inverse Voltage (PIV)	-	-	-	600	Vdc
Average DC Output Current (I_o)	$T_A = +75^\circ\text{C}$	-	-	1.0	Amps
Average DC Output Current (I_o)	$T_A = +100^\circ\text{C}$	-	-	.75	Amps
Peak Single Cycle Surge Current (I_{fsm})	$t_p = 8.3 \text{ ms Single Half Cycle Sine Wave, Superimposed On Rated Load}$	-	-	25	Amps(pk)
Operating and Storage Temp. (T_{op} & T_{stg})	-	-65	-	+175	$^\circ\text{C}$
Thermal Resistance (θ_{JL})	$d = 0.375"$	-	-	38	$^\circ\text{C/W}$
Thermal Resistance (θ_{JEC})	Junction to end caps	-	-	7.0	$^\circ\text{C/W}$


ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	CONDITIONS	MIN.	TYP.	MAX.	UNIT
Maximum Forward Voltage (V_f)	$I_f = 3.0\text{A}$ (300 μsec pulse, duty cycle < 2%)	-	-	1.6	Volts
Maximum Instantaneous Reverse Current At Rated PIV (I_R)	$T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$	-	-	0.5 25	μAmps
Reverse Recovery Time (t_{rr})	$I_f = 0.5\text{A}$, $I_r = 0.5\text{A}$, $I_{rr} = 50\text{mA}$	-	-	250	nsec

SENSITRON

TECHNICAL DATA
DATA SHEET 175, REV. B


AXIAL LEAD RECTIFIER OUTLINES



Note: Cathode side of device is indicated by a dark band marked on body.

PACKAGE STYLE	DIMENSIONS - INCHES / MILLIMETERS			
	ϕB	ϕD	G	L
102	.065/.110 1.65/2.79	.026/.033 .66/.84	.130/.225 3.30/5.72	1.00/1.30 25.4/33.0

MELF PACKAGE OUTLINES



Note: Cathode side of device is indicated by a dark band marked on body.

PACKAGE STYLE	DIMENSIONS - INCHES / MILLIMETERS			
	A	B	C	D
MELF-1	.168/.230 4.2/5.9	0.019/.028 .48/.72	.003 Min .076 Min	.091/.128 3.4/3.8

SENSITRON

**TECHNICAL DATA
DATA SHEET 175, REV. B**

DISCLAIMER:

- 1- *The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).*
- 2- *In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.*
- 3- *In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.*
- 4- *In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.*
- 5- *No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.*
- 6- *The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.*
- 7- *The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.*