


# 3M™ MetPak™ 2-FB Socket

2 mm 4/5-Row, Solder Tail or Press-Fit With Tail Cover, Right Angle

MP2 Series



- End-to-end stackable
- Offset dual-beam contact minimizes insertion force
- Expanded pin counts
- Protective Push-Cap
- Monoblockable
- Press or heat stake peg
- 12 mm modular units
- Meets global IEC 61076-4-104 Futurebus+® standard
- See the Regulatory Information Appendix (RIA) in the “RoHS compliance” section of [www.3Mconnectors.com](http://www.3Mconnectors.com) for compliance information (RIA E1 & C1 apply)

Date Modified: September 17, 2013

TS-1115-D  
Sheet 1 of 4

## Physical

### Insulation:

Material: High Temp LCP  
Flammability: UL 94V-0  
Color: Beige

### Contact:

Material: Copper Alloy

### Plating:

Underplating: 50 μ" (1.27 μm) Nickel  
Wiping Area: See Ordering Information  
Solder Tails: See Ordering Information

## Electrical

**Current Rating:** Signal: 1.5 A - All contacts simultaneously

**Insulation Resistance:** 10<sup>3</sup> MΩ

**Withstanding Voltage:** 1,000 V<sub>AC</sub>

## Environmental

**Temperature Rating:** -55° C to 125° C

**Process Temperature Rating:** 260°C (Profile per J-STD-020C)

**Moisture Sensitivity Level:** 1 (per J-STD-020C)

UL File No.: E68080

MetPak is a trademark of 3M Company.  
Futurebus+ is a registered trademark of the Institute of Electrical and Electronic Engineers, Inc. (IEEE)

**3M**


Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnectors.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

# 3M™ MetPak™ 2-FB Socket

2 mm 4/5-Row, Solder Tail or Press-Fit With Tail Cover, Right Angle

MP2 Series



Note:

1. Refer to IEC 61076-4-104 Futurebus+® global standard.
2. "Press Fit" describes a contact tail having a compliant section designed to make a reliable electrical connection with a plated through-hole (PTH) in a printed circuit board, typically a "back plane."

## Ordering Information

**MP2 - SXXX - X1XX - X - XXXX**

Contact Count  
(See Table 1)

Rows  
4 = 4 Rows  
5 = 5 Rows

Termination Style  
M = Solder Tail (Press Peg)  
(press peg requiring arbor press for PCB assembly)  
(Contact 3M Sales Rep)  
P = Press Fit (w/ Tail Cover)

Tail Length  
(See Table 2)

Plating Options:  
(See Table 3)

C = Capped Solder Tail  
Blank = Press-Fit

TS-1115-D  
Sheet 2 of 4



Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnectors.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

# 3M™ MetPak™ 2-FB Socket

2 mm 4/5-Row, Solder Tail or Press-Fit With Tail Cover, Right Angle

MP2 Series

| Table 1 - Connector & Row Lengths |                   |         |                   |         |      |             |
|-----------------------------------|-------------------|---------|-------------------|---------|------|-------------|
| Pin Count                         | Dim "A" mm (Inch) |         | Dim "B" mm (Inch) |         | Rows | Block Count |
| 024                               | 11.95             | [0.471] | 10.00             | [0.394] | 4    | 1           |
| 048                               | 23.95             | [0.943] | 22.00             | [0.866] | 4    | 2           |
| 072                               | 35.95             | [1.415] | 34.00             | [1.339] | 4    | 3           |
| 096                               | 47.95             | [1.889] | 46.00             | [1.811] | 4    | 4           |
| 120                               | 59.95             | [2.36]  | 58.00             | [2.283] | 4    | 5           |
| 144                               | 71.95             | [2.833] | 70.00             | [2.756] | 4    | 6           |
| 168                               | 83.95             | [3.305] | 82.00             | [3.228] | 4    | 7           |
| 192                               | 95.95             | [3.778] | 94.00             | [3.701] | 4    | 8           |
| 030                               | 11.95             | [0.471] | 10.00             | [0.394] | 5    | 1           |
| 060                               | 23.95             | [0.943] | 22.00             | [0.866] | 5    | 2           |
| 090                               | 35.95             | [1.415] | 34.00             | [1.339] | 5    | 3           |
| 120                               | 47.95             | [1.888] | 46.00             | [1.811] | 5    | 4           |
| 150                               | 59.95             | [2.361] | 58.00             | [2.283] | 5    | 5           |
| 180                               | 71.95             | [2.833] | 70.00             | [2.756] | 5    | 6           |
| 210                               | 83.95             | [3.305] | 82.00             | [3.228] | 5    | 7           |
| 240                               | 95.95             | [3.778] | 94.00             | [3.701] | 5    | 8           |

| Table 2 - Tail & Post Lengths                   |            |              |              |
|-------------------------------------------------|------------|--------------|--------------|
| Contact-to-PC Board Tail Termination Option No. |            | Dim "C"      | Dim. "D"     |
| Solder                                          | Press-Fit* |              |              |
| M1                                              |            | 2.72 [0.107] | 3.57 [0.141] |
| M2                                              | P1         | 3.53 [0.139] | 3.57 [0.141] |

\*Compliant-Pin Tail

| Table 3 - Plating |                     |                     |                                                                                                                                                                                 |
|-------------------|---------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plating Suffix    | Press-Fit Tails*    | Solder Tails        | Plating Composition                                                                                                                                                             |
| KR                | (RIA E1 & C1 apply) | (RIA E1 & C1 apply) | 0.76 µm [30 µ"] Min. Au Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over                                          |
| LR                | (RIA E1 & C1 apply) | (RIA E1 & C1 apply) | 0.08 µm [3 µ"] Min. Au Contact Area<br>0.67 µm [27 µ"] Min. PdNi Contact Area<br>2.54 µm [100 µ"] Min. Matt Whisker Mitigating Sn Tail Area<br>1.27 µm [50 µ"] Min. Ni all over |

\*Compliant-Pin Tail

TS-1115-D  
Sheet 3 of 4



Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnectors.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
**800-225-5373**

# 3M™ MetPak™ 2-FB Socket

2 mm 4/5-Row, Solder Tail or Press-Fit With Tail Cover, Right Angle

MP2 Series




Table 4: HOLE PLATING FINISHES

| HOLE | Finished Dia.<br>mm [in]     | Cu Thickness<br>mm [in]      | Immersion Matte Sn<br>Thickness<br>microns [μ"] | Electrolytic Au<br>Thickness<br>microns [μ"] | OSP ENTEK<br>Thickness<br>microns [μ"] | Drilled Hole Dia.<br>mm [in]                                  |
|------|------------------------------|------------------------------|-------------------------------------------------|----------------------------------------------|----------------------------------------|---------------------------------------------------------------|
| "D"  | 0.700-0.800<br>[.0276-.0315] | 0.025-0.045<br>[0.001-0.002] | 0.5 - 2.5<br>[20 - 100]                         | 0.1 - 0.5<br>[4 - 20]                        | 0.2 - 0.5<br>[8 - 20]                  | 0.830-0.860 [.0330-.0340] or<br>0.85mm [ #66 ] TWIST<br>DRILL |

TS-1115-D  
Sheet 4 of 4



Electronic Solutions Division  
Interconnect Solutions  
<http://www.3Mconnectors.com>

3M is a trademark of 3M Company.  
For technical, sales or ordering information call  
800-225-5373

3M is a trademark of 3M Company.

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### **Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



#### **3M Electronics Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
U.S.A.  
1-800-225-5373  
[www.3Mconnectors.com](http://www.3Mconnectors.com)

Please recycle. Printed in USA.  
© 3M 2013. All rights reserved.  
RIA-2217B-E