

Flexible RF cable RG_188_A/U-60

Description

RG: RG type RF cables

RG188, 50 Ohm, 3 GHz, 200°C, ø2.6 mm, FEP jacket, UL AWM style 1354



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 9010 - wh	2.6 mm +/- 0.1

Print: HUBER+SUHNER RG 188 A/U-60 50 Ohm (UL logo) AWM Style 1354 (production order number)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Screening effectiveness	≥ 41 dB (up to 1 GHz)
Operating voltage	≤ 1.45 kV _{rms} (at sea level)
Test voltage	1.7 kV _{rms} (50 Hz/1 min)
Voltage Rating UL	30 V

Mechanical Data

Weight		1.7 kg/100 m
Min. bending radius	static	15 mm
	dynamic	26 mm
		39 mm

Environmental Data

Temperature range	-65 °C ... +200 °C
Temperature rating UL	80 °C
Installation temperature	-20 °C... +60 °C
Flame propagation test	UL (horizontal flame test),
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

Additional Information

Ordering Information

Order as	RG_188_A/U-60
----------	---------------

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U2 2 mm / 50 Ohm
-------------	------------------

Flexible RF cable RG_188_A/U-60

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.7501

b = 0.0884

f_{max} = 3

P at 1GHz = 180

Frequency	Nom. attenuation	Nom. attenuation	Max. CW power
(GHz)	(dB / m)	(dB / ft)	(W)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,15	0,3	0,093	465
0,3	0,44	0,133	329
0,45	0,54	0,165	268
0,6	0,63	0,193	232
0,75	0,72	0,218	208
0,9	0,79	0,241	190
1,05	0,86	0,263	176
1,2	0,93	0,283	164
1,35	0,99	0,302	155
1,5	1,05	0,320	147
1,65	1,11	0,338	140
1,8	1,17	0,355	134
1,95	1,22	0,372	129
2,1	1,27	0,388	124
2,25	1,32	0,404	120
2,4	1,37	0,419	116
2,55	1,42	0,434	113
2,7	1,47	0,448	110
2,85	1,52	0,463	107
3,0	1,56	0,477	104