



MCMN2012


Features

- TrenchFET Power MOSFET
- Small package
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: N2012

Maximum Ratings @ 25°C Unless Otherwise Specified


Symbol	Parameter	Rating	Unit
V_{DS}	Drain-source Voltage	20	V
I_D	Drain Current-Continuous	12	A
I_{DM}	Pulsed Drain Current (note1)	40	A
V_{GS}	Gate-source Voltage	± 10	V
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	167	$^{\circ}\text{C}/\text{W}$
T_J	Operating Junction Temperature	-55 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature	-55 to +150	$^{\circ}\text{C}$

Equivalent Circuit



N-Channel Enhancement Mode Field Effect Transistor

DFN2020-6J



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.028	.032	0.700	0.800	
B	0.008REF.		0.203REF.		
C	0.000	0.002	0.000	0.050	
D	0.076	0.082	1.924	2.076	
E	0.076	0.082	1.924	2.076	
F	0.031	0.039	0.800	1.000	
G	0.033	0.041	0.850	1.050	
H	0.008	0.016	0.200	0.400	
J	0.008	---	0.200	---	
K	0.018	0.026	0.460	0.660	
L	0.026TYP.		0.650TYP.		
M	0.010	0.014	0.250	0.350	
N	0.007	0.013	0.174	0.326	

ELECTRICAL CHARACTERISTICS($T_a=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	20			V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 20V, V_{GS} = 0V$			1	μA
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 10V, V_{DS} = 0V$			± 100	nA
Gate threshold voltage (note 3)	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	0.35	0.7	1	V
Drain-source on-resistance(note 3)	$R_{DS(on)}$	$V_{GS} = 4.5V, I_D = 9.7A$		9	11	m Ω
		$V_{GS} = 2.5V, I_D = 9A$		12	13	m Ω
		$V_{GS} = 1.8V, I_D = 8.1A$		15.5	16	m Ω
		$V_{GS} = 1.5V, I_D = 4.5A$		21	22	m Ω
		$V_{GS} = 1.2V, I_D = 2.4A$			41	m Ω
Forward tranconductance(note 3)	g_{FS}	$V_{DS} = 4V, I_D = 9.7A$	20			S
Diode forward voltage (note 3)	V_{SD}	$I_S = 10A, V_{GS} = 0V$			1.2	V
DYNAMIC PARAMETERS (note 4)						
Input Capacitance	C_{iss}	$V_{DS} = 4V, V_{GS} = 0V, f = 1MHz$		1800		pF
Output Capacitance	C_{oss}			650		pF
Reverse Transfer Capacitance	C_{rss}			450		pF
Gate Resistance	R_g	$f = 1MHz$		2.5		Ω
SWITCHING PARAMETERS (note 4)						
Turn-on delay time	$t_{d(on)}$	$V_{GEN} = 4.5V, V_{DD} = 4V, I_D = 10A, R_g = 1\Omega, R_L = 0.4\Omega$		12	20	ns
Turn-on rise time	t_r			10	15	ns
Turn-off delay time	$t_{d(off)}$			65	100	ns
Turn-off fall time	t_f			20	30	ns
Total Gate Charge	Q_g	$V_{DS} = 4V, V_{GS} = 5V, I_D = 10A$			32	nC
Gate-Source Chage	Q_{gs}			2.5		nC
Gage-Drain Charge	Q_{gd}			6.5		nC

Notes :





- 1.Surface mounted on FR4 board using 1 square inch pad size,1oz copper.
- 2.Surface mounted on FR4 board using the minimum pad size,1oz copper.
3. Pulse test : Pulse width=300 μ s, duty cycles \leq 2%.
4. These parameters have no way to verify.

Typical Characteristics


Output Characteristics



Transfer Characteristics



Threshold Voltage





Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.