

**General ordering data**

Order No.	0376860000
Part designation	ASK 1/15
Version	Fuse terminal, 4 mm ² , Screw connection, PA 66, beige, TS 15
EAN	4008190141202
Qty.	100 pc(s).

Product notes

Note, technical data	Note: max. conductor size = 2.5 mm ² when using the cross-connection. Twin wire-end ferrules ZH 0.5 - ZH 1.5 can be used.
Note, accessories	Contact Sleeve order no. 0553300000; AP ASK 1 order no. 0380360000.

Additional technical data

Colour of insulating material	beige
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 15
Insulating material	PA 66
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 100 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V2
Version	Fuse terminal

CSA rating data

Voltage (CSA)	300 V
CSA current	6.3 A
Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

Conductors for clamping (additional connection)Flexible with ferrule, min. (DIN 46228 pt 1) 0.5 mm²Flexible with ferrule, max. (DIN 46228 pt 1) 4 mm²**Conductors for clamping (rated connection)**Clamping range, min. 0.13 mm²Clamping range, max. 4 mm²

Type of connection Screw connection

2nd type of connection screwed

Connection direction on side

No. of connections 2

Stripping length 9 mm

Clamping screw M 3

Blade size 0.6 x 3.5 mm

Tightening torque range 0.5...1.0 Nm

Torque level with DMS electric screwdriver 2

Gauge to IEC 60947-1 A3

Solid, min. 0.5 mm²Solid, max. 4 mm²Stranded, min. 1.5 mm²Stranded, max. 4 mm²Flexible, min. 0.5 mm²Flexible, max. 4 mm²Flexible with ferrule, min. (DIN 46228/1) 0.5 mm²Flexible with ferrule, max. (DIN 46228/1) 4 mm²Flexible, min., ferrule with plastic collar (DIN 46228 pt 4) 0.5 mm²Flexible, max., ferrule with plastic collar (DIN 46228 pt 4) 4 mm²Twin wire-end ferrule, min. 0.5 mm²Twin wire end ferrule, max. 1.5 mm²

AWG conductor size, min. AWG 26

AWG conductor size, max. AWG 12

AWG conductor size, min. 0.13 mm²AWG conductor size, max. 3.31 mm²**Dimensions**

Width 8 mm

Height of lowest version 34 mm

Length 58 mm

TS 15 offset 26 mm

Disconnect terminals

Torque level with DMS electric screwdriver 2

Display element

Operating voltage for display, max. 500 V

Type of voltage for indicator AC/DC

Fuse terminals

Cartridge fuse G-Si. 5 x 20

Fuse terminals

Display	Without LED
Fuse holder (cartridge holder)	Pivoting
Operating voltage, max.	400 V
Type of voltage for indicator	AC/DC

Rating data

Rated cross-section	4 mm ²
Rated voltage	500 V
Rated impulse voltage	6 kV
Rated current	6.3 A
Current with max. conductor	6.3 A
Pollution severity	3

UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 22
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes

**Classifications**

ETIM 2.0	EC000899
ETIM 3.0	EC000899
eClass 4.1	27-14-11-16
eClass 5.0	27-14-11-16
eClass 5.1	27-14-11-16

Similar products

Order No.	Part designation	Version
-----------	------------------	---------