

Specification Status: RELEASED

BENEFITS

- Industry-leading lowest capacitance; provides lowest insertion loss for high speed data signals
- Small size ESD protection diodes for high speed data signals (0402 size devices)
- Helps protect electronic circuits against damage from Electrostatic Discharge (ESD), surge and cable discharge events
- Assists equipment to pass IEC61000-4-2, level 4 testing



FEATURES

- Low capacitance: 0.20 pF (200fF) (typ)
- Low leakage current : 25nA @ 5V (typ)
- Low clamping voltage: +9.20 / -0.80V (typ)
@ (tp=8x20 μ s, Ipp=2A)
- ESD maximum rating per IEC61000-4-2 standard:
 - 20kV contact discharge
 - 20kV air discharge
- Surge: 2A (max) @ (tp=8x20 μ s) per IEC61000-4-5
- Small size and low profile: XDFN packages

APPLICATIONS

- Consumer, mobile and portable electronics
- Tablet PC and external storage with high speed interfaces
- Ultra-high speed data lines
- USB 3.0/2.0, HDMI 1.3/1.4, DisplayPort, Thunderbolt (Light Peak), V-by-One HS, and LVDS interfaces
- Applications requiring high ESD performance in small packages

AEC-Q101 QUALIFIED

MATERIALS INFORMATION

RoHS Compliant ELV Compliant Halogen Free * Lead Free

Directive 2000/53/EC
Compliant

Directive 2002/95/EC
Compliant



* Halogen Free refers to: Br<900ppm Cl<900ppm Br+Cl<1500ppm

SESD devices meet MSI -1 Requirements

DEN case epoxy meets UL 94 V-0

PART NUMBERING


The diagram illustrates the mapping of X1UN part number segments to device characteristics:

- SESD 0402 X1UN** - The first four digits represent the package type: SMD 0402.
- 0020** - The next two digits represent the breakdown voltage: 9.0V (typ).
- 090** - The final two digits represent the input capacitance: 0.20 pF (typ).
- Series** - The first digit of the part number.
- EIA Size** - The second digit of the part number.
- Package Type** - The third digit of the part number.
- X - XDFN** - The fourth digit of the part number.
- 1 - one channel** - The fifth digit of the part number.
- Breakdown Voltage** - Indicated by a bracket under the 090 segment.
- 9.0V (typ)** - The typical breakdown voltage value.
- Input Capacitance** - Indicated by a bracket under the 090 segment.
- 0.20 pF (typ)** - The typical input capacitance value.
- N - No Common pin** - Indicated by a bracket under the 090 segment.
- U - Unidirectional** - Indicated by a bracket under the 090 segment.

PART MARKING

Cathode Band  **Factory Code Marking**
- Unidirectional - Factory 2 : Single alphanumeric character

PIN CONFIGURATION AND SCHEMATIC



* Drawing not to scale

DEVICE MAXIMUM RATING

ESD Withstand ⁽¹⁾ (IEC 61000-4-2, level 4)		Temperature		Peak Current (tp=8x20μs)
Contact (kV)	Air (kV)	Operating (°C)	Storage (°C)	I _{pp} (A)
20	20	-55 to +125	-55 to +150	2.0

⁽¹⁾ 20kV @ 1 pulse; 10kV @ 100 pulses; 8kV @ 1,000 pulses (under IEC6100-4-2)

- Maximum leakage current post 15kV & 20kV pulses is less than 1 μA
- Device maximum rating @ T = 25°C, unless otherwise specified
- Caution: Stress exceeding Device Maximum Ratings may damage the device


Prolonged exposure to stresses above the recommended operating conditions may affect device reliability

DEVICE ELECTRICAL CHARACTERISTICS

Input Capacitance @ V _R = 0V, f = 3GHz, I/O to GND (pF)		Breakdown Voltage V _{BR} @ I _T =1mA (V)	Reverse Working Voltage (V)		Reverse Leakage Current I _L @ V _{RWM} =5.0V (nA)		Clamping Voltage V _{CL} @ I _{pp} =2.0A (V)
Typ	Maximum	Typ	Min	Max	Typ	Max	Typ
0.20	0.25	+9.00 / -0.80	0	+7.00	25.0	50.0	+9.20 / -0.80



- All device electrical characteristics @ T = 25°C, unless otherwise specified

FIGURE 1. INSERTION LOSS DIAGRAM




Application	Bit Rate (Gbps)	@Freq (GHz)	Ins. Loss (dB)
HDMI 1.4 (1080P)	2.25	1.13	-0.23
DisplayPort	2.70	1.35	-0.26
HDMI 1.4 (4K / QuadHD)*	3.40	1.70	-0.30
USB3.0	5.00	2.50	-0.38
eSATA	6.00	3.00	-0.44
Thunderbolt	10.0	5.00	-0.69

*HDMI 4K / QuadHD resolutions (4096 x 2160) ready

FIGURE 2. DEVICE IV CURVE

DEVICE DIMENSIONS


SESD0402X1UN-0020-090						
Dim	Milimeters (mm)			Inches (in)		
	Min	Nom	Max	Min	Nom	Max
A	0.33	0.38	0.43	0.013	0.015	0.017
A1	0	-	0.05	0	-	0.002
A3	0.13 ref.			0.005 ref.		
D	0.55	0.60	0.65	0.022	0.024	0.026
E	0.95	1.00	1.05	0.037	0.039	0.041
K	0.35	0.40	0.45	0.014	0.016	0.018
b	0.45	0.50	0.55	0.018	0.020	0.022
L	0.20	0.25	0.30	0.008	0.010	0.012
e	0.65 BSC			0.026 BSC		


BSC – Basic Spacing between Centers

RECOMMENDED LANDING PATTERN:



SESD Landing Pad Layout		
0402 Package		
Symbol	Milimeters (mm)	Inches (in)
A	0.60	0.024
B	1.00	0.039
D	0.35	0.014
F	0.30	0.012

PACKAGING

Packaging	Tape & Reel	Standard Box
SESD0402X1UN-0020-090	10,000	50,000

REEL DIMENSIONS


Dimensions	A	B	C	D	E	F	G	H
(mm)	180 ± 2.00	1.50 (min)	13.10 ± 0.20	20.20 (min)	60 ± 1.00	8.75 ± 1.00	11.6 ± 1.00	9.4 (max)

CARRIER TAPE DIMENSIONS


A ₀	0.70 ± 0.05
B ₀	1.15 ± 0.05
K ₀	0.47 ± 0.05
F	3.50 ± 0.05
P ₁	2.00 ± 0.10
W	8.00 ± 0.10

Note 1. All dimensions in mm

Note 2. Measured from centerline of pocket to centerline of sprocket hole

Note 3. Cumulative tolerance of 20 sprocket holes is ± 0.20

Note 4. Tolerances unless noted ± 0.20

Single Channel

Silicon ESD Protector


Overvoltage Protection Device

 DOCUMENT: SCD28186
 REV LETTER: G
 REV DATE: MAY 15, 2013
 PAGE NO.: 6 OF 6

SOLDER REFLOW RECOMMENDATION

A	Temperature ramp up 1	From ambient to Preheating temperature	30s to 60s
B	Preheating	140°C - 160°C	60s to 120s
C	Temperature ramp up 2	From Preheating to Main heating temperature	20s to 40s
D	Main heating	at 200°C at 220°C at 240°C at 260°C	60s ~ 70s 50s ~ 60s 30s ~ 40s 5s ~ 10s
E	Cooling	From main heating temperature to 100°C	4°C/s (max)

FIGURE 3. REFLOW PROFILE



All information, including illustrations, is believed to be accurate and reliable. Users, however, should independently evaluate the suitability of and test each product selected for their application. Tyco Electronics Corporation and/or its Affiliates in the TE Connectivity Ltd. family of companies ("TE") makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. TE's only obligations are those in the TE Standard Terms and Conditions of Sale and in no case will TE be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products. Specifications are subject to change without notice. In addition, TE reserves the right to make changes to materials or processing that do not affect compliance with any applicable specification without notification to Buyer. Without expressed written consent by an officer of TE, TE does not authorize the use of any of its products as components in nuclear facility applications, aerospace, or in critical life support devices or systems.

TE Connectivity, TE Connectivity (logo), and TE (logo) are trademarks.

Other logos, products and /or company names might be trademarks of their respective owners.