

**Part Number: 79108-0004**


**2.00mm Pitch Milli-Grid™ Flex-to-Board Vertical Receptacle Dual Row Through-Hole, 0.38µm Gold (Au) Selective Plating, 10 Circuits, Tin/Lead**

Image not available

**Status:** **OBSOLETE**  
**Replacement:** [791081004](#)  
**Series:** [79108](#)  
**Category:** FFC/FPC Connectors  
**Overview:** [Milli-Grid™ Connector System](#)

Series image - Reference only

**Product Environmental Compliance**

**EU RoHS:** Not RoHS Compliant  
**China RoHS:**   
**REACH SVHC:** Contains SVHC: No  
**Low-Halogen Status:** Not Reviewed

**Part Detail****General**

<b>Status</b>	<b>Obsolete</b>
Category	FFC/FPC Connectors
Series	<a href="#">79108</a>
Obsolete Date	2005/06/01
Overview	<a href="#">Milli-Grid™ Connector System</a>
Product Name	Milli-Grid™

**Physical**

Circuits (Loaded)	10
Contact Position	Top
Durability (mating cycles max)	50
Entry Angle	90° Angle
Number of Rows	2
Orientation	Right Angle
PC Tail Length	1.27mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	0.60mm
Packaging Type	Tube
Pitch - Mating Interface	2.00mm
Polarized to PCB	No
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +105°C
Termination Interface: Style	Through Hole
Wire/Cable Type	FFC/FPC

**Electrical**

**(Please review the Product Specification for specific details.)**

Current - Maximum per Contact	1A
Voltage - Maximum	125V

**Solder Process Data**

Replacement RoHS Compliant Part Number	0791081004
--	------------

**Material Info****Application Tooling**

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

**Previously Available Application Tooling**

[Check our list of old tooling that used to be available for this part](#)

