

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DOC. NO. SPC-F005 * Effective: 12/21/98 * DCP No: 480					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1116	C	Drawing Was CRS-TV-***	JWM	6/11/01	JC	6/20/01	JC	6/20/01
1199	D	Redrawn & Bulk Items added	JWM	4/11/02	JC	4/11/02	JC	4/11/02

Notes:

Material: Electro-tin plated Copper
Insulating Material: Vinyl (PVC) UL94V-0
Voltage Rating: 600V
Operating Temp: -40°F to 221°F (-40°C ~ 105°C)

SPC Type No.	Package Qty.	Wire Range (AWG)	Stud Size	W	C	L	E	Thickness	"T" Barrel I.D.	"M" Max. Insulator Diameter	Color	
CRS-TV-1006	50	12 ~ 10	6	.28	.29	.98	.84	.040	.135	.250	Yellow	
SPC3763	500											8
CRS-TV-1008	50		10	.38	.29	1.03						
SPC3764	500											
CRS-TV-1010	50	12 ~ 10	1/4	.53	.44	1.26	.99	.030	.090	0.145	Red	
SPC3765	500											5/16
CRS-TV-1025	50		3/8	.25	.22	.80						
SPC3766	500											6
CRS-TV-1031	50	16 ~ 14	8	.31	.33	.93	.78	.030	.090	0.17	Blue	
SPC3767	500											10
CRS-TV-1037	50		1/4	.47	.40	1.08	.85					
CRS-TV-1406	100											22 ~ 18
SPC3760	1000	4	.22	.80	.67							
CRS-TV-1406-S	100					6	.25	.22	.80	.67		
SPC3899	1000	8	.31	.33	.93						.78	
CRS-TV-1408	100					16 ~ 14	10	.33	.29	.90		.74
SPC3761	1000	1/4	.47	.40	1.08						.85	
CRS-TV-1408-S	100						2	.25	.23	.80		.68
CRS-TV-1410	100	4	.22	.80	.67							
SPC3756	1000					22 ~ 18	6	.25	.22	.80	.67	
CRS-TV-1410-S	100	8	.31	.33	.93							.78
CRS-TV-1425	100						10	.31	.33	.93	.78	
SPC3762	1000	16 ~ 14	1/4	.47	.40							1.08
CRS-TV-1802	100					2	.25	.23	.80	.68		
CRS-TV-1804	100		4	.22	.80						.67	
SPC3755	1000					6	.25	.22	.80	.67		
CRS-TV-1806	100	22 ~ 18	8	.31	.33						.93	.78
SPC3756	1000					10	.31	.33	.93	.78		
CRS-TV-1808	100		1/4	.47	.40						1.08	.85
SPC3757	1000					16 ~ 14	10	.31	.33	.93		
CRS-TV-1810	100	1/4	.47	.40	1.08						.85	
SPC3758	1000						2	.25	.23	.80		.68
CRS-TV-1825	100	4	.22	.80	.67							
SPC3759	1000					6	.25	.22	.80	.67		