



# Numonyx™ Axcell™ M29EW Datasheet

256-Mbit, 512-Mbit, 1-Gbit, 2-Gbit (x8/x16, uniform block)  
3 V supply flash memory

## Features

- Supply voltage
  - $V_{CC}$  = 2.7 to 3.6 V for Program, Erase and Read
  - $V_{CCQ}$  = 1.65 to 3.6 V for I/O buffers
- Asynchronous Random/Page Read
  - Page size: 16 words or 32 bytes
  - Page access: 25 ns
  - Random access: 100ns (Fortified BGA); 110 ns (TSOP)
- Buffer Program
  - 512-word program buffer
- Programming time
  - 0.88  $\mu$ s per byte (1.14MB/s) typical when using full buffer size in buffer program
- Memory organization
  - Uniform blocks, 128 Kbytes/64 Kwords each
- Program/Erase controller
  - Embedded byte/word program algorithms
- Program/ Erase Suspend and Resume
  - Read from any block during Program Suspend
  - Read and Program another block during Erase Suspend
- Blank Check to verify an erased block
- Unlock Bypass/Block Erase/Chip Erase/Write to Buffer
  - Faster Buffered/Batch Programming
  - Faster Block and Chip Erase
- Vpp/WP# pin protection
  - Protects first or last block regardless of block protection settings
- Software protection
  - Volatile Protection
  - Non-Volatile Protection
  - Password Protection
  - Password Access
- Extended Memory block
  - 128-word/256-byte block for permanent, secure identification.
  - can be programmed and locked by factory or by the customer
- Low power consumption
  - Standby
- Minimum 100,000 Program/Erase cycles per block
- ETOX™\* X (65nm) MLC technology
- Fortified BGA and TSOP packages
- JESD47E Compliant
- Green packages available
  - RoHS Compliant
  - Halogen Free

|          |                                                             |           |
|----------|-------------------------------------------------------------|-----------|
| <b>1</b> | <b>Description .....</b>                                    | <b>7</b>  |
| <b>2</b> | <b>Signal Descriptions .....</b>                            | <b>13</b> |
| 2.1      | Address inputs (A0-Amax) .....                              | 13        |
| 2.2      | Data inputs/outputs (DQ0-DQ7) .....                         | 13        |
| 2.3      | Data inputs/outputs (DQ8-DQ14) .....                        | 13        |
| 2.4      | Data input/output or address input (DQ15/A-1) .....         | 13        |
| 2.5      | Chip Enable (CE#) .....                                     | 13        |
| 2.6      | Output Enable (OE#) .....                                   | 13        |
| 2.7      | Write Enable (WE#) .....                                    | 14        |
| 2.8      | V <sub>PP</sub> /Write Protect (V <sub>PP</sub> /WP#) ..... | 14        |
| 2.9      | Reset (RST#) .....                                          | 15        |
| 2.10     | Ready/Busy output (RY/BY#) .....                            | 15        |
| 2.11     | Byte/Word organization select (BYTE#) .....                 | 15        |
| 2.12     | V <sub>CC</sub> supply voltage .....                        | 15        |
| 2.13     | V <sub>CCQ</sub> input/output supply voltage .....          | 15        |
| 2.14     | V <sub>SS</sub> ground .....                                | 16        |
| <b>3</b> | <b>Bus Operations .....</b>                                 | <b>17</b> |
| 3.1      | Bus Read .....                                              | 17        |
| 3.2      | Bus Write .....                                             | 17        |
| 3.3      | Output Disable .....                                        | 17        |
| 3.4      | Standby .....                                               | 17        |
| 3.5      | Reset .....                                                 | 18        |
| 3.6      | Auto Select mode .....                                      | 18        |
| 3.6.1    | Read electronic signature .....                             | 18        |
| 3.6.2    | Verify Extended Memory Block protection indicator .....     | 18        |
| 3.6.3    | Verify block protection status .....                        | 18        |
| 3.6.4    | Hardware Block Protect .....                                | 19        |
| <b>4</b> | <b>Hardware Protection .....</b>                            | <b>23</b> |
| <b>5</b> | <b>Software Protection .....</b>                            | <b>23</b> |
| 5.1      | Volatile Protection mode .....                              | 24        |
| 5.2      | Non-Volatile Protection mode .....                          | 24        |

|          |                                               |           |
|----------|-----------------------------------------------|-----------|
| 5.2.1    | Non-Volatile Protection bits                  | 24        |
| 5.2.2    | Non-Volatile Protection Bit Lock bit          | 25        |
| 5.3      | Password Protection mode                      | 25        |
| <b>6</b> | <b>Command Interface</b>                      | <b>27</b> |
| 6.1      | Standard commands                             | 27        |
| 6.1.1    | Read/Reset command                            | 27        |
| 6.1.2    | Auto Select command                           | 27        |
| 6.1.3    | Read CFI Query command                        | 28        |
| 6.1.4    | Chip Erase command                            | 28        |
| 6.1.5    | Block Erase command                           | 28        |
| 6.1.6    | Blank Check command                           | 29        |
| 6.1.7    | Erase Suspend command                         | 30        |
| 6.1.8    | Erase Resume command                          | 30        |
| 6.1.9    | Program Suspend command                       | 31        |
| 6.1.10   | Program Resume command                        | 31        |
| 6.1.11   | Program command                               | 31        |
| 6.2      | Fast Program commands                         | 35        |
| 6.2.1    | Write to Buffer Program command               | 35        |
| 6.2.2    | Buffered Program Abort and Reset command      | 38        |
| 6.2.3    | Write to Buffer Program Confirm command       | 39        |
| 6.2.4    | Unlock Bypass command                         | 39        |
| 6.2.5    | Unlock Bypass Program command                 | 39        |
| 6.2.6    | Unlock Bypass Block Erase command             | 39        |
| 6.2.7    | Unlock Bypass Chip Erase command              | 40        |
| 6.2.8    | Unlock Bypass Write to Buffer Program command | 40        |
| 6.2.9    | Unlock Bypass Reset command                   | 40        |
| 6.3      | Protection commands                           | 43        |
| 6.3.1    | Enter Extended Memory Block command           | 43        |
| 6.3.2    | Exit Extended Memory Block command            | 43        |
| 6.3.3    | Lock Register command set                     | 44        |
| 6.3.4    | Password Protection mode command set          | 44        |
| 6.3.5    | Non-Volatile Protection mode command set      | 45        |
| 6.3.6    | NVPB Lock Bit command set                     | 47        |
| 6.3.7    | Volatile Protection mode command set          | 47        |
| 6.3.8    | Exit Protection command set                   | 47        |

|                   |                                             |            |
|-------------------|---------------------------------------------|------------|
| <b>7</b>          | <b>Registers</b>                            | <b>52</b>  |
| 7.1               | Lock Register                               | 52         |
| 7.1.1             | Password Protection Mode Lock bit (DQ2)     | 52         |
| 7.1.2             | Non-Volatile Protection Mode Lock bit (DQ1) | 52         |
| 7.1.3             | Extended Memory Block Protection bit (DQ0)  | 52         |
| 7.2               | Status Register                             | 55         |
| 7.2.1             | Data Polling bit (DQ7)                      | 55         |
| 7.2.2             | Toggle bit (DQ6)                            | 55         |
| 7.2.3             | Error bit (DQ5)                             | 55         |
| 7.2.4             | Erase Timer bit (DQ3)                       | 56         |
| 7.2.5             | Alternative Toggle bit (DQ2)                | 56         |
| 7.2.6             | Buffered Program Abort bit (DQ1)            | 56         |
| <b>8</b>          | <b>Maximum Ratings</b>                      | <b>61</b>  |
| <b>9</b>          | <b>DC and AC Parameters</b>                 | <b>62</b>  |
| <b>10</b>         | <b>Programming and Erase Performance</b>    | <b>77</b>  |
| <b>11</b>         | <b>Package Mechanical Specifications</b>    | <b>78</b>  |
| <b>12</b>         | <b>Ordering Information</b>                 | <b>80</b>  |
| <b>Appendix A</b> | <b>Memory Address Table</b>                 | <b>81</b>  |
| <b>Appendix B</b> | <b>Common Flash Interface (CFI)</b>         | <b>112</b> |
| <b>Appendix C</b> | <b>Extended Memory Block</b>                | <b>116</b> |
| C.1               | Numonyx pre-locked Extended Memory Block    | 116        |
| C.2               | Customer-lockable Extended Memory Block     | 117        |
| <b>Appendix D</b> | <b>Revision History</b>                     | <b>118</b> |

|           |                                                                                            |     |
|-----------|--------------------------------------------------------------------------------------------|-----|
| Table 1.  | Signal Descriptions . . . . .                                                              | 8   |
| Table 2.  | V <sub>PP</sub> /WP# functions . . . . .                                                   | 14  |
| Table 3.  | Bus operations, 8-bit mode . . . . .                                                       | 20  |
| Table 4.  | Bus operations, 16-bit mode . . . . .                                                      | 20  |
| Table 5.  | Read electronic signature - auto select mode - programmer method (8-bit mode) . . . . .    | 21  |
| Table 6.  | Read electronic signature - auto select mode - programmer method (16-bit mode) . . . . .   | 21  |
| Table 7.  | Block protection - auto select mode - programmer method (8-bit mode) . . . . .             | 22  |
| Table 8.  | Block protection - auto select mode - programmer method (16-bit mode) . . . . .            | 22  |
| Table 9.  | Standard commands, 8-bit mode . . . . .                                                    | 33  |
| Table 10. | Standard commands, 16-bit mode . . . . .                                                   | 34  |
| Table 11. | Fast Program commands, 8-bit mode . . . . .                                                | 41  |
| Table 12. | Fast Program commands, 16-bit mode . . . . .                                               | 41  |
| Table 13. | Block Protection commands, 8-bit mode . . . . .                                            | 48  |
| Table 14. | Block Protection commands, 16-bit mode . . . . .                                           | 50  |
| Table 15. | Lock Register bits . . . . .                                                               | 53  |
| Table 16. | Block Protection Status . . . . .                                                          | 53  |
| Table 17. | Status Register bits . . . . .                                                             | 57  |
| Table 18. | Absolute maximum ratings . . . . .                                                         | 61  |
| Table 19. | Operating and AC measurement conditions . . . . .                                          | 62  |
| Table 20. | Power-up wait timings . . . . .                                                            | 63  |
| Table 21. | Device capacitance . . . . .                                                               | 64  |
| Table 22. | DC characteristics . . . . .                                                               | 64  |
| Table 23. | Read AC characteristics . . . . .                                                          | 66  |
| Table 24. | Write AC characteristics, Write Enable Controlled . . . . .                                | 70  |
| Table 25. | Write AC characteristics, Chip Enable Controlled . . . . .                                 | 73  |
| Table 26. | Reset AC characteristics . . . . .                                                         | 74  |
| Table 27. | Accelerated Program and Data Polling/Data Toggle AC characteristics . . . . .              | 76  |
| Table 28. | Programming and Erase Performance . . . . .                                                | 77  |
| Table 29. | TSOP56 – 56 lead thin small-outline package, 14 x 20 mm, package mechanical data . . . . . | 78  |
| Table 30. | Fortified BGA64 11 x 13 mm - 8 x 8 active ball array, package mechanical data . . . . .    | 79  |
| Table 31. | Ordering information scheme . . . . .                                                      | 80  |
| Table 32. | Valid Combinations of M29EW Part Numbers . . . . .                                         | 80  |
| Table 33. | Block Address Table for Discrete Device (Up to 1-Gbit) . . . . .                           | 81  |
| Table 34. | Query structure overview . . . . .                                                         | 112 |
| Table 35. | CFI query identification string . . . . .                                                  | 112 |
| Table 36. | CFI query system interface information . . . . .                                           | 113 |
| Table 37. | Device geometry definition . . . . .                                                       | 114 |
| Table 38. | Primary algorithm-specific extended query table . . . . .                                  | 115 |
| Table 39. | Extended Memory Block address and data . . . . .                                           | 117 |
| Table 40. | Document revision history . . . . .                                                        | 118 |

|            |                                                                                    |    |
|------------|------------------------------------------------------------------------------------|----|
| Figure 1.  | Logic diagram . . . . .                                                            | 8  |
| Figure 2.  | 2-Gbit (1-Gbit/1-Gbit stack) configurations . . . . .                              | 9  |
| Figure 3.  | TSOP connections . . . . .                                                         | 10 |
| Figure 4.  | Fortified BGA connections (top and bottom views). . . . .                          | 11 |
| Figure 5.  | Block addresses . . . . .                                                          | 12 |
| Figure 6.  | Software protection scheme . . . . .                                               | 26 |
| Figure 7.  | Boundary condition of program buffer size . . . . .                                | 36 |
| Figure 8.  | Write to Buffer Program fletcher and pseudo code. . . . .                          | 37 |
| Figure 9.  | NVPB Program/Erase algorithm . . . . .                                             | 46 |
| Figure 10. | Lock Register program flowchart . . . . .                                          | 54 |
| Figure 11. | Data polling flow chart . . . . .                                                  | 58 |
| Figure 12. | Toggle flow chart . . . . .                                                        | 59 |
| Figure 13. | Status Register Polling Flow Chart . . . . .                                       | 60 |
| Figure 14. | AC measurement load circuit . . . . .                                              | 62 |
| Figure 15. | AC measurement I/O waveform . . . . .                                              | 62 |
| Figure 16. | Power-up wait timings. . . . .                                                     | 63 |
| Figure 17. | Random Read AC waveforms (8-bit mode) . . . . .                                    | 65 |
| Figure 18. | Random Read AC waveforms (16-bit mode) . . . . .                                   | 65 |
| Figure 19. | BYTE# Transition AC Waveform . . . . .                                             | 66 |
| Figure 20. | Page Read AC waveforms (16-bit mode). . . . .                                      | 66 |
| Figure 21. | Write Enable Controlled Program waveforms (8-bit mode) . . . . .                   | 67 |
| Figure 22. | Write Enable Controlled Program waveforms (16-bit mode) . . . . .                  | 69 |
| Figure 23. | Chip Enable Controlled Program waveforms (8-bit mode) . . . . .                    | 71 |
| Figure 24. | Chip Enable Controlled Program waveforms (16-bit mode) . . . . .                   | 72 |
| Figure 25. | Chip/Block Erase waveforms (8-bit mode) . . . . .                                  | 73 |
| Figure 26. | Reset AC waveforms (no program/erase in progress) . . . . .                        | 74 |
| Figure 27. | Reset during program/erase operation AC waveforms. . . . .                         | 74 |
| Figure 28. | Accelerated program timing waveforms . . . . .                                     | 75 |
| Figure 29. | Data polling AC waveforms . . . . .                                                | 75 |
| Figure 30. | Toggle/Alternative Toggle bit polling AC waveforms (8-bit mode) . . . . .          | 76 |
| Figure 31. | TSOP56 – 56 lead thin small-outline package, 14 x 20 mm, package outline . . . . . | 78 |
| Figure 32. | Fortified BGA64 11 x 13 mm - 8 x 8 active ball array, package outline . . . . .    | 79 |

# 1 Description

The Numonyx™ Axcell™ M29EW flash memory based on 65nm MLC technology is the world's leading line of parallel NOR flash for embedded applications. It can be read, erased and reprogrammed; and these operations can be performed using a single low voltage (2.7 to 3.6 V) supply. Upon power-up, the memory defaults to its array read mode.

The main memory array is divided into 64-Kword/128-Kbyte uniform blocks that can be erased independently so that valid data can be preserved while old data is purged. Program and Erase commands are written to the command interface of the memory. An on-chip Program/Erase controller simplifies the process of programming or erasing the memory by taking care of all of the special operations that are required to update the memory contents. The end of a program or erase operation can be detected and any error condition can be identified. The command set required to control the memory is consistent with JEDEC standards.

Chip Enable, Output Enable and Write Enable signals control the bus operation of the memory. They allow simple connection to most microprocessors, often without additional logic.

The M29EW supports Asynchronous Random Read and Page Read from all blocks of the memory array. It also features an internal program buffer which improves throughput by programming 512 words via one command sequence.

The M29EW contains a 128-word Extended Memory Block which overlaps addresses with array block 0. The user can program this additional space; then protect it to permanently secure its contents.

The device features different levels of hardware and software protection to secure blocks from unwanted modification (program or erase):

- 1 Hardware protection:
  - The  $V_{PP}/WP\#$  provides a hardware protection of either the highest (M29EWH) or the lowest (M29EWL) block of the main memory array.
- 1 Software protection:
  - Volatile Protection
  - Non-Volatile Protection
  - Password Protection
  - Password Access

The M29EW is offered in TSOP56 (14 x 20 mm) and Fortified BGA64 (11 x 13 mm, 1 mm pitch) packages.


The memories are delivered with all the bits erased (set to '1').

Also see [Appendix B: Common Flash Interface \(CFI\) on page 112](#) and [Table 5: Block addresses on page 12](#) for a full list of the block addresses.

**Table 1. Signal Descriptions**


| Name                                | Description                        | Direction |
|-------------------------------------|------------------------------------|-----------|
| A0-Amax                             | Address inputs                     | Inputs    |
| DQ0-DQ7                             | Data inputs/outputs                | I/O       |
| DQ8-DQ14                            | Data inputs/outputs                | I/O       |
| DQ15/A-1                            | Data input/output or address input | I/O       |
| CE#                                 | Chip Enable                        | Input     |
| OE#                                 | Output Enable                      | Input     |
| WE#                                 | Write Enable                       | Input     |
| RST#                                | Reset                              | Input     |
| RY/BY#                              | Ready/Busy output                  | Output    |
| BYTE#                               | Byte/word organization select      | Input     |
| V <sub>CCQ</sub>                    | Input/output buffer supply voltage | Supply    |
| V <sub>CC</sub>                     | Supply voltage                     | Supply    |
| V <sub>PP</sub> /WP# <sup>(1)</sup> | V <sub>PP</sub> /Write Protect     | Input     |
| V <sub>SS</sub>                     | Ground                             | -         |
| NC                                  | Not connected                      | -         |

1. V<sub>PP</sub>/WP# may be left unconnected as it is internally connected to a pull-up resistor, which enables Program/Erase operations.

**Figure 1. Logic diagram**


1. A23 is valid for 256-Mbit density and above; otherwise, it is RFU.
2. A24 is valid for 512-Mbit density and above; otherwise, it is RFU.
3. A25 is valid for 1-Gbit density and above; otherwise, it is RFU.
4. A26 is valid for 2-Gbit (1-Gbit/1-Gbit stack) density only; otherwise it's RFU.
5. RFU stands for Reserved for Future Use and should be not connect.

Figure 2. 2-Gbit (1-Gbit/1-Gbit stack) configurations




1.  $A_{\max} = V_{IH}$  selects the Upper Die;  $A_{\max} = V_{IL}$  selects the Lower Die.

Figure 3. TSOP connections




1. A-1 is the least significant address bit in x8 mode.
2. A<sub>23</sub> is valid for 256-Mbit density and above; otherwise, it is RFU.
3. A<sub>24</sub> is valid for 512-Mbit density and above; otherwise, it is RFU.
4. A<sub>25</sub> is valid for 1-Gbit density and above; otherwise, it is RFU.
5. A<sub>26</sub> is valid for 2-Gbit (1-Gbit/1-Gbit stack) density only; otherwise it's RFU.
6. RFU stands for Reserved for Future Use and should be not connect.

Figure 4. Fortified BGA connections (top and bottom views)



1. A-1 is the least significant address bit in x8 mode.
2. A23 is valid for 256-Mbit density and above; otherwise, it is RFU.
3. A24 is valid for 512-Mbit density and above; otherwise, it is RFU.
4. A25 is valid for 1-Gbit density and above; otherwise, it is RFU.
5. A26 is valid for 2-Gbit (1-Gbit/1-Gbit stack) density only; otherwise it's RFU.
6. RFU stands for Reserved for Future Use and should be not connect.

Figure 5. Block addresses



## 2 Signal Descriptions

See [Figure 1: Logic diagram](#), and [Table 1: Signal Descriptions](#), for a brief overview of the signals connected to this device.

### 2.1 Address inputs (A0-Amax)

The Address inputs select the cells in the memory array to access during Bus Read operations. During Bus Write operations they control the commands sent to the command interface of the Program/Erase controller.

### 2.2 Data inputs/outputs (DQ0-DQ7)

The Data I/O outputs the data stored at the selected address during a Bus Read operation. During Bus Write operations they represent the commands sent to the command interface of the internal state machine.

### 2.3 Data inputs/outputs (DQ8-DQ14)

The Data I/O outputs the data stored at the selected address during a Bus Read operation when BYTE# is High,  $V_{IH}$ . When BYTE# is Low,  $V_{IL}$ , these pins are not used and are high impedance. During Bus Write operations the Command Register does not use these bits. When reading the Status Register these bits should be ignored.

### 2.4 Data input/output or address input (DQ15/A-1)

When the device operates in x16 bus mode, this pin behaves as a Data input/output pin, together with DQ8-DQ14. When the device operates in x8 bus mode, this pin behaves as the least significant bit of the address. Throughout the text consider references to the Data input/output to include this pin when the device operates in x16 bus mode and references to the Address inputs to include this pin when the device operates in x8 bus mode except when stated explicitly otherwise.

### 2.5 Chip Enable (CE#)

The Chip Enable pin, CE#, activates the memory, allowing Bus Read and Bus Write operations to be performed. When Chip Enable is High,  $V_{IH}$ , all other pins are ignored.

### 2.6 Output Enable (OE#)

The Output Enable pin, OE#, controls the Bus Read operation of the memory.

## 2.7 Write Enable (WE#)

The Write Enable pin, WE#, controls the Bus Write operation of the memory's command interface.

## 2.8 V<sub>PP</sub>/Write Protect (V<sub>PP</sub>/WP#)

The V<sub>PP</sub>/Write Protect pin provides two functions, Write Protect function and the V<sub>PPH</sub> function, which protect the lowest or highest block and allow the memory to enter unlock bypass mode respectively.

The Write Protect function provides a hardware method of protecting the highest or lowest block (see [Section 1: Description](#)). When V<sub>PP</sub>/Write Protect is Low, V<sub>IL</sub>, the highest or lowest block is protected. Program and Erase operations on this block are ignored while V<sub>PP</sub>/Write Protect is Low.

When V<sub>PP</sub>/Write Protect is High, V<sub>IH</sub>, the memory reverts to the previous protection status of the highest or lowest block. Program and Erase operations can now modify the data in this block unless the block is protected using Block protection.

When V<sub>PP</sub>/Write Protect is raised to V<sub>PPH</sub> the memory automatically enters the Unlock Bypass mode (see [Section 6.2.4](#)).

When V<sub>PP</sub>/Write Protect returns to V<sub>IH</sub> or V<sub>IL</sub> normal operation resumes. See the description of the Unlock Bypass command in the command interface section. The transitions from V<sub>IH</sub> to V<sub>PPH</sub> and from V<sub>PPH</sub> to V<sub>IH</sub> must be slower than t<sub>VHVPP</sub> (see [Figure 28: Accelerated program timing waveforms](#)).

Never raise V<sub>PP</sub>/Write Protect to V<sub>PPH</sub> from any mode except Read mode, otherwise the memory may be left in an indeterminate state. A 0.1 μF capacitor should be connected between the V<sub>PP</sub>/Write Protect pin and the V<sub>SS</sub> ground pin to decouple the current surges from the power supply. The PCB track widths must be sufficient to carry the currents required during Unlock Bypass Program (see I<sub>PP1</sub>, I<sub>PP2</sub>, I<sub>PP3</sub>, I<sub>PP4</sub> in [Table 22: DC characteristics](#)).

The V<sub>PP</sub>/Write Protect pin may be left unconnected as it features an internal pull-up resistor.

**Note:** For 2-Gbit (1-Gbit/1-Gbit stack) device, When V<sub>PP</sub>/WP# pin is low, both the highest block and the lowest block are hardware-protected, namely block 0 and block 2047.

Refer to [Table 2](#) for a summary of V<sub>PP</sub>/WP# functions.

**Table 2. V<sub>PP</sub>/WP# functions**

| V <sub>PP</sub> /WP# | Function                                                                                                                              |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| V <sub>IL</sub>      | Highest block protected or lowest block protected. <sup>(1)</sup>                                                                     |
| V <sub>IH</sub>      | Highest and lowest block unprotected unless a software protection is activated (see <a href="#">Section 4: Hardware Protection</a> ). |
| V <sub>PPH</sub>     | Unlock bypass mode.                                                                                                                   |

1. For 2-Gbit (1-Gbit/1-Gbit stack) device, both the highest block and the lowest block are hardware-protected, namely block 0 and block 2047.

## 2.9 Reset (RST#)

The Reset pin can be used to apply a Hardware Reset to the memory. A Hardware Reset is achieved by holding Reset Low,  $V_{IL}$ , for at least  $t_{PLPX}$ . After Reset goes High,  $V_{IH}$ , the memory will be ready for Bus Read and Bus Write operations after  $t_{PHEL}$  or  $t_{RHEL}$ , whichever occurs last. See [Section 2.10: Ready/Busy output \(RY/BY#\)](#), [Table 26: Reset AC characteristics](#), [Figure 26](#) and [Figure 27](#) for more details.

## 2.10 Ready/Busy output (RY/BY#)

The Ready/Busy pin is an open-drain output that can be used to identify when the device is performing a program or erase operation. During program or erase operations Ready/Busy is Low,  $V_{OL}$  (see [Table 17: Status Register bits](#)). Ready/Busy is high-impedance during Read mode, Auto Select mode and Erase Suspend mode.

After a Hardware Reset, Bus Read and Bus Write operations cannot begin until Ready/Busy becomes high-impedance. See [Table 26: Reset AC characteristics](#), [Figure 26](#) and [Figure 27](#).

The use of an open-drain output allows the Ready/Busy pins from several memories to be connected to a single pull-up resistor. A low value will then indicate that one, or more, of the memories is busy. The 10Kohm or bigger resistor is recommended as pull-up resistor to achieve 0.1V  $V_{OL}$ .

## 2.11 Byte/Word organization select (BYTE#)

The BYTE# pin is used to switch between the x8 and x16 Bus modes of the memory. When Byte/Word organization select is Low,  $V_{IL}$ , the memory is in x8 mode, when it is High,  $V_{IH}$ , the memory is in x16 mode.

## 2.12 $V_{CC}$ supply voltage

$V_{CC}$  provides the power supply for all operations (Read, Program and Erase). The command interface is disabled when the  $V_{CC}$  supply voltage is less than the Lockout voltage,  $V_{LKO}$ . This prevents Bus Write operations from accidentally damaging the data during power-up, power-down and power surges. If the Program/Erase controller is programming or erasing during this time then the operation aborts and the memory contents being altered will be invalid.

A 0.1  $\mu F$  capacitor should be connected between the  $V_{CC}$  supply voltage pin and the  $V_{SS}$  ground pin to decouple the current surges from the power supply. The PCB track widths must be sufficient to carry the currents required during program and erase operations (see  $I_{CC1}$ ,  $I_{CC2}$ ,  $I_{CC3}$  in [Table 22: DC characteristics](#)).

## 2.13 $V_{CCQ}$ input/output supply voltage

$V_{CCQ}$  provides the power supply to the I/O pins and enables all outputs to be powered independently from  $V_{CC}$ .

## 2.14 $V_{SS}$ ground

$V_{SS}$  is the reference for all voltage measurements. The device features two  $V_{SS}$  pins; both of which must be connected to the system ground.

## 3 Bus Operations

There are five standard bus operations that control the device. These are Bus Read (Random and Page modes), Bus Write, Output Disable and Standby.

See [Table 3: Bus operations, 8-bit mode](#) and [Table 4: Bus operations, 16-bit mode](#) for a summary. Typical glitches of less than 3ns on Chip Enable, Write Enable, and Reset pins are ignored by the memory and do not affect bus operations.

### 3.1 Bus Read

Bus Read operations read from the memory cells, or specific registers in the command interface. To speed up the read operation the memory array can be read in Page mode where data is internally read and stored in a page buffer. The page has a size of 16 words (or 32bytes) and is addressed by the address inputs A3-A0 in x16 bus mode and A3-A0 plus DQ15/A-1 in x8 bus mode. The page read mode is not supported for reading Extended Memory Blocks and CFI information.

A valid Bus Read operation involves setting the desired address on the Address inputs, applying a Low signal,  $V_{IL}$ , to Chip Enable and Output Enable and keeping Write Enable High,  $V_{IH}$ . The Data inputs/outputs will output the value, see [Figure 17: Random Read AC waveforms \(8-bit mode\)](#), [Figure 20: Page Read AC waveforms \(16-bit mode\)](#), and [Table 23: Read AC characteristics](#), for details of when the output becomes valid.

### 3.2 Bus Write

Bus Write operations write to the command interface. A valid Bus Write operation begins by setting the desired address on the Address inputs. The Address inputs are latched by the command interface on the falling edge of Chip Enable or Write Enable, whichever occurs last. The Data inputs/outputs are latched by the command interface on the rising edge of Chip Enable or Write Enable, whichever occurs first. Output Enable must remain High,  $V_{IH}$ , during the whole Bus Write operation. See [Figure 21](#), and [Figure 22](#), Write AC waveforms, and [Table 24](#) and [Table 25](#), Write AC characteristics, for details of the timing requirements.

### 3.3 Output Disable

The Data inputs/outputs are in the high impedance state when Output Enable is High,  $V_{IH}$ .

### 3.4 Standby

Driving Chip Enable High in Read mode, causes the memory to enter Standby mode and the data inputs/outputs pins are placed in the high-impedance state. To reduce the Supply current to the Standby Supply current,  $I_{CC2}$ , Chip Enable should be held within  $V_{CC} \pm 0.3$  V. For the Standby current level see [Table 22: DC characteristics](#).

During program or erase operations the memory will continue to use the Program/Erase Supply current,  $I_{CC3}$ , for Program or Erase operations until the operation completes.

### 3.5 Reset

During Reset mode the memory is deselected and the outputs are high impedance. The memory is in Reset mode when RST# is at V<sub>IL</sub>. The power consumption is reduced to the standby level, independently from the Chip Enable, Output Enable or Write Enable inputs.

### 3.6 Auto Select mode

The Auto Select mode allows the system or the programming equipment to read the electronic signature, verify the protection status of the Extended Memory Block, and apply/remove Block protection. For example, this mode can be used by programming equipment to automatically match a device and the application code to be programmed.

At power-up, the device is in Read mode, and can then be put in Auto Select mode by issuing the Auto Select command (see [Section 6.1.2](#)).

The device cannot enter Auto Select mode when a program or erase operation is in progress (RY/BY# Low). However, Auto Select mode can be entered if the program or erase operation has been suspended by issuing a Program Suspend or Erase Suspend command (see [Section 6.1.7](#)).

The Auto Select mode is exited by performing a reset. The device is returned to Read mode, except if the Auto Select mode was entered after an Erase Suspend or a Program Suspend command. In this case, it returns to the Erase or Program Suspend mode.

#### 3.6.1 Read electronic signature

The memory has two codes, the manufacturer code and the device code used to identify the memory. These codes can be accessed by performing read operations with control signals and addresses set as shown in [Table 5: Read electronic signature - auto select mode - programmer method \(8-bit mode\)](#) and [Table 6: Read electronic signature - auto select mode - programmer method \(16-bit mode\)](#).

These codes can also be accessed by issuing an Auto Select command (see [Section 6.1.2: Auto Select command](#)).

#### 3.6.2 Verify Extended Memory Block protection indicator

The Extended Memory Block is either Numonyx pre-locked or customer-lockable.

The protection status of the Extended Memory Block (pre-locked or customer-lockable) can be accessed by reading the Extended Memory Block protection indicator. It can be read in Auto Select mode using either the programmer (see [Table 7](#) and [Table 8](#)) or the in-system method (see [Table 9](#) and [Table 10](#)).

The protection status of the Extended Memory Block is then output on bit DQ7 of the Data input/outputs (see [Table 3](#) and [Table 4](#), Bus operations in 8-bit and 16-bit mode).

#### 3.6.3 Verify block protection status

The protection status of a block can be determined by performing a read operation with control signals and addresses set as shown in [Table 7](#) and [Table 8](#).

If the block is protected, then 01h (in x 8 mode) is output on Data input/outputs DQ0-DQ7, otherwise 00h is output.

### 3.6.4 Hardware Block Protect

The  $V_{PP}/WP\#$  pin can be used to protect the highest or lowest block. When  $V_{PP}/WP\#$  is at  $V_{IL}$ , the highest block (M29EWH) or the lowest block (M29EWL) is protected and the other blocks remain with their own protection status.

**Table 3. Bus operations, 8-bit mode**

| Operation <sup>(1)</sup> | CE#             | OE#             | WE#             | RST#            | V <sub>PP</sub> /WP#           | Address Inputs    | Data Inputs/Outputs |                           |
|--------------------------|-----------------|-----------------|-----------------|-----------------|--------------------------------|-------------------|---------------------|---------------------------|
|                          |                 |                 |                 |                 |                                | Amax-A0, DQ15/A-1 | DQ14-DQ8            | DQ7-DQ0                   |
| Bus Read                 | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X                              | Cell address      | Hi-Z                | Data output               |
| Bus Write                | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> <sup>(2)</sup> | Command address   | Hi-Z                | Data input <sup>(3)</sup> |
| Standby                  | V <sub>IH</sub> | X               | X               | V <sub>IH</sub> | V <sub>IH</sub>                | X                 | Hi-Z                | Hi-Z                      |
| Output Disable           | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X                              | X                 | Hi-Z                | Hi-Z                      |
| Reset                    | X               | X               | X               | V <sub>IL</sub> | X                              | X                 | Hi-Z                | Hi-Z                      |

1. X = V<sub>IL</sub> or V<sub>IH</sub>.

2. If WP# is Low, V<sub>IL</sub>, the outermost block remains protected.

3. Data input as required when issuing a command sequence, performing data polling or block protection.

**Table 4. Bus operations, 16-bit mode**

| Operation <sup>(1)</sup> | CE#             | OE#             | WE#             | RST#            | V <sub>PP</sub> /WP#           | Address Inputs  | Data Inputs/Outputs       |
|--------------------------|-----------------|-----------------|-----------------|-----------------|--------------------------------|-----------------|---------------------------|
|                          |                 |                 |                 |                 |                                | Amax-A0         | DQ15/A-1, DQ14-DQ0        |
| Bus Read                 | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X                              | Cell address    | Data output               |
| Bus Write                | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> <sup>(2)</sup> | Command address | Data input <sup>(3)</sup> |
| Standby                  | V <sub>IH</sub> | X               | X               | V <sub>IH</sub> | V <sub>IH</sub>                | X               | Hi-Z                      |
| Output Disable           | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X                              | X               | Hi-Z                      |
| Reset                    | X               | X               | X               | V <sub>IL</sub> | X                              | X               | Hi-Z                      |

1. X = V<sub>IL</sub> or V<sub>IH</sub>.

2. If WP# is Low, V<sub>IL</sub>, the outermost block remains protected.

3. Data input as required when issuing a command sequence, performing data polling or block protection.

**Table 5. Read electronic signature - auto select mode - programmer method (8-bit mode)**

| Read cycle <sup>(1)</sup> | CE#             | OE#             | WE#             | Address inputs  |                 |                 |                 |                 | Data inputs/outputs |          |                                                                  |
|---------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|---------------------|----------|------------------------------------------------------------------|
|                           |                 |                 |                 | Amax-A4         | A3              | A2              | A1              | A0              | DQ15/A-1            | DQ14-DQ8 | DQ7-DQ0                                                          |
| Manufacturer code         | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | X                   | X        | 89h                                                              |
| Device code (cycle 1)     |                 |                 |                 |                 | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | X                   | X        | 7Eh                                                              |
| Device code (cycle 2)     |                 |                 |                 |                 | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IL</sub> | X                   | X        | 22h (256-Mbit)<br>23h (512-Mbit)<br>28h (1-Gbit)<br>48h (2-Gbit) |
| Device code (cycle 3)     |                 |                 |                 |                 | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X                   | X        | 01h                                                              |

1. X = V<sub>IL</sub> or V<sub>IH</sub>.**Table 6. Read electronic signature - auto select mode - programmer method (16-bit mode)**

| Read cycle <sup>(1)</sup> | CE#             | OE#             | WE#             | Address inputs  |                 |                 |                 |                 | Data inputs/outputs                                                      |  |
|---------------------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------------------------------------------------------------------|--|
|                           |                 |                 |                 | Amax-A4         | A3              | A2              | A1              | A0              | DQ15/A-1, DQ14-DQ0                                                       |  |
| Manufacturer code         | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | 0089h                                                                    |  |
| Device code (cycle 1)     |                 |                 |                 |                 | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | 227Eh                                                                    |  |
| Device code (cycle 2)     |                 |                 |                 |                 | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IL</sub> | 2222h (256-Mbit)<br>2223h (512-Mbit)<br>2228h (1-Gbit)<br>2248h (2-Gbit) |  |
| Device code (cycle 3)     |                 |                 |                 |                 | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | V <sub>IH</sub> | 2201h                                                                    |  |

1. X = V<sub>IL</sub> or V<sub>IH</sub>.

**Table 7. Block protection - auto select mode - programmer method (8-bit mode)**

| Operation <sup>(1)</sup>                                    |        | CE#             | OE#             | WE#             | Address inputs  |                 |                 |    | Data inputs/outputs |                                                     |
|-------------------------------------------------------------|--------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|----|---------------------|-----------------------------------------------------|
|                                                             |        |                 |                 |                 | Amax-A16        | A15-A2          | A1              | A0 | DQ15/A-1            | DQ14-DQ8                                            |
| Verify Extended Memory Block protection indicator (bit DQ7) | M29EWL | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | X  | X                   | 89h (Numonyx pre-locked)<br>09h (customer-lockable) |
|                                                             | M29EWH |                 |                 |                 |                 |                 |                 |    |                     | 99h (Numonyx pre-locked)<br>19h (customer-lockable) |
| Verify block protection status                              |        |                 |                 |                 |                 | BBA             |                 |    | V <sub>IL</sub>     |                                                     |

1. X = V<sub>IL</sub> or V<sub>IH</sub>. BBA = Block Base Address.

**Table 8. Block protection - auto select mode - programmer method (16-bit mode)**

| Operation <sup>(1)</sup>                         |        | CE#             | OE#             | WE#             | Address inputs  |                 |                 |                 | Data inputs/outputs                                     |                    |
|--------------------------------------------------|--------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|---------------------------------------------------------|--------------------|
|                                                  |        |                 |                 |                 | Amax-A16        | A15-A2          |                 | A1              | A0                                                      | DQ15/A-1, DQ14-DQ0 |
| Verify Extended Memory Block indicator (bit DQ7) | M29EWL | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IL</sub> | V <sub>IL</sub> | V <sub>IH</sub> | V <sub>IH</sub> | 0089h (Numonyx pre-locked)<br>0009h (customer-lockable) |                    |
|                                                  | M29EWH |                 |                 |                 |                 |                 |                 |                 | 0099h (Numonyx pre-locked)<br>0019h (customer-lockable) |                    |
| Verify block protection status                   |        |                 |                 |                 |                 |                 |                 |                 |                                                         | BBA                |

1. X = V<sub>IL</sub> or V<sub>IH</sub>. BBA = Block Base Address.

## 4 Hardware Protection

The M29EW features a  $V_{PP}/WP\#$  pin that protects the highest or lowest block. Refer to [Section 2: Signal Descriptions](#) for a detailed description of the signal.

## 5 Software Protection

The M29EW has four different software protection modes:

- Volatile Protection
- Non-Volatile Protection
- Password Protection
- Password Access

On first use all parts default to operate in non-volatile Protection mode and the customer is free to activate the non-volatile or the password protection mode.

The desired protection mode is activated by setting either the one-time programmable Non-Volatile Protection Mode Lock bit, or the Password Protection Mode Lock bit of the Lock Register (see [Section 7.1: Lock Register](#)). Programming the Non-Volatile Protection Mode Lock bit or the Password Protection Mode Lock bit, to '0' will permanently activate the Non-volatile or the Password Protection mode, respectively. These two bits are one-time programmable and non-volatile: once the protection mode has been programmed, it cannot be changed and the device will permanently operate in the selected protection mode. It is recommended to activate the desired software protection mode when first programming the device.

The Non-volatile and Password Protection modes both provide non-volatile Protection. Volatilely protected blocks and non-volatilely protected blocks can co-exist within the memory array. However, the volatile Protection only control the protection scheme for blocks that are not protected using the non-volatile or password protection.

If the user attempts to program or erase a protected block, the device ignores the command and returns to read mode.

The device is shipped with all blocks unprotected. The block protection status can be read either by performing a read electronic signature (see [Table 5](#) and [Table 6](#)) or by issuing an Auto Select command (see [Table 16: Block Protection Status](#)).

For the lowest and highest blocks, an even higher level of block protection can be achieved by locking the blocks using the non-volatile Protection and then by holding the  $V_{PP}/WP\#$  pin Low.

Password Access is a security enhancement offered on the M29EW device. This feature protects information stored in the main-array blocks by preventing content alteration or reads until a valid 64-bit password is received. Password Access may be combined with Non-Volatile and/or Volatile Protection to create a multi-tiered solution.

Please contact your Numonyx Sales for further details concerning Password Access feature.

## 5.1 Volatile Protection mode

The volatile Protection allows the software application to easily protect blocks against inadvertent change. However, the protection can be easily disabled when changes are needed. Volatile Protection bits, VPBs, are volatile and unique for each block and can be individually modified. VPBs only control the protection scheme for unprotected blocks that have their non-volatile Protection bits, NVPBs, cleared (erased to '1') (see [Section 5.2: Non-Volatile Protection mode](#) and [Section 6.3.5: Non-Volatile Protection mode command set](#)).

By issuing the VPB Program or VPB Clear commands, the VPBs are set (programmed to '0') or cleared (erased to '1'), thus placing associated blocks in the protected or unprotected state respectively. The VPBs can be set (programmed to '0') or cleared (erased to '1') as often as needed.

When the parts are first shipped, or after a power-up or hardware reset, the VPBs default to be cleared.

Refer to [Section 6.3.7](#) for a description of the volatile Protection mode command set.

## 5.2 Non-Volatile Protection mode

### 5.2.1 Non-Volatile Protection bits

A non-volatile Protection bit (NVPB) is assigned to each block.

When a NVPB is set to '0', the associated block is protected, preventing any program or erase operations in this block.

The NVPB bits can be set individually by issuing a NVPB Program command. They are non-volatile and will remain set through a hardware reset or a power-down/power-up sequence.

The NVPBs cannot be cleared individually, they can only be all cleared at the same time by issuing a Clear all Non-Volatile Protection bits command.

The NVPBs can be protected all at a time by setting a volatile bit, the NVPB Lock bit (see [Section 5.2.2: Non-Volatile Protection Bit Lock bit](#)).

If one of the non-volatile protected blocks needs to be unprotected (corresponding NVPB set to '1'), a few more steps are required:

1. First, the NVPB Lock bit must be '1' by either putting the device through a power cycle, or hardware reset.
2. The NVPBs can then be changed to reflect the desired settings.
3. The NVPB Lock bit must be set to '0' once again to lock the NVPBs by associated command. The device operates normally again.

- Note:*
- 1 To achieve the best protection, it is recommended to execute the NVPB Lock Bit Program command early in the boot code and to protect the boot code by holding  $V_{PP}/WP\#$  Low,  $V_{IL}$ .
  - 2 The NVPBs and VPBs have the same function when  $V_{PP}/WP\#$  pin is High,  $V_{IH}$ , as they do when  $V_{PP}/WP\#$  pin is at the voltage for program acceleration ( $V_{PPH}$ ).

Refer to [Table 16: Block Protection Status](#) and [Figure 6: Software protection scheme](#) for details on the block protection mechanism, and to [Section 6.3.5](#) for a description of the Non-Volatile Protection mode command set.

## 5.2.2 Non-Volatile Protection Bit Lock bit

The Non-Volatile Protection Bit Lock bit (NVPB Lock bit) is a global volatile bit for all NVPBs.

When set (programmed to '0'), it prevents changing the state of the NVPBs. When reset to '1', the NVPBs can be set and reset using the NVPB Program command and Clear all NVPBs command, respectively.

There is only one NVPB Lock bit per device.

Refer to [Section 6.3.6](#) for a description of the NVPB Lock bit command set.

- Note:**
- 1 *No software command unlocks this bit unless the device is in password protection mode; in standard non-volatile Protection mode, it can be cleared only by taking the device through a hardware reset or a power-up.*
  - 2 *The NVPB Lock bit must be set (programmed to '0') only after all NVPBs are configured to the desired settings.*

## 5.3 Password Protection mode

The password protection mode provides an even higher level of security than the Non-Volatile Protection mode by requiring a 64-bit password for unlocking the device NVPB Lock bit.

In addition to this password requirement, the NVPB Lock bit is set '0' after power-up and reset to maintain the device in password protection mode. Successful execution of the Password Unlock command by entering the correct password clears the NVPB Lock bit, allowing for block NVPBs to be modified.


If the password provided is incorrect, the NVPB Lock bit remains locked and the state of the NVPBs cannot be modified.

To place the device in password protection mode, the following steps are required:

1. Prior to activating the password protection mode, it is necessary to set a 64-bit password and to verify it (see [Password Program command](#) and [Password Read command](#)). Password verification is only allowed before the password protection mode is activated.
2. The password protection mode is then activated by programming the Password Protection Mode Lock bit to '0'. This operation is not reversible and once the bit is programmed it cannot be erased, the device permanently remains in password protection mode, and the 64-bit password can neither be retrieved nor reprogrammed. Moreover, all commands to the address where the password is stored, are disabled. Refer to [Table 16: Block Protection Status](#) and [Figure 6: Software protection scheme](#) for details on the block protection scheme.

Refer to [Section 6.3.4](#) for a description of the Password Protection mode command set.

- Note:**
- There is no means to verify the password after Password Protection mode is enabled. If the password is lost after enabling the Password Protection mode, there is no way to clear the NVPB Lock bit.*

**Figure 6. Software protection scheme**

1. NVPBs default to '1' (block unprotected) when shipped from Numonyx. A block is protected or unprotected when its NVPB is set to '0' and '1', respectively. NVPBs are programmed individually and cleared collectively.
2. VPB default status depends on ordering option. A block is protected or unprotected when its VPB is set to '0' and '1', respectively. VPBs can be programmed and cleared individually.
3. The NVPB Lock bit is volatile and default to '1' (NVPB bits unlocked) after power-up or hardware reset. NVPB bits are locked by setting the NVPB Lock bit to '0'. Once programmed to '0', the NVPB Lock bit can only be reset to '1' by taking the device through a power-up or hardware reset.

## 6 Command Interface

All Bus Write operations to the memory are interpreted by the command interface. Commands consist of one or more sequential Bus Write operations. Failure to observe a valid sequence of Bus Write operations will result in the memory returning to Read mode. The long command sequences are imposed to maximize data security.

The address used for the commands changes depending on whether the memory is in 16-bit or 8-bit mode.

*Note:* For 2-Gbit (1-Gbit/1-Gbit) device, all the set-up command should be re-issued to the device when different die is selected.

### 6.1 Standard commands

See either [Table 9](#), or [Table 10](#), depending on the configuration that is being used, for a summary of the standard commands.

#### 6.1.1 Read/Reset command

The device enters read mode of main array memory after a reset or power-up sequence.

The Read/Reset command returns the memory to Read mode. It also resets the errors in the Status Register. Either one or three Bus Write operations can be used to issue the Read/Reset command.

The Read/Reset command can be issued, between Bus Write cycles before the start of a program or erase operation, to return the device to Read mode. If the Read/Reset command is issued during the time-out of a Block erase operation, the memory will take up to 10  $\mu$ s to abort. During the abort period no valid data can be read from the memory.

The Read/Reset command will not abort an Erase operation when issued while in Erase Suspend.

#### 6.1.2 Auto Select command

The Auto Select command puts the device in Auto Select mode, once in Auto Select mode, the system can read the manufacturer code, the device code, the protection status of each block (Block Protection status) and the Extended Memory Block protection indicator.

Three consecutive Bus Write operations are required to issue the Auto Select command. Once the Auto Select command is issued Bus Read operations to specific addresses output the manufacturer code, the device code, the Extended Memory Block protection indicator and a block protection status (see [Table 9](#) and [Table 10](#) in conjunction with [Table 5](#), [Table 6](#), [Table 7](#), and [Table 8](#)). The memory remains in Auto Select mode until a Read/Reset or CFI Query command is issued.

### 6.1.3 Read CFI Query command

The memory contains an information area, named CFI data structure, which contains a description of various electrical and timing parameters, density information and functions supported by the memory. See [Appendix B](#), [Table 34](#), [Table 35](#), [Table 36](#), [Table 37](#) and [Table 38](#) for details on the information contained in the Common Flash Interface (CFI) memory area.

The Read CFI Query command is used to put the memory in Read CFI Query mode. Once in Read CFI Query mode, Bus Read operations to the memory will output data from the Common Flash Interface (CFI) memory area. One Bus Write cycle is required to issue the Read CFI Query command. This command is valid only when the device is in the Read Array or Auto Select mode.

The Read/Reset command must be issued to return the device to the previous mode (the Read Array mode or Auto Select mode). A second Read/Reset command is required to put the device in Read Array mode from Auto Select mode.

### 6.1.4 Chip Erase command

The Chip Erase command can be used to erase the entire chip. Six Bus Write operations are required to issue the Chip Erase command and start the Program/Erase controller.

If some block are protected, then these are ignored and all the other blocks are erased. If all of the blocks are protected the Chip Erase operation appears to start but will terminate within about 100  $\mu$ s, leaving the data unchanged. No error condition is given when protected blocks are ignored.

During the Erase operation the memory will ignore all commands, including the Erase Suspend command. It is not possible to issue any command to abort the operation. Typical Chip Erase times are given in [Table 28](#). All Bus Read operations during the Chip Erase operation will output the Status Register on the Data inputs/outputs. See [Section 7.2: Status Register](#) for more details.

After the Chip Erase operation has completed the memory will return to the Read mode, unless an error has occurred. When an error occurs the memory will continue to output the Status Register. A Read/Reset command must be issued to reset the error condition and return to Read mode.

The Chip Erase command sets all of the bits in unprotected blocks of the memory to '1'. All previous data is lost.

The Chip Erase operation is aborted by performing a reset or powering down the device. In this case, data integrity cannot be ensured, and it is recommended to erase again the entire chip.

### 6.1.5 Block Erase command

The Block Erase command can be used to erase a list of one or more blocks. It sets all of the bits in the unprotected selected blocks to '1'. All previous data in the selected blocks is lost.

Six Bus Write operations are required to select the first block in the list. Each additional block in the list can be selected by repeating the sixth Bus Write operation using the address of the additional block. After the command sequence is written, a Block Erase time-out occurs. During the time-out period, additional sector addresses and sector erase commands may be written. Once the Program/Erase controller has started, it is not possible to select

any more blocks. Each additional block must therefore be selected within the time-out period of the last block. The time-out timer restarts when an additional block is selected. After the sixth Bus Write operation, a Bus Read operation outputs the Status Register. See [Figure 21: Write Enable Controlled Program waveforms \(8-bit mode\)](#) and [Figure 22: Write Enable Controlled Program waveforms \(16-bit mode\)](#) for details on how to identify if the Program/Erase controller has started the Block Erase operation.

After the Block Erase operation has completed, the memory returns to the Read mode, unless an error has occurred. When an error occurs, Bus Read operations will continue to output the Status Register. A Read/Reset command must be issued to reset the error condition and return to Read mode.

If any selected blocks are protected then these are ignored and all the other selected blocks are erased. If all of the selected blocks are protected the Block Erase operation appears to start but will terminate within about 100  $\mu$ s, leaving the data unchanged. No error condition is given when protected blocks are ignored.

During the Block Erase operation the memory ignores all commands except the Erase Suspend command and the Read/Reset command which is only accepted during the time-out period. Typical Block Erase time and Block Erase time-out are given in [Table 28: Programming and Erase Performance](#).

The Block Erase operation is aborted by performing a reset or powering down the device. In this case, data integrity cannot be ensured, and it is recommended to erase again the blocks aborted.

### 6.1.6 Blank Check command

The Blank Check operation determines whether a specified block is blank (i.e. completely erased). Without Blank Check, Block Erase would be the only other way to ensure a block is completely erased. Blank Check can be used to determine whether or not a prior erase operation was successful; this includes erase operations that may have been interrupted by power-loss. The Blank Check operation checks for cells that are programmed as well as cells that are over-erased. If any cells are programmed or over-erased, Blank Check will return a failure status, indicating that the block is not blank. If a Blank Check operation returns a passing status, the block is guaranteed blank (all 1's) and ready to program. The erase algorithm will do Blank Check for the target block firstly. If it's blank (all 1's) then the actual erase operation will be skipped. Otherwise, the actual erase operation will continue. This could benefit the overall cycle performance when erase happens on a blank block.

Blank check can occur in only one block at a time, and no operations other than Status Register Reads are allowed during Blank Check (e.g. reading array data, program, erase etc). Blank Check is not supported during any suspended operations. The status register can be examined for Blank Check progress and errors by reading any address within the device.

After the Blank Check operation has completed the memory will return to the Read mode, unless an error has occurred. When an error occurs, Bus Read operations to the memory continue to output the Status Register. A Read/Reset command must be issued to reset the error condition and return to Read mode.

### 6.1.7 Erase Suspend command

The Erase Suspend command can be used to temporarily suspend a Block Erase operation. One Bus Write operation is required to issue the command together with the block address.

After the command sequence is written, a minimum Block Erase time-out occurs (see [Section 6.1.7: Erase Suspend command](#)). During the time-out period, additional block addresses and block erase commands can be written.

The Program/Erase controller suspends the erase operation within the Erase Suspend Latency time of the Erase Suspend command being issued. However, when the Erase Suspend command is written during the Block Erase time-out, the device immediately terminates the time-out period and suspends the erase operation.

Once the Program/Erase controller has stopped, the memory operates in Read mode and the Erase is suspended.

During Erase Suspend it is possible to read and execute Program or Write to Buffer Program operations in blocks that are not suspended; both read and program operations behave as normal on these blocks. Reading from blocks that are suspended will output the Status Register. If any attempt is made to program in a protected block or in the suspended block then the Program command is ignored and the data remains unchanged. In this case the Status Register is not read and no error condition is given.

It is also possible to issue the Auto Select, Read CFI Query and Unlock Bypass commands during an Erase Suspend. The Read/Reset command must be issued to return the device to Read Array mode before the Resume command will be accepted.

During Erase Suspend a Bus Read operation to the Extended Memory Block will output the Extended Memory Block data. Once in the Extended Memory Block mode, the Exit Extended Memory Block command must be issued before the erase operation can be resumed.

The Erase Suspend command is ignored if written during Chip Erase operations.

Refer to [Table 28: Programming and Erase Performance](#) for the values of Block Erase time-out and Block Erase Suspend latency time.

If the Erase Suspend operation is aborted by performing a reset or powering down the device, data integrity cannot be ensured, and it is recommended to erase again the blocks suspended.

### 6.1.8 Erase Resume command

The Erase Resume command is used to restart the Program/Erase controller after an Erase Suspend.

The device must be in Read Array mode before the Resume command will be accepted. An erase can be suspended and resumed more than once.

### 6.1.9 Program Suspend command

The Program Suspend command allows the system to interrupt a program operation so that data can be read from any block. When the Program Suspend command is issued during a program operation, the device suspends the program operation within the Program Suspend latency time (see [Table 28: Programming and Erase Performance](#)) and updates the Status Register bits.

After the program operation has been suspended, the system can read array data from any address. However, data read from program-suspended addresses is not valid.

The Program Suspend command may also be issued during a program operation while an erase is suspended. In this case, data may be read from any addresses not in Erase Suspend or Program Suspend. If a read is needed from the Extended Memory Block area (one-time program area), the user must use the proper command sequences to enter and exit this region.

The system may also issue the Auto Select command sequence when the device is in the Program Suspend mode. The system can read as many Auto Select codes as required. When the device exits the Auto Select mode, the device reverts to the Program Suspend mode, and is ready for another valid operation. See Auto Select command sequence for more information.

If the Program Suspend operation is aborted by performing a reset or powering down the device, data integrity cannot be ensured, and it is recommended to program again the words or bytes aborted.

### 6.1.10 Program Resume command

After the Program Resume command is issued, the device reverts to programming. The controller can determine the status of the program operation using the DQ7 or DQ6 status bits, just as in the standard program operation. Refer to [Figure 21: Write Enable Controlled Program waveforms \(8-bit mode\)](#) and [Figure 22: Write Enable Controlled Program waveforms \(16-bit mode\)](#) for details.

The system must issue a Program Resume command, to exit the Program Suspend mode and to continue the programming operation.

Further issuing of the Resume command is ignored. Another Program Suspend command can be written after the device has resumed programming.

### 6.1.11 Program command

The Program command can be used to program a value to one address in the memory array at a time. The command requires four Bus Write operations, the final write operation latches the address and data in the internal state machine and starts the Program/Erase controller.

Programming can be suspended and then resumed by issuing a Program Suspend command and a Program Resume command, respectively (see [Section 6.1.9: Program Suspend command](#) and [Section 6.1.10: Program Resume command](#)).

If the address falls in a protected block then the Program command is ignored, the data remains unchanged. The Status Register is never read and no error condition is given.

After programming has started, Bus Read operations output the Status Register content. See [Figure 21: Write Enable Controlled Program waveforms \(8-bit mode\)](#) and [Figure 22:](#)

[Write Enable Controlled Program waveforms \(16-bit mode\)](#) for more details. Typical program times are given in [Table 28: Programming and Erase Performance](#).

After the program operation has completed the memory will return to the Read mode, unless an error has occurred. When an error occurs, Bus Read operations to the memory continue to output the Status Register. A Read/Reset command must be issued to reset the error condition and return to Read mode.

One of the Erase commands must be used to set all the bits in a block or in the whole memory from '0' to '1'.

The Program operation is aborted by performing a reset or powering-down the device. In this case data integrity cannot be ensured, and it is recommended to reprogram the word or byte aborted.

Table 9. Standard commands, 8-bit mode

| Command                      |                                            | Length | Bus operations <sup>(1)</sup> |      |     |      |     |      |        |        |     |      |     |      |
|------------------------------|--------------------------------------------|--------|-------------------------------|------|-----|------|-----|------|--------|--------|-----|------|-----|------|
|                              |                                            |        | 1st                           |      | 2nd |      | 3rd |      | 4th    |        | 5th |      | 6th |      |
|                              |                                            |        | Add                           | Data | Add | Data | Add | Data | Add    | Data   | Add | Data | Add | Data |
| Read/Reset                   |                                            | 1      | X                             | F0   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
|                              |                                            | 3      | AAA                           | AA   | 555 | 55   | X   | F0   | -      | -      | -   | -    | -   | -    |
| Auto Select                  | Manufacturer code                          | 3      | AAA                           | AA   | 555 | 55   | AAA | 90   | (2)(3) | (2)(3) | -   | -    | -   | -    |
|                              | Device code                                |        |                               |      |     |      |     |      |        |        |     |      |     |      |
|                              | Extended Memory Block protection indicator |        |                               |      |     |      |     |      |        |        |     |      |     |      |
|                              | Block protection status                    |        |                               |      |     |      |     |      |        |        |     |      |     |      |
| Program <sup>(4)</sup>       |                                            | 4      | AAA                           | AA   | 555 | 55   | AAA | A0   | PA     | PD     | -   | -    | -   | -    |
| Chip Erase                   |                                            | 6      | AAA                           | AA   | 555 | 55   | AAA | 80   | AAA    | AA     | 555 | 55   | AAA | 10   |
| Block Erase                  |                                            | 6+     | AAA                           | AA   | 555 | 55   | AAA | 80   | AAA    | AA     | 555 | 55   | BAd | 30   |
| Erase/Program Suspend        |                                            | 1      | X                             | B0   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Erase/Program Resume         |                                            | 1      | X                             | 30   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Read CFI Query               |                                            | 1      | AA                            | 98   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Blank Check setup            |                                            | 6      | AAA                           | AA   | 555 | 55   | BAd | EB   | BAd    | 76     | BAd | 00   | BAd | 00   |
| Blank Check confirm and read |                                            | 2      | BAd                           | 29   | BAd | (2)  | -   | -    | -      | -      | -   | -    | -   | -    |

1. X = Don't care, PA = Program Address, PD = Program Data, BAd = Any address in the Block. All values in the table are in hexadecimal.

2. These cells represent Read cycles. The other cells are Write cycles.

3. The Auto Select addresses and data are given in [Table 5: Read electronic signature - auto select mode - programmer method \(8-bit mode\)](#), and [Table 7: Block protection - auto select mode - programmer method \(8-bit mode\)](#), except for A9 that is 'Don't care'.

4. In Unlock Bypass, the first two unlock cycles are no more needed (see [Table 11: Fast Program commands, 8-bit mode](#) and [Table 12: Fast Program commands, 16-bit mode](#)).

Table 10. Standard commands, 16-bit mode

| Command                      |                                            | Length | Bus operations <sup>(1)</sup> |      |     |      |     |      |        |        |     |      |     |      |
|------------------------------|--------------------------------------------|--------|-------------------------------|------|-----|------|-----|------|--------|--------|-----|------|-----|------|
|                              |                                            |        | 1st                           |      | 2nd |      | 3rd |      | 4th    |        | 5th |      | 6th |      |
|                              |                                            |        | Add                           | Data | Add | Data | Add | Data | Add    | Data   | Add | Data | Add | Data |
| Read/Reset                   |                                            | 1      | X                             | F0   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
|                              |                                            | 3      | 555                           | AA   | 2AA | 55   | X   | F0   | -      | -      | -   | -    | -   | -    |
| Auto Select                  | Manufacturer code                          | 3      | 555                           | AA   | 2AA | 55   | 555 | 90   | (2)(3) | (2)(3) | -   | -    | -   | -    |
|                              | Device code                                |        |                               |      |     |      |     |      |        |        |     |      |     |      |
|                              | Extended Memory Block protection indicator |        |                               |      |     |      |     |      |        |        |     |      |     |      |
|                              | Block protection status                    |        |                               |      |     |      |     |      |        |        |     |      |     |      |
| Program <sup>(4)</sup>       |                                            | 4      | 555                           | AA   | 2AA | 55   | 555 | A0   | PA     | PD     | -   | -    | -   | -    |
| Chip Erase                   |                                            | 6      | 555                           | AA   | 2AA | 55   | 555 | 80   | 555    | AA     | 2AA | 55   | 555 | 10   |
| Block Erase                  |                                            | 6+     | 555                           | AA   | 2AA | 55   | 555 | 80   | 555    | AA     | 2AA | 55   | BAd | 30   |
| Erase/Program Suspend        |                                            | 1      | X                             | B0   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Erase/Program Resume         |                                            | 1      | X                             | 30   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Read CFI Query               |                                            | 1      | 55                            | 98   | -   | -    | -   | -    | -      | -      | -   | -    | -   | -    |
| Blank Check setup            |                                            | 6      | 555                           | AA   | 2AA | 55   | BAd | EB   | BAd    | 76     | BAd | 00   | BAd | 00   |
| Blank Check confirm and read |                                            | 2      | BAd                           | 29   | BAd | (2)  | -   | -    | -      | -      | -   | -    | -   | -    |

1. X = Don't care, PA = Program Address, PD = Program Data, BAd = any address in the Block. All values in the table are in hexadecimal.
2. These cells represent Read cycles. The other cells are Write cycles.
3. The Auto Select addresses and data are given in [Table 6: Read electronic signature - auto select mode - programmer method \(16-bit mode\)](#), and [Table 8: Block protection - auto select mode - programmer method \(16-bit mode\)](#), except for A9 that is 'Don't care'.
4. In Unlock Bypass, the first two unlock cycles are no more needed (see [Table 11](#) and [Table 12](#) Fast Program commands, 8-bit and 16-bit mode).

## 6.2 Fast Program commands

The M29EW offers a set of Fast Program commands to improve the programming throughput:

- Write to Buffer Program
- Unlock Bypass

See either [Table 11: Fast Program commands, 8-bit mode on page 41](#) or [Table 12: Fast Program commands, 16-bit mode on page 41](#) depending on the configuration that is being used, for a summary of the Fast Program commands.

When  $V_{PPH}$  is applied to the  $V_{PP}$ /Write Protect pin the memory automatically enters Unlock Bypass mode (see [Section 6.2.4: Unlock Bypass command](#)).

After programming has started, Bus Read operations in the memory output the Status Register content. Write to Buffer Program command can be suspended and then resumed by issuing a Program Suspend command and a Program Resume command, respectively (see [Section 6.1.9: Program Suspend command](#) and [Section 6.1.10: Program Resume command](#)).

After the fast program operation has completed, the memory will return to the Read mode, unless an error has occurred. When an error occurs Bus Read operations to the memory will continue to output the Status Register. A Read/Reset command must be issued to reset the error condition and return to Read mode. One of the Erase commands must be used to set all the bits in a block or in the whole memory from '0' to '1'.

Typical program times are given in [Table 28: Programming and Erase Performance](#).

### 6.2.1 Write to Buffer Program command

The Write to Buffer Program command makes use of the device's 512-word program buffer to speed up programming. A maximum of 512 words can be loaded into the program buffer. The Write to Buffer Program command dramatically reduces system programming time compared to the standard non-buffered Program command.

When issuing a Write to Buffer Program command, the  $V_{PP}/WP\#$  pin can be either held High,  $V_{IH}$ , or raised to  $V_{PPH}$ .

See [Table 28](#) for details on typical Write to Buffer Program times in both cases.

Five successive steps are required to issue the Write to Buffer Program command:

1. The Write to Buffer Program command starts with two unlock cycles.
2. The third Bus Write cycle sets up the Write to Buffer Program command. The set-up code can be addressed to any location within the targeted block.
3. The fourth Bus Write cycle sets up the number of words/bytes to be programmed. Value N is written to the same block address, where N+1 is the number of words/bytes to be programmed. N+1 must not exceed the size of the program buffer or the operation will abort.
4. The fifth cycle loads the first address and data to be programmed.
5. Use N Bus Write cycles to load the address and data for each word/byte into the program buffer. Addresses must lie within the range from the start address+1 to the start address + N-1. Optimum programming performance and lower power usage are obtained by aligning the starting address at the beginning of a 512-word boundary ( $A[8:0] = 0x000h$ ). Any buffer size smaller than 512-word is allowed within 512-word boundary, while All the addresses used in the Write to Buffer Program operation must

lie within the 512-word boundary. In addition, any crossing boundary buffer program will result in a program abort. See [Figure 7](#) for details of the available program buffer size.

To program the content of the program buffer, this command must be followed by a Write to Buffer Program Confirm command.

If an address is written several times during a Write to Buffer Program operation, the address/data counter will be decremented at each data load operation and the data will be programmed to the last word loaded into the buffer.

Invalid address combinations or failing to follow the correct sequence of Bus Write cycles will abort the Write to Buffer Program.

The Status Register bits DQ1, DQ5, DQ6, DQ7 can be used to monitor the device status during a Write to Buffer Program operation.

It is possible to detect Program operation fails when changing programmed data from '0' to '1', that is when reprogramming data in a portion of memory already programmed. The resulting data will be the logical OR between the previous value and the current value.

See [Figure 8: Write to Buffer Program fletcher and pseudo code](#), for a suggested flow chart on using the Write to Buffer Program command.

**Figure 7. Boundary condition of program buffer size**





Figure 8. Write to Buffer Program fletcher and pseudo code



1.  $n+1$  is the number of addresses to be programmed.
2. A Write to Buffer Program Abort and Reset must be issued to return the device in Read mode.
3. When the block address is specified, any address in the selected block address space is acceptable. However when

loading program buffer address with data, all addresses must fall within the selected program buffer page.

4. DQ7 must be checked since DQ5 and DQ7 may change simultaneously.
5. If this flow chart location is reached because DQ5='1', then the Write to Buffer Program command failed. If this flow chart location is reached because DQ1='1', then the Write to Buffer Program command aborted. In both cases, the appropriate reset command must be issued to return the device in Read mode: a Reset command if the operation failed, a Write to Buffer Program Abort and Reset command if the operation aborted.
6. See [Table 9](#) and [Table 10](#), for details on Write to Buffer Program command sequence.

## 6.2.2 Buffered Program Abort and Reset command

A Buffered Program Abort and Reset command must be issued to abort the Buffer Program operation and reset the device in Read mode.

The buffer programming sequence can be aborted in the following ways:

- Load a value that is greater than the page buffer size during the number of locations to program step in the Write to Buffer Program command.
- Write to an address in a block different than the one specified during the write-buffer-load command.
- Write an address/data pair to a different write-buffer-page than the one selected by the starting address during the program buffer data loading stage of the operation.
- Write data other than the Confirm command after the specified number of data load cycles.

The abort condition is indicated by DQ1 = 1, DQ7 =  $\overline{\text{DQ7}}$  (for the last address location loaded), DQ6 = toggle, and DQ5 = 0 (all of which are Status Register bits). A Buffered Program Abort and Reset command sequence must be written to reset the device for the next operation. Note that the full 3-cycle Buffered Program Abort and Reset command sequence is required when using Buffer Programming features in Unlock Bypass mode.

### 6.2.3 Write to Buffer Program Confirm command

The Write to Buffer Program Confirm command is used to confirm a Write to Buffer Program command and to program the N+1 words/bytes loaded in the program buffer by this command.

### 6.2.4 Unlock Bypass command

The Unlock Bypass command is used to place the device in Unlock Bypass mode. When the device enters the Unlock Bypass mode, the two initial unlock cycles required in the standard program command sequence are no more needed, and only two write cycles are required to program data, instead of the normal four cycles (see [Note 4](#) below [Table 9](#) and [Table 10](#)). This results in a faster total programming time.

Unlock Bypass command is consequently used in conjunction with the Unlock Bypass Program command to program the memory faster than with the standard program commands. When the cycle time to the device is long, considerable time saving can be made by using these commands. Three Bus Write operations are required to issue the Unlock Bypass command.

When in Unlock Bypass mode, only the Unlock Bypass Program, Unlock Bypass Block Erase, Unlock Bypass Chip Erase, and Unlock Bypass Reset commands are valid:

- The Unlock Bypass Program command can be issued to program addresses within the memory.
- The Unlock Bypass Block Erase command can then be issued to erase one or more memory blocks.
- The Unlock Bypass Chip Erase command can be issued to erase the whole memory array.
- The Unlock Bypass Write to Buffer Program command can be issued to speed up programming operation.
- The Unlock Bypass Reset command can be issued to return the memory to Read mode.

In Unlock Bypass mode the memory can be read as if in Read mode.

### 6.2.5 Unlock Bypass Program command

The Unlock Bypass Program command can be used to program one address in the memory array at a time. The command requires two Bus Write operations, the final write operation latches the address and data and starts the Program/Erase controller.

The Program operation using the Unlock Bypass Program command behaves identically to the Program operation using the Program command. The operation cannot be aborted, a Bus Read operation to the memory outputs the Status Register. See the program command in [Table 11.: Fast Program commands, 8-bit mode](#) and [Table 12.: Fast Program commands, 16-bit mode](#) for more details.

### 6.2.6 Unlock Bypass Block Erase command

The Unlock Bypass Block Erase command can be used to Erase one or more memory blocks at a time. The command requires two Bus Write operations instead of six using the standard Block Erase command. The final Bus Write operation latches the address of the block and starts the Program/Erase controller.

To erase multiple block (after the first two Bus Write operations have selected the first block in the list), each additional block in the list can be selected by repeating the second Bus Write operation using the address of the additional block.

The Unlock Bypass Block Erase command behaves in the same way as the Block Erase command: the operation cannot be aborted, and a Bus Read operation to the memory outputs the Status Register (see [Section 6.1.5: Block Erase command](#) for details).

### 6.2.7 Unlock Bypass Chip Erase command

The Unlock Bypass Chip Erase command can be used to erase all memory blocks at a time. The command requires two Bus Write operations only instead of six using the standard Chip Erase command. The final Bus Write operation starts the Program/Erase controller.

The Unlock Bypass Chip Erase command behaves in the same way as the Chip Erase command: the operation cannot be aborted, and a Bus Read operation to the memory outputs the Status Register (see [Section 6.1.4: Chip Erase command](#) for details).

### 6.2.8 Unlock Bypass Write to Buffer Program command

The Unlock Bypass Write to Buffer command can be used to program the memory in Fast Program mode. The command requires two Bus Write operations less than the standard Write to Buffer Program command.

The Unlock Bypass Write to Buffer Program command behaves in the same way as the Write to Buffer Program command: the operation cannot be aborted and a Bus Read operation to the memory outputs the Status Register (see [Section 6.2.1: Write to Buffer Program command](#) for details).

The Write to Buffer Program Confirm command is used to confirm an Unlock Bypass Write to Buffer Program command and to program the N+1 words/bytes loaded in the program buffer by this command.

### 6.2.9 Unlock Bypass Reset command

The Unlock Bypass Reset command can be used to return to Read/Reset mode from Unlock Bypass mode. Two Bus Write operations are required to issue the Unlock Bypass Reset command. Read/Reset command does not exit from Unlock Bypass mode.

**Table 11. Fast Program commands, 8-bit mode**

| Command                               | Length | Bus Write operations <sup>(1)</sup> |      |     |                  |                   |      |     |                  |                   |      |
|---------------------------------------|--------|-------------------------------------|------|-----|------------------|-------------------|------|-----|------------------|-------------------|------|
|                                       |        | 1st                                 |      | 2nd |                  | 3rd               |      | 4th |                  | 5th               |      |
|                                       |        | Add                                 | Data | Add | Data             | Add               | Data | Add | Data             | Add               | Data |
| Write to Buffer Program               | N+5    | AAA                                 | AA   | 555 | 55               | BAd               | 25   | BAd | N <sup>(2)</sup> | PA <sup>(3)</sup> | PD   |
| Write to Buffer Program Confirm       | 1      | BAd <sup>(4)</sup>                  | 29   | -   | -                | -                 | -    | -   | -                | -                 | -    |
| Buffered Program Abort and Reset      | 3      | AAA                                 | AA   | 555 | 55               | AAA               | F0   | -   | -                | -                 | -    |
| Unlock Bypass                         | 3      | AAA                                 | AA   | 555 | 55               | AAA               | 20   | -   | -                | -                 | -    |
| Unlock Bypass Program                 | 2      | X                                   | A0   | PA  | PD               | -                 | -    | -   | -                | -                 | -    |
| Unlock Bypass Block Erase             | 2+     | X                                   | 80   | BAd | 30               | -                 | -    | -   | -                | -                 | -    |
| Unlock Bypass Chip Erase              | 2      | X                                   | 80   | X   | 10               | -                 | -    | -   | -                | -                 | -    |
| Unlock Bypass Write to Buffer Program | N+3    | BAd                                 | 25   | BAd | N <sup>(2)</sup> | PA <sup>(3)</sup> | PD   | -   | -                | -                 | -    |
| Unlock Bypass Reset                   | 2      | X                                   | 90   | X   | 00               | -                 | -    | -   | -                | -                 | -    |

1. X = Don't care, PA = Program Address, PD = Program Data, BAd = Any address in the Block. All values in the table are in hexadecimal.
2. The maximum number of cycles in the buffer program command sequence is 261. The maximum number of cycles in the unlock bypass buffer program command sequence is 259. N+1 is the number of bytes to be programmed during the Write to Buffer Program operation.
3. Amax-A7 address pin should be consistently unchanged. A0-A6 and A-1 pins are used to select a byte within the N+1 byte page.
4. BAd must be identical to the address loaded during the Write to Buffer Program 3rd and 4th cycles.

**Table 12. Fast Program commands, 16-bit mode**

| Command                          | Length | Bus Write operations <sup>(1)</sup> |      |     |      |     |      |     |                  |                   |      |
|----------------------------------|--------|-------------------------------------|------|-----|------|-----|------|-----|------------------|-------------------|------|
|                                  |        | 1st                                 |      | 2nd |      | 3rd |      | 4th |                  | 5th               |      |
|                                  |        | Add                                 | Data | Add | Data | Add | Data | Add | Data             | Add               | Data |
| Write to Buffer Program          | N+5    | 555                                 | AA   | 2AA | 55   | BAd | 25   | BAd | N <sup>(2)</sup> | PA <sup>(3)</sup> | PD   |
| Write to Buffer Program Confirm  | 1      | BAd <sup>(4)</sup>                  | 29   | -   | -    | -   | -    | -   | -                | -                 | -    |
| Buffered Program Abort and Reset | 3      | 555                                 | AA   | 2AA | 55   | 555 | F0   | -   | -                | -                 | -    |
| Unlock Bypass                    | 3      | 555                                 | AA   | 2AA | 55   | 555 | 20   | -   | -                | -                 | -    |

**Table 12. Fast Program commands, 16-bit mode**

| Command                               | Length | Bus Write operations <sup>(1)</sup> |      |     |                  |                   |      |     |      |     |      |
|---------------------------------------|--------|-------------------------------------|------|-----|------------------|-------------------|------|-----|------|-----|------|
|                                       |        | 1st                                 |      | 2nd |                  | 3rd               |      | 4th |      | 5th |      |
|                                       |        | Add                                 | Data | Add | Data             | Add               | Data | Add | Data | Add | Data |
| Unlock Bypass Program                 | 2      | X                                   | A0   | PA  | PD               | -                 | -    | -   | -    | -   | -    |
| Unlock Bypass Block Erase             | 2+     | X                                   | 80   | BAd | 30               | -                 | -    | -   | -    | -   | -    |
| Unlock Bypass Chip Erase              | 2      | X                                   | 80   | X   | 10               | -                 | -    | -   | -    | -   | -    |
| Unlock Bypass Write to Buffer Program | N+3    | BAd                                 | 25   | BAd | N <sup>(2)</sup> | PA <sup>(3)</sup> | PD   | -   | -    | -   | -    |
| Unlock Bypass Reset                   | 2      | X                                   | 90   | X   | 00               | -                 | -    | -   | -    | -   | -    |

1. X = Don't care, PA = Program Address, PD = Program Data, BAd = Any address in the Block. All values in the table are in hexadecimal.
2. The maximum number of cycles in the buffer program command sequence is 517. The maximum number of cycles in the unlock bypass buffer program command sequence is 515. N+1 is the number of bytes to be programmed during the Write to Buffer Program operation.
3. Amax-A9 address pins should be consistently unchanged. A0-A8 pins are used to select a word within the N+1 word page.
4. BAd must be identical to the address loaded during the Write to Buffer Program 3rd and 4th cycles.

## 6.3 Protection commands

Blocks can be protected individually against accidental program, erase or read operations. The device block protection scheme is shown in [Figure 6: Software protection scheme](#). See either [Table 13](#), or [Table 14](#), depending on the configuration that is being used, for a summary of the Block Protection commands.

Block protection commands are available both in 8-bit and 16-bit configuration.

The protections of both memory blocks and Extended Memory Block protection are configured through the Lock register (see [Section 7.1: Lock Register](#)).

### 6.3.1 Enter Extended Memory Block command

The M29EW has one extra 128-word Extended Memory Block that can only be accessed using the Enter Extended Memory Block command.

Three Bus Write cycles are required to issue the Enter Extended Memory Block command. Once the command has been issued the device enters the Extended Memory Block mode where all Bus Read or Program operations are conducted on the Extended Memory Block. Once the device is in the Extended Memory Block mode, the Extended Memory Block is addressed by using the addresses occupied by block 0 in the other operating modes (see [Figure 5: Block addresses on page 12](#)).

The device remains in Extended Memory Block mode until the Exit Extended Memory Block command is issued or power is removed from the device. After a power-up sequence or hardware reset, the device will revert to reading from memory blocks in the main array.

The Extended Memory Block cannot be erased, and each bit of the Extended Memory Block can only be programmed once.

In Extended Memory Block mode, Erase, Chip Erase, Erase Suspend and Erase Resume commands are not allowed.

To exit from the Extended Memory Block mode the Exit Extended Memory Block command must be issued.

The Extended Memory Block is protected from further modification by programming Lock Register bit 0 (see [Section 7.1: Lock Register](#)). Once invoked, this protection cannot be undone.

### 6.3.2 Exit Extended Memory Block command

The Exit Extended Memory Block command is used to exit from the Extended Memory Block mode and return the device to Read mode. Four Bus Write operations are required to issue the command.

### 6.3.3 Lock Register command set

The M29EW offers a set of commands to access the Lock Register and to configure and verify its content. See the following sections in conjunction with [Section 7.1: Lock Register](#), [Table 13](#) and [Table 14](#).

#### Enter Lock Register Command Set command

Three Bus Write cycles are required to issue the Enter Lock Register Command Set command. Once the command has been issued, all Bus Read or Program operations are issued to the Lock Register.

#### Lock Register Program and Lock Register Read command

The Lock Register Program command allows to configure the Lock Register. The programmed data can then be checked by issuing a Lock Register Read command.

An Exit Protection Command Set command must then be issued to return the device to Read mode (see [Section 6.3.8: Exit Protection command set](#)).

### 6.3.4 Password Protection mode command set

#### Enter Password Protection Command Set command

Three Bus Write cycles are required to issue the Enter Password Protection Command Set command. Once the command has been issued, the commands related to the Password Protection mode can be issued to the device.

#### Password Program command

The Password Program command is used to program the 64-bit password used in the Password Protection mode.

To program the 64-bit password, the complete command sequence must be entered eight times at eight consecutive addresses selected by A1-A0 plus DQ15/A-1 in 8-bit mode, or four times at four consecutive addresses selected by A1-A0 in 16-bit mode.

The password can be checked by issuing a Password Read command.

Once Password Program operation has completed, an Exit Protection Command Set command must be issued to return the device to Read mode. The Password Protection mode can then be selected.

By default, all Password bits are set to '1'.

*Note: In order to use password protection feature on 2-Gbit (1-Gbit/1-Gbit stack) device, the password must be programmed to both upper die and bottom die respectively.*

#### Password Read command

The Password Read command is used to verify the Password used in Password Protection mode.

To verify the 64-bit password, the complete command sequence must be entered eight times at eight consecutive addresses selected by A1-A0 plus DQ15/A-1 in 8-bit mode, or four times at four consecutive addresses selected by A1-A0 in 16-bit mode.

If the Password Mode Lock bit is programmed and the user attempts to read the password, the device will output FFh onto the I/O data bus.

An Exit Protection Command Set command must be issued to return the device to Read mode.

### **Password Unlock command**

The Password Unlock command is used to clear the NVPB Lock bit allowing to modify the NVPBs.

The Password Unlock command must be issued along with the correct password.

There must be a 1  $\mu$ s delay between successive Password Unlock commands in order to prevent hackers from cracking the password by trying all possible 64-bit combinations. If this delay is not respected, the latest command will be ignored.

Approximately 1  $\mu$ s is required for unlocking the device after the valid 64-bit password has been provided.

## **6.3.5 Non-Volatile Protection mode command set**

### **Enter Non-Volatile Protection Command Set command**

Three Bus Write cycles are required to issue the Enter Non-Volatile Protection Command Set command. Once the command has been issued, the commands related to the Non-Volatile Protection mode can be issued to the device.

### **Non-Volatile Protection Bit Program command (NVPB Program)**

A block can be protected from program or erase by issuing a Non-Volatile Protection Bit command along with the block address. This command sets the NVPB to '1' for a given block.


### **Read Non-Volatile Protection Bit Status command (Read NVPB Status)**

The status of a NVPB for a given block or group of blocks can be read by issuing a Read Non-Volatile Modify Protection Bit command along with the block address.

### **Clear all Non-Volatile Protection Bits command (Clear all NVPBs)**

The NVPBs are erased simultaneously by issuing a Clear all Non-Volatile Protection Bits command. No specific block address is required. If the NVPB Lock bit is set to '0', the command fails.

Figure 9. NVPB Program/Erase algorithm



AI14242

### 6.3.6 NVPB Lock Bit command set

#### Enter NVPB Lock Bit Command Set command

Three bus Write cycles are required to issue the Enter NVPB Lock Bit Command Set command. Once the command has been issued, the commands allowing to set the NVPB Lock bit can be issued to the device.

#### NVPB Lock Bit Program command

This command is used to set the NVPB Lock bit to '0' thus locking the NVPBs, and preventing them from being modified.

#### Read NVPB Lock Bit Status command

This command is used to read the status of the NVPB Lock bit.

### 6.3.7 Volatile Protection mode command set

#### Enter Volatile Protection Command Set command

Three bus Write cycles are required to issue the Enter Volatile Protection Command Set command. Once the command has been issued, the commands related to the Volatile Protection mode can be issued to the device.

#### Volatile Protection Bit Program command (VPB Program)

The VPB Program command individually sets a VPB to '0' for a given block.

If the NVPB for the same block is set, the block is locked regardless of the value of the VPB bit. (see [Table 16: Block Protection Status](#)).

#### Read VPB Status command

The status of a VPB for a given block can be read by issuing a Read VPB Status command along with the block address.

#### VPB Clear command

The VPB Clear command individually clears (sets to '1') the VPB for a given block.

If the NVPB for the same block is set, the block is locked regardless of the value of the VPB bit. (see [Table 16: Block Protection Status](#)).

### 6.3.8 Exit Protection command set

The Exit Protection Command Set command is used to exit from the Lock Register, Password Protection, Non-Volatile Protection, Volatile Protection, and NVPB Lock Bit Command Set mode. It return the device to Read mode.

**Table 13. Block Protection commands, 8-bit mode<sup>(1)(2)(3)</sup>**

| Command                                     |                                                          | Length | Bus operations |                     |                  |                     |     |                  |     |                  |     |                  |     |                  |     |                  |     |                  |     |                  |      |                  |      |      |
|---------------------------------------------|----------------------------------------------------------|--------|----------------|---------------------|------------------|---------------------|-----|------------------|-----|------------------|-----|------------------|-----|------------------|-----|------------------|-----|------------------|-----|------------------|------|------------------|------|------|
|                                             |                                                          |        | 1st            |                     | 2nd              |                     | 3rd |                  | 4th |                  | 5th |                  | 6th |                  | 7th |                  | 8th |                  | 9th |                  | 10th |                  | 11th |      |
|                                             |                                                          |        | Ad             | Data                | Ad               | Data                | Ad  | Data             | Ad  | Data             | Ad  | Data             | Ad  | Data             | Ad  | Data             | Ad  | Data             | Ad  | Data             | Ad   | Data             | Ad   | Data |
| Lock Register                               | Enter Lock Register Command Set <sup>(4)</sup>           | 3      | AAA            | AA                  | 555              | 55                  | AAA | 40               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Lock Register Program                                    | 2      | X              | A0                  | X                | DATA <sup>(5)</sup> | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Lock Register Read                                       | 1      | X              | DATA <sup>(5)</sup> | -                | -                   | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| Password Protection                         | Enter Password Protection Command Set <sup>(4)</sup>     | 3      | AAA            | AA                  | 555              | 55                  | AAA | 60               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Password Program <sup>(6)(7)</sup>                       | 2      | X              | A0                  | PWA <sub>n</sub> | PWD <sub>n</sub>    | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Password Read                                            | 8      | 00             | PWD <sub>0</sub>    | 01               | PWD <sub>1</sub>    | 02  | PW <sub>D2</sub> | 03  | PW <sub>D3</sub> | 04  | PW <sub>D4</sub> | 05  | PW <sub>D5</sub> | 06  | PW <sub>D6</sub> | 07  | PW <sub>D7</sub> | -   | -                | -    | -                | -    | -    |
|                                             | Password Unlock <sup>(7)</sup>                           | 11     | 00             | 25                  | 00               | 03                  | 00  | PW <sub>D0</sub> | 01  | PW <sub>D1</sub> | 02  | PW <sub>D2</sub> | 03  | PW <sub>D3</sub> | 04  | PW <sub>D4</sub> | 05  | PW <sub>D5</sub> | 06  | PW <sub>D6</sub> | 07   | PW <sub>D7</sub> | 00   | 29   |
|                                             |                                                          |        |                |                     |                  |                     |     |                  |     |                  |     |                  |     |                  |     |                  |     |                  |     |                  |      |                  |      |      |
| Non-Volatile Protection                     | Enter Non-Volatile Protection Command Set <sup>(4)</sup> | 3      | AAA            | AA                  | 555              | 55                  | AAA | C0               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | NVPB Program <sup>(8)</sup>                              | 2      | X              | A0                  | BAd              | 00                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Clear all NVPBs <sup>(9)</sup>                           | 2      | X              | 80                  | 00               | 30                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Read NVPB Status <sup>(8)</sup>                          | 1      | BAd            | RD(0)               | -                | -                   | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| NVPB Lock bit                               | Enter NVPB Lock Bit Command Set                          | 3      | AAA            | AA                  | 555              | 55                  | AAA | 50               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | NVPB Lock Bit Program <sup>(8)</sup>                     | 2      | X              | A0                  | X                | 00                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Read NVPB Lock Bit Status <sup>(8)</sup>                 | 1      | X              | RD(0)               | -                | -                   | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| Volatile Protection                         | Enter Volatile Protection Command Set                    | 3      | AAA            | AA                  | 555              | 55                  | AAA | E0               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | VPB Program <sup>(8)</sup>                               | 2      | X              | A0                  | BAd              | 00                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | Read VPB Status                                          | 1      | BAd            | RD(0)               | -                | -                   | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
|                                             | VPB Clear <sup>(8)</sup>                                 | 2      | X              | A0                  | BAd              | 01                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| Exit Protection Command Set <sup>(10)</sup> |                                                          | 2      | X              | 90                  | X                | 00                  | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| Enter Extended Memory Block <sup>(4)</sup>  |                                                          | 3      | AAA            | AA                  | 555              | 55                  | AAA | 88               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |
| Exit Extended Memory Block                  |                                                          | 4      | AAA            | AA                  | 555              | 55                  | AAA | 90               | X   | 00               | -   | -                | -   | -                | -   | -                | -   | -                | -   | -                | -    | -                | -    | -    |

1. Ad = address; Dat = data; BAd = Any address in the Block; RD = Read data; PWDn = Password byte 0 to 7; PWA<sub>n</sub> = Password Address (n = 0 to 7); X = Don't care. All values in the table are in hexadecimal.
2. Grey cells represent Read cycles. The other cells are Write cycles.
3. DQ15 to DQ8 are 'Don't care' during unlock and command cycles. Amax to A16 are 'Don't care' during unlock and command cycles unless an address is required.
4. An Enter command sequence must be issued prior to any operation. It disables read and write operations from and to block 0. Read and write operations from any other block are allowed.
5. DATA = Lock Register content.
6. Only one portion of password can be programmed or read by each Password Program command.
7. The password portion can be entered or read in any order as long as the entire 64-bit password is entered or read.
8. Protected and unprotected states correspond to 00 and 01, respectively.
9. The Clear all NVPBs command programs all NVPBs before erasure in order to prevent the over-erasure of previously cleared Non Volatile Modify Protection bits.
10. If an Entry Command Set command is issued, an Exit Protection Command Set command must be issued to return the device to Read mode.

**Table 14. Block Protection commands, 16-bit mode<sup>(1)(2)(3)</sup>**

| Command                                     |                                                          | Length | Bus operations |                     |      |                     |     |      |     |      |     |      |     |      |     |      |
|---------------------------------------------|----------------------------------------------------------|--------|----------------|---------------------|------|---------------------|-----|------|-----|------|-----|------|-----|------|-----|------|
|                                             |                                                          |        | 1st            |                     | 2nd  |                     | 3rd |      | 4th |      | 5th |      | 6th |      | 7th |      |
|                                             |                                                          |        | Ad             | Data                | Ad   | Data                | Ad  | Data | Ad  | Data | Ad  | Data | Ad  | Data | Ad  | Data |
| Lock register                               | Enter Lock Register Command Set <sup>(4)</sup>           | 3      | 555            | AA                  | 2AA  | 55                  | 555 | 40   | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Lock Register Program                                    | 2      | X              | A0                  | X    | DATA <sup>(5)</sup> | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Lock Register Read                                       | 1      | X              | DATA <sup>(5)</sup> | -    | -                   | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
| Password Protection                         | Enter Password Protection Command Set <sup>(4)</sup>     | 3      | 555            | AA                  | 2AA  | 55                  | 555 | 60   | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Password Program <sup>(6)(7)</sup>                       | 2      | X              | A0                  | PWAn | PWDn                | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Password Read                                            | 4      | 00             | PWD0                | 01   | PWD1                | 02  | PWD2 | 03  | PWD3 | -   | -    | -   | -    | -   | -    |
|                                             | Password Unlock <sup>(7)</sup>                           | 7      | 00             | 25                  | 00   | 03                  | 00  | PWD0 | 01  | PWD1 | 02  | PWD2 | 03  | PWD3 | 00  | 29   |
| Non-Volatile Protection                     | Enter Non-Volatile Protection Command Set <sup>(4)</sup> | 3      | 555            | AA                  | 2AA  | 55                  | 555 | C0   | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | NVPB Program <sup>(8)</sup>                              | 2      | X              | A0                  | BAd  | 00                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Clear all NVPBs <sup>(9)</sup>                           | 2      | X              | 80                  | 00   | 30                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Read NVPB Status                                         | 1      | BAd            | RD(0)               | -    | -                   | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
| NVPB Lock bit                               | Enter NVPB Lock Bit Command Set                          | 3      | 555            | AA                  | 2AA  | 55                  | 555 | 50   | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | NVPB Lock Bit Program                                    | 2      | X              | A0                  | X    | 00                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Read NVPB Lock Bit Status                                | 1      | X              | RD(0)               | -    | -                   | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
| Volatile Protection                         | Enter Volatile Protection Command Set                    | 3      | 555            | AA                  | 2AA  | 55                  | 555 | E0   | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | VPB Program                                              | 2      | X              | A0                  | BAd  | 00                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | Read VPB Status                                          | 1      | BAd            | RD(0)               | -    | -                   | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
|                                             | VPB Clear                                                | 2      | X              | A0                  | BAd  | 01                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
| Exit Protection Command Set <sup>(10)</sup> |                                                          | 2      | X              | 90                  | X    | 00                  | -   | -    | -   | -    | -   | -    | -   | -    | -   | -    |
| Enter Extended Memory Block <sup>(4)</sup>  |                                                          | 3      | 555            | AA                  | 2AA  | 55                  | 555 | 88   | -   | -    | -   | -    | -   | -    | -   | -    |
| Exit Extended Memory Block                  |                                                          | 4      | 555            | AA                  | 2AA  | 55                  | 555 | 90   | X   | 00   | -   | -    | -   | -    | -   | -    |

1. Ad = address; Dat = data; BAd = Any address in the Block; RD = Read data; PWDn = Password byte 0 to 3; PWAn = Password Address (n = 0 to 3); X = Don't care. All values in the table are in hexadecimal.
2. Grey cells represent Read cycles. The other cells are Write cycles.
3. DQ15 to DQ8 are 'Don't care' during unlock and command cycles. Amax to A16 are 'Don't care' during unlock and command cycles unless an address is required.
4. An Enter command sequence must be issued prior to any operation. It disables read and write operations from and to block 0. Read and write operations from any other block are allowed.
5. DATA = Lock Register content.
6. Only one portion of password can be programmed or read by each Password Program command.
7. The password portion can be entered or read in any order as long as the entire 64-bit password is entered or read.
8. Protected and unprotected states correspond to 00 and 01, respectively.
9. The Clear all NVPBs command programs all NVPBs before erasure in order to prevent the over-erasure of previously cleared Non-volatile Modify Protection bits.
10. If an Entry Command Set command is issued, an Exit Protection Command Set command must be issued to return the device to Read mode.

## 7 Registers

The device features two registers:

1. A Lock Register that allows to configure the memory blocks and Extended Memory Block protection (see [Table 16: Block Protection Status](#))
2. A Status Register that provides information on the current or previous Program or Erase operations.

### 7.1 Lock Register

The Lock Register is a 16-bit one-time programmable register. The bits in the Lock Register are summarized in [Table 15: Lock Register bits](#).

See [Section 6.3.3: Lock Register command set](#) for a description of the commands allowing to read and program the Lock Register.

#### 7.1.1 Password Protection Mode Lock bit (DQ2)

The Password Protection Mode Lock bit, DQ0, is one-time programmable. Programming (setting to '0') this bit permanently places the device in Password Protection mode.

Any attempt to program the Password Protection mode Lock bit when the Non-Volatile Protection Mode bit is programmed causes the operation to abort and the device to return to Read mode.

#### 7.1.2 Non-Volatile Protection Mode Lock bit (DQ1)

The Non-Volatile Protection Mode Lock bit, DQ1, is one-time programmable. Programming (setting to '0') this bit permanently places the device in Non-Volatile Protection mode.

When shipped from Numonyx factory, all parts default to operate in Non-Volatile Protection mode. The memory blocks are unprotected (NVPBs set to '1').

Any attempt to program the Non-Volatile Protection mode Lock bit when the Password Protection Mode bit is programmed causes the operation to abort and the device to return to Read mode.

#### 7.1.3 Extended Memory Block Protection bit (DQ0)

If the device is shipped with the Extended Memory Block unlocked, the block can be protected by setting the Extended Memory Block Protection bit, DQ0, to '0'. However, this bit is one-time programmable and once protected the Extended Memory Block cannot be unprotected any more.

The Extended Memory Block protection status can be read in Auto Select mode by issuing an Auto Select command (see [Table 9](#) and [Table 10](#)).

**Table 15. Lock Register bits<sup>(1)</sup>**

| DQ15-3 <sup>(2)</sup> | DQ2                               | DQ1                                   | DQ0                                  |
|-----------------------|-----------------------------------|---------------------------------------|--------------------------------------|
| Reserved              | Password Protection Mode Lock bit | Non-Volatile Protection Mode Lock bit | Extended Memory Block Protection bit |


1. DQ0, DQ1 and DQ2 Lock Register bits are set to '1' when shipped from the Numonyx.
2. DQ15 to DQ3 are reserved and default to '1'.

**Table 16. Block Protection Status**

| NVPB Lock bit <sup>(1)</sup> | Block NVPB <sup>(2)</sup> | Block VPB <sup>(3)</sup> | Block protection status | Block Protection Status                             |
|------------------------------|---------------------------|--------------------------|-------------------------|-----------------------------------------------------|
| 1                            | 1                         | 1                        | 00h                     | Block unprotected (NVPB changeable)                 |
| 1                            | 1                         | 0                        | 01h                     | Block protected by VPB (NVPB changeable)            |
| 1                            | 0                         | 1                        | 01h                     | Block protected by NVPB (NVPB changeable)           |
| 1                            | 0                         | 0                        | 01h                     | Block protected by NVPB and VPB (NVPB changeable)   |
| 0                            | 1                         | 1                        | 00h                     | Block unprotected (NVPB unchangeable)               |
| 0                            | 1                         | 0                        | 01h                     | Block protected by VPB (NVPB unchangeable)          |
| 0                            | 0                         | 1                        | 01h                     | Block protected by NVPB (NVPB unchangeable)         |
| 0                            | 0                         | 0                        | 01h                     | Block protected by NVPB and VPB (NVPB unchangeable) |

1. If the NVPB Lock bit is set to '0', all NVPBs are locked. If the NVPB Lock bit is set to '1', all NVPBs are unlocked.
2. If the Block NVPB is set to '0', the block is protected, if set to '1', it is unprotected.
3. If the Block VPB is set to '0', the block is protected, if set to '1', it is unprotected.

Figure 10. Lock Register program flowchart



1. PD is the programmed data (see [Table 15: Lock Register bits](#)).
2. Each bit of the Lock Register can only be programmed once.

## 7.2 Status Register

The M29EW discrete device has one Status Register. The various bits convey information and errors on the current and previous program/erase operation. Bus Read operations from any address within the memory, always read the Status Register during Program and Erase operations. It is also read during Erase Suspend when an address within a block being erased is accessed.

The bits in the Status Register are summarized in [Table 17: Status Register bits](#).

### 7.2.1 Data Polling bit (DQ7)

The Data Polling bit can be used to identify whether the Program/Erase controller has successfully completed its operation or if it has responded to an Erase Suspend. The Data Polling bit is output on DQ7 when the Status Register is read.

During Program operations the Data Polling bit outputs the complement of the bit being programmed to DQ7. After successful completion of the Program operation the memory returns to Read mode and Bus Read operations, from the address just programmed, output DQ7, not its complement.

During Erase or Blank Check operations the Data Polling bit outputs '0', the complement of the erased state of DQ7. When the algorithm is complete, Data Polling produces a '1' on DQ7. After successful completion of the Erase or Blank Check operation the memory returns to Read mode.

In Erase Suspend mode the Data Polling bit will output a '1' during a Bus Read operation within a block being erased. The Data Polling bit will change from '0' to '1' when the Program/Erase controller has suspended the Erase operation.

[Figure 11: Data polling flow chart](#), gives an example of how to use the Data Polling bit. A Valid Address is the address being programmed or an address within the block being erased or blank checked.

### 7.2.2 Toggle bit (DQ6)

The Toggle bit can be used to identify whether the Program/Erase controller has successfully completed its operation or if it has responded to an Erase Suspend. The Toggle bit is output on DQ6 when the Status Register is read.

During a Program/Erase operation the Toggle bit changes from '0' to '1' to '0', etc., with successive Bus Read operations at any address. After successful completion of the operation the memory returns to Read mode.

During Erase Suspend mode the Toggle bit will output when addressing a cell within a block being erased. The Toggle bit will stop toggling when the Program/Erase controller has suspended the Erase operation.

[Figure 12: Toggle flow chart](#), gives an example of how to use the Data Toggle bit.

### 7.2.3 Error bit (DQ5)

The Error bit can be used to identify errors detected by the Program/Erase controller. The Error bit is set to '1' when a Program, Block Erase or Chip Erase operation fails to write the correct data to the memory, or a Blank Check operation fails. If the Error bit is set a

Read/Reset command must be issued before other commands are issued. The Error bit is output on DQ5 when the Status Register is read.

Note that the Program command cannot change a bit set to '0' back to '1' and attempting to do so will set DQ5 to '1'. A Bus Read operation to that address will show the bit is still '0'. One of the Erase commands must be used to set all the bits in a block or in the whole memory from '0' to '1'.

#### 7.2.4 Erase Timer bit (DQ3)

The Erase Timer bit can be used to identify the start of Program/Erase controller operation during a Block Erase command. Once the Program/Erase controller starts erasing the Erase Timer bit is set to '1'. Before the Program/Erase controller starts the Erase Timer bit is set to '0' and additional blocks to be erased may be written to the command interface. The Erase Timer bit is output on DQ3 when the Status Register is read.

#### 7.2.5 Alternative Toggle bit (DQ2)

The Alternative Toggle bit can be used to monitor the Program/Erase controller during Erase operations. The Alternative Toggle bit is output on DQ2 when the Status Register is read.

During Chip Erase and Block Erase operations the Toggle bit changes from '0' to '1' to '0', etc., with successive Bus Read operations from addresses within the blocks being erased. A protected block is treated the same as a block not being erased. Once the operation completes the memory returns to Read mode.

During Erase Suspend the Alternative Toggle bit changes from '0' to '1' to '0', etc. with successive Bus Read operations from addresses within the blocks being erased. Bus Read operations to addresses within blocks not being erased will output the memory array data as if in Read mode.

#### 7.2.6 Buffered Program Abort bit (DQ1)

The Buffered Program Abort bit, DQ1, is set to '1' when a Buffer Program operation aborts. The Buffered Program Abort and Reset command must be issued to return the device to Read mode (see Write to Buffer Program in [Section 6.1: Standard commands](#)).

For the complete polling flow chart, please refer to [Figure 13.: Status Register Polling Flow Chart](#).

Table 17. Status Register bits<sup>(1)</sup>

| Operation                             | Address                     | DQ7                     | DQ6       | DQ5 | DQ3 | DQ2       | DQ1 | RY/BY# |
|---------------------------------------|-----------------------------|-------------------------|-----------|-----|-----|-----------|-----|--------|
| Program <sup>(2)</sup>                | Any address                 | $\overline{\text{DQ7}}$ | Toggle    | 0   | –   | No Toggle | 0   | 0      |
| Program During Erase Suspend          | Any address                 | $\overline{\text{DQ7}}$ | Toggle    | 0   | –   | –         | –   | 0      |
| Buffered Program Abort <sup>(2)</sup> | Any address                 | $\overline{\text{DQ7}}$ | Toggle    | 0   | –   | –         | 1   | 0      |
| Program Error                         | Any address                 | $\overline{\text{DQ7}}$ | Toggle    | 1   | –   | –         | –   | Hi-Z   |
| Chip Erase                            | Any address                 | 0                       | Toggle    | 0   | 1   | Toggle    | –   | 0      |
| Block Erase before timeout            | Erasing block               | 0                       | Toggle    | 0   | 0   | Toggle    | –   | 0      |
|                                       | Non-erasing block           | 0                       | Toggle    | 0   | 0   | No toggle | –   | 0      |
| Block Erase/Blank Check               | Erasing/Verifying block     | 0                       | Toggle    | 0   | 1   | Toggle    | –   | 0      |
|                                       | Non-erasing/Verifying block | 0                       | Toggle    | 0   | 1   | No toggle | –   | 0      |
| Erase/Blank Check Suspend             | Erasing/Verifying block     | 1                       | No Toggle | 0   | –   | Toggle    | –   | Hi-Z   |
|                                       | Non-erasing/Verifying block | Data read as normal     |           |     |     |           | –   | Hi-Z   |
| Erase/Blank Check Error               | Any address                 | 0                       | Toggle    | 1   | 1   | Toggle    | –   | Hi-Z   |

1. Unspecified data bits should be ignored.

2.  $\overline{\text{DQ7}}$  for Buffer Program is related to the last address location loaded.

Figure 11. Data polling flow chart




Figure 12. Toggle flow chart





Figure 13. Status Register Polling Flow Chart



## 8 Maximum Ratings

Stressing the device above the rating listed in [Table 18: Absolute maximum ratings](#) may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. These are stress ratings only and operation of the device at these or any other conditions above those indicated in the operating sections of this specification is not implied. Refer also to the relevant quality documents from Numonyx.

**Table 18. Absolute maximum ratings**

| Symbol          | Parameter                                 | Min  | Max            | Unit |
|-----------------|-------------------------------------------|------|----------------|------|
| $T_{BIAS}$      | Temperature under bias                    | -50  | 125            | °C   |
| $T_{STG}$       | Storage temperature                       | -65  | 150            | °C   |
| $V_{IO}$        | Input or output voltage <sup>(1)(2)</sup> | -0.6 | $V_{CC} + 0.6$ | V    |
| $V_{CC}$        | Supply voltage                            | -0.6 | 4              | V    |
| $V_{CCQ}$       | Input/output supply voltage               | -0.6 | 4              | V    |
| $V_{PPH}^{(3)}$ | Program voltage                           | -0.6 | 14.5           | V    |

1. Minimum voltage may undershoot to -2 V during transition and for less than 20ns during transitions.
2. Maximum voltage may overshoot to  $V_{CC} + 2$  V during transition and for less than 20ns during transitions.
3.  $V_{PPH}$  must not remain at 12 V for more than a total of 80hrs.


## 9 DC and AC Parameters

This section summarizes the operating measurement conditions, and the DC and AC characteristics of the device. The parameters in the DC and AC characteristics tables that follow, are derived from tests performed under the measurement conditions summarized in [Table 19: Operating and AC measurement conditions](#). Designers should check that the operating conditions in their circuit match the operating conditions when relying on the quoted parameters.


**Table 19. Operating and AC measurement conditions**

| Parameter                                          | Min            | Max  | Unit |
|----------------------------------------------------|----------------|------|------|
| $V_{CC}$ supply voltage                            | 2.7            | 3.6  | V    |
| $V_{CCQ}$ supply voltage ( $V_{CCQ} \leq V_{CC}$ ) | 1.65           | 3.6  | V    |
| $V_{PP}$ supply voltage                            | -2.0           | 12.5 | V    |
| Ambient operating temperature                      | -40            | 85   | °C   |
| Load capacitance ( $C_L$ )                         | 30             |      | pF   |
| Input rise and fall times                          |                | 10   | ns   |
| Input pulse voltages                               | 0 to $V_{CCQ}$ |      | V    |
| Input and output timing ref. voltages              | $V_{CCQ}/2$    |      | V    |

**Figure 14. AC measurement load circuit**



**Figure 15. AC measurement I/O waveform**



**Table 20. Power-up wait timings**

| Symbol             | Alt.       | Parameter                                   | Min | Unit    |
|--------------------|------------|---------------------------------------------|-----|---------|
| $t_{VCHVCQH}$      | -          | $V_{CC}^{(1)}$ High to $V_{CCQ}^{(1)}$ High | 0   | $\mu s$ |
| $t_{VCHPH}^{(2)}$  | $t_{VCS}$  | $V_{CC}$ High to rising edge of RST#        | 300 | $\mu s$ |
| $t_{VCQHPH}^{(2)}$ | $t_{VIOS}$ | $V_{CCQ}$ High to rising edge of RST#       | 0   | $\mu s$ |
| $t_{PHEL}$         | $t_{RH}$   | RST# High to Chip Enable Low                | 50  | ns      |
| $t_{PHWL}$         | -          | RST# High to Write Enable Low               | 150 | ns      |

1.  $V_{CC}$  and  $V_{CCQ}$  ramps must be synchronized during power-up.
2. If RST# is not stable for  $t_{VCHRH}$  or  $t_{VCQHRH}$ , the device does not permit any Read and Write operations and a hardware reset is required.


**Figure 16. Power-up wait timings**

Table 21. Device capacitance<sup>(1)</sup>

| Symbol           | Parameter                                    | Test condition         | Min | Max | Unit |
|------------------|----------------------------------------------|------------------------|-----|-----|------|
| C <sub>IN</sub>  | Input capacitance for 256-Mbit and 512-Mbit  | V <sub>IN</sub> = 0 V  | 3   | 8   | pF   |
|                  | Input capacitance for 1-Gbit                 |                        | 4   | 9   |      |
|                  | Input capacitance for 2-Gbit (1-Gbit/1-Gbit) |                        | 8   | 18  |      |
| C <sub>OUT</sub> | Output capacitance                           | V <sub>OUT</sub> = 0 V | 3   | 6   |      |

1. Sampled only, not 100% tested.

Table 22. DC characteristics

| Symbol                          | Parameter                                                |                                 | Test condition                                                                                                 |                                                              | Min                  | Typ  | Max                   | Unit |
|---------------------------------|----------------------------------------------------------|---------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|----------------------|------|-----------------------|------|
| I <sub>LI</sub> <sup>(1)</sup>  | Input leakage current                                    |                                 | 0 V ≤ V <sub>IN</sub> ≤ V <sub>CC</sub>                                                                        |                                                              | -                    | -    | ±1                    | μA   |
| I <sub>LO</sub>                 | Output leakage current                                   |                                 | 0 V ≤ V <sub>OUT</sub> ≤ V <sub>CC</sub>                                                                       |                                                              | -                    | -    | ±1                    | μA   |
| I <sub>CC1</sub>                | Read current                                             | Random Read                     | CE# = V <sub>IL</sub> , OE# = V <sub>IH</sub> ,<br>f = 5 MHz                                                   |                                                              | -                    | 26   | 31                    | mA   |
|                                 |                                                          | Page Read                       | CE# = V <sub>IL</sub> , OE# = V <sub>IH</sub> ,<br>f = 13 MHz                                                  |                                                              | -                    | 12   | 16                    | mA   |
| I <sub>CC2</sub>                | Supply current<br>(Standby)                              | 256-Mbit                        | CE# = V <sub>CCQ</sub> ± 0.2 V,<br>RST# = V <sub>CCQ</sub> ± 0.2 V                                             |                                                              | -                    | 65   | 210                   | μA   |
|                                 |                                                          | 512-Mbit                        |                                                                                                                |                                                              | -                    | 70   | 225                   |      |
|                                 |                                                          | 1-Gbit                          |                                                                                                                |                                                              | -                    | 75   | 240                   |      |
|                                 |                                                          | 2-Gbit                          |                                                                                                                |                                                              | -                    | 150  | 480                   |      |
| I <sub>CC3</sub> <sup>(2)</sup> | Supply current<br>(Program/Erase/Blank Check)            |                                 | Program/Erase<br>controller active                                                                             | V <sub>PP</sub> /WP# =<br>V <sub>IL</sub> or V <sub>IH</sub> | -                    | 35   | 50                    | mA   |
|                                 |                                                          |                                 |                                                                                                                | V <sub>PP</sub> /WP# = V <sub>PPH</sub>                      | -                    | 35   | 50                    | mA   |
| I <sub>PP1</sub>                | V <sub>PP</sub> current                                  | Read                            | V <sub>PP</sub> /WP# ≤ V <sub>CC</sub>                                                                         |                                                              | -                    | 0.2  | 5                     | μA   |
|                                 |                                                          | Standby                         | V <sub>PP</sub> /WP# ≤ V <sub>CC</sub>                                                                         |                                                              | -                    | 2    | 15                    | μA   |
| I <sub>PP2</sub>                |                                                          | Reset                           | RST# = V <sub>SS</sub> ± 0.2 V                                                                                 |                                                              | -                    | 0.2  | 5                     | μA   |
| I <sub>PP3</sub>                |                                                          | Program<br>operation<br>ongoing | V <sub>PP</sub> /WP# = 12 V ± 5%                                                                               |                                                              | -                    | 0.05 | 0.10                  | mA   |
|                                 |                                                          |                                 | V <sub>PP</sub> /WP# = V <sub>CC</sub>                                                                         |                                                              | -                    | 0.05 | 0.10                  | mA   |
| I <sub>PP4</sub>                |                                                          | Erase<br>operation<br>ongoing   | V <sub>PP</sub> /WP# = 12 V ± 5%                                                                               |                                                              | -                    | 0.05 | 0.10                  | mA   |
|                                 |                                                          |                                 | V <sub>PP</sub> /WP# = V <sub>CC</sub>                                                                         |                                                              | -                    | 0.05 | 0.10                  | mA   |
| V <sub>IL</sub>                 | Input Low voltage                                        |                                 | V <sub>CC</sub> ≥ 2.7 V                                                                                        |                                                              | -0.5                 | -    | 0.8                   | V    |
| V <sub>IH</sub>                 | Input High voltage                                       |                                 | V <sub>CC</sub> ≥ 2.7 V                                                                                        |                                                              | 0.7V <sub>CCQ</sub>  | -    | V <sub>CCQ</sub> +0.4 | V    |
| V <sub>OL</sub>                 | Output Low voltage                                       |                                 | I <sub>OL</sub> = 100 μA, V <sub>CC</sub> = V <sub>CC(min)</sub> ,<br>V <sub>CCQ</sub> = V <sub>CCQ(min)</sub> |                                                              | -                    | -    | 0.15V <sub>CCQ</sub>  | V    |
| V <sub>OH</sub>                 | Output High voltage                                      |                                 | I <sub>OH</sub> = 100 μA, V <sub>CC</sub> = V <sub>CC(min)</sub> ,<br>V <sub>CCQ</sub> = V <sub>CCQ(min)</sub> |                                                              | 0.85V <sub>CCQ</sub> | -    | -                     | V    |
| V <sub>PPLK</sub>               | V <sub>PP</sub> Lock-Out voltage                         |                                 | -                                                                                                              |                                                              | -                    | -    | 0.4                   | V    |
| V <sub>PPH</sub>                | Voltage for V <sub>PP</sub> /WP# Program<br>acceleration |                                 | -                                                                                                              |                                                              | 11.5                 | -    | 12.5                  | V    |
| V <sub>LKO</sub> <sup>(2)</sup> | Program/Erase lockout supply<br>voltage                  |                                 | -                                                                                                              |                                                              | 2.3                  | -    | -                     | V    |

1. The maximum input leakage current is  $\pm 5 \mu\text{A}$  on the  $V_{PP}/WP\#$  pin.
2. Sampled only, not 100% tested.



**Figure 17. Random Read AC waveforms (8-bit mode)****Figure 18. Random Read AC waveforms (16-bit mode)**

Figure 19. BYTE# Transition AC Waveform




Figure 20. Page Read AC waveforms (16-bit mode)




Table 23. Read AC characteristics


| Symbol           | Alt.       | Parameter                            | Test condition                       | Limit | M29EW         |      | Unit |
|------------------|------------|--------------------------------------|--------------------------------------|-------|---------------|------|------|
|                  |            |                                      |                                      |       | Fortified BGA | TSOP |      |
| $t_{AVAV}$       | $t_{RC}$   | Address Valid to Next Address Valid  | $CE\# = V_{IL}$ ,<br>$OE\# = V_{IL}$ | Min   | 100           | 110  | ns   |
| $t_{AVQV}$       | $t_{ACC}$  | Address Valid to Output Valid        | $CE\# = V_{IL}$ ,<br>$OE\# = V_{IL}$ | Max   | 100           | 110  | ns   |
| $t_{AVQV1}$      | $t_{PAGE}$ | Address Valid to Output Valid (Page) | $CE\# = V_{IL}$ ,<br>$OE\# = V_{IL}$ | Max   | 25            |      | ns   |
| $t_{ELQX}^{(1)}$ | $t_{LZ}$   | Chip Enable Low to Output Transition | $OE\# = V_{IL}$                      | Min   | 0             |      | ns   |

Table 23. Read AC characteristics

| Symbol                                 | Alt.                     | Parameter                                                             | Test condition  | Limit | M29EW         |      | Unit    |
|----------------------------------------|--------------------------|-----------------------------------------------------------------------|-----------------|-------|---------------|------|---------|
|                                        |                          |                                                                       |                 |       | Fortified BGA | TSOP |         |
| $t_{ELQV}$                             | $t_E$                    | Chip Enable Low to Output Valid                                       | $OE\# = V_{IL}$ | Max   | 100           | 110  | ns      |
| $t_{GLQX}^{(1)}$                       | $t_{OLZ}$                | Output Enable Low to Output Transition                                | $CE\# = V_{IL}$ | Min   | 0             |      | ns      |
| $t_{GLQV}$                             | $t_{OE}$                 | Output Enable Low to Output Valid                                     | $CE\# = V_{IL}$ | Max   | 25            |      | ns      |
| $t_{EHQZ}^{(1)}$                       | $t_{HZ}$                 | Chip Enable High to Output Hi-Z                                       | $OE\# = V_{IL}$ | Max   | 20            |      | ns      |
| $t_{GHQZ}^{(1)}$                       | $t_{DF}$                 | Output Enable High to Output Hi-Z                                     | $CE\# = V_{IL}$ | Max   | 15            |      | ns      |
| $t_{EHQX}$<br>$t_{GHQX}$<br>$t_{AXQX}$ | $t_{OH}$                 | Chip Enable, Output Enable or Address Transition to Output Transition | -               | Min   | 0             |      | ns      |
| $t_{ELBL}$<br>$t_{ELBH}$               | $t_{ELFL}$<br>$t_{ELFH}$ | Chip Enable to BYTE# Low or High                                      | -               | Max   | 10            |      | ns      |
| $t_{BLQV}$                             | $t_{FLQV}$               | BYTE# Low to Output Valid                                             | -               | Max   | 1             |      | $\mu s$ |
| $t_{BHQV}$                             | $t_{FHQV}$               | BYTE# High to Output Valid                                            | -               | Max   | 1             |      | $\mu s$ |

1. Sampled only, not 100% tested.


Figure 21. Write Enable Controlled Program waveforms (8-bit mode)



1. Only the third and fourth cycles of the Program command are represented. The Program command is followed by the check of Status Register Data Polling bit and by a read operation that outputs the data, DOUT, programmed by the previous

Program command.

2. PA is the address of the memory location to be programmed. PD is the data to be programmed.
3. DQ7 is the complement of the data bit being programmed to DQ7 (see [Section 7.2.1: Data Polling bit \(DQ7\)](#)).
4. See [Table 24: Write AC characteristics, Write Enable Controlled](#), [Table 25: Write AC characteristics, Chip Enable Controlled](#) and [Table 23: Read AC characteristics](#) for details on the timings.


**Figure 22. Write Enable Controlled Program waveforms (16-bit mode)**

1. Only the third and fourth cycles of the Program command are represented. The Program command is followed by the check of Status Register Data Polling bit and by a read operation that outputs the data, DOUT, programmed by the previous Program command.
2. PA is the address of the memory location to be programmed. PD is the data to be programmed.
3. DQ7 is the complement of the data bit being programmed to DQ7 (see [Section 7.2.1: Data Polling bit \(DQ7\)](#)).
4. See [Table 24: Write AC characteristics, Write Enable Controlled](#), [Table 25: Write AC characteristics, Chip Enable Controlled](#) and [Table 23: Read AC characteristics](#) for details on the timings.


**Table 24. Write AC characteristics, Write Enable Controlled**

| Symbol           | Alt         | Parameter                                  | Limit | Fortified BGA | TSOP | Unit    |
|------------------|-------------|--------------------------------------------|-------|---------------|------|---------|
| $t_{AVAV}$       | $t_{WC}$    | Address Valid to Next Address Valid        | Min   | 100           | 110  | ns      |
| $t_{ELWL}$       | $t_{CS}$    | Chip Enable Low to Write Enable Low        | Min   | 0             |      | ns      |
| $t_{WLWH}$       | $t_{WP}$    | Write Enable Low to Write Enable High      | Min   | 35            |      | ns      |
| $t_{DVWH}^{(1)}$ | $t_{DS}$    | Input Valid to Write Enable High           | Min   | 30            |      | ns      |
| $t_{WHDX}$       | $t_{DH}$    | Write Enable High to Input Transition      | Min   | 0             |      | ns      |
| $t_{WHEH}$       | $t_{CH}$    | Write Enable High to Chip Enable High      | Min   | 0             |      | ns      |
| $t_{WHWL}$       | $t_{WPH}$   | Write Enable High to Write Enable Low      | Min   | 20            |      | ns      |
| $t_{AVWL}$       | $t_{AS}$    | Address Valid to Write Enable Low          | Min   | 0             |      | ns      |
| $t_{WLAX}$       | $t_{AH}$    | Write Enable Low to Address Transition     | Min   | 45            |      | ns      |
| $t_{GHWL}$       | -           | Output Enable High to Write Enable Low     | Min   | 0             |      | ns      |
| $t_{WHGL}$       | $t_{OEH}$   | Write Enable High to Output Enable Low     | Min   | 0             |      | ns      |
| $t_{WHRL}^{(2)}$ | $t_{BUSY}$  | Program/Erase Valid to RY/BY# Low          | Max   | 30            |      | ns      |
| $t_{VCHEL}$      | $t_{VCS}$   | $V_{CC}$ High to Chip Enable Low           | Min   | 300           |      | $\mu$ s |
| $t_{WHWH1}$      | $t_{WHWH1}$ | write buffer program operation (512 Words) | Typ   | 900           |      | $\mu$ s |
|                  |             | program operation single word or byte      | Typ   | 210           |      | $\mu$ s |

1. This specification must be complied with by customer's writing timing. Any violation to this timing specification may damage the flash device permanently.
2. Sampled only, not 100% tested.


**Figure 23. Chip Enable Controlled Program waveforms (8-bit mode)**

1. Only the third and fourth cycles of the Program command are represented. The Program command is followed by the check of Status Register Data Polling bit.
2. PA is the address of the memory location to be programmed. PD is the data to be programmed.
3. DQ7 is the complement of the data bit being programmed to DQ7 (see [Section 7.2.1: Data Polling bit \(DQ7\)](#)).
4. See [Table 24: Write AC characteristics, Write Enable Controlled](#), [Table 25: Write AC characteristics, Chip Enable Controlled](#) and [Table 23: Read AC characteristics](#) for details on the timings.

**Figure 24. Chip Enable Controlled Program waveforms (16-bit mode)**

1. Only the third and fourth cycles of the Program command are represented. The Program command is followed by the check of Status Register Data Polling bit.
2. PA is the address of the memory location to be programmed. PD is the data to be programmed.
3. DQ7 is the complement of the data bit being programmed to DQ7 (see [Section 7.2.1: Data Polling bit \(DQ7\)](#)).
4. See [Table 24: Write AC characteristics, Write Enable Controlled](#), [Table 25: Write AC characteristics, Chip Enable Controlled](#) and [Table 23: Read AC characteristics](#) for details on the timings.

Figure 25. Chip/Block Erase waveforms (8-bit mode)



1. For a Chip Erase command, addresses and data are 555h and 10h, respectively, while they are BAd and 30h for a Block Erase command.
2. BAd is the block address.
3. See [Table 24: Write AC characteristics, Write Enable Controlled](#), [Table 25: Write AC characteristics, Chip Enable Controlled](#) and [Table 23: Read AC characteristics](#) for details on the timings.

Table 25. Write AC characteristics, Chip Enable Controlled

| Symbol           | Alt.        | Parameter                                  | Limit | Fortified BGA | TSOP | Unit    |
|------------------|-------------|--------------------------------------------|-------|---------------|------|---------|
| $t_{AVAV}$       | $t_{WC}$    | Address Valid to Next Address Valid        | Min   | 100           | 110  | ns      |
| $t_{WLEL}$       | $t_{WS}$    | Write Enable Low to Chip Enable Low        | Min   | 0             |      | ns      |
| $t_{ELEH}$       | $t_{CP}$    | Chip Enable Low to Chip Enable High        | Min   | 35            |      | ns      |
| $t_{DVEH}^{(1)}$ | $t_{DS}$    | Input Valid to Chip Enable High            | Min   | 30            |      | ns      |
| $t_{EHDX}$       | $t_{DH}$    | Chip Enable High to Input Transition       | Min   | 0             |      | ns      |
| $t_{EHWL}$       | $t_{WH}$    | Chip Enable High to Write Enable High      | Min   | 0             |      | ns      |
| $t_{EHEL}$       | $t_{CPH}$   | Chip Enable High to Chip Enable Low        | Min   | 20            |      | ns      |
| $t_{AVEL}$       | $t_{AS}$    | Address Valid to Chip Enable Low           | Min   | 0             |      | ns      |
| $t_{ELAX}$       | $t_{AH}$    | Chip Enable Low to Address Transition      | Min   | 45            |      | ns      |
| $t_{GHEL}$       | -           | Output Enable High Chip Enable Low         | Min   | 0             |      | ns      |
| $t_{WVWH1}$      | $t_{WVWH1}$ | write buffer program operation (512 Words) | Typ   | 900           |      | $\mu s$ |
|                  |             | program operation single word or byte      | Typ   | 210           |      | $\mu s$ |

1. This specification must be complied with by customer's writing timing. The result would be unpredictable if there's any violation to this timing specification.

Figure 26. Reset AC waveforms (no program/erase in progress)




Figure 27. Reset during program/erase operation AC waveforms




Table 26. Reset AC characteristics

| Symbol                     | Alt.        | Parameter                                                           | Min | Max | Unit    |
|----------------------------|-------------|---------------------------------------------------------------------|-----|-----|---------|
| $t_{PLRH}^{(1)}$           | $t_{READY}$ | RST# Low to Read mode, during Program or Erase                      | -   | 32  | $\mu s$ |
| $t_{PLPH}$                 | $t_{RP}$    | RST# Pulse width                                                    | 100 | -   | ns      |
| $t_{PHEL}, t_{PHGL}^{(1)}$ | $t_{RH}$    | RST# High to Write Enable Low, Chip Enable Low, Output Enable Low   | 50  | -   | ns      |
| -                          | $t_{RPD}$   | RST# Low to Standby mode, during Read mode                          | 10  | -   | $\mu s$ |
|                            |             | RST# Low to Standby mode, during Program or Erase                   | 50  | -   | $\mu s$ |
| $t_{RHEL}, t_{RHGL}^{(1)}$ | $t_{RB}$    | RY/BY# High to Write Enable Low, Chip Enable Low, Output Enable Low | 0   | -   | ns      |

1. Sampled only, not 100% tested.

Figure 28. Accelerated program timing waveforms






Figure 29. Data polling AC waveforms



1. DQ7 returns valid data bit when the ongoing Program or Erase command is completed.
2. See [Table 27: Accelerated Program and Data Polling/Data Toggle AC characteristics](#) and [Table 23: Read AC characteristics](#) for details on the timings.

**Figure 30. Toggle/Alternative Toggle bit polling AC waveforms (8-bit mode)**

1. DQ6 stops toggling when the ongoing Program or Erase command is completed. DQ2 stops toggling when the in-progress Chip Erase or Block Erase command is completed.
2. See [Table 27: Accelerated Program and Data Polling/Data Toggle AC characteristics](#) and [Table 23: Read AC characteristics](#) for details on the timings.

**Table 27. Accelerated Program and Data Polling/Data Toggle AC characteristics**

| Symbol                 | Alt        | Parameter                                                         | Min | Max | Unit |
|------------------------|------------|-------------------------------------------------------------------|-----|-----|------|
| $t_{VHVPP}$            | -          | $V_{PP}/WP\#$ raising or falling time                             | 250 | -   | ns   |
| $t_{AXGL}$             | $t_{ASO}$  | Address setup time to Output Enable Low during Toggle bit polling | 15  | -   | ns   |
| $t_{GHAX}, t_{EHAX}$   | $t_{AHT}$  | Address hold time from Output Enable during Toggle bit polling    | 0   | -   | ns   |
| $t_{EHEL2}$            | $t_{EPH}$  | Chip Enable High during Toggle bit polling                        | 30  | -   | ns   |
| $t_{WHGL2}, t_{GHGL2}$ | $t_{OEHL}$ | Output Hold time during Data and Toggle bit polling               | 20  | -   | ns   |
| $t_{WHRL}$             | $t_{BUSY}$ | Program/Erase Valid to RY/BY# Low                                 | -   | 90  | ns   |

## 10 Programming and Erase Performance

**Table 28. Programming and Erase Performance**

| Parameter                        |                                            | Buffer Size | Byte | Word | Min     | Typ <sup>(1)(2)</sup> | Max <sup>(2)</sup> | Unit   |
|----------------------------------|--------------------------------------------|-------------|------|------|---------|-----------------------|--------------------|--------|
| Block Erase (128 kbytes)         |                                            | -           | -    | -    | -       | 0.8                   | 4                  | s      |
| Erase Suspend latency time       |                                            | -           | -    | -    | -       | 27                    | 32                 | μs     |
| Block Erase time-out             |                                            | -           | -    | -    | 50      | -                     | -                  | μs     |
| Byte Program                     | Single Byte Program                        | -           | -    | -    | -       | 210                   | 456                | μs     |
|                                  | Byte Write to Buffer Program               | 64          | 64   | -    | -       | 270                   | 716                | μs     |
|                                  |                                            | 128         | 128  | -    | -       | 310                   | 900                |        |
|                                  |                                            | 256         | 256  | -    | -       | 375                   | 1140               |        |
|                                  | Effective Write to Buffer Program per Byte | 64          | 1    | -    | -       | 4.22                  | 11.2               | μs     |
|                                  |                                            | 128         | 1    | -    | -       | 2.42                  | 7.00               |        |
|                                  |                                            | 256         | 1    | -    | -       | 1.46                  | 4.45               |        |
| Word Program                     | Single Word Program                        | -           | -    | -    | -       | 210                   | 456                | μs     |
|                                  | Word Write to Buffer Program               | 32          | -    | 32   | -       | 270                   | 716                | μs     |
|                                  |                                            | 64          | -    | 64   | -       | 310                   | 900                |        |
|                                  |                                            | 128         | -    | 128  | -       | 375                   | 1140               |        |
|                                  |                                            | 256         | -    | 256  | -       | 505                   | 1690               |        |
|                                  |                                            | 512         | -    | 512  | -       | 900                   | 3016               |        |
|                                  | Effective Write to Buffer Program per Word | 32          | -    | 1    | -       | 8.44                  | 22.4               | μs     |
|                                  |                                            | 64          | -    | 1    | -       | 4.84                  | 14.1               |        |
|                                  |                                            | 128         | -    | 1    | -       | 2.93                  | 8.90               |        |
|                                  |                                            | 256         | -    | 1    | -       | 1.97                  | 6.60               |        |
| 512                              |                                            | -           | 1    | -    | 1.76    | 5.89                  |                    |        |
| Program Suspend latency time     |                                            | -           | -    | -    | -       | 27                    | 32                 | μs     |
| Blank Check                      |                                            | -           | -    | -    | -       | 3.2                   | -                  | ms     |
| Program/Erase cycles (per block) |                                            | -           | -    | -    | 100,000 | -                     | -                  | Cycles |
| Erase to Suspend <sup>(3)</sup>  |                                            | -           | -    | -    | -       | 500                   | -                  | μs     |

1. Typical values measured at room temperature and nominal voltages.


2. Sampled, but not 100% tested.

3. Erase to Suspend is a typical time between an initial block erase or erase resume command and the a subsequent erase suspend command. Violating the specification repeatedly during any particular block erase may cause erase failures.

## 11 Package Mechanical Specifications

Numonyx offers these devices in lead-free TSOP, lead-free Fortified BGA, and leaded Fortified BGA packages. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label.

**Figure 31. TSOP56 – 56 lead thin small-outline package, 14 x 20 mm, package outline**




1. Drawing is not to scale.

**Table 29. TSOP56 – 56 lead thin small-outline package, 14 x 20 mm, package mechanical data**

| Symbol           | Millimeters |       |       | Inches |        |        |
|------------------|-------------|-------|-------|--------|--------|--------|
|                  | Typ         | Min   | Max   | Typ    | Min    | Max    |
| A                | –           | –     | 1.20  | –      | –      | 0.047  |
| A1               | 0.10        | 0.05  | 0.15  | 0.004  | 0.002  | 0.006  |
| A2               | 1.00        | 0.95  | 1.05  | 0.039  | 0.037  | 0.041  |
| B <sup>(1)</sup> | 0.22        | 0.17  | 0.27  | 0.0087 | 0.0067 | 0.0106 |
| C                | –           | 0.10  | 0.21  | –      | 0.004  | 0.008  |
| CP               | –           | –     | 0.10  | –      | –      | 0.004  |
| E                | 14.00       | 13.90 | 14.10 | 0.551  | 0.547  | 0.555  |
| D                | 20.00       | 19.80 | 20.20 | 0.787  | 0.780  | 0.795  |
| D1               | 18.40       | 18.30 | 18.50 | 0.724  | 0.720  | 0.728  |
| e                | 0.50        | –     | –     | 0.020  | –      | –      |
| L                | 0.60        | 0.50  | 0.70  | 0.024  | 0.020  | 0.028  |
| α                | 3           | 0     | 5     | 3      | 0      | 5      |

1. For legacy lead width, 0.15mm (Typ), 0.10mm (Min), 0.20mm (Max).

**Figure 32. Fortified BGA64 11 x 13 mm - 8 x 8 active ball array, package outline**

1. Drawing is not to scale.
2. Drawing is bottom view.

**Table 30. Fortified BGA64 11 x 13 mm - 8 x 8 active ball array, package mechanical data**

| Symbol | millimeters |       |       |
|--------|-------------|-------|-------|
|        | Typ         | Min   | Max   |
| A      | —           | —     | 1.40  |
| A1     | 0.49        | 0.40  | —     |
| A2     | 0.80        | —     | —     |
| b      | 0.60        | 0.55  | 0.65  |
| D      | 11.00       | 10.90 | 11.10 |
| D1     | 7.00        | —     | —     |
| ddd    | —           | —     | 0.10  |
| e      | 1.00        | —     | —     |
| E      | 13.00       | 12.90 | 13.10 |
| E1     | 7.00        | —     | —     |
| FD     | 2.00        | —     | —     |
| FE     | 3.00        | —     | —     |
| SD     | 0.50        | —     | —     |
| SE     | 0.50        | —     | —     |

## 12 Ordering Information

**Table 31. Ordering information scheme**

Example:

RC 28F 256 M29EW H \*

**Package**

RC = Fortified BGA64: 11 x 13 mm, leaded

JS = TSOP56: 14 x 20 mm, lead free, halogen free, RoHS compliant

PC = Fortified BGA64: 11 x 13 mm, lead free, halogen free, RoHS compliant

**Discrete/SCSP**

28F= NOR Parallel Interface

**Device Density**

256=256-Mbit

512=512-Mbit

00A=1-Gbit

00B=2-Gbit

**Device Type**

M29EW = 3V core, page, uniform block flash memory

**Device function**

H = highest block protected by  $V_{PP}/WP\#$

L = lowest block protected by  $V_{PP}/WP\#$

**Device features**

\* = Random digit to cover a combination of features, including packing media, special features, and specific customer request information.

**Note:** This product is also available with the Extended Memory Block Numonyx pre-locked. For further details and ordering information contact your nearest Numonyx sales office.

Devices are shipped from Numonyx factory with the memory content bits erased to '1'. For a list of available options (package, High/Low protect, etc.) or for further information on any aspect of the device, please contact your nearest Numonyx Sales Office.

**Table 32. Valid Combinations of M29EW Part Numbers**

| 256-Mbit        | 512-Mbit        | 1-Gbit          | 2-Gbit          |
|-----------------|-----------------|-----------------|-----------------|
| JS28F256M29EWH* | JS28F512M29EWH* | JS28F00AM29EWH* | JS28F00BM29EWH* |
| JS28F256M29EWL* | JS28F512M29EWL* | JS28F00AM29EWL* | PC28F00BM29EWH* |
| PC28F256M29EWH* | PC28F512M29EWH* | PC28F00AM29EWH* | RC28F00BM29EWH* |
| PC28F256M29EWL* | PC28F512M29EWL* | PC28F00AM29EWL* |                 |
| RC28F256M29EWH* | RC28F512M29EWH* | RC28F00AM29EWH* |                 |
| RC28F256M29EWL* | RC28F512M29EWL* | RC28F00AM29EWL* |                 |

**Note:** For further information on ordering products or for product part numbers, go to:  
<http://www.numonyx.com/en-US/MemoryProducts/Pages/PartNumberLookup.aspx>.

## Appendix A Memory Address Table

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 0            | 128 / 64                        | 0000000-001FFFF     | 0000000-000FFFF      |
| 1            | 128 / 64                        | 0020000-003FFFF     | 0010000-001FFFF      |
| 2            | 128 / 64                        | 0040000-005FFFF     | 0020000-002FFFF      |
| 3            | 128 / 64                        | 0060000-007FFFF     | 0030000-003FFFF      |
| 4            | 128 / 64                        | 0080000-009FFFF     | 0040000-004FFFF      |
| 5            | 128 / 64                        | 00A0000-00BFFFF     | 0050000-005FFFF      |
| 6            | 128 / 64                        | 00C0000-00DFFFF     | 0060000-006FFFF      |
| 7            | 128 / 64                        | 00E0000-00FFFFFF    | 0070000-007FFFF      |
| 8            | 128 / 64                        | 0100000-011FFFF     | 0080000-008FFFF      |
| 9            | 128 / 64                        | 0120000-013FFFF     | 0090000-009FFFF      |
| 10           | 128 / 64                        | 0140000-015FFFF     | 00A0000-00AFFFF      |
| 11           | 128 / 64                        | 0160000-017FFFF     | 00B0000-00BFFFF      |
| 12           | 128 / 64                        | 0180000-019FFFF     | 00C0000-00CFFFF      |
| 13           | 128 / 64                        | 01A0000-01BFFFF     | 00D0000-00DFFFF      |
| 14           | 128 / 64                        | 01C0000-01DFFFF     | 00E0000-00EFFFF      |
| 15           | 128 / 64                        | 01E0000-01FFFFFF    | 00F0000-00FFFFFF     |
| 16           | 128 / 64                        | 0200000-021FFFF     | 0100000-010FFFF      |
| 17           | 128 / 64                        | 0220000-023FFFF     | 0110000-011FFFF      |
| 18           | 128 / 64                        | 0240000-025FFFF     | 0120000-012FFFF      |
| 19           | 128 / 64                        | 0260000-027FFFF     | 0130000-013FFFF      |
| 20           | 128 / 64                        | 0280000-029FFFF     | 0140000-014FFFF      |
| 21           | 128 / 64                        | 02A0000-02BFFFF     | 0150000-015FFFF      |
| 22           | 128 / 64                        | 02C0000-02DFFFF     | 0160000-016FFFF      |
| 23           | 128 / 64                        | 02E0000-02FFFFFF    | 0170000-017FFFF      |
| 24           | 128 / 64                        | 0300000-031FFFF     | 0180000-018FFFF      |
| 25           | 128 / 64                        | 0320000-033FFFF     | 0190000-019FFFF      |
| 26           | 128 / 64                        | 0340000-035FFFF     | 01A0000-01AFFFF      |
| 27           | 128 / 64                        | 0360000-037FFFF     | 01B0000-01BFFFF      |
| 28           | 128 / 64                        | 0380000-039FFFF     | 01C0000-01CFFFF      |
| 29           | 128 / 64                        | 03A0000-03BFFFF     | 01D0000-01DFFFF      |
| 30           | 128 / 64                        | 03C0000-03DFFFF     | 01E0000-01EFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 31           | 128 / 64                        | 03E0000-03FFFFFF    | 01F0000-01FFFFFF     |
| 32           | 128 / 64                        | 0400000-041FFFFF    | 0200000-020FFFFF     |
| 33           | 128 / 64                        | 0420000-043FFFFF    | 0210000-021FFFFF     |
| 34           | 128 / 64                        | 0440000-045FFFFF    | 0220000-022FFFFF     |
| 35           | 128 / 64                        | 0460000-047FFFFF    | 0230000-023FFFFF     |
| 36           | 128 / 64                        | 0480000-049FFFFF    | 0240000-024FFFFF     |
| 37           | 128 / 64                        | 04A0000-04BFFFFF    | 0250000-025FFFFF     |
| 38           | 128 / 64                        | 04C0000-04DFFFFF    | 0260000-026FFFFF     |
| 39           | 128 / 64                        | 04E0000-04FFFFFF    | 0270000-027FFFFF     |
| 40           | 128 / 64                        | 0500000-051FFFFF    | 0280000-028FFFFF     |
| 41           | 128 / 64                        | 0520000-053FFFFF    | 0290000-029FFFFF     |
| 42           | 128 / 64                        | 0540000-055FFFFF    | 02A0000-02AFFFFF     |
| 43           | 128 / 64                        | 0560000-057FFFFF    | 02B0000-02BFFFFF     |
| 44           | 128 / 64                        | 0580000-059FFFFF    | 02C0000-02CFFFFF     |
| 45           | 128 / 64                        | 05A0000-05BFFFFF    | 02D0000-02DFFFFF     |
| 46           | 128 / 64                        | 05C0000-05DFFFFF    | 02E0000-02EFFFFF     |
| 47           | 128 / 64                        | 05E0000-05FFFFFF    | 02F0000-02FFFFFF     |
| 48           | 128 / 64                        | 0600000-061FFFFF    | 0300000-030FFFFF     |
| 49           | 128 / 64                        | 0620000-063FFFFF    | 0310000-031FFFFF     |
| 50           | 128 / 64                        | 0640000-065FFFFF    | 0320000-032FFFFF     |
| 51           | 128 / 64                        | 0660000-067FFFFF    | 0330000-033FFFFF     |
| 52           | 128 / 64                        | 0680000-069FFFFF    | 0340000-034FFFFF     |
| 53           | 128 / 64                        | 06A0000-06BFFFFF    | 0350000-035FFFFF     |
| 54           | 128 / 64                        | 06C0000-06DFFFFF    | 0360000-036FFFFF     |
| 55           | 128 / 64                        | 06E0000-06FFFFFF    | 0370000-037FFFFF     |
| 56           | 128 / 64                        | 0700000-071FFFFF    | 0380000-038FFFFF     |
| 57           | 128 / 64                        | 0720000-073FFFFF    | 0390000-039FFFFF     |
| 58           | 128 / 64                        | 0740000-075FFFFF    | 03A0000-03AFFFFF     |
| 59           | 128 / 64                        | 0760000-077FFFFF    | 03B0000-03BFFFFF     |
| 60           | 128 / 64                        | 0780000-079FFFFF    | 03C0000-03CFFFFF     |
| 61           | 128 / 64                        | 07A0000-07BFFFFF    | 03D0000-03DFFFFF     |
| 62           | 128 / 64                        | 07C0000-07DFFFFF    | 03E0000-03EFFFFF     |
| 63           | 128 / 64                        | 07E0000-07FFFFFF    | 03F0000-03FFFFFF     |
| 64           | 128 / 64                        | 0800000-081FFFFF    | 0400000-040FFFFF     |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 65           | 128 / 64                        | 0820000-083FFFF     | 0410000-041FFFF      |
| 66           | 128 / 64                        | 0840000-085FFFF     | 0420000-042FFFF      |
| 67           | 128 / 64                        | 0860000-087FFFF     | 0430000-043FFFF      |
| 68           | 128 / 64                        | 0880000-089FFFF     | 0440000-044FFFF      |
| 69           | 128 / 64                        | 08A0000-08BFFFF     | 0450000-045FFFF      |
| 70           | 128 / 64                        | 08C0000-08DFFFF     | 0460000-046FFFF      |
| 71           | 128 / 64                        | 08E0000-08FFFFFF    | 0470000-047FFFF      |
| 72           | 128 / 64                        | 0900000-091FFFF     | 0480000-048FFFF      |
| 73           | 128 / 64                        | 0920000-093FFFF     | 0490000-049FFFF      |
| 74           | 128 / 64                        | 0940000-095FFFF     | 04A0000-04AFFFF      |
| 75           | 128 / 64                        | 0960000-097FFFF     | 04B0000-04BFFFF      |
| 76           | 128 / 64                        | 0980000-099FFFF     | 04C0000-04CFFFF      |
| 77           | 128 / 64                        | 09A0000-09BFFFF     | 04D0000-04DFFFF      |
| 78           | 128 / 64                        | 09C0000-09DFFFF     | 04E0000-04EFFFF      |
| 79           | 128 / 64                        | 09E0000-09FFFFFF    | 04F0000-04FFFFFF     |
| 80           | 128 / 64                        | 0A00000-0A1FFFF     | 0500000-050FFFF      |
| 81           | 128 / 64                        | 0A20000-0A3FFFF     | 0510000-051FFFF      |
| 82           | 128 / 64                        | 0A40000-0A5FFFF     | 0520000-052FFFF      |
| 83           | 128 / 64                        | 0A60000-0A7FFFF     | 0530000-053FFFF      |
| 84           | 128 / 64                        | 0A80000-0A9FFFF     | 0540000-054FFFF      |
| 85           | 128 / 64                        | 0AA0000-0ABFFFF     | 0550000-055FFFF      |
| 86           | 128 / 64                        | 0AC0000-0ADFFFF     | 0560000-056FFFF      |
| 87           | 128 / 64                        | 0AE0000-0AFFFFFF    | 0570000-057FFFF      |
| 88           | 128 / 64                        | 0B00000-0B1FFFF     | 0580000-058FFFF      |
| 89           | 128 / 64                        | 0B20000-0B3FFFF     | 0590000-059FFFF      |
| 90           | 128 / 64                        | 0B40000-0B5FFFF     | 05A0000-05AFFFF      |
| 91           | 128 / 64                        | 0B60000-0B7FFFF     | 05B0000-05BFFFF      |
| 92           | 128 / 64                        | 0B80000-0B9FFFF     | 05C0000-05CFFFF      |
| 93           | 128 / 64                        | 0BA0000-0BBFFFF     | 05D0000-05DFFFF      |
| 94           | 128 / 64                        | 0BC0000-0BDFFFF     | 05E0000-05EFFFF      |
| 95           | 128 / 64                        | 0BE0000-0BFFFFFF    | 05F0000-05FFFFFF     |
| 96           | 128 / 64                        | 0C00000-0C1FFFF     | 0600000-060FFFF      |
| 97           | 128 / 64                        | 0C20000-0C3FFFF     | 0610000-061FFFF      |
| 98           | 128 / 64                        | 0C40000-0C5FFFF     | 0620000-062FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 99           | 128 / 64                        | 0C60000-0C7FFFF     | 0630000-063FFFF      |
| 100          | 128 / 64                        | 0C80000-0C9FFFF     | 0640000-064FFFF      |
| 101          | 128 / 64                        | 0CA0000-0CBFFFF     | 0650000-065FFFF      |
| 102          | 128 / 64                        | 0CC0000-0CDFFFF     | 0660000-066FFFF      |
| 103          | 128 / 64                        | 0CE0000-0CFFFFFF    | 0670000-067FFFF      |
| 104          | 128 / 64                        | 0D00000-0D1FFFF     | 0680000-068FFFF      |
| 105          | 128 / 64                        | 0D20000-0D3FFFF     | 0690000-069FFFF      |
| 106          | 128 / 64                        | 0D40000-0D5FFFF     | 06A0000-06AFFFF      |
| 107          | 128 / 64                        | 0D60000-0D7FFFF     | 06B0000-06BFFFF      |
| 108          | 128 / 64                        | 0D80000-0D9FFFF     | 06C0000-06CFFFF      |
| 109          | 128 / 64                        | 0DA0000-0DBFFFF     | 06D0000-06DFFFF      |
| 110          | 128 / 64                        | 0DC0000-0DDFFFF     | 06E0000-06EFFFF      |
| 111          | 128 / 64                        | 0DE0000-0DFFFFFF    | 06F0000-06FFFFFF     |
| 112          | 128 / 64                        | 0E00000-0E1FFFF     | 0700000-070FFFF      |
| 113          | 128 / 64                        | 0E20000-0E3FFFF     | 0710000-071FFFF      |
| 114          | 128 / 64                        | 0E40000-0E5FFFF     | 0720000-072FFFF      |
| 115          | 128 / 64                        | 0E60000-0E7FFFF     | 0730000-073FFFF      |
| 116          | 128 / 64                        | 0E80000-0E9FFFF     | 0740000-074FFFF      |
| 117          | 128 / 64                        | 0EA0000-0EBFFFF     | 0750000-075FFFF      |
| 118          | 128 / 64                        | 0EC0000-0EDFFFF     | 0760000-076FFFF      |
| 119          | 128 / 64                        | 0EE0000-0EFFFFFF    | 0770000-077FFFF      |
| 120          | 128 / 64                        | 0F00000-0F1FFFF     | 0780000-078FFFF      |
| 121          | 128 / 64                        | 0F20000-0F3FFFF     | 0790000-079FFFF      |
| 122          | 128 / 64                        | 0F40000-0F5FFFF     | 07A0000-07AFFFF      |
| 123          | 128 / 64                        | 0F60000-0F7FFFF     | 07B0000-07BFFFF      |
| 124          | 128 / 64                        | 0F80000-0F9FFFF     | 07C0000-07CFFFF      |
| 125          | 128 / 64                        | 0FA0000-0FBFFFF     | 07D0000-07DFFFF      |
| 126          | 128 / 64                        | 0FC0000-0FDFFFF     | 07E0000-07EFFFF      |
| 127          | 128 / 64                        | 0FE0000-0FFFFFF     | 07F0000-07FFFFFF     |
| 128          | 128 / 64                        | 1000000-101FFFF     | 0800000-080FFFF      |
| 129          | 128 / 64                        | 1020000-103FFFF     | 0810000-081FFFF      |
| 130          | 128 / 64                        | 1040000-105FFFF     | 0820000-082FFFF      |
| 131          | 128 / 64                        | 1060000-107FFFF     | 0830000-083FFFF      |
| 132          | 128 / 64                        | 1080000-109FFFF     | 0840000-084FFFF      |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 133          | 128 / 64                        | 10A0000-10BFFFF     | 0850000-085FFFF      |
| 134          | 128 / 64                        | 10C0000-10DFFFF     | 0860000-086FFFF      |
| 135          | 128 / 64                        | 10E0000-10FFFFFF    | 0870000-087FFFF      |
| 136          | 128 / 64                        | 1100000-111FFFF     | 0880000-088FFFF      |
| 137          | 128 / 64                        | 1120000-113FFFF     | 0890000-089FFFF      |
| 138          | 128 / 64                        | 1140000-115FFFF     | 08A0000-08AFFFF      |
| 139          | 128 / 64                        | 1160000-117FFFF     | 08B0000-08BFFFF      |
| 140          | 128 / 64                        | 1180000-119FFFF     | 08C0000-08CFFFF      |
| 141          | 128 / 64                        | 11A0000-11BFFFF     | 08D0000-08DFFFF      |
| 142          | 128 / 64                        | 11C0000-11DFFFF     | 08E0000-08EFFFF      |
| 143          | 128 / 64                        | 11E0000-11FFFFFF    | 08F0000-08FFFFFF     |
| 144          | 128 / 64                        | 1200000-121FFFF     | 0900000-090FFFF      |
| 145          | 128 / 64                        | 1220000-123FFFF     | 0910000-091FFFF      |
| 146          | 128 / 64                        | 1240000-125FFFF     | 0920000-092FFFF      |
| 147          | 128 / 64                        | 1260000-127FFFF     | 0930000-093FFFF      |
| 148          | 128 / 64                        | 1280000-129FFFF     | 0940000-094FFFF      |
| 149          | 128 / 64                        | 12A0000-12BFFFF     | 0950000-095FFFF      |
| 150          | 128 / 64                        | 12C0000-12DFFFF     | 0960000-096FFFF      |
| 151          | 128 / 64                        | 12E0000-12FFFFFF    | 0970000-097FFFF      |
| 152          | 128 / 64                        | 1300000-131FFFF     | 0980000-098FFFF      |
| 153          | 128 / 64                        | 1320000-133FFFF     | 0990000-099FFFF      |
| 154          | 128 / 64                        | 1340000-135FFFF     | 09A0000-09AFFFF      |
| 155          | 128 / 64                        | 1360000-137FFFF     | 09B0000-09BFFFF      |
| 156          | 128 / 64                        | 1380000-139FFFF     | 09C0000-09CFFFF      |
| 157          | 128 / 64                        | 13A0000-13BFFFF     | 09D0000-09DFFFF      |
| 158          | 128 / 64                        | 13C0000-13DFFFF     | 09E0000-09EFFFF      |
| 159          | 128 / 64                        | 13E0000-13FFFFFF    | 09F0000-09FFFFFF     |
| 160          | 128 / 64                        | 1400000-141FFFF     | 0A00000-0A0FFFF      |
| 161          | 128 / 64                        | 1420000-143FFFF     | 0A10000-0A1FFFF      |
| 162          | 128 / 64                        | 1440000-145FFFF     | 0A20000-0A2FFFF      |
| 163          | 128 / 64                        | 1460000-147FFFF     | 0A30000-0A3FFFF      |
| 164          | 128 / 64                        | 1480000-149FFFF     | 0A40000-0A4FFFF      |
| 165          | 128 / 64                        | 14A0000-14BFFFF     | 0A50000-0A5FFFF      |
| 166          | 128 / 64                        | 14C0000-14DFFFF     | 0A60000-0A6FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 167          | 128 / 64                        | 14E0000-14FFFFFF    | 0A70000-0A7FFFFF     |
| 168          | 128 / 64                        | 1500000-151FFFFF    | 0A80000-0A8FFFFF     |
| 169          | 128 / 64                        | 1520000-153FFFFF    | 0A90000-0A9FFFFF     |
| 170          | 128 / 64                        | 1540000-155FFFFF    | 0AA0000-0AAFFFFF     |
| 171          | 128 / 64                        | 1560000-157FFFFF    | 0AB0000-0ABFFFFF     |
| 172          | 128 / 64                        | 1580000-159FFFFF    | 0AC0000-0ACFFFFF     |
| 173          | 128 / 64                        | 15A0000-15BFFFFF    | 0AD0000-0ADFFFFF     |
| 174          | 128 / 64                        | 15C0000-15DFFFFF    | 0AE0000-0AEFFFFF     |
| 175          | 128 / 64                        | 15E0000-15FFFFFFF   | 0AF0000-0AFFFFFF     |
| 176          | 128 / 64                        | 1600000-161FFFFF    | 0B00000-0B0FFFFF     |
| 177          | 128 / 64                        | 1620000-163FFFFF    | 0B10000-0B1FFFFF     |
| 178          | 128 / 64                        | 1640000-165FFFFF    | 0B20000-0B2FFFFF     |
| 179          | 128 / 64                        | 1660000-167FFFFF    | 0B30000-0B3FFFFF     |
| 180          | 128 / 64                        | 1680000-169FFFFF    | 0B40000-0B4FFFFF     |
| 181          | 128 / 64                        | 16A0000-16BFFFFF    | 0B50000-0B5FFFFF     |
| 182          | 128 / 64                        | 16C0000-16DFFFFF    | 0B60000-0B6FFFFF     |
| 183          | 128 / 64                        | 16E0000-16FFFFFFF   | 0B70000-0B7FFFFF     |
| 184          | 128 / 64                        | 1700000-171FFFFF    | 0B80000-0B8FFFFF     |
| 185          | 128 / 64                        | 1720000-173FFFFF    | 0B90000-0B9FFFFF     |
| 186          | 128 / 64                        | 1740000-175FFFFF    | 0BA0000-0BAFFFFF     |
| 187          | 128 / 64                        | 1760000-177FFFFF    | 0BB0000-0BBFFFFF     |
| 188          | 128 / 64                        | 1780000-179FFFFF    | 0BC0000-0BCFFFFF     |
| 189          | 128 / 64                        | 17A0000-17BFFFFF    | 0BD0000-0BDFFFFF     |
| 190          | 128 / 64                        | 17C0000-17DFFFFF    | 0BE0000-0BEFFFFF     |
| 191          | 128 / 64                        | 17E0000-17FFFFFFF   | 0BF0000-0BFFFFFFF    |
| 192          | 128 / 64                        | 1800000-181FFFFF    | 0C00000-0C0FFFFF     |
| 193          | 128 / 64                        | 1820000-183FFFFF    | 0C10000-0C1FFFFF     |
| 194          | 128 / 64                        | 1840000-185FFFFF    | 0C20000-0C2FFFFF     |
| 195          | 128 / 64                        | 1860000-187FFFFF    | 0C30000-0C3FFFFF     |
| 196          | 128 / 64                        | 1880000-189FFFFF    | 0C40000-0C4FFFFF     |
| 197          | 128 / 64                        | 18A0000-18BFFFFF    | 0C50000-0C5FFFFF     |
| 198          | 128 / 64                        | 18C0000-18DFFFFF    | 0C60000-0C6FFFFF     |
| 199          | 128 / 64                        | 18E0000-18FFFFFFF   | 0C70000-0C7FFFFF     |
| 200          | 128 / 64                        | 1900000-191FFFFF    | 0C80000-0C8FFFFF     |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 201          | 128 / 64                        | 1920000-193FFFF     | 0C90000-0C9FFFF      |
| 202          | 128 / 64                        | 1940000-195FFFF     | 0CA0000-0CAFFFF      |
| 203          | 128 / 64                        | 1960000-197FFFF     | 0CB0000-0CBFFFF      |
| 204          | 128 / 64                        | 1980000-199FFFF     | 0CC0000-0CCFFFF      |
| 205          | 128 / 64                        | 19A0000-19BFFFF     | 0CD0000-0CDFFFF      |
| 206          | 128 / 64                        | 19C0000-19DFFFF     | 0CE0000-0CEFFFF      |
| 207          | 128 / 64                        | 19E0000-19FFFFFF    | 0CF0000-0CFFFFFF     |
| 208          | 128 / 64                        | 1A00000-1A1FFFF     | 0D00000-0D0FFFF      |
| 209          | 128 / 64                        | 1A20000-1A3FFFF     | 0D10000-0D1FFFF      |
| 210          | 128 / 64                        | 1A40000-1A5FFFF     | 0D20000-0D2FFFF      |
| 211          | 128 / 64                        | 1A60000-1A7FFFF     | 0D30000-0D3FFFF      |
| 212          | 128 / 64                        | 1A80000-1A9FFFF     | 0D40000-0D4FFFF      |
| 213          | 128 / 64                        | 1AA0000-1ABFFFF     | 0D50000-0D5FFFF      |
| 214          | 128 / 64                        | 1AC0000-1ADFFFF     | 0D60000-0D6FFFF      |
| 215          | 128 / 64                        | 1AE0000-1AFFFFFF    | 0D70000-0D7FFFF      |
| 216          | 128 / 64                        | 1B00000-1B1FFFF     | 0D80000-0D8FFFF      |
| 217          | 128 / 64                        | 1B20000-1B3FFFF     | 0D90000-0D9FFFF      |
| 218          | 128 / 64                        | 1B40000-1B5FFFF     | 0DA0000-0DAFFFF      |
| 219          | 128 / 64                        | 1B60000-1B7FFFF     | 0DB0000-0DBFFFF      |
| 220          | 128 / 64                        | 1B80000-1B9FFFF     | 0DC0000-0DCFFFF      |
| 221          | 128 / 64                        | 1BA0000-1BBFFFF     | 0DD0000-0DDFFFF      |
| 222          | 128 / 64                        | 1BC0000-1BDFFFF     | 0DE0000-0DEFFFF      |
| 223          | 128 / 64                        | 1BE0000-1BFFFFFF    | 0DF0000-0DFFFFFF     |
| 224          | 128 / 64                        | 1C00000-1C1FFFF     | 0E00000-0E0FFFF      |
| 225          | 128 / 64                        | 1C20000-1C3FFFF     | 0E10000-0E1FFFF      |
| 226          | 128 / 64                        | 1C40000-1C5FFFF     | 0E20000-0E2FFFF      |
| 227          | 128 / 64                        | 1C60000-1C7FFFF     | 0E30000-0E3FFFF      |
| 228          | 128 / 64                        | 1C80000-1C9FFFF     | 0E40000-0E4FFFF      |
| 229          | 128 / 64                        | 1CA0000-1CBFFFF     | 0E50000-0E5FFFF      |
| 230          | 128 / 64                        | 1CC0000-1CDFFFF     | 0E60000-0E6FFFF      |
| 231          | 128 / 64                        | 1CE0000-1CFFFFFF    | 0E70000-0E7FFFF      |
| 232          | 128 / 64                        | 1D00000-1D1FFFF     | 0E80000-0E8FFFF      |
| 233          | 128 / 64                        | 1D20000-1D3FFFF     | 0E90000-0E9FFFF      |
| 234          | 128 / 64                        | 1D40000-1D5FFFF     | 0EA0000-0EAFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 235          | 128 / 64                        | 1D60000-1D7FFFF     | 0EB0000-0EBFFFF      |
| 236          | 128 / 64                        | 1D80000-1D9FFFF     | 0EC0000-0ECFFFF      |
| 237          | 128 / 64                        | 1DA0000-1DBFFFF     | 0ED0000-0EDFFFF      |
| 238          | 128 / 64                        | 1DC0000-1DDFFFF     | 0EE0000-0EEFFFF      |
| 239          | 128 / 64                        | 1DE0000-1DFFFFFF    | 0EF0000-0EFFFFFF     |
| 240          | 128 / 64                        | 1E00000-1E1FFFF     | 0F00000-0F0FFFF      |
| 241          | 128 / 64                        | 1E20000-1E3FFFF     | 0F10000-0F1FFFF      |
| 242          | 128 / 64                        | 1E40000-1E5FFFF     | 0F20000-0F2FFFF      |
| 243          | 128 / 64                        | 1E60000-1E7FFFF     | 0F30000-0F3FFFF      |
| 244          | 128 / 64                        | 1E80000-1E9FFFF     | 0F40000-0F4FFFF      |
| 245          | 128 / 64                        | 1EA0000-1EBFFFF     | 0F50000-0F5FFFF      |
| 246          | 128 / 64                        | 1EC0000-1EDFFFF     | 0F60000-0F6FFFF      |
| 247          | 128 / 64                        | 1EE0000-1EFFFFFF    | 0F70000-0F7FFFF      |
| 248          | 128 / 64                        | 1F00000-1F1FFFF     | 0F80000-0F8FFFF      |
| 249          | 128 / 64                        | 1F20000-1F3FFFF     | 0F90000-0F9FFFF      |
| 250          | 128 / 64                        | 1F40000-1F5FFFF     | 0FA0000-0FAFFFF      |
| 251          | 128 / 64                        | 1F60000-1F7FFFF     | 0FB0000-0FBFFFF      |
| 252          | 128 / 64                        | 1F80000-1F9FFFF     | 0FC0000-0FCFFFF      |
| 253          | 128 / 64                        | 1FA0000-1FBFFFF     | 0FD0000-0FDFFFF      |
| 254          | 128 / 64                        | 1FC0000-1FDFFFF     | 0FE0000-0FEFFFF      |
| 255          | 128 / 64                        | 1FE0000-1FFFFFF     | 0FF0000-0FFFFFF      |
| 256          | 128 / 64                        | 2000000-201FFFF     | 1000000-100FFFF      |
| 257          | 128 / 64                        | 2020000-203FFFF     | 1010000-101FFFF      |
| 258          | 128 / 64                        | 2040000-205FFFF     | 1020000-102FFFF      |
| 259          | 128 / 64                        | 2060000-207FFFF     | 1030000-103FFFF      |
| 260          | 128 / 64                        | 2080000-209FFFF     | 1040000-104FFFF      |
| 261          | 128 / 64                        | 20A0000-20BFFFF     | 1050000-105FFFF      |
| 262          | 128 / 64                        | 20C0000-20DFFFF     | 1060000-106FFFF      |
| 263          | 128 / 64                        | 20E0000-20FFFFFF    | 1070000-107FFFF      |
| 264          | 128 / 64                        | 2100000-211FFFF     | 1080000-108FFFF      |
| 265          | 128 / 64                        | 2120000-213FFFF     | 1090000-109FFFF      |
| 266          | 128 / 64                        | 2140000-215FFFF     | 10A0000-10AFFFF      |
| 267          | 128 / 64                        | 2160000-217FFFF     | 10B0000-10BFFFF      |
| 268          | 128 / 64                        | 2180000-219FFFF     | 10C0000-10CFFFF      |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 269          | 128 / 64                        | 21A0000-21BFFFF     | 10D0000-10DFFFF      |
| 270          | 128 / 64                        | 21C0000-21DFFFF     | 10E0000-10EFFFF      |
| 271          | 128 / 64                        | 21E0000-21FFFFFF    | 10F0000-10FFFFFF     |
| 272          | 128 / 64                        | 2200000-221FFFF     | 1100000-110FFFF      |
| 273          | 128 / 64                        | 2220000-223FFFF     | 1110000-111FFFF      |
| 274          | 128 / 64                        | 2240000-225FFFF     | 1120000-112FFFF      |
| 275          | 128 / 64                        | 2260000-227FFFF     | 1130000-113FFFF      |
| 276          | 128 / 64                        | 2280000-229FFFF     | 1140000-114FFFF      |
| 277          | 128 / 64                        | 22A0000-22BFFFF     | 1150000-115FFFF      |
| 278          | 128 / 64                        | 22C0000-22DFFFF     | 1160000-116FFFF      |
| 279          | 128 / 64                        | 22E0000-22FFFFFF    | 1170000-117FFFF      |
| 280          | 128 / 64                        | 2300000-231FFFF     | 1180000-118FFFF      |
| 281          | 128 / 64                        | 2320000-233FFFF     | 1190000-119FFFF      |
| 282          | 128 / 64                        | 2340000-235FFFF     | 11A0000-11AFFFF      |
| 283          | 128 / 64                        | 2360000-237FFFF     | 11B0000-11BFFFF      |
| 284          | 128 / 64                        | 2380000-239FFFF     | 11C0000-11CFFFF      |
| 285          | 128 / 64                        | 23A0000-23BFFFF     | 11D0000-11DFFFF      |
| 286          | 128 / 64                        | 23C0000-23DFFFF     | 11E0000-11EFFFF      |
| 287          | 128 / 64                        | 23E0000-23FFFFFF    | 11F0000-11FFFFFF     |
| 288          | 128 / 64                        | 2400000-241FFFF     | 1200000-120FFFF      |
| 289          | 128 / 64                        | 2420000-243FFFF     | 1210000-121FFFF      |
| 290          | 128 / 64                        | 2440000-245FFFF     | 1220000-122FFFF      |
| 291          | 128 / 64                        | 2460000-247FFFF     | 1230000-123FFFF      |
| 292          | 128 / 64                        | 2480000-249FFFF     | 1240000-124FFFF      |
| 293          | 128 / 64                        | 24A0000-24BFFFF     | 1250000-125FFFF      |
| 294          | 128 / 64                        | 24C0000-24DFFFF     | 1260000-126FFFF      |
| 295          | 128 / 64                        | 24E0000-24FFFFFF    | 1270000-127FFFF      |
| 296          | 128 / 64                        | 2500000-251FFFF     | 1280000-128FFFF      |
| 297          | 128 / 64                        | 2520000-253FFFF     | 1290000-129FFFF      |
| 298          | 128 / 64                        | 2540000-255FFFF     | 12A0000-12AFFFF      |
| 299          | 128 / 64                        | 2560000-257FFFF     | 12B0000-12BFFFF      |
| 300          | 128 / 64                        | 2580000-259FFFF     | 12C0000-12CFFFF      |
| 301          | 128 / 64                        | 25A0000-25BFFFF     | 12D0000-12DFFFF      |
| 302          | 128 / 64                        | 25C0000-25DFFFF     | 12E0000-12EFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 303          | 128 / 64                        | 25E0000-25FFFFFF    | 12F0000-12FFFFFF     |
| 304          | 128 / 64                        | 2600000-261FFFFF    | 1300000-130FFFFF     |
| 305          | 128 / 64                        | 2620000-263FFFFF    | 1310000-131FFFFF     |
| 306          | 128 / 64                        | 2640000-265FFFFF    | 1320000-132FFFFF     |
| 307          | 128 / 64                        | 2660000-267FFFFF    | 1330000-133FFFFF     |
| 308          | 128 / 64                        | 2680000-269FFFFF    | 1340000-134FFFFF     |
| 309          | 128 / 64                        | 26A0000-26BFFFFF    | 1350000-135FFFFF     |
| 310          | 128 / 64                        | 26C0000-26DFFFFF    | 1360000-136FFFFF     |
| 311          | 128 / 64                        | 26E0000-26FFFFFF    | 1370000-137FFFFF     |
| 312          | 128 / 64                        | 2700000-271FFFFF    | 1380000-138FFFFF     |
| 313          | 128 / 64                        | 2720000-273FFFFF    | 1390000-139FFFFF     |
| 314          | 128 / 64                        | 2740000-275FFFFF    | 13A0000-13AFFFFF     |
| 315          | 128 / 64                        | 2760000-277FFFFF    | 13B0000-13BFFFFF     |
| 316          | 128 / 64                        | 2780000-279FFFFF    | 13C0000-13CFFFFF     |
| 317          | 128 / 64                        | 27A0000-27BFFFFF    | 13D0000-13DFFFFF     |
| 318          | 128 / 64                        | 27C0000-27DFFFFF    | 13E0000-13EFFFFF     |
| 319          | 128 / 64                        | 27E0000-27FFFFFF    | 13F0000-13FFFFFF     |
| 320          | 128 / 64                        | 2800000-281FFFFF    | 1400000-140FFFFF     |
| 321          | 128 / 64                        | 2820000-283FFFFF    | 1410000-141FFFFF     |
| 322          | 128 / 64                        | 2840000-285FFFFF    | 1420000-142FFFFF     |
| 323          | 128 / 64                        | 2860000-287FFFFF    | 1430000-143FFFFF     |
| 324          | 128 / 64                        | 2880000-289FFFFF    | 1440000-144FFFFF     |
| 325          | 128 / 64                        | 28A0000-28BFFFFF    | 1450000-145FFFFF     |
| 326          | 128 / 64                        | 28C0000-28DFFFFF    | 1460000-146FFFFF     |
| 327          | 128 / 64                        | 28E0000-28FFFFFF    | 1470000-147FFFFF     |
| 328          | 128 / 64                        | 2900000-291FFFFF    | 1480000-148FFFFF     |
| 329          | 128 / 64                        | 2920000-293FFFFF    | 1490000-149FFFFF     |
| 330          | 128 / 64                        | 2940000-295FFFFF    | 14A0000-14AFFFFF     |
| 331          | 128 / 64                        | 2960000-297FFFFF    | 14B0000-14BFFFFF     |
| 332          | 128 / 64                        | 2980000-299FFFFF    | 14C0000-14CFFFFF     |
| 333          | 128 / 64                        | 29A0000-29BFFFFF    | 14D0000-14DFFFFF     |
| 334          | 128 / 64                        | 29C0000-29DFFFFF    | 14E0000-14EFFFFF     |
| 335          | 128 / 64                        | 29E0000-29FFFFFF    | 14F0000-14FFFFFF     |
| 336          | 128 / 64                        | 2A00000-2A1FFFFF    | 1500000-150FFFFF     |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 337          | 128 / 64                        | 2A20000-2A3FFFF     | 1510000-151FFFF      |
| 338          | 128 / 64                        | 2A40000-2A5FFFF     | 1520000-152FFFF      |
| 339          | 128 / 64                        | 2A60000-2A7FFFF     | 1530000-153FFFF      |
| 340          | 128 / 64                        | 2A80000-2A9FFFF     | 1540000-154FFFF      |
| 341          | 128 / 64                        | 2AA0000-2ABFFFF     | 1550000-155FFFF      |
| 342          | 128 / 64                        | 2AC0000-2ADFFFF     | 1560000-156FFFF      |
| 343          | 128 / 64                        | 2AE0000-2AFFFFF     | 1570000-157FFFF      |
| 344          | 128 / 64                        | 2B00000-2B1FFFF     | 1580000-158FFFF      |
| 345          | 128 / 64                        | 2B20000-2B3FFFF     | 1590000-159FFFF      |
| 346          | 128 / 64                        | 2B40000-2B5FFFF     | 15A0000-15AFFFF      |
| 347          | 128 / 64                        | 2B60000-2B7FFFF     | 15B0000-15BFFFF      |
| 348          | 128 / 64                        | 2B80000-2B9FFFF     | 15C0000-15CFFFF      |
| 349          | 128 / 64                        | 2BA0000-2BBFFFF     | 15D0000-15DFFFF      |
| 350          | 128 / 64                        | 2BC0000-2BDFFFF     | 15E0000-15EFFFF      |
| 351          | 128 / 64                        | 2BE0000-2BFFFFF     | 15F0000-15FFFFF      |
| 352          | 128 / 64                        | 2C00000-2C1FFFF     | 1600000-160FFFF      |
| 353          | 128 / 64                        | 2C20000-2C3FFFF     | 1610000-161FFFF      |
| 354          | 128 / 64                        | 2C40000-2C5FFFF     | 1620000-162FFFF      |
| 355          | 128 / 64                        | 2C60000-2C7FFFF     | 1630000-163FFFF      |
| 356          | 128 / 64                        | 2C80000-2C9FFFF     | 1640000-164FFFF      |
| 357          | 128 / 64                        | 2CA0000-2CBFFFF     | 1650000-165FFFF      |
| 358          | 128 / 64                        | 2CC0000-2CDFFFF     | 1660000-166FFFF      |
| 359          | 128 / 64                        | 2CE0000-2CFFFFF     | 1670000-167FFFF      |
| 360          | 128 / 64                        | 2D00000-2D1FFFF     | 1680000-068FFFF      |
| 361          | 128 / 64                        | 2D20000-2D3FFFF     | 1690000-169FFFF      |
| 362          | 128 / 64                        | 2D40000-2D5FFFF     | 16A0000-16AFFFF      |
| 363          | 128 / 64                        | 2D60000-2D7FFFF     | 16B0000-16BFFFF      |
| 364          | 128 / 64                        | 2D80000-2D9FFFF     | 16C0000-16CFFFF      |
| 365          | 128 / 64                        | 2DA0000-2DBFFFF     | 16D0000-16DFFFF      |
| 366          | 128 / 64                        | 2DC0000-2DDFFFF     | 16E0000-16EFFFF      |
| 367          | 128 / 64                        | 2DE0000-2DFFFFF     | 16F0000-16FFFFF      |
| 368          | 128 / 64                        | 2E00000-2E1FFFF     | 1700000-170FFFF      |
| 369          | 128 / 64                        | 2E20000-2E3FFFF     | 1710000-171FFFF      |
| 370          | 128 / 64                        | 2E40000-2E5FFFF     | 1720000-172FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 371          | 128 / 64                        | 2E60000-2E7FFFF     | 1730000-173FFFF      |
| 372          | 128 / 64                        | 2E80000-2E9FFFF     | 1740000-174FFFF      |
| 373          | 128 / 64                        | 2EA0000-2EBFFFF     | 1750000-175FFFF      |
| 374          | 128 / 64                        | 2EC0000-2EDFFFF     | 1760000-176FFFF      |
| 375          | 128 / 64                        | 2EE0000-2EFFFFF     | 1770000-177FFFF      |
| 376          | 128 / 64                        | 2F00000-2F1FFFF     | 1780000-178FFFF      |
| 377          | 128 / 64                        | 2F20000-2F3FFFF     | 1790000-179FFFF      |
| 378          | 128 / 64                        | 2F40000-2F5FFFF     | 17A0000-17AFFFF      |
| 379          | 128 / 64                        | 2F60000-2F7FFFF     | 17B0000-17BFFFF      |
| 380          | 128 / 64                        | 2F80000-2F9FFFF     | 17C0000-17CFFFF      |
| 381          | 128 / 64                        | 2FA0000-2FBFFFF     | 17D0000-17DFFFF      |
| 382          | 128 / 64                        | 2FC0000-2FDFFFF     | 17E0000-17EFFFF      |
| 383          | 128 / 64                        | 2FE0000-2FFFFFF     | 17F0000-17FFFFFF     |
| 384          | 128 / 64                        | 3000000-301FFFF     | 1800000-180FFFF      |
| 385          | 128 / 64                        | 3020000-303FFFF     | 1810000-181FFFF      |
| 386          | 128 / 64                        | 3040000-305FFFF     | 1820000-182FFFF      |
| 387          | 128 / 64                        | 3060000-307FFFF     | 1830000-183FFFF      |
| 388          | 128 / 64                        | 3080000-309FFFF     | 1840000-184FFFF      |
| 389          | 128 / 64                        | 30A0000-30BFFFF     | 1850000-185FFFF      |
| 390          | 128 / 64                        | 30C0000-30DFFFF     | 1860000-186FFFF      |
| 391          | 128 / 64                        | 30E0000-30FFFFFF    | 1870000-187FFFF      |
| 392          | 128 / 64                        | 3100000-311FFFF     | 1880000-188FFFF      |
| 393          | 128 / 64                        | 3120000-313FFFF     | 1890000-189FFFF      |
| 394          | 128 / 64                        | 3140000-315FFFF     | 18A0000-18AFFFF      |
| 395          | 128 / 64                        | 3160000-317FFFF     | 18B0000-18BFFFF      |
| 396          | 128 / 64                        | 3180000-319FFFF     | 18C0000-18CFFFF      |
| 397          | 128 / 64                        | 31A0000-31BFFFF     | 18D0000-18DFFFF      |
| 398          | 128 / 64                        | 31C0000-31DFFFF     | 18E0000-18EFFFF      |
| 399          | 128 / 64                        | 31E0000-31FFFFFF    | 18F0000-18FFFFFF     |
| 400          | 128 / 64                        | 3200000-321FFFF     | 1900000-190FFFF      |
| 401          | 128 / 64                        | 3220000-323FFFF     | 1910000-191FFFF      |
| 402          | 128 / 64                        | 3240000-325FFFF     | 1920000-192FFFF      |
| 403          | 128 / 64                        | 3260000-327FFFF     | 1930000-193FFFF      |
| 404          | 128 / 64                        | 3280000-329FFFF     | 1940000-194FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 405          | 128 / 64                        | 32A0000-32BFFFF     | 1950000-195FFFF      |
| 406          | 128 / 64                        | 32C0000-32DFFFF     | 1960000-196FFFF      |
| 407          | 128 / 64                        | 32E0000-32FFFFFF    | 1970000-197FFFF      |
| 408          | 128 / 64                        | 3300000-331FFFF     | 1980000-198FFFF      |
| 409          | 128 / 64                        | 3320000-333FFFF     | 1990000-199FFFF      |
| 410          | 128 / 64                        | 3340000-335FFFF     | 19A0000-19AFFFF      |
| 411          | 128 / 64                        | 3360000-337FFFF     | 19B0000-19BFFFF      |
| 412          | 128 / 64                        | 3380000-339FFFF     | 19C0000-19CFFFF      |
| 413          | 128 / 64                        | 33A0000-33BFFFF     | 19D0000-19DFFFF      |
| 414          | 128 / 64                        | 33C0000-33DFFFF     | 19E0000-19EFFFF      |
| 415          | 128 / 64                        | 33E0000-33FFFFFF    | 19F0000-19FFFFFF     |
| 416          | 128 / 64                        | 3400000-341FFFF     | 1A00000-1A0FFFF      |
| 417          | 128 / 64                        | 3420000-343FFFF     | 1A10000-1A1FFFF      |
| 418          | 128 / 64                        | 3440000-345FFFF     | 1A20000-1A2FFFF      |
| 419          | 128 / 64                        | 3460000-347FFFF     | 1A30000-1A3FFFF      |
| 420          | 128 / 64                        | 3480000-349FFFF     | 1A40000-1A4FFFF      |
| 421          | 128 / 64                        | 34A0000-34BFFFF     | 1A50000-1A5FFFF      |
| 422          | 128 / 64                        | 34C0000-34DFFFF     | 1A60000-1A6FFFF      |
| 423          | 128 / 64                        | 34E0000-34FFFFFF    | 1A70000-1A7FFFF      |
| 424          | 128 / 64                        | 3500000-351FFFF     | 1A80000-1A8FFFF      |
| 425          | 128 / 64                        | 3520000-353FFFF     | 1A90000-1A9FFFF      |
| 426          | 128 / 64                        | 3540000-355FFFF     | 1AA0000-1AAFFFF      |
| 427          | 128 / 64                        | 3560000-357FFFF     | 1AB0000-1ABFFFF      |
| 428          | 128 / 64                        | 3580000-359FFFF     | 1AC0000-1ACFFFF      |
| 429          | 128 / 64                        | 35A0000-35BFFFF     | 1AD0000-1ADFFFF      |
| 430          | 128 / 64                        | 35C0000-35DFFFF     | 1AE0000-1AEFFFF      |
| 431          | 128 / 64                        | 35E0000-35FFFFFF    | 1AF0000-1AFFFFFF     |
| 432          | 128 / 64                        | 3600000-361FFFF     | 1B00000-1B0FFFF      |
| 433          | 128 / 64                        | 3620000-363FFFF     | 1B10000-1B1FFFF      |
| 434          | 128 / 64                        | 3640000-365FFFF     | 1B20000-1B2FFFF      |
| 435          | 128 / 64                        | 3660000-367FFFF     | 1B30000-1B3FFFF      |
| 436          | 128 / 64                        | 3680000-369FFFF     | 1B40000-1B4FFFF      |
| 437          | 128 / 64                        | 36A0000-36BFFFF     | 1B50000-1B5FFFF      |
| 438          | 128 / 64                        | 36C0000-36DFFFF     | 1B60000-1B6FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 439          | 128 / 64                        | 36E0000-36FFFFFF    | 1B70000-1B7FFFFF     |
| 440          | 128 / 64                        | 3700000-371FFFFF    | 1B80000-1B8FFFFF     |
| 441          | 128 / 64                        | 3720000-373FFFFF    | 1B90000-1B9FFFFF     |
| 442          | 128 / 64                        | 3740000-375FFFFF    | 1BA0000-1BAFFFFF     |
| 443          | 128 / 64                        | 3760000-377FFFFF    | 1BB0000-1BBFFFFF     |
| 444          | 128 / 64                        | 3780000-379FFFFF    | 1BC0000-1BCFFFFF     |
| 445          | 128 / 64                        | 37A0000-37BFFFFF    | 1BD0000-1BDFFFFF     |
| 446          | 128 / 64                        | 37C0000-37DFFFFF    | 1BE0000-1BEFFFFF     |
| 447          | 128 / 64                        | 37E0000-37FFFFFF    | 1BF0000-1BFFFFFFF    |
| 448          | 128 / 64                        | 3800000-381FFFFF    | 1C00000-1C0FFFFF     |
| 449          | 128 / 64                        | 3820000-383FFFFF    | 1C10000-1C1FFFFF     |
| 450          | 128 / 64                        | 3840000-385FFFFF    | 1C20000-1C2FFFFF     |
| 451          | 128 / 64                        | 3860000-387FFFFF    | 1C30000-1C3FFFFF     |
| 452          | 128 / 64                        | 3880000-389FFFFF    | 1C40000-1C4FFFFF     |
| 453          | 128 / 64                        | 38A0000-38BFFFFF    | 1C50000-1C5FFFFF     |
| 454          | 128 / 64                        | 38C0000-38DFFFFF    | 1C60000-1C6FFFFF     |
| 455          | 128 / 64                        | 38E0000-38FFFFFF    | 1C70000-1C7FFFFF     |
| 456          | 128 / 64                        | 3900000-391FFFFF    | 1C80000-1C8FFFFF     |
| 457          | 128 / 64                        | 3920000-393FFFFF    | 1C90000-1C9FFFFF     |
| 458          | 128 / 64                        | 3940000-395FFFFF    | 1CA0000-1CAFFFFF     |
| 459          | 128 / 64                        | 3960000-397FFFFF    | 1CB0000-1CBFFFFF     |
| 460          | 128 / 64                        | 3980000-399FFFFF    | 1CC0000-1CCFFFFF     |
| 461          | 128 / 64                        | 39A0000-39BFFFFF    | 1CD0000-1CDFFFFF     |
| 462          | 128 / 64                        | 39C0000-39DFFFFF    | 1CE0000-1CEFFFFF     |
| 463          | 128 / 64                        | 39E0000-39FFFFFF    | 1CF0000-1CFFFFFFF    |
| 464          | 128 / 64                        | 3A00000-3A1FFFFF    | 1D00000-1D0FFFFF     |
| 465          | 128 / 64                        | 3A20000-3A3FFFFF    | 1D10000-1D1FFFFF     |
| 466          | 128 / 64                        | 3A40000-3A5FFFFF    | 1D20000-1D2FFFFF     |
| 467          | 128 / 64                        | 3A60000-3A7FFFFF    | 1D30000-1D3FFFFF     |
| 468          | 128 / 64                        | 3A80000-3A9FFFFF    | 1D40000-1D4FFFFF     |
| 469          | 128 / 64                        | 3AA0000-3ABFFFFF    | 1D50000-1D5FFFFF     |
| 470          | 128 / 64                        | 3AC0000-3ADFFFFF    | 1D60000-1D6FFFFF     |
| 471          | 128 / 64                        | 3AE0000-3AFFFFFF    | 1D70000-1D7FFFFF     |
| 472          | 128 / 64                        | 3B00000-3B1FFFFF    | 1D80000-1D8FFFFF     |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 473          | 128 / 64                        | 3B20000-3B3FFFF     | 1D90000-1D9FFFF      |
| 474          | 128 / 64                        | 3B40000-3B5FFFF     | 1DA0000-1DAFFFF      |
| 475          | 128 / 64                        | 3B60000-3B7FFFF     | 1DB0000-1DBFFFF      |
| 476          | 128 / 64                        | 3B80000-3B9FFFF     | 1DC0000-1DCFFFF      |
| 477          | 128 / 64                        | 3BA0000-3BBFFFF     | 1DD0000-1DDFFFF      |
| 478          | 128 / 64                        | 3BC0000-3BDFFFF     | 1DE0000-1DEFFFF      |
| 479          | 128 / 64                        | 3BE0000-3BFFFFF     | 1DF0000-1DFFFFFF     |
| 480          | 128 / 64                        | 3C00000-3C1FFFF     | 1E00000-1E0FFFF      |
| 481          | 128 / 64                        | 3C20000-3C3FFFF     | 1E10000-1E1FFFF      |
| 482          | 128 / 64                        | 3C40000-3C5FFFF     | 1E20000-1E2FFFF      |
| 483          | 128 / 64                        | 3C60000-3C7FFFF     | 1E30000-1E3FFFF      |
| 484          | 128 / 64                        | 3C80000-3C9FFFF     | 1E40000-1E4FFFF      |
| 485          | 128 / 64                        | 3CA0000-3CBFFFF     | 1E50000-1E5FFFF      |
| 486          | 128 / 64                        | 3CC0000-3CDFFFF     | 1E60000-1E6FFFF      |
| 487          | 128 / 64                        | 3CE0000-3CFFFFFF    | 1E70000-1E7FFFF      |
| 488          | 128 / 64                        | 3D00000-3D1FFFF     | 1E80000-1E8FFFF      |
| 489          | 128 / 64                        | 3D20000-3D3FFFF     | 1E90000-1E9FFFF      |
| 490          | 128 / 64                        | 3D40000-3D5FFFF     | 1EA0000-1EAFFFF      |
| 491          | 128 / 64                        | 3D60000-3D7FFFF     | 1EB0000-1EBFFFF      |
| 492          | 128 / 64                        | 3D80000-3D9FFFF     | 1EC0000-1ECFFFF      |
| 493          | 128 / 64                        | 3DA0000-3DBFFFF     | 1ED0000-1EDFFFF      |
| 494          | 128 / 64                        | 3DC0000-3DDFFFF     | 1EE0000-1EEFFFF      |
| 495          | 128 / 64                        | 3DE0000-3DFFFFFF    | 1EF0000-1EFFFFFF     |
| 496          | 128 / 64                        | 3E00000-3E1FFFF     | 1F00000-1F0FFFF      |
| 497          | 128 / 64                        | 3E20000-3E3FFFF     | 1F10000-1F1FFFF      |
| 498          | 128 / 64                        | 3E40000-3E5FFFF     | 1F20000-1F2FFFF      |
| 499          | 128 / 64                        | 3E60000-3E7FFFF     | 1F30000-1F3FFFF      |
| 500          | 128 / 64                        | 3E80000-3E9FFFF     | 1F40000-1F4FFFF      |
| 501          | 128 / 64                        | 3EA0000-3EBFFFF     | 1F50000-1F5FFFF      |
| 502          | 128 / 64                        | 3EC0000-3EDFFFF     | 1F60000-1F6FFFF      |
| 503          | 128 / 64                        | 3EE0000-3EFFFFFF    | 1F70000-1F7FFFF      |
| 504          | 128 / 64                        | 3F00000-3F1FFFF     | 1F80000-1F8FFFF      |
| 505          | 128 / 64                        | 3F20000-3F3FFFF     | 1F90000-1F9FFFF      |
| 506          | 128 / 64                        | 3F40000-3F5FFFF     | 1FA0000-1FAFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 507          | 128 / 64                        | 3F60000-3F7FFFF     | 1FB0000-1FBFFFF      |
| 508          | 128 / 64                        | 3F80000-3F9FFFF     | 1FC0000-1FCFFFF      |
| 509          | 128 / 64                        | 3FA0000-3FBFFFF     | 1FD0000-1FDFFFF      |
| 510          | 128 / 64                        | 3FC0000-3FDFFFF     | 1FE0000-1FEFFFF      |
| 511          | 128 / 64                        | 3FE0000-3FFFFFF     | 1FF0000-1FFFFFF      |
| 512          | 128 / 64                        | 4000000-401FFFF     | 2000000-200FFFF      |
| 513          | 128 / 64                        | 4020000-403FFFF     | 2010000-201FFFF      |
| 514          | 128 / 64                        | 4040000-405FFFF     | 2020000-202FFFF      |
| 515          | 128 / 64                        | 4060000-407FFFF     | 2030000-203FFFF      |
| 516          | 128 / 64                        | 4080000-409FFFF     | 2040000-204FFFF      |
| 517          | 128 / 64                        | 40A0000-40BFFFF     | 2050000-205FFFF      |
| 518          | 128 / 64                        | 40C0000-40DFFFF     | 2060000-206FFFF      |
| 519          | 128 / 64                        | 40E0000-40FFFFFF    | 2070000-207FFFF      |
| 520          | 128 / 64                        | 4100000-411FFFF     | 2080000-208FFFF      |
| 521          | 128 / 64                        | 4120000-413FFFF     | 2090000-209FFFF      |
| 522          | 128 / 64                        | 4140000-415FFFF     | 20A0000-20AFFFF      |
| 523          | 128 / 64                        | 4160000-417FFFF     | 20B0000-20BFFFF      |
| 524          | 128 / 64                        | 4180000-419FFFF     | 20C0000-20CFFFF      |
| 525          | 128 / 64                        | 41A0000-41BFFFF     | 20D0000-20DFFFF      |
| 526          | 128 / 64                        | 41C0000-41DFFFF     | 20E0000-20EFFFF      |
| 527          | 128 / 64                        | 41E0000-41FFFFFF    | 20F0000-20FFFFFF     |
| 528          | 128 / 64                        | 4200000-421FFFF     | 2100000-210FFFF      |
| 529          | 128 / 64                        | 4220000-423FFFF     | 2110000-211FFFF      |
| 530          | 128 / 64                        | 4240000-425FFFF     | 2120000-212FFFF      |
| 531          | 128 / 64                        | 4260000-427FFFF     | 2130000-213FFFF      |
| 532          | 128 / 64                        | 4280000-429FFFF     | 2140000-214FFFF      |
| 533          | 128 / 64                        | 42A0000-42BFFFF     | 2150000-215FFFF      |
| 534          | 128 / 64                        | 42C0000-42DFFFF     | 2160000-216FFFF      |
| 535          | 128 / 64                        | 42E0000-42FFFFFF    | 2170000-217FFFF      |
| 536          | 128 / 64                        | 4300000-431FFFF     | 2180000-218FFFF      |
| 537          | 128 / 64                        | 4320000-433FFFF     | 2190000-219FFFF      |
| 538          | 128 / 64                        | 4340000-435FFFF     | 21A0000-21AFFFF      |
| 539          | 128 / 64                        | 4360000-437FFFF     | 21B0000-21BFFFF      |
| 540          | 128 / 64                        | 4380000-439FFFF     | 21C0000-21CFFFF      |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 541          | 128 / 64                        | 43A0000-43BFFFF     | 21D0000-21DFFFF      |
| 542          | 128 / 64                        | 43C0000-43DFFFF     | 21E0000-21EFFFF      |
| 543          | 128 / 64                        | 43E0000-43FFFFFF    | 21F0000-21FFFFFF     |
| 544          | 128 / 64                        | 4400000-441FFFF     | 2200000-220FFFF      |
| 545          | 128 / 64                        | 4420000-443FFFF     | 2210000-221FFFF      |
| 546          | 128 / 64                        | 4440000-445FFFF     | 2220000-222FFFF      |
| 547          | 128 / 64                        | 4460000-447FFFF     | 2230000-223FFFF      |
| 548          | 128 / 64                        | 4480000-449FFFF     | 2240000-224FFFF      |
| 549          | 128 / 64                        | 44A0000-44BFFFF     | 2250000-225FFFF      |
| 550          | 128 / 64                        | 44C0000-44DFFFF     | 2260000-226FFFF      |
| 551          | 128 / 64                        | 44E0000-44FFFFFF    | 2270000-227FFFF      |
| 552          | 128 / 64                        | 4500000-451FFFF     | 2280000-228FFFF      |
| 553          | 128 / 64                        | 4520000-453FFFF     | 2290000-229FFFF      |
| 554          | 128 / 64                        | 4540000-455FFFF     | 22A0000-22AFFFF      |
| 555          | 128 / 64                        | 4560000-457FFFF     | 22B0000-22BFFFF      |
| 556          | 128 / 64                        | 4580000-459FFFF     | 22C0000-22CFFFF      |
| 557          | 128 / 64                        | 45A0000-45BFFFF     | 22D0000-22DFFFF      |
| 558          | 128 / 64                        | 45C0000-45DFFFF     | 22E0000-22EFFFF      |
| 559          | 128 / 64                        | 45E0000-45FFFFFF    | 22F0000-22FFFFFF     |
| 560          | 128 / 64                        | 4600000-461FFFF     | 2300000-230FFFF      |
| 561          | 128 / 64                        | 4620000-463FFFF     | 2310000-231FFFF      |
| 562          | 128 / 64                        | 4640000-465FFFF     | 2320000-232FFFF      |
| 563          | 128 / 64                        | 4660000-467FFFF     | 2330000-233FFFF      |
| 564          | 128 / 64                        | 4680000-469FFFF     | 2340000-234FFFF      |
| 565          | 128 / 64                        | 46A0000-46BFFFF     | 2350000-235FFFF      |
| 566          | 128 / 64                        | 46C0000-46DFFFF     | 2360000-236FFFF      |
| 567          | 128 / 64                        | 46E0000-46FFFFFF    | 2370000-237FFFF      |
| 568          | 128 / 64                        | 4700000-471FFFF     | 2380000-238FFFF      |
| 569          | 128 / 64                        | 4720000-473FFFF     | 2390000-239FFFF      |
| 570          | 128 / 64                        | 4740000-475FFFF     | 23A0000-23AFFFF      |
| 571          | 128 / 64                        | 4760000-477FFFF     | 23B0000-23BFFFF      |
| 572          | 128 / 64                        | 4780000-479FFFF     | 23C0000-23CFFFF      |
| 573          | 128 / 64                        | 47A0000-47BFFFF     | 23D0000-23DFFFF      |
| 574          | 128 / 64                        | 47C0000-47DFFFF     | 23E0000-23EFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 575          | 128 / 64                        | 47E0000-47FFFFFF    | 23F0000-23FFFFFF     |
| 576          | 128 / 64                        | 4800000-481FFFFF    | 2400000-240FFFFF     |
| 577          | 128 / 64                        | 4820000-483FFFFF    | 2410000-241FFFFF     |
| 578          | 128 / 64                        | 4840000-485FFFFF    | 2420000-242FFFFF     |
| 579          | 128 / 64                        | 4860000-487FFFFF    | 2430000-243FFFFF     |
| 580          | 128 / 64                        | 4880000-489FFFFF    | 2440000-244FFFFF     |
| 581          | 128 / 64                        | 48A0000-48BFFFFF    | 2450000-245FFFFF     |
| 582          | 128 / 64                        | 48C0000-48DFFFFF    | 2460000-246FFFFF     |
| 583          | 128 / 64                        | 48E0000-48FFFFFF    | 2470000-247FFFFF     |
| 584          | 128 / 64                        | 4900000-491FFFFF    | 2480000-248FFFFF     |
| 585          | 128 / 64                        | 4920000-493FFFFF    | 2490000-249FFFFF     |
| 586          | 128 / 64                        | 4940000-495FFFFF    | 24A0000-24AFFFFF     |
| 587          | 128 / 64                        | 4960000-497FFFFF    | 24B0000-24BFFFFF     |
| 588          | 128 / 64                        | 4980000-499FFFFF    | 24C0000-24CFFFFF     |
| 589          | 128 / 64                        | 49A0000-49BFFFFF    | 24D0000-24DFFFFF     |
| 590          | 128 / 64                        | 49C0000-49DFFFFF    | 24E0000-24EFFFFF     |
| 591          | 128 / 64                        | 49E0000-49FFFFFF    | 24F0000-24FFFFFF     |
| 592          | 128 / 64                        | 4A00000-4A1FFFFF    | 2500000-250FFFFF     |
| 593          | 128 / 64                        | 4A20000-4A3FFFFF    | 2510000-251FFFFF     |
| 594          | 128 / 64                        | 4A40000-4A5FFFFF    | 2520000-252FFFFF     |
| 595          | 128 / 64                        | 4A60000-4A7FFFFF    | 2530000-253FFFFF     |
| 596          | 128 / 64                        | 4A80000-4A9FFFFF    | 2540000-254FFFFF     |
| 597          | 128 / 64                        | 4AA0000-4ABFFFFF    | 2550000-255FFFFF     |
| 598          | 128 / 64                        | 4AC0000-4ADFFFFF    | 2560000-256FFFFF     |
| 599          | 128 / 64                        | 4AE0000-4AFFFFFF    | 2570000-257FFFFF     |
| 600          | 128 / 64                        | 4B00000-4B1FFFFF    | 2580000-258FFFFF     |
| 601          | 128 / 64                        | 4B20000-4B3FFFFF    | 2590000-259FFFFF     |
| 602          | 128 / 64                        | 4B40000-4B5FFFFF    | 25A0000-25AFFFFF     |
| 603          | 128 / 64                        | 4B60000-4B7FFFFF    | 25B0000-25BFFFFF     |
| 604          | 128 / 64                        | 4B80000-4B9FFFFF    | 25C0000-25CFFFFF     |
| 605          | 128 / 64                        | 4BA0000-4BBFFFFF    | 25D0000-25DFFFFF     |
| 606          | 128 / 64                        | 4BC0000-4BDFFFFF    | 25E0000-25EFFFFF     |
| 607          | 128 / 64                        | 4BE0000-4BFFFFFF    | 25F0000-25FFFFFF     |
| 608          | 128 / 64                        | 4C00000-4C1FFFFF    | 2600000-260FFFFF     |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 609          | 128 / 64                        | 4C20000-4C3FFFF     | 2610000-261FFFF      |
| 610          | 128 / 64                        | 4C40000-4C5FFFF     | 2620000-262FFFF      |
| 611          | 128 / 64                        | 4C60000-4C7FFFF     | 2630000-263FFFF      |
| 612          | 128 / 64                        | 4C80000-4C9FFFF     | 2640000-264FFFF      |
| 613          | 128 / 64                        | 4CA0000-4CBFFFF     | 2650000-265FFFF      |
| 614          | 128 / 64                        | 4CC0000-4CDFFFF     | 2660000-266FFFF      |
| 615          | 128 / 64                        | 4CE0000-4CFFFFFF    | 2670000-267FFFF      |
| 616          | 128 / 64                        | 4D00000-4D1FFFF     | 2680000-268FFFF      |
| 617          | 128 / 64                        | 4D20000-4D3FFFF     | 2690000-269FFFF      |
| 618          | 128 / 64                        | 4D40000-4D5FFFF     | 26A0000-26AFFFF      |
| 619          | 128 / 64                        | 4D60000-4D7FFFF     | 26B0000-26BFFFF      |
| 620          | 128 / 64                        | 4D80000-4D9FFFF     | 26C0000-26CFFFF      |
| 621          | 128 / 64                        | 4DA0000-4DBFFFF     | 26D0000-26DFFFF      |
| 622          | 128 / 64                        | 4DC0000-4DDFFFF     | 26E0000-26EFFFF      |
| 623          | 128 / 64                        | 4DE0000-4DFFFFFF    | 26F0000-26FFFFFF     |
| 624          | 128 / 64                        | 4E00000-4E1FFFF     | 2700000-270FFFF      |
| 625          | 128 / 64                        | 4E20000-4E3FFFF     | 2710000-271FFFF      |
| 626          | 128 / 64                        | 4E40000-4E5FFFF     | 2720000-272FFFF      |
| 627          | 128 / 64                        | 4E60000-4E7FFFF     | 2730000-273FFFF      |
| 628          | 128 / 64                        | 4E80000-4E9FFFF     | 2740000-274FFFF      |
| 629          | 128 / 64                        | 4EA0000-4EBFFFF     | 2750000-275FFFF      |
| 630          | 128 / 64                        | 4EC0000-4EDFFFF     | 2760000-276FFFF      |
| 631          | 128 / 64                        | 4EE0000-4EFFFFFF    | 2770000-277FFFF      |
| 632          | 128 / 64                        | 4F00000-4F1FFFF     | 2780000-278FFFF      |
| 633          | 128 / 64                        | 4F20000-4F3FFFF     | 2790000-279FFFF      |
| 634          | 128 / 64                        | 4F40000-4F5FFFF     | 27A0000-27AFFFF      |
| 635          | 128 / 64                        | 4F60000-4F7FFFF     | 27B0000-27BFFFF      |
| 636          | 128 / 64                        | 4F80000-4F9FFFF     | 27C0000-27CFFFF      |
| 637          | 128 / 64                        | 4FA0000-4FBFFFF     | 27D0000-27DFFFF      |
| 638          | 128 / 64                        | 4FC0000-4FDFFFF     | 27E0000-27EFFFF      |
| 639          | 128 / 64                        | 4FE0000-4FFFFFF     | 27F0000-27FFFFFF     |
| 640          | 128 / 64                        | 5000000-501FFFF     | 2800000-280FFFF      |
| 641          | 128 / 64                        | 5020000-503FFFF     | 2810000-281FFFF      |
| 642          | 128 / 64                        | 5040000-505FFFF     | 2820000-282FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 643          | 128 / 64                        | 5060000-507FFFF     | 2830000-283FFFF      |
| 644          | 128 / 64                        | 5080000-509FFFF     | 2840000-284FFFF      |
| 645          | 128 / 64                        | 50A0000-50BFFFF     | 2850000-285FFFF      |
| 646          | 128 / 64                        | 50C0000-50DFFFF     | 2860000-286FFFF      |
| 647          | 128 / 64                        | 50E0000-50FFFFFF    | 2870000-287FFFF      |
| 648          | 128 / 64                        | 5100000-511FFFF     | 2880000-288FFFF      |
| 649          | 128 / 64                        | 5120000-513FFFF     | 2890000-289FFFF      |
| 650          | 128 / 64                        | 5140000-515FFFF     | 28A0000-28AFFFF      |
| 651          | 128 / 64                        | 5160000-517FFFF     | 28B0000-28BFFFF      |
| 652          | 128 / 64                        | 5180000-519FFFF     | 28C0000-28CFFFF      |
| 653          | 128 / 64                        | 51A0000-51BFFFF     | 28D0000-28DFFFF      |
| 654          | 128 / 64                        | 51C0000-51DFFFF     | 28E0000-28EFFFF      |
| 655          | 128 / 64                        | 51E0000-51FFFFFF    | 28F0000-28FFFFFF     |
| 656          | 128 / 64                        | 5200000-521FFFF     | 2900000-290FFFF      |
| 657          | 128 / 64                        | 5220000-523FFFF     | 2910000-291FFFF      |
| 658          | 128 / 64                        | 5240000-525FFFF     | 2920000-292FFFF      |
| 659          | 128 / 64                        | 5260000-527FFFF     | 2930000-293FFFF      |
| 660          | 128 / 64                        | 5280000-529FFFF     | 2940000-294FFFF      |
| 661          | 128 / 64                        | 52A0000-52BFFFF     | 2950000-295FFFF      |
| 662          | 128 / 64                        | 52C0000-52DFFFF     | 2960000-296FFFF      |
| 663          | 128 / 64                        | 52E0000-52FFFFFF    | 2970000-297FFFF      |
| 664          | 128 / 64                        | 5300000-531FFFF     | 2980000-298FFFF      |
| 665          | 128 / 64                        | 5320000-533FFFF     | 2990000-299FFFF      |
| 666          | 128 / 64                        | 5340000-535FFFF     | 29A0000-29AFFFF      |
| 667          | 128 / 64                        | 5360000-537FFFF     | 29B0000-29BFFFF      |
| 668          | 128 / 64                        | 5380000-539FFFF     | 29C0000-29CFFFF      |
| 669          | 128 / 64                        | 53A0000-53BFFFF     | 29D0000-29DFFFF      |
| 670          | 128 / 64                        | 53C0000-53DFFFF     | 29E0000-29EFFFF      |
| 671          | 128 / 64                        | 53E0000-53FFFFFF    | 29F0000-29FFFFFF     |
| 672          | 128 / 64                        | 5400000-541FFFF     | 2A00000-2A0FFFF      |
| 673          | 128 / 64                        | 5420000-543FFFF     | 2A10000-2A1FFFF      |
| 674          | 128 / 64                        | 5440000-545FFFF     | 2A20000-2A2FFFF      |
| 675          | 128 / 64                        | 5460000-547FFFF     | 2A30000-2A3FFFF      |
| 676          | 128 / 64                        | 5480000-549FFFF     | 2A40000-2A4FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 677          | 128 / 64                        | 54A0000-54BFFFF     | 2A50000-2A5FFFF      |
| 678          | 128 / 64                        | 54C0000-54DFFFF     | 2A60000-2A6FFFF      |
| 679          | 128 / 64                        | 54E0000-54FFFFFF    | 2A70000-2A7FFFF      |
| 680          | 128 / 64                        | 5500000-551FFFF     | 2A80000-2A8FFFF      |
| 681          | 128 / 64                        | 5520000-553FFFF     | 2A90000-2A9FFFF      |
| 682          | 128 / 64                        | 5540000-555FFFF     | 2AA0000-2AAFFFF      |
| 683          | 128 / 64                        | 5560000-557FFFF     | 2AB0000-2ABFFFF      |
| 684          | 128 / 64                        | 5580000-559FFFF     | 2AC0000-2ACFFFF      |
| 685          | 128 / 64                        | 55A0000-55BFFFF     | 2AD0000-2ADFFFF      |
| 686          | 128 / 64                        | 55C0000-55DFFFF     | 2AE0000-2AEFFFF      |
| 687          | 128 / 64                        | 55E0000-55FFFFFF    | 2AF0000-2AFFFFF      |
| 688          | 128 / 64                        | 5600000-561FFFF     | 2B00000-2B0FFFF      |
| 689          | 128 / 64                        | 5620000-563FFFF     | 2B10000-2B1FFFF      |
| 690          | 128 / 64                        | 5640000-565FFFF     | 2B20000-2B2FFFF      |
| 691          | 128 / 64                        | 5660000-567FFFF     | 2B30000-2B3FFFF      |
| 692          | 128 / 64                        | 5680000-569FFFF     | 2B40000-2B4FFFF      |
| 693          | 128 / 64                        | 56A0000-56BFFFF     | 2B50000-2B5FFFF      |
| 694          | 128 / 64                        | 56C0000-56DFFFF     | 2B60000-2B6FFFF      |
| 695          | 128 / 64                        | 56E0000-56FFFFFF    | 2B70000-2B7FFFF      |
| 696          | 128 / 64                        | 5700000-571FFFF     | 2B80000-2B8FFFF      |
| 697          | 128 / 64                        | 5720000-573FFFF     | 2B90000-2B9FFFF      |
| 698          | 128 / 64                        | 5740000-575FFFF     | 2BA0000-2BAFFFF      |
| 699          | 128 / 64                        | 5760000-577FFFF     | 2BB0000-2BBFFFF      |
| 700          | 128 / 64                        | 5780000-579FFFF     | 2BC0000-2BCFFFF      |
| 701          | 128 / 64                        | 57A0000-57BFFFF     | 2BD0000-2BDFFFF      |
| 702          | 128 / 64                        | 57C0000-57DFFFF     | 2BE0000-2BEFFFF      |
| 703          | 128 / 64                        | 57E0000-57FFFFFF    | 2BF0000-2BFFFFFF     |
| 704          | 128 / 64                        | 5800000-581FFFF     | 2C00000-2C0FFFF      |
| 705          | 128 / 64                        | 5820000-583FFFF     | 2C10000-2C1FFFF      |
| 706          | 128 / 64                        | 5840000-585FFFF     | 2C20000-2C2FFFF      |
| 707          | 128 / 64                        | 5860000-587FFFF     | 2C30000-2C3FFFF      |
| 708          | 128 / 64                        | 5880000-589FFFF     | 2C40000-2C4FFFF      |
| 709          | 128 / 64                        | 58A0000-58BFFFF     | 2C50000-2C5FFFF      |
| 710          | 128 / 64                        | 58C0000-58DFFFF     | 2C60000-2C6FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 711          | 128 / 64                        | 58E0000-58FFFFFF    | 2C70000-2C7FFFF      |
| 712          | 128 / 64                        | 5900000-591FFFF     | 2C80000-2C8FFFF      |
| 713          | 128 / 64                        | 5920000-593FFFF     | 2C90000-2C9FFFF      |
| 714          | 128 / 64                        | 5940000-595FFFF     | 2CA0000-2CAFFFF      |
| 715          | 128 / 64                        | 5960000-597FFFF     | 2CB0000-2CBFFFF      |
| 716          | 128 / 64                        | 5980000-599FFFF     | 2CC0000-2CCFFFF      |
| 717          | 128 / 64                        | 59A0000-59BFFFF     | 2CD0000-2CDFFFF      |
| 718          | 128 / 64                        | 59C0000-59DFFFF     | 2CE0000-2CEFFFF      |
| 719          | 128 / 64                        | 59E0000-59FFFFFF    | 2CF0000-2CFFFFFF     |
| 720          | 128 / 64                        | 5A00000-5A1FFFF     | 2D00000-2D0FFFF      |
| 721          | 128 / 64                        | 5A20000-5A3FFFF     | 2D10000-2D1FFFF      |
| 722          | 128 / 64                        | 5A40000-5A5FFFF     | 2D20000-2D2FFFF      |
| 723          | 128 / 64                        | 5A60000-5A7FFFF     | 2D30000-2D3FFFF      |
| 724          | 128 / 64                        | 5A80000-5A9FFFF     | 2D40000-2D4FFFF      |
| 725          | 128 / 64                        | 5AA0000-5ABFFFF     | 2D50000-2D5FFFF      |
| 726          | 128 / 64                        | 5AC0000-5ADFFFF     | 2D60000-2D6FFFF      |
| 727          | 128 / 64                        | 5AE0000-5AFFFFFF    | 2D70000-2D7FFFF      |
| 728          | 128 / 64                        | 5B00000-5B1FFFF     | 2D80000-2D8FFFF      |
| 729          | 128 / 64                        | 5B20000-5B3FFFF     | 2D90000-2D9FFFF      |
| 730          | 128 / 64                        | 5B40000-5B5FFFF     | 2DA0000-2DAFFFF      |
| 731          | 128 / 64                        | 5B60000-5B7FFFF     | 2DB0000-2DBFFFF      |
| 732          | 128 / 64                        | 5B80000-5B9FFFF     | 2DC0000-2DCFFFF      |
| 733          | 128 / 64                        | 5BA0000-5BBFFFF     | 2DD0000-2DDFFFF      |
| 734          | 128 / 64                        | 5BC0000-5BDFFFF     | 2DE0000-2DEFFFF      |
| 735          | 128 / 64                        | 5BE0000-5BFFFFFF    | 2DF0000-2DFFFFFF     |
| 736          | 128 / 64                        | 5C00000-5C1FFFF     | 2E00000-2E0FFFF      |
| 737          | 128 / 64                        | 5C20000-5C3FFFF     | 2E10000-2E1FFFF      |
| 738          | 128 / 64                        | 5C40000-5C5FFFF     | 2E20000-2E2FFFF      |
| 739          | 128 / 64                        | 5C60000-5C7FFFF     | 2E30000-2E3FFFF      |
| 740          | 128 / 64                        | 5C80000-5C9FFFF     | 2E40000-2E4FFFF      |
| 741          | 128 / 64                        | 5CA0000-5CBFFFF     | 2E50000-2E5FFFF      |
| 742          | 128 / 64                        | 5CC0000-5CDFFFF     | 2E60000-2E6FFFF      |
| 743          | 128 / 64                        | 5CE0000-5CFFFFFF    | 2E70000-2E7FFFF      |
| 744          | 128 / 64                        | 5D00000-5D1FFFF     | 2E80000-2E8FFFF      |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 745          | 128 / 64                        | 5D20000-5D3FFFF     | 2E90000-2E9FFFF      |
| 746          | 128 / 64                        | 5D40000-5D5FFFF     | 2EA0000-2EAFFFF      |
| 747          | 128 / 64                        | 5D60000-5D7FFFF     | 2EB0000-2EBFFFF      |
| 748          | 128 / 64                        | 5D80000-5D9FFFF     | 2EC0000-2ECFFFF      |
| 749          | 128 / 64                        | 5DA0000-5DBFFFF     | 2ED0000-2EDFFFF      |
| 750          | 128 / 64                        | 5DC0000-5DDFFFF     | 2EE0000-2EEFFFF      |
| 751          | 128 / 64                        | 5DE0000-5DFFFFF     | 2EF0000-2EFFFFF      |
| 752          | 128 / 64                        | 5E00000-5E1FFFF     | 2F00000-2F0FFFF      |
| 753          | 128 / 64                        | 5E20000-5E3FFFF     | 2F10000-2F1FFFF      |
| 754          | 128 / 64                        | 5E40000-5E5FFFF     | 2F20000-2F2FFFF      |
| 755          | 128 / 64                        | 5E60000-5E7FFFF     | 2F30000-2F3FFFF      |
| 756          | 128 / 64                        | 5E80000-5E9FFFF     | 2F40000-2F4FFFF      |
| 757          | 128 / 64                        | 5EA0000-5EBFFFF     | 2F50000-2F5FFFF      |
| 758          | 128 / 64                        | 5EC0000-5EDFFFF     | 2F60000-2F6FFFF      |
| 759          | 128 / 64                        | 5EE0000-5EFFFFF     | 2F70000-2F7FFFF      |
| 760          | 128 / 64                        | 5F00000-5F1FFFF     | 2F80000-2F8FFFF      |
| 761          | 128 / 64                        | 5F20000-5F3FFFF     | 2F90000-2F9FFFF      |
| 762          | 128 / 64                        | 5F40000-5F5FFFF     | 22FA0000-2FAFFFF     |
| 763          | 128 / 64                        | 5F60000-5F7FFFF     | 2FB0000-2FBFFFF      |
| 764          | 128 / 64                        | 5F80000-5F9FFFF     | 2FC0000-2FCFFFF      |
| 765          | 128 / 64                        | 5FA0000-5FBFFFF     | 2FD0000-2FDFFFF      |
| 766          | 128 / 64                        | 5FC0000-5FDFFFF     | 2FE0000-2FEFFFF      |
| 767          | 128 / 64                        | 5FE0000-5FFFFFFF    | 2FF0000-2FFFFFFF     |
| 768          | 128 / 64                        | 6000000-601FFFF     | 3000000-300FFFF      |
| 769          | 128 / 64                        | 6020000-603FFFF     | 3010000-301FFFF      |
| 770          | 128 / 64                        | 6040000-605FFFF     | 3020000-302FFFF      |
| 771          | 128 / 64                        | 6060000-607FFFF     | 3030000-303FFFF      |
| 772          | 128 / 64                        | 6080000-609FFFF     | 3040000-304FFFF      |
| 773          | 128 / 64                        | 60A0000-60BFFFF     | 3050000-305FFFF      |
| 774          | 128 / 64                        | 60C0000-60DFFFF     | 3060000-306FFFF      |
| 775          | 128 / 64                        | 60E0000-60FFFFFF    | 3070000-307FFFF      |
| 776          | 128 / 64                        | 6100000-611FFFF     | 3080000-308FFFF      |
| 777          | 128 / 64                        | 6120000-613FFFF     | 3090000-309FFFF      |
| 778          | 128 / 64                        | 6140000-615FFFF     | 30A0000-30AFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 779          | 128 / 64                        | 6160000-617FFFF     | 30B0000-30BFFFF      |
| 780          | 128 / 64                        | 6180000-619FFFF     | 30C0000-30CFFFF      |
| 781          | 128 / 64                        | 61A0000-61BFFFF     | 30D0000-30DFFFF      |
| 782          | 128 / 64                        | 61C0000-61DFFFF     | 30E0000-30EFFFF      |
| 783          | 128 / 64                        | 61E0000-61FFFFFF    | 30F0000-30FFFFFF     |
| 784          | 128 / 64                        | 6200000-621FFFF     | 3100000-310FFFF      |
| 785          | 128 / 64                        | 6220000-623FFFF     | 3110000-311FFFF      |
| 786          | 128 / 64                        | 6240000-625FFFF     | 3120000-312FFFF      |
| 787          | 128 / 64                        | 6260000-627FFFF     | 3130000-313FFFF      |
| 788          | 128 / 64                        | 6280000-629FFFF     | 3140000-314FFFF      |
| 789          | 128 / 64                        | 62A0000-62BFFFF     | 3150000-315FFFF      |
| 790          | 128 / 64                        | 62C0000-62DFFFF     | 3160000-316FFFF      |
| 791          | 128 / 64                        | 62E0000-62FFFFFF    | 3170000-317FFFF      |
| 792          | 128 / 64                        | 6300000-631FFFF     | 3180000-318FFFF      |
| 793          | 128 / 64                        | 6320000-633FFFF     | 3190000-319FFFF      |
| 794          | 128 / 64                        | 6340000-635FFFF     | 31A0000-31AFFFF      |
| 795          | 128 / 64                        | 6360000-637FFFF     | 31B0000-31BFFFF      |
| 796          | 128 / 64                        | 6380000-639FFFF     | 31C0000-31CFFFF      |
| 797          | 128 / 64                        | 63A0000-63BFFFF     | 31D0000-31DFFFF      |
| 798          | 128 / 64                        | 63C0000-63DFFFF     | 31E0000-31EFFFF      |
| 799          | 128 / 64                        | 63E0000-63FFFFFF    | 31F0000-31FFFFFF     |
| 800          | 128 / 64                        | 6400000-641FFFF     | 3200000-320FFFF      |
| 801          | 128 / 64                        | 6420000-643FFFF     | 3210000-321FFFF      |
| 802          | 128 / 64                        | 6440000-645FFFF     | 3220000-322FFFF      |
| 803          | 128 / 64                        | 6460000-647FFFF     | 3230000-323FFFF      |
| 804          | 128 / 64                        | 6480000-649FFFF     | 3240000-324FFFF      |
| 805          | 128 / 64                        | 64A0000-64BFFFF     | 3250000-325FFFF      |
| 806          | 128 / 64                        | 64C0000-64DFFFF     | 3260000-326FFFF      |
| 807          | 128 / 64                        | 64E0000-64FFFFFF    | 3270000-327FFFF      |
| 808          | 128 / 64                        | 6500000-651FFFF     | 3280000-328FFFF      |
| 809          | 128 / 64                        | 6520000-653FFFF     | 3290000-329FFFF      |
| 810          | 128 / 64                        | 6540000-655FFFF     | 32A0000-32AFFFF      |
| 811          | 128 / 64                        | 6560000-657FFFF     | 32B0000-32BFFFF      |
| 812          | 128 / 64                        | 6580000-659FFFF     | 32C0000-32CFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 813          | 128 / 64                        | 65A0000-65BFFFF     | 32D0000-32DFFFF      |
| 814          | 128 / 64                        | 65C0000-65DFFFF     | 32E0000-32EFFFF      |
| 815          | 128 / 64                        | 65E0000-65FFFFFF    | 32F0000-32FFFFFF     |
| 816          | 128 / 64                        | 6600000-661FFFF     | 3300000-330FFFF      |
| 817          | 128 / 64                        | 6620000-663FFFF     | 3310000-331FFFF      |
| 818          | 128 / 64                        | 6640000-665FFFF     | 3320000-332FFFF      |
| 819          | 128 / 64                        | 6660000-667FFFF     | 3330000-333FFFF      |
| 820          | 128 / 64                        | 6680000-669FFFF     | 3340000-334FFFF      |
| 821          | 128 / 64                        | 66A0000-66BFFFF     | 3350000-335FFFF      |
| 822          | 128 / 64                        | 66C0000-66DFFFF     | 3360000-336FFFF      |
| 823          | 128 / 64                        | 66E0000-66FFFFFF    | 3370000-337FFFF      |
| 824          | 128 / 64                        | 6700000-671FFFF     | 3380000-338FFFF      |
| 825          | 128 / 64                        | 6720000-673FFFF     | 3390000-339FFFF      |
| 826          | 128 / 64                        | 6740000-675FFFF     | 33A0000-33AFFFF      |
| 827          | 128 / 64                        | 6760000-677FFFF     | 33B0000-33BFFFF      |
| 828          | 128 / 64                        | 6780000-679FFFF     | 33C0000-33CFFFF      |
| 829          | 128 / 64                        | 67A0000-67BFFFF     | 33D0000-33DFFFF      |
| 830          | 128 / 64                        | 67C0000-67DFFFF     | 33E0000-33EFFFF      |
| 831          | 128 / 64                        | 67E0000-67FFFFFF    | 33F0000-33FFFFFF     |
| 832          | 128 / 64                        | 6800000-681FFFF     | 3400000-340FFFF      |
| 833          | 128 / 64                        | 6820000-683FFFF     | 3410000-341FFFF      |
| 834          | 128 / 64                        | 6840000-685FFFF     | 3420000-342FFFF      |
| 835          | 128 / 64                        | 6860000-687FFFF     | 3430000-343FFFF      |
| 836          | 128 / 64                        | 6880000-689FFFF     | 3440000-344FFFF      |
| 837          | 128 / 64                        | 68A0000-68BFFFF     | 3450000-345FFFF      |
| 838          | 128 / 64                        | 68C0000-68DFFFF     | 3460000-346FFFF      |
| 839          | 128 / 64                        | 68E0000-68FFFFFF    | 3470000-347FFFF      |
| 840          | 128 / 64                        | 6900000-691FFFF     | 3480000-348FFFF      |
| 841          | 128 / 64                        | 6920000-693FFFF     | 3490000-349FFFF      |
| 842          | 128 / 64                        | 6940000-695FFFF     | 34A0000-34AFFFF      |
| 843          | 128 / 64                        | 6960000-697FFFF     | 34B0000-34BFFFF      |
| 844          | 128 / 64                        | 6980000-699FFFF     | 34C0000-34CFFFF      |
| 845          | 128 / 64                        | 69A0000-69BFFFF     | 34D0000-34DFFFF      |
| 846          | 128 / 64                        | 69C0000-69DFFFF     | 34E0000-34EFFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 847          | 128 / 64                        | 69E0000-69FFFFFF    | 34F0000-34FFFFFF     |
| 848          | 128 / 64                        | 6A00000-6A1FFFFF    | 3500000-350FFFFFFF   |
| 849          | 128 / 64                        | 6A20000-6A3FFFFF    | 3510000-351FFFFFFF   |
| 850          | 128 / 64                        | 6A40000-6A5FFFFF    | 3520000-352FFFFFFF   |
| 851          | 128 / 64                        | 6A60000-6A7FFFFF    | 3530000-353FFFFFFF   |
| 852          | 128 / 64                        | 6A80000-6A9FFFFF    | 3540000-354FFFFFFF   |
| 853          | 128 / 64                        | 6AA0000-6ABFFFFF    | 3550000-355FFFFFFF   |
| 854          | 128 / 64                        | 6AC0000-6ADFFFFF    | 3560000-356FFFFFFF   |
| 855          | 128 / 64                        | 6AE0000-6AFFFFFF    | 3570000-357FFFFFFF   |
| 856          | 128 / 64                        | 6B00000-6B1FFFFF    | 3580000-358FFFFFFF   |
| 857          | 128 / 64                        | 6B20000-6B3FFFFF    | 3590000-359FFFFFFF   |
| 858          | 128 / 64                        | 6B40000-6B5FFFFF    | 35A0000-35AFFFFFFF   |
| 859          | 128 / 64                        | 6B60000-6B7FFFFF    | 35B0000-35BFFFFFFF   |
| 860          | 128 / 64                        | 6B80000-6B9FFFFF    | 35C0000-35CFFFFFFF   |
| 861          | 128 / 64                        | 6BA0000-6BBFFFFF    | 35D0000-35DFFFFFFF   |
| 862          | 128 / 64                        | 6BC0000-6BDFFFFF    | 35E0000-35EFFFFFFF   |
| 863          | 128 / 64                        | 6BE0000-6BFFFFFFF   | 35F0000-35FFFFFFF    |
| 864          | 128 / 64                        | 6C00000-6C1FFFFF    | 3600000-360FFFFFFF   |
| 865          | 128 / 64                        | 6C20000-6C3FFFFF    | 3610000-361FFFFFFF   |
| 866          | 128 / 64                        | 6C40000-6C5FFFFF    | 3620000-362FFFFFFF   |
| 867          | 128 / 64                        | 6C60000-6C7FFFFF    | 3630000-363FFFFFFF   |
| 868          | 128 / 64                        | 6C80000-6C9FFFFF    | 3640000-364FFFFFFF   |
| 869          | 128 / 64                        | 6CA0000-6CBFFFFF    | 3650000-365FFFFFFF   |
| 870          | 128 / 64                        | 6CC0000-6CDFFFFF    | 3660000-366FFFFFFF   |
| 871          | 128 / 64                        | 6CE0000-6CFFFFFFF   | 3670000-367FFFFFFF   |
| 872          | 128 / 64                        | 6D00000-6D1FFFFF    | 3680000-368FFFFFFF   |
| 873          | 128 / 64                        | 6D20000-6D3FFFFF    | 3690000-369FFFFFFF   |
| 874          | 128 / 64                        | 6D40000-6D5FFFFF    | 36A0000-36AFFFFFFF   |
| 875          | 128 / 64                        | 6D60000-6D7FFFFF    | 36B0000-36BFFFFFFF   |
| 876          | 128 / 64                        | 6D80000-6D9FFFFF    | 36C0000-36CFFFFFFF   |
| 877          | 128 / 64                        | 6DA0000-6DBFFFFF    | 36D0000-36DFFFFFFF   |
| 878          | 128 / 64                        | 6DC0000-6DDFFFFF    | 36E0000-36EFFFFFFF   |
| 879          | 128 / 64                        | 6DE0000-6DFFFFFFF   | 36F0000-36FFFFFFF    |
| 880          | 128 / 64                        | 6E00000-6E1FFFFF    | 3700000-370FFFFFFF   |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 881          | 128 / 64                        | 6E20000-6E3FFFF     | 3710000-371FFFF      |
| 882          | 128 / 64                        | 6E40000-6E5FFFF     | 3720000-372FFFF      |
| 883          | 128 / 64                        | 6E60000-6E7FFFF     | 3730000-373FFFF      |
| 884          | 128 / 64                        | 6E80000-6E9FFFF     | 3740000-374FFFF      |
| 885          | 128 / 64                        | 6EA0000-6EBFFFF     | 3750000-375FFFF      |
| 886          | 128 / 64                        | 6EC0000-6EDFFFF     | 3760000-376FFFF      |
| 887          | 128 / 64                        | 6EE0000-6EFFFFF     | 3770000-377FFFF      |
| 888          | 128 / 64                        | 6F00000-6F1FFFF     | 3780000-378FFFF      |
| 889          | 128 / 64                        | 6F20000-6F3FFFF     | 3790000-379FFFF      |
| 890          | 128 / 64                        | 6F40000-6F5FFFF     | 37A0000-37AFFFF      |
| 891          | 128 / 64                        | 6F60000-6F7FFFF     | 37B0000-37BFFFF      |
| 892          | 128 / 64                        | 6F80000-6F9FFFF     | 37C0000-37CFFFF      |
| 893          | 128 / 64                        | 6FA0000-6FBFFFF     | 37D0000-37DFFFF      |
| 894          | 128 / 64                        | 6FC0000-6FDFFFF     | 37E0000-37EFFFF      |
| 895          | 128 / 64                        | 6FE0000-6FFFFFF     | 37F0000-37FFFFFF     |
| 896          | 128 / 64                        | 7000000-701FFFF     | 3800000-380FFFF      |
| 897          | 128 / 64                        | 7020000-703FFFF     | 3810000-381FFFF      |
| 898          | 128 / 64                        | 7040000-705FFFF     | 3820000-382FFFF      |
| 899          | 128 / 64                        | 7060000-707FFFF     | 3830000-383FFFF      |
| 900          | 128 / 64                        | 7080000-709FFFF     | 3840000-384FFFF      |
| 901          | 128 / 64                        | 70A0000-70BFFFF     | 3850000-385FFFF      |
| 902          | 128 / 64                        | 70C0000-70DFFFF     | 3860000-386FFFF      |
| 903          | 128 / 64                        | 70E0000-70FFFFFF    | 3870000-387FFFF      |
| 904          | 128 / 64                        | 7100000-711FFFF     | 3880000-388FFFF      |
| 905          | 128 / 64                        | 7120000-713FFFF     | 3890000-389FFFF      |
| 906          | 128 / 64                        | 7140000-715FFFF     | 38A0000-38AFFFF      |
| 907          | 128 / 64                        | 7160000-717FFFF     | 38B0000-38BFFFF      |
| 908          | 128 / 64                        | 7180000-719FFFF     | 38C0000-38CFFFF      |
| 909          | 128 / 64                        | 71A0000-71BFFFF     | 38D0000-38DFFFF      |
| 910          | 128 / 64                        | 71C0000-71DFFFF     | 38E0000-38EFFFF      |
| 911          | 128 / 64                        | 71E0000-71FFFFFF    | 38F0000-38FFFFFF     |
| 912          | 128 / 64                        | 7200000-721FFFF     | 3900000-390FFFF      |
| 913          | 128 / 64                        | 7220000-723FFFF     | 3910000-391FFFF      |
| 914          | 128 / 64                        | 7240000-725FFFF     | 3920000-392FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 915          | 128 / 64                        | 7260000-727FFFF     | 3930000-393FFFF      |
| 916          | 128 / 64                        | 7280000-729FFFF     | 3940000-394FFFF      |
| 917          | 128 / 64                        | 72A0000-72BFFFF     | 3950000-395FFFF      |
| 918          | 128 / 64                        | 72C0000-72DFFFF     | 3960000-396FFFF      |
| 919          | 128 / 64                        | 72E0000-72FFFFFF    | 3970000-397FFFF      |
| 920          | 128 / 64                        | 7300000-731FFFF     | 3980000-398FFFF      |
| 921          | 128 / 64                        | 7320000-733FFFF     | 3990000-399FFFF      |
| 922          | 128 / 64                        | 7340000-735FFFF     | 39A0000-39AFFFF      |
| 923          | 128 / 64                        | 7360000-737FFFF     | 39B0000-39BFFFF      |
| 924          | 128 / 64                        | 7380000-739FFFF     | 39C0000-39CFFFF      |
| 925          | 128 / 64                        | 73A0000-73BFFFF     | 39D0000-39DFFFF      |
| 926          | 128 / 64                        | 73C0000-73DFFFF     | 39E0000-39EFFFF      |
| 927          | 128 / 64                        | 73E0000-73FFFFFF    | 39F0000-39FFFFFF     |
| 928          | 128 / 64                        | 7400000-741FFFF     | 3A00000-3A0FFFF      |
| 929          | 128 / 64                        | 7420000-743FFFF     | 3A10000-3A1FFFF      |
| 930          | 128 / 64                        | 7440000-745FFFF     | 3A20000-3A2FFFF      |
| 931          | 128 / 64                        | 7460000-747FFFF     | 3A30000-3A3FFFF      |
| 932          | 128 / 64                        | 7480000-749FFFF     | 3A40000-3A4FFFF      |
| 933          | 128 / 64                        | 74A0000-74BFFFF     | 3A50000-3A5FFFF      |
| 934          | 128 / 64                        | 74C0000-74DFFFF     | 3A60000-3A6FFFF      |
| 935          | 128 / 64                        | 74E0000-74FFFFFF    | 3A70000-3A7FFFF      |
| 936          | 128 / 64                        | 7500000-751FFFF     | 3A80000-3A8FFFF      |
| 937          | 128 / 64                        | 7520000-753FFFF     | 3A90000-3A9FFFF      |
| 938          | 128 / 64                        | 7540000-755FFFF     | 3AA0000-3AAFFFF      |
| 939          | 128 / 64                        | 7560000-757FFFF     | 3AB0000-3ABFFFF      |
| 940          | 128 / 64                        | 7580000-759FFFF     | 3AC0000-3ACFFFF      |
| 941          | 128 / 64                        | 75A0000-75BFFFF     | 3AD0000-3ADFFFF      |
| 942          | 128 / 64                        | 75C0000-75DFFFF     | 3AE0000-3AEFFFF      |
| 943          | 128 / 64                        | 75E0000-75FFFFFF    | 3AF0000-3AFFFFFF     |
| 944          | 128 / 64                        | 7600000-761FFFF     | 3B00000-3B0FFFF      |
| 945          | 128 / 64                        | 7620000-763FFFF     | 3B10000-3B1FFFF      |
| 946          | 128 / 64                        | 7640000-765FFFF     | 3B20000-3B2FFFF      |
| 947          | 128 / 64                        | 7660000-767FFFF     | 3B30000-3B3FFFF      |
| 948          | 128 / 64                        | 7680000-769FFFF     | 3B40000-3B4FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 949          | 128 / 64                        | 76A0000-76BFFFF     | 3B50000-3B5FFFF      |
| 950          | 128 / 64                        | 76C0000-76DFFFF     | 3B60000-3B6FFFF      |
| 951          | 128 / 64                        | 76E0000-76FFFFFF    | 3B70000-3B7FFFF      |
| 952          | 128 / 64                        | 7700000-771FFFF     | 3B80000-3B8FFFF      |
| 953          | 128 / 64                        | 7720000-773FFFF     | 3B90000-3B9FFFF      |
| 954          | 128 / 64                        | 7740000-775FFFF     | 3BA0000-3BAFFFF      |
| 955          | 128 / 64                        | 7760000-777FFFF     | 3BB0000-3BBFFFF      |
| 956          | 128 / 64                        | 7780000-779FFFF     | 3BC0000-3BCFFFF      |
| 957          | 128 / 64                        | 77A0000-77BFFFF     | 3BD0000-3BDFFFF      |
| 958          | 128 / 64                        | 77C0000-77DFFFF     | 3BE0000-3BEFFFF      |
| 959          | 128 / 64                        | 77E0000-77FFFFFF    | 3BF0000-3BFFFFFF     |
| 960          | 128 / 64                        | 7800000-781FFFF     | 3C00000-3C0FFFF      |
| 961          | 128 / 64                        | 7820000-783FFFF     | 3C10000-3C1FFFF      |
| 962          | 128 / 64                        | 7840000-785FFFF     | 3C20000-3C2FFFF      |
| 963          | 128 / 64                        | 7860000-787FFFF     | 3C30000-3C3FFFF      |
| 964          | 128 / 64                        | 7880000-789FFFF     | 3C40000-3C4FFFF      |
| 965          | 128 / 64                        | 78A0000-78BFFFF     | 3C50000-3C5FFFF      |
| 966          | 128 / 64                        | 78C0000-78DFFFF     | 3C60000-3C6FFFF      |
| 967          | 128 / 64                        | 78E0000-78FFFFFF    | 3C70000-3C7FFFF      |
| 968          | 128 / 64                        | 7900000-791FFFF     | 3C80000-3C8FFFF      |
| 969          | 128 / 64                        | 7920000-793FFFF     | 3C90000-3C9FFFF      |
| 970          | 128 / 64                        | 7940000-795FFFF     | 3CA0000-3CAFFFF      |
| 971          | 128 / 64                        | 7960000-797FFFF     | 3CB0000-3CBFFFF      |
| 972          | 128 / 64                        | 7980000-799FFFF     | 3CC0000-3CCFFFF      |
| 973          | 128 / 64                        | 79A0000-79BFFFF     | 3CD0000-3CDFFFF      |
| 974          | 128 / 64                        | 79C0000-79DFFFF     | 3CE0000-3CEFFFF      |
| 975          | 128 / 64                        | 79E0000-79FFFFFF    | 3CF0000-3CFFFFFF     |
| 976          | 128 / 64                        | 7A00000-7A1FFFF     | 3D00000-3D0FFFF      |
| 977          | 128 / 64                        | 7A20000-7A3FFFF     | 3D10000-3D1FFFF      |
| 978          | 128 / 64                        | 7A40000-7A5FFFF     | 3D20000-3D2FFFF      |
| 979          | 128 / 64                        | 7A60000-7A7FFFF     | 3D30000-3D3FFFF      |
| 980          | 128 / 64                        | 7A80000-7A9FFFF     | 3D40000-3D4FFFF      |
| 981          | 128 / 64                        | 7AA0000-7ABFFFF     | 3D50000-3D5FFFF      |
| 982          | 128 / 64                        | 7AC0000-7ADFFFF     | 3D60000-3D6FFFF      |

Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 983          | 128 / 64                        | 7AE0000-7AFFFFFF    | 3D70000-3D7FFFF      |
| 984          | 128 / 64                        | 7B00000-7B1FFFF     | 3D80000-3D8FFFF      |
| 985          | 128 / 64                        | 7B20000-7B3FFFF     | 3D90000-3D9FFFF      |
| 986          | 128 / 64                        | 7B40000-7B5FFFF     | 3DA0000-3DAFFFF      |
| 987          | 128 / 64                        | 7B60000-7B7FFFF     | 3DB0000-3DBFFFF      |
| 988          | 128 / 64                        | 7B80000-7B9FFFF     | 3DC0000-3DCFFFF      |
| 989          | 128 / 64                        | 7BA0000-7BBFFFF     | 3DD0000-3DDFFFF      |
| 990          | 128 / 64                        | 7BC0000-7BDFFFF     | 3DE0000-3DEFFFF      |
| 991          | 128 / 64                        | 7BE0000-7BFFFFF     | 3DF0000-3DFFFFFF     |
| 992          | 128 / 64                        | 7C00000-7C1FFFF     | 3E00000-3E0FFFF      |
| 993          | 128 / 64                        | 7C20000-7C3FFFF     | 3E10000-3E1FFFF      |
| 994          | 128 / 64                        | 7C40000-7C5FFFF     | 3E20000-3E2FFFF      |
| 995          | 128 / 64                        | 7C60000-7C7FFFF     | 3E30000-3E3FFFF      |
| 996          | 128 / 64                        | 7C80000-7C9FFFF     | 3E40000-3E4FFFF      |
| 997          | 128 / 64                        | 7CA0000-7CBFFFF     | 3E50000-3E5FFFF      |
| 998          | 128 / 64                        | 7CC0000-7CDFFFF     | 3E60000-3E6FFFF      |
| 999          | 128 / 64                        | 7CE0000-7CFFFFFF    | 3E70000-3E7FFFF      |
| 1000         | 128 / 64                        | 7D00000-7D1FFFF     | 3E80000-3E8FFFF      |
| 1001         | 128 / 64                        | 7D20000-7D3FFFF     | 3E90000-3E9FFFF      |
| 1002         | 128 / 64                        | 7D40000-7D5FFFF     | 3EA0000-3EAFFFF      |
| 1003         | 128 / 64                        | 7D60000-7D7FFFF     | 3EB0000-3EBFFFF      |
| 1004         | 128 / 64                        | 7D80000-7D9FFFF     | 3EC0000-3ECFFFF      |
| 1005         | 128 / 64                        | 7DA0000-7DBFFFF     | 3ED0000-3EDFFFF      |
| 1006         | 128 / 64                        | 7DC0000-7DDFFFF     | 3EE0000-3EEFFFF      |
| 1007         | 128 / 64                        | 7DE0000-7DFFFFFF    | 3EF0000-3EFFFFFF     |
| 1008         | 128 / 64                        | 7E00000-7E1FFFF     | 3F00000-3F0FFFF      |
| 1009         | 128 / 64                        | 7E20000-7E3FFFF     | 3F10000-3F1FFFF      |
| 1010         | 128 / 64                        | 7E40000-7E5FFFF     | 3F20000-3F2FFFF      |
| 1011         | 128 / 64                        | 7E60000-7E7FFFF     | 3F30000-3F3FFFF      |
| 1012         | 128 / 64                        | 7E80000-7E9FFFF     | 3F40000-3F4FFFF      |
| 1013         | 128 / 64                        | 7EA0000-7EBFFFF     | 3F50000-3F5FFFF      |
| 1014         | 128 / 64                        | 7EC0000-7EDFFFF     | 3F60000-3F6FFFF      |
| 1015         | 128 / 64                        | 7EE0000-7EFFFFFF    | 3F70000-3F7FFFF      |
| 1016         | 128 / 64                        | 7F00000-7F1FFFF     | 3F80000-3F8FFFF      |

**Table 33. Block Address Table for Descrete Device (Up to 1-Gbit)<sup>(1)(2)(3)(4)</sup>**

| Block Number | Block Size<br>(Kbytes / Kwords) | x8 Address<br>(HEX) | x16 Address<br>(HEX) |
|--------------|---------------------------------|---------------------|----------------------|
| 1017         | 128 / 64                        | 7F20000-7F3FFFF     | 3F90000-3F9FFFF      |
| 1018         | 128 / 64                        | 7F40000-7F5FFFF     | 3FA0000-3FAFFFF      |
| 1019         | 128 / 64                        | 7F60000-7F7FFFF     | 3FB0000-3FBFFFF      |
| 1020         | 128 / 64                        | 7F80000-7F9FFFF     | 3FC0000-3FCFFFF      |
| 1021         | 128 / 64                        | 7FA0000-7FBFFFF     | 3FD0000-3FDFFFF      |
| 1022         | 128 / 64                        | 7FC0000-7FDFFFF     | 3FE0000-3FEFFFF      |
| 1023         | 128 / 64                        | 7FE0000-7FFFFFF     | 3FF0000-3FFFFFF      |

1. The 256-Mbit device consists of 256 blocks, from block 0 to block 255.
2. The 512-Mbit device consists of 512 blocks, from block 0 to block 511.
3. The 1-Gbit device consists of 1024 blocks, from block 0 to block 1023.
4. The 2-Gbit device is a 1-Gbit/1-Gbit stack; there're in total 2048 blocks, from block 0 to block 2047, including upper die and bottom die.

## Appendix B Common Flash Interface (CFI)

The Common Flash Interface is a JEDEC approved, standardized data structure that can be read from the Flash memory device. It allows a system software to query the device to determine various electrical and timing parameters, density information and functions supported by the memory. The system can interface easily with the device, enabling the software to upgrade itself when necessary.

When the Read CFI Query command is issued, the memory enters Read CFI Query mode and read operations output the CFI data. [Table 34](#), [Table 35](#), [Table 36](#), [Table 37](#) and [Table 38](#) and show the addresses (A-1, A0-A7) used to retrieve the data.

**Table 34. Query structure overview<sup>(1)</sup>**

| Address |     | Sub-section name                                | Description                                                         |
|---------|-----|-------------------------------------------------|---------------------------------------------------------------------|
| x16     | x8  |                                                 |                                                                     |
| 10h     | 20h | CFI query identification string                 | Command set ID and algorithm data offset                            |
| 1Bh     | 36h | System interface information                    | Device timing & voltage information                                 |
| 27h     | 4Eh | Device geometry definition                      | Flash device layout                                                 |
| 40h     | 80h | Primary algorithm-specific extended query table | Additional information specific to the primary algorithm (optional) |

1. Query data are always presented on the lowest order data outputs.

**Table 35. CFI query identification string<sup>(1)</sup>**

| Address |     | Data  | Description                                                                                              | Value          |
|---------|-----|-------|----------------------------------------------------------------------------------------------------------|----------------|
| x16     | x8  |       |                                                                                                          |                |
| 10h     | 20h | 0051h | Query Unique ASCII String 'QRY'                                                                          | 'Q'            |
| 11h     | 22h | 0052h |                                                                                                          | 'R'            |
| 12h     | 24h | 0059h |                                                                                                          | 'Y'            |
| 13h     | 26h | 0002h | Primary algorithm command set and control interface ID code 16 bit ID code defining a specific algorithm | AMD compatible |
| 14h     | 28h | 0000h |                                                                                                          |                |
| 15h     | 2Ah | 0040h | Address for primary algorithm extended query table (see <a href="#">Table 38</a> )                       | P = 40h        |
| 16h     | 2Ch | 0000h |                                                                                                          |                |
| 17h     | 2Eh | 0000h | Alternate vendor command set and control interface ID code second vendor - specified algorithm supported | NA             |
| 18h     | 30h | 0000h |                                                                                                          |                |
| 19h     | 32h | 0000h | Address for alternate algorithm extended query table                                                     | NA             |
| 1Ah     | 34h | 0000h |                                                                                                          |                |

1. Query data are always presented on the lowest order data outputs (DQ7-DQ0) only. DQ8-DQ15 are '0'.

Table 36. CFI query system interface information<sup>(1)</sup>

| Address |     | Data                             | Description                                                                                                                          | Value                                                                |
|---------|-----|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| x16     | x8  |                                  |                                                                                                                                      |                                                                      |
| 1Bh     | 36h | 0027h                            | V <sub>CC</sub> logic supply minimum Program/Erase voltage<br>bit 7 to 4BCD value in volts<br>bit 3 to 0BCD value in 100 mV          | 2.7 V                                                                |
| 1Ch     | 38h | 0036h                            | V <sub>CC</sub> logic supply maximum Program/Erase voltage<br>bit 7 to 4BCD value in volts<br>bit 3 to 0BCD value in 100 mV          | 3.6 V                                                                |
| 1Dh     | 3Ah | 00B5h                            | V <sub>PPH</sub> [programming] supply minimum Program/Erase voltage<br>bit 7 to 4HEX value in volts<br>bit 3 to 0BCD value in 100 mV | 11.5 V                                                               |
| 1Eh     | 3Ch | 00C5h                            | V <sub>PPH</sub> [programming] supply maximum Program/Erase voltage<br>bit 7 to 4HEX value in volts<br>bit 3 to 0BCD value in 10 mV  | 12.5 V                                                               |
| 1Fh     | 3Eh | 0009h                            | Typical time-out for single byte/word program = 2 <sup>n</sup> μs                                                                    | 512 μs                                                               |
| 20h     | 40h | 000Ah                            | Typical time-out for maximum size buffer program = 2 <sup>n</sup> μs                                                                 | 1024 μs                                                              |
| 21h     | 42h | 000Ah                            | Typical time-out for individual block erase = 2 <sup>n</sup> ms                                                                      | 1 s                                                                  |
| 22h     | 44h | 0012h / 0013h /<br>0014h / 0015h | Typical time-out for full Chip Erase = 2 <sup>n</sup> ms                                                                             | 256-Mbit 262 s<br>512-Mbit 524 s<br>1-Gbit 1048 s<br>2-Gbit 2097 s   |
| 23h     | 46h | 0001h                            | Maximum time-out for byte/word program = 2 <sup>n</sup> times<br>typical time-out                                                    | 1024 μs                                                              |
| 24h     | 48h | 0002h                            | Maximum time-out for buffer program = 2 <sup>n</sup> times<br>typical time-out                                                       | 4096 μs                                                              |
| 25h     | 4Ah | 0002h                            | Maximum time-out per individual block erase = 2 <sup>n</sup><br>times typical time-out                                               | 4 s                                                                  |
| 26h     | 4Ch | 0002h                            | Maximum time-out for Chip Erase = 2 <sup>n</sup> times typical<br>time-out                                                           | 256-Mbit 1048 s<br>512-Mbit 2096 s<br>1-Gbit 4194 s<br>2-Gbit 8388 s |

1. The values given in the above table are valid for both packages.

Table 37. Device geometry definition

| Address                  |                          | Data                                                           | Description                                                                                                            | Value                                              |
|--------------------------|--------------------------|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| x16                      | x8                       |                                                                |                                                                                                                        |                                                    |
| 27h                      | 4Eh                      | 0019h / 001Ah / 001Bh/001Ch                                    | Device size = 2 <sup>n</sup> in number of bytes                                                                        | 32 Mbytes<br>64 Mbytes<br>128 Mbytes<br>256 Mbytes |
| 28h<br>29h               | 50h<br>52h               | 0002h<br>0000h                                                 | Flash device interface code description                                                                                | x8, x16<br>Async.                                  |
| 2Ah<br>2Bh               | 54h<br>56h               | 000Ah<br>0000h                                                 | Maximum number of bytes in multiple-byte program or page= 2 <sup>n</sup>                                               | 1024 <sup>(1)</sup>                                |
| 2Ch                      | 58h                      | 0001h                                                          | Number of Erase block regions. It specifies the number of regions containing contiguous Erase blocks of the same size. | 1                                                  |
| 2Dh<br>2Eh               | 5Ah<br>5Ch               | 00FFh / 00FFh / 00FFh / 00FFh<br>0000h / 0001h / 0003h / 0007h | Erase block region 1 information<br>Number of Erase blocks of identical size = 00FFh + 1 / 01FFh +1 / 03FFh + 1        | 256<br>512<br>1024<br>2048                         |
| 2Fh<br>30h               | 5Eh<br>60h               | 0000h<br>0002h                                                 | Erase block region 1 information<br>Block size in region 1 = 0200h * 256 byte                                          | 128 Kbytes                                         |
| 31h<br>32h<br>33h<br>34h | 62h<br>64h<br>66h<br>68h | 0000h<br>0000h<br>0000h<br>0000h                               | Erase block region 2 information                                                                                       | 0                                                  |
| 35h<br>36h<br>37h<br>38h | 6Ah<br>6Ch<br>6Eh<br>70h | 0000h<br>0000h<br>0000h<br>0000h                               | Erase block region 3 information                                                                                       | 0                                                  |
| 39h<br>3Ah<br>3Bh<br>3Ch | 72h<br>74h<br>76h<br>78h | 0000h<br>0000h<br>0000h<br>0000h                               | Erase block region 4 information                                                                                       | 0                                                  |

1. For X16/X8 mode, the maximum buffer size is 1024 bytes/256 bytes respectively.

**Table 38. Primary algorithm-specific extended query table <sup>(1)</sup>**

| Address |     | Data  | Description                                                                                                                                         | Value                                                             |
|---------|-----|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| x16     | x8  |       |                                                                                                                                                     |                                                                   |
| 40h     | 80h | 0050h | Primary algorithm extended query table unique ASCII string "PRI"                                                                                    | 'P'                                                               |
| 41h     | 82h | 0052h |                                                                                                                                                     | 'R'                                                               |
| 42h     | 84h | 0049h |                                                                                                                                                     | 'I'                                                               |
| 43h     | 86h | 0031h | Major version number, ASCII                                                                                                                         | '1'                                                               |
| 44h     | 88h | 0033h | Minor version number, ASCII                                                                                                                         | '3'                                                               |
| 45h     | 8Ah | 0018h | Address sensitive unlock (bits 1 to 0)<br>00 = required, 01 = not required<br>Silicon revision number (bits 7 to 2)                                 | Required                                                          |
| 46h     | 8Ch | 0002h | Erase Suspend<br>00 = not supported, 01 = Read only, 02 = read and write                                                                            | 2                                                                 |
| 47h     | 8Eh | 0001h | Block protection<br>00 = not supported, x = number of blocks per group                                                                              | 1                                                                 |
| 48h     | 90h | 0000h | Temporary block unprotect<br>00 = not supported, 01 = supported                                                                                     | Not supported                                                     |
| 49h     | 92h | 0008h | Block protect / unprotect<br>08 = M29EWH/M29EWL                                                                                                     | 8                                                                 |
| 4Ah     | 94h | 0000h | Simultaneous operations: not supported                                                                                                              | NA                                                                |
| 4Bh     | 96h | 0000h | Burst mode, 00 = not supported, 01 = supported                                                                                                      | Not supported                                                     |
| 4Ch     | 98h | 0003h | Page mode, 00 = not supported, 01 = 8-word page<br>02 = 8-word page, 03 = 16-word page                                                              | 16-word page                                                      |
| 4Dh     | 9Ah | 00B5h | V <sub>PPH</sub> supply minimum Program/Erase voltage<br>bit 7 to 4 HEX value in volts<br>bit 3 to 0 BCD value in 100 mV                            | 11.5 V                                                            |
| 4Eh     | 9Ch | 00C5h | V <sub>PPH</sub> supply maximum Program/Erase voltage<br>bit 7 to 4 HEX value in volts<br>bit 3 to 0 BCD value in 100 mV                            | 12.5 V                                                            |
| 4Fh     | 9Eh | 00xxh | Top/bottom boot block flag<br>xx = 04h: Uniform device, HW protection for lowest block<br>xx = 05h: Uniform device, HW protection for highest block | Uniform + V <sub>PP</sub> /WP# protecting highest or lowest block |
| 50h     | A0h | 0001h | Program suspend, 00 = not supported, 01 = supported                                                                                                 | Supported                                                         |

1. The values given in the above table are valid for both packages.

## Appendix C Extended Memory Block

The M29EW has an extra block, the Extended Memory Block, that can be accessed using a dedicated command. This Extended Memory Block is 128words in x16 mode and 256bytes in x8 mode. It is used as a security block (to provide a permanent security identification number) or to store additional information.

The device can be shipped either with the Extended Memory Block pre-locked by Numonyx, or unlocked.

If the Extended Memory Block is not pre-locked by Numonyx, it can be customer-lockable. Its status is indicated by bit DQ7 of Extended Memory Block Verify Indicator. This bit is permanently set to either '1' or '0' at the Numonyx factory and cannot be changed. When set to '1', it indicates that the device is pre-locked by Numonyx and the Extended Memory Block is protected. When set to '0', it indicates that the device is customer-lockable. Bit DQ7 being permanently locked to either '1' or '0' is another security feature which ensures that a customer-lockable device cannot be used instead of a Numonyx pre-locked one.

Bit DQ7 is the most significant bit in the Extended Memory Block Verify Indicator. It can be read in Auto Select mode using either the Programmer (see [Table 7](#) and [Table 8](#)) or the In-system method (see [Table 9](#) and [Table 10](#)).

The Extended Memory Block can only be accessed when the device is in Extended Memory Block mode. For details of how the Extended Memory Block mode is entered and exited, refer to the [Section 6.3.1: Enter Extended Memory Block command](#) and [Section 6.3.2: Exit Extended Memory Block command](#), and to [Table 13](#) and [Table 9](#).

### C.1 Numonyx pre-locked Extended Memory Block

If devices of which the Extended Memory Block is pre-locked upon customer request, the 128bits security identification number is written to the Extended Memory Block address space (see [Table 39: Extended Memory Block address and data](#)) in Numonyx factory. The contents in the Extended Memory Block cannot be changed any more.

## C.2 Customer-lockable Extended Memory Block

A device where the Extended Memory Block is customer-lockable is delivered with the DQ7 bit set to '0' and the Extended Memory Block unprotected. It is up to the customer to program and protect the Extended Memory Block but care must be taken because the protection of the Extended Memory Block is not reversible.

If the device has not been shipped with the Extended Memory Block pre-protected, the block can be protected by setting the Extended Memory Block Protection bit, DQ0, to '0'.

However, this bit can only be programmed once; and once it is protected the Extended Memory Block cannot be unprotected.

Once the Extended Memory Block is programmed, the Exit Extended Memory Block command must be issued to exit the Extended Memory Block mode and return the device to Read mode.

**Table 39. Extended Memory Block address and data**

| Address <sup>(1)</sup> |                 | Data                         |                                   |                              |
|------------------------|-----------------|------------------------------|-----------------------------------|------------------------------|
| x8                     | x16             | Numonyx pre-locked           | Customer-lockable                 |                              |
| 000000h-00000Fh        | 000000h-000007h | Secure identification number | Determined by customers (default) | Secure identification number |
| 000010h-0000FFh        | 000008h-00007Fh | Protected and unavailable    |                                   | Determined by customers      |

## Appendix D Revision History

**Table 40. Document revision history**

| Date     | Version | Changes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|----------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| May 2008 | 01      | Initial release                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Oct 2008 | 02      | Update $t_{AVAV}$ values in <a href="#">Table 24</a> and <a href="#">Table 25</a><br>Move buffer program flow chart to Chapter 6.2.1, as <a href="#">Figure 8</a><br>Minor wording changes                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Dec 2008 | 03      | Apply Axcell™ as M29EW's branding name<br>Change the names of timing parameters in <a href="#">Table 20</a> , <a href="#">Table 26</a> and <a href="#">Table 27</a><br>Modify many waveforms to align the signal names<br>Some wording changes<br>Spec change of $t_{EHEL2}$ from 20ns to 30ns, in <a href="#">Table 27</a><br>Remove "Numonyx Confidential"<br>Remove conventions section and set Revision History as <a href="#">Appendix D</a><br>Update physical dimension information in <a href="#">Table 29</a><br>Add Document Number<br>Add 1-Gbit and 512-Mbit information into the data sheet<br>Correct some typo error |
| Mar 2009 | 04      | Correct the buffer write cycle numbers and wording correction in <a href="#">Table 11</a> and <a href="#">Table 12</a><br>Fix a text corruption in <a href="#">Figure 8</a><br>Remove invalid ship options in <a href="#">Chapter 5.1</a><br>Add <a href="#">Figure 7</a> to explain the buffer programming<br>Add buffer write misalignment description to better explain buffer programming usage in <a href="#">Chapter 6.2.1</a><br>Move the disclaimer to the end of the data sheet<br>Add 10Kohm pull-up resistor description for RY/BY# pin<br>Update Fortified BGA physical dimension of ball size <a href="#">Table 30</a> |
| Apr 2009 | 05      | Remove notes about Enhanced Buffer Programming in <a href="#">Chapter 6.2.2</a><br>Change $V_{PPH}$ spec in <a href="#">Table 18</a> and <a href="#">Table 19</a><br>Change the address for VPB read in <a href="#">Table 13</a> and <a href="#">Table 14</a><br>Correct the DQ2 toggling states in <a href="#">Table 17</a>                                                                                                                                                                                                                                                                                                        |
| Jun 2009 | 06      | Add technology information in cover page and <a href="#">Chapter 1</a><br>Add RoHS and Halogen Free information in cover page<br>Add block address information in <a href="#">Chapter Appendix A</a><br>Move programming and erase performance as separate chapter in <a href="#">Chapter 10</a><br>Add leaded, RoHS, halogen free information in <a href="#">Chapter 12</a>                                                                                                                                                                                                                                                        |
| Oct 2009 | 07      | Add 2-Gbit (1-Gbit/1-Gbit) stack device related information                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

| Date     | Version | Changes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Feb 2010 | 08      | <p>Revised part numbers in the <a href="#">Table 32.: Valid Combinations of M29EW Part Numbers</a></p> <p>Update programming performance specifications and suspend latency specifications in <a href="#">Table 28: Programming and Erase Performance</a></p> <p>Update CFI information of program max timeout in <a href="#">Table 36: CFI query system interface information</a></p> <p>Add Erase to Suspend specification in <a href="#">Table 28: Programming and Erase Performance</a></p> <p>Add note for tDVWH in <a href="#">Table 24: Write AC characteristics, Write Enable Controlled</a></p> <p>Add note for tDVEH in <a href="#">Table 25: Write AC characteristics, Chip Enable Controlled</a></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Apr 2010 | 09      | <p>Update JEDEC compliance in cover page</p> <p>Correct the buffer programming boundary limitation in <a href="#">Section 6.2.1: Write to Buffer Program command</a></p> <p>Update the specification of t<sub>PLRH</sub>(t<sub>READY</sub>) in <a href="#">Table 26: Reset AC characteristics</a></p> <p>Update the description of V<sub>PP</sub>/WP# pin in <a href="#">Chapter 2.8: V<sub>PP</sub>/Write Protect (V<sub>PP</sub>/WP#)</a></p> <p>Add BYTE# transition waveform as <a href="#">Figure 19: BYTE# Transition AC Waveform</a></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| May 2010 | 10      | <p>Update the Random Read AC waveforms about BYTE# pin in <a href="#">Section 9: DC and AC Parameters</a></p> <p>Put a link for product part numbers in <a href="#">Section 12: Ordering Information</a></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Apr 2011 | 11      | <p>Add a block diagram <a href="#">Figure 2: 2-Gbit (1-Gbit/1-Gbit stack) configurations</a> to emphasize 2G part is 1G/1G stack, not discrete one</p> <p>Remove the invalid automatic standby mode from front page and <a href="#">Section 3: Bus Operations on page 17</a></p> <p>Add t<sub>WHWH1</sub> specification at <a href="#">Table 24: Write AC characteristics, Write Enable Controlled</a> and <a href="#">Table 25: Write AC characteristics, Chip Enable Controlled</a></p> <p>At CFI table offset 2Ah/2Bh (X16), add a note for X8 mode to emphasize its maximum buffer size is 256 bytes</p> <p>For read ID and read protection status, align with device about higher address pins input status at <a href="#">Table 5</a>, <a href="#">Table 6</a>, <a href="#">Table 7</a> and <a href="#">Table 8</a></p> <p>Add JEDEC standard lead width for TSOP56 package at <a href="#">Table 29: TSOP56 – 56 lead thin small-outline package, 14 x 20 mm, package mechanical data on page 78</a></p> <p>Correct the glitch filter from 5ns to 3ns</p> <p>Remove the invalid statement about applying VID to A9 to enter Auto Select mode at <a href="#">Section 7.1.3: Extended Memory Block Protection bit (DQ0)</a></p> <p>Add Blank Check related information</p> <p>Align with device about DQ2 toggle status when Erase/Blank Check Error happens at <a href="#">Table 17: Status Register bits</a></p> |

**Please Read Carefully:**

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH NUMONYX® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN NUMONYX'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, NUMONYX ASSUMES NO LIABILITY WHATSOEVER, AND NUMONYX DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF NUMONYX PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

Numonyx products are not intended for use in medical, life saving, life sustaining, critical control or safety systems, or in nuclear facility applications.

Numonyx may make changes to specifications and product descriptions at any time, without notice.

Numonyx, B.V. may have patents or pending patent applications, trademarks, copyrights, or other intellectual property rights that relate to the presented subject matter. The furnishing of documents and other materials and information does not provide any license, express or implied, by estoppel or otherwise, to any such patents, trademarks, copyrights, or other intellectual property rights.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Numonyx reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

Contact your local Numonyx sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an order number and are referenced in this document, or other Numonyx literature may be obtained by visiting Numonyx's website at <http://www.numonyx.com>.

Numonyx™ Axcell is a trademark or registered trademark of Numonyx or its subsidiaries in the United States and other countries.

\*Other names and brands may be claimed as the property of others.

Copyright © 2009, Numonyx, B.V., All Rights Reserved.