



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939 Fax:

SDB201 THRU SDB207

Glass Passivated Bridge Rectifier 50 to 1000 Volts

2 Amp Single Phase

SDB-1 Notch in Case

DIMENSIONS								
	INCHES		ММ					
DIM	MIN	MAX	MIN	MAX	NOTE			
Α	.316	.335	8.05	8.51				
В	.245	.255	6.20	6.50				
O	.040	.060	1.02	1.50				
D	.360	.410	9.40	10.4				
Ш	.102	.130	2.60	3.30				
Ð	.003	.013	.076	.330				
Ι	.195	.205	5.00	5.20				
K	.038	.047	1.00	1.20				

Suggested Solder Pad

Layout .344 .205"

Features

- Surface Mount Package
- Glass Passivated Diode Construction
- High Surge Current Capability
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information) Halogen free available upon request by adding suffix "-HF"

ıum Ratings

- Operating Temperature: -55°C to +150°C Storage Temperature: -55°C to +150°C
- UL Recognized File # E165989

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SDB201	SDB201	50V	35V	50V
SDB202	SDB202	100V	70V	100V
SDB203	SDB203	200V	140V	200V
SDB204	SDB204	400V	280V	400V
SDB205	SDB205	600V	420V	600V
SDB206	SDB206	800V	560V	800V
SDB207	SDB207	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

iooti ioui onuluotoliotioo 😸 20°0 omooo otiioi mioo opoonio					
Average Forward Current	$I_{F(AV)}$	2.0 A	T _A = 40°C		
Peak Forward Surge Current	I _{FSM}	60A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage	V _F	1.2V	I _F = 2.0A; T _A = 25°C		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	10μA 0.5mA	$T_{J} = 25^{\circ}C$ $T_{J} = 125^{\circ}C$		
Typical Junction Capacitance	C	25pF	Measured at 1.0MHz, V _R =4.0V		
Rating For Fusing	l ² t	14.9A ² s	t<8.3ms		


Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7

SDB201 thru SDB207



Micro Commercial Components

FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT






FIG.3-TYPICAL JUNCTION CAPACITANCE

REVERSE VOLTAGE, (VOLTS)




FIG.4-TYPICAL FORWARD CHARACTERISTICS





FIG.5-TYPICAL REVERSE CHARACTERISTICS





Ordering Information

Device	Packing	
(Part Number)-TP	Tape&Reel1.5Kpcs/Reel	
(Part Number)-BP	Bulk; 5K/Box	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.