

Digi One® IA

Industrial Serial Server

Easy, reliable serial-to-Ethernet and Modbus-to-Modbus/
TCP connectivity for industrial automation applications.



Overview

Digi One IA provides reliable, cost-effective network connectivity for serial devices. This unobtrusive and easy-to-use serial server delivers serial-to-Ethernet connectivity to Programmable Logic Controllers (PLCs), Remote Terminal Units (RTUs), bar-code readers and other industrial devices.

Digi One IA supports most industrial automation protocols through TCP/UDP connections, serial bridging or COM port redirection using Digi's patented RealPort® software. RealPort enables existing applications to communicate with serial devices over the Ethernet. By creating a Modbus bridge, multiple Modbus/TCP masters can share Modbus serial slaves, or Modbus serial masters can access Modbus/TCP slaves.

Digi One IA is easy to install locally or remotely. The IP address can be configured using DHCP, ARP-Ping or Setup, an application included with the installation CD that detects Digi One devices on the network. Using the web interface, users can configure advanced functions into their application.

Related Products



Digi One® IAP



Digi One® IAP Haz



Digi One® SP IA




PortServer® TS H MEI



Power Supply
76000736

Application Highlight



Features/Benefits

- Patented RealPort for COM/TTY port control and management
- TCP/UDP Socket Services for broad device connectivity and application use
- Modbus serial to Modbus/TCP protocol conversion
- Switch selectable RS-232/422/485 for simple interfacing to any type of serial device
- Industrial DIN rail mounting for use in space-prohibitive control cabinets
- Galvanic isolation (between power and serial)
- Tunable for low latency or optimized throughput




Specifications


Digi One® IA

Features	
Management	HTTP configuration, Digi Port Authority - Remote management diagnostics and auto-discovery tool
Protocols	Telnet, Reverse Telnet and extended Telnet RFC 2217; TCP/UDP Socket Services; UDP, support 32 concurrent socket connections; DHCP/RARP, ARP-Ping; Modbus ASCII/RTU to Modbus TCP conversion; Modbus Ethernet-to-Serial Bridge Function supporting Modbus/TCP, Modbus/UDP, Modbus/RTU, Modbus/ASCII; Modbus bridge supports TCP and UDP Encapsulation of Modbus/RTU, Modbus/ASCII
Software	Patented RealPort for COM/TTY ports
Operating Systems	AIX, HP-UX, Linux®, SCO® OpenServer™ 5, SCO® OpenServer™ 6, Solaris™ Intel, Solaris™ SPARC, Windows XP®, Windows Server® 2003, Windows Server® 2008, Windows Vista®
Status LEDs	Serial signals, Power, Ethernet, Diagnostics
Dimensions (L x W x D)	4.70 in x 0.90 in x 4.0 in (12.00 cm x 2.30 cm x 10.10 cm)
Weight	2.25 oz (64.00 g)
Other	Full modem and hardware flow control, Flash upgradeable firmware, 35 mm DIN rail mounting
Interfaces	
Serial Ports	1 RS-232/422/485 (switch selectable)
Serial Connector	DB-9M or screw terminal connectors
Serial Throughput	Up to 230 Kbps
Ethernet Physical Layer	10/100Base-T
Power Requirements	
Power Input	9-30VDC @ .5 Amps max
Power Connector	Screw terminal block power jack for external supply
Surge Protection	2 kV isolation between power supply and serial ground product
Environmental	
Operating Temperature	0° C to 60° C (32° F to 140° F)
Relative Humidity	5% to 90% (non-condensing)
Ethernet Isolation	1500VAC min per IEEE 802.3/ANSI X3.263
Serial Port Protection (ESD)	+15 kV air GAP and +8 kV contact discharge per IEC 1000-4-2
Regulatory Approvals	
Safety	UL 60950, UL1604 (Class 1 Div 2), EN60950, CAN/CSA C22.2 No.60950
Emissions/Immunity	FCC Part 15 Subpart B (Class A), EN55024, EN55022 (Class A), EN61000-6-2

Digi One IA - Top



Digi One IA - Bottom



Visit www.digi.com for part numbers.

DIGI SERVICE AND SUPPORT - You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. www.digi.com/support

Digi International
877-912-3444
952-912-3444
info@digi.com

Digi International France
+33-1-55-61-98-98
www.digi.fr

Digi International KK
+81-3-5428-0261
www.digi-intl.co.jp

Digi International (HK) Limited
+852-2833-1008
www.digi.cn

BUY ONLINE • www.digi.com

91001156
E1/809

© 1999-2009 Digi International Inc.

All rights reserved. Digi, Digi International, the Digi logo, Digi One, PortServer and RealPort are trademarks or registered trademarks of Digi International Inc. in the United States and other countries worldwide. All other trademarks are the property of their respective owners.

