


HW-14-08-G-S-300-100



DW-11-20-T-D-825



(2,54 mm) .100"

DW, EW, ZW, HW SERIES

FLEXIBLE .025" SQ BOARD STACKERS

Mates with:

SSW, SSQ, ESW, ESQ, CES, SLW, BSW, BCS, SSM, IDSS, IDSD, HLE, PHF, SMSD, SMSS

SPECIFICATIONS

For complete specifications see www.samtec.com?DW, www.samtec.com?EW, www.samtec.com?ZW or www.samtec.com?HW-TH

Insulator Material:
DW, EW, ZW: Black Glass Filled Polyester
HW: Natural Liquid Crystal Polymer
Terminal Material:
Phosphor Bronze
Plating:
Au or Sn over 50µ" (1,27 µm) Ni

Operating Temp Range:
-55°C to +125°C with Gold
-55°C to +105°C with Tin
RoHS Compliant:
Yes
Lead-Free Solderable:
DW, EW, ZW: Wave Only
HW: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



ALSO AVAILABLE (MOQ Required)

- Other platings
- Contact Samtec.

Note: For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

Note: This Series is non-standard, non-returnable.

| TYPE STRIP | NO. PINS PER ROW | LEAD STYLE | PLATING OPTION | ROW OPTION | STACKER HEIGHT | OTHER OPTIONS | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------------------------|---|--|---|--|---|--------------------------|---|--|---|-----|--------------|-----|--------------|-----|---------------|-----|---------------|-----|---------------|-----|--------------|-----|--------------|-----|--------------|-----|---------------|-----|---------------|---|--|--|
| DW = (2,79 mm) .110" Tail | <p>Specify LEAD STYLE from chart</p> <table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>OAL</th> </tr> </thead> <tbody> <tr><td>-07</td><td>(10,92) .430</td></tr> <tr><td>-08</td><td>(13,46) .530</td></tr> <tr><td>-09</td><td>(18,54) .730</td></tr> <tr><td>-10</td><td>(21,08) .830</td></tr> <tr><td>-11</td><td>(23,62) .930</td></tr> <tr><td>-12</td><td>(26,16) 1.030</td></tr> <tr><td>-13</td><td>(31,24) 1.230</td></tr> <tr><td>-14</td><td>(36,32) 1.430</td></tr> <tr><td>-15</td><td>(16,00) .630</td></tr> <tr><td>-16</td><td>(11,30) .445</td></tr> <tr><td>-17</td><td>(12,19) .480</td></tr> <tr><td>-19</td><td>(33,78) 1.330</td></tr> <tr><td>-20</td><td>(28,70) 1.130</td></tr> </tbody> </table> | LEAD STYLE | OAL | -07 | (10,92) .430 | -08 | (13,46) .530 | -09 | (18,54) .730 | -10 | (21,08) .830 | -11 | (23,62) .930 | -12 | (26,16) 1.030 | -13 | (31,24) 1.230 | -14 | (36,32) 1.430 | -15 | (16,00) .630 | -16 | (11,30) .445 | -17 | (12,19) .480 | -19 | (33,78) 1.330 | -20 | (28,70) 1.130 | <p>-S = Single Row</p> <p>-D = Double Row</p> <p>-T = Triple Row</p> <p>-Q = Double Row .200" (5,08 mm) row space</p> | <p>"XXX" = Stacker Height</p> | <p>"XXX" = ZW or HW Tail Length</p> |
| LEAD STYLE | | OAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -07 | | (10,92) .430 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -08 | | (13,46) .530 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -09 | | (18,54) .730 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -10 | | (21,08) .830 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -11 | | (23,62) .930 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -12 | | (26,16) 1.030 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -13 | | (31,24) 1.230 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -14 | | (36,32) 1.430 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -15 | (16,00) .630 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -16 | (11,30) .445 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -17 | (12,19) .480 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -19 | (33,78) 1.330 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -20 | (28,70) 1.130 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| EW = (8,38 mm) .330" Tail | <p>01 thru 50</p> | <p>-F = Gold flash on contact, Matte Tin on tail</p> <p>-L = 10µ" (0,25 µm) Gold on contact area of longer tail, Matte Tin on tail</p> <p>-G = 10µ" (0,25 µm) Gold on contact area of longer tail, Gold flash on balance</p> <p>-T = Matte Tin</p> | <p>-LL = Locking Lead (Shortest dimension between the tail and the post is the end that will be crimped. Available on tails from (2,29 mm) .090" to (7,87 mm) .310" only.) Single row, 01 & 02 positions & -Q row not available</p> <p>"XXX" = Polarized Specify omitted pin position</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ZW = Custom Tail | | <p>01 thru 50</p> | <p>-S</p> <p>-D</p> <p>-T or -Q*</p> <p>-Q* = Same as -T except middle row of pins missing.</p> | <p>-F = Gold flash on contact, Matte Tin on tail</p> <p>-L = 10µ" (0,25 µm) Gold on contact area of longer tail, Matte Tin on tail</p> <p>-G = 10µ" (0,25 µm) Gold on contact area of longer tail, Gold flash on balance</p> <p>-T = Matte Tin</p> | <p>-LL = Locking Lead (Shortest dimension between the tail and the post is the end that will be crimped. Available on tails from (2,29 mm) .090" to (7,87 mm) .310" only.) Single row, 01 & 02 positions & -Q row not available</p> <p>"XXX" = Polarized Specify omitted pin position</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HW = High Temp Custom Tail | | | | | | <p>01 thru 50</p> | <p>-S</p> <p>-D</p> <p>-T or -Q*</p> <p>-Q* = Same as -T except middle row of pins missing.</p> | <p>-F = Gold flash on contact, Matte Tin on tail</p> <p>-L = 10µ" (0,25 µm) Gold on contact area of longer tail, Matte Tin on tail</p> <p>-G = 10µ" (0,25 µm) Gold on contact area of longer tail, Gold flash on balance</p> <p>-T = Matte Tin</p> | <p>-LL = Locking Lead (Shortest dimension between the tail and the post is the end that will be crimped. Available on tails from (2,29 mm) .090" to (7,87 mm) .310" only.) Single row, 01 & 02 positions & -Q row not available</p> <p>"XXX" = Polarized Specify omitted pin position</p> | | | | | | | | | | | | | | | | | | | | | | | |

