


You are here: [Products](#) » [Heatsinks f.cool](#) » [Accessories for electronic components](#) » [Mounting material for single semiconductors and heatsinks](#) » [Insulating clamping parts for power transistors](#) » [ISP 220](#) » [ISP 220](#)

- Heatsinks f.cool
 - Profile heatsinks and fluid coolers
 - Heatsinks and active heatsinks for processors
 - Finger shapes heatsinks and small heatsinks
 - Cooling aggregates
- Accessories for electronic components
 - Thermally conductive material
 - Fixing material for mechanical components
 - Mounting material for single semiconductors and heatsinks
 - Mounting kits for insulation of power transistors
 - Insulating clamping parts for power transistors
 - Mounts
 - Mounting parts for heatsinks
 - Insulating caps and insulator sleeves
- Cases f.case
- Connectors f.con

Insulating clamping parts for power transistors

ISP 220
for semiconductor-design TO 220

add to request



Features	Technical Drawing	Service
for transistor material	TO 220	
heat distortion	polyamide 6, GF reinforced	
dielectric strength	205(1,8 MPa)135(8 MPa)	
dielectric constant	>27 kV/mm	
dielectric loss factor	8 [100 Hz] / 4.5 [1 MHz]	
specific volume resistance	1300 [100 Hz] 450 [1 MHz]	
colour	>10 ¹³ Ω/cm	
class of flammibility	black	
	UL 94 V-0	