

Duplex Singlemode 8.3/125 Fiber Patch Cable (LC/ST), 30M (100-ft.)

MODEL NUMBER: N368-30M



Description

Tripp Lite's 30-meter (100ft), singlemode duplex fiber optic LC/ST patch cable is manufactured from 8.3/125 zipcord fiber. The cable has LC connectors on one end, ST connectors on the other, a PVC jacket, and is FDDI and OFNR rated. Duplex singlemode fiber is most commonly used in LAN applications.

Features

- Manufactured from 8.3/125 duplex (zipcord) fiber
- PVC jacket
- Length: 30-meter (100ft) Connectors: 2 LC and 2 ST connectors on each end
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Fiber made from glass (not a polymer)
- · Color coded shrouds identify transmit and receive
- Fiber optic distributed data interface (FDDI) rated
- · OFNR (riser rated)

Specifications

General Info		
Product Group	NETWORK CABLES	
OVERVIEW		
Fiber Type	8.3/125	
Intended Application	Computer Networking (Fiber)	

Highlights

- Premium PVC 8.3/125 micron singlemode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Twice the bandwidth throughput of multimode cable

Applications

 Networking equipment that requires singlemode fiber optic patch cables

System Requirements

 Any fiber optic hardware or NIC card requiring singlemode duplex cable with LC/ST connectors

Package Includes

30-meter (100ft) Duplex
 Singlemode Fiber Patch Cable,
 LC/ST



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Cable Type	SINGLEMODE 8.3/125 FIBER OPTIC	
Model Type	LC/ST	
INPUT		
Cable Length (m)	30	
UPC ASSIGNMENT		
Unit Carton UPC#	037332134813	
PHYSICAL		
Color	Yellow	
Style	Fiber Optic	
CONNECTIONS		
Connector A	LC	
Connector B	ST	
Number of Connectors	4	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.