



FEATURES:

- Used for kitting and to help organize the workstation
- Constructed from durable polystyrene plastic
- Die-cut drop-in covers available separately
- Reusable, ensuring best value
- Great container for Kanban
- Made in the United States of America

SPECIFICATIONS:

Property	Typical Value	Test Method
Specific Gravity	1.09	ASTM D-792
Tensile Strength	4,200 psi	ASTM D-638
Tensile Elongation	40%	ASTM D-638
Flexural Modulus	220,000 psi	ASTM D-790
Flexural Strength	6,700 psi	ASTM D-790
Total/Free Sulfur	<0.15% / <0.004%	
Chlorides	<0.3 PPM	
Outgassing & Corrosivity	Low	
5KV Decay Time	<0.01 sec @ 10% RH	
Surface Resistance	1×10^4 to $< 1 \times 10^{11}$ ohms	ANSI/ESD STM11.13

Item	Size (Inches)	Cavity Size (Inches)	# of Cavities
39206	10-1/2" x 8-3/4" x 1-1/2"	2" x 1-7/8" x 1"	12
39201	14-1/2" x 10-1/8" x 1-7/8"	3-1/2" x 2-3/4" x 1-1/4"	9
39202	14-3/8" x 10-1/8" x 1-3/4"	3" x 3" x 1-1/4"	12
39209	9-7/8" x 7-9/16" x 1"	3" x 1-1/2" x 1"	10
39203	Lid for Kitting Tray 39206		
39204	Lid for Kitting Tray 39201		
39205	Lid for Kitting Tray 39202		
39212	Lid for Kitting Tray 39209		

Tolerances are +/- 1/16" unless otherwise specified

Note: Per Packaging standard ANSI/ESD S541 section 6.1 Inside an EPA "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be: 1. Low charge generation, 2. Dissipative or conductive materials for intimate contact."

Specifications and procedures are subject to change without notice.



Made in the
United States of America

KITTING TRAYS

PROTEKTIVE PAK

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
39201

DATE:
June
2024