

Flush-type connector - SACC-DSI-MINMS-3CON-UNF PCB - 1455007

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/actuator flush-type plug, 3-pos., 7/8", PCB mounting with 7/8" fastening thread



Key commercial data

Packing unit	1 1
Custom tariff number	85366990
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C (Plug)
Degree of protection	IP67

General

Rated current at 40°C	12 A
Rated voltage	250 V
Number of positions	3
Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Status display	No
Surge voltage category	II
Pollution degree	3
Connection method	Solder pins
Mounting type	PCB mounting 7/8"

Material

Inflammability class according to UL 94	HB
Contact material	CuZn

Flush-type connector - SACC-DSI-MINMS-3CON-UNF PCB - 1455007

Technical data

Material

Contact surface material	Au
Contact carrier material	PUR
Material, knurls	Zinc die-cast, nickel-plated
Sealing material	Viton

Classifications

eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27449001

ETIM

ETIM 4.0	EC002061
ETIM 5.0	EC002061

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals

Flush-type connector - SACC-DSI-MINMS-3CON-UNF PCB - 1455007

Approvals

Approvals submitted

Approval details

UL Recognized 	
mm²/AWG/kcmil	20
Nominal current I _N	10 A
Nominal voltage U _N	600 V


cUL Recognized 	
mm²/AWG/kcmil	20
Nominal current I _N	10 A
Nominal voltage U _N	600 V

GOST 	
--	--


cULus Recognized 	
--	--

Drawings

Dimensioned drawing




Schematic diagram




Connector pin assignment

Flush-type connector - SACC-DSI-MINMS-3CON-UNF PCB - 1455007

Drilling diagram



Dimensioned drawing



7/8" flush-type plug