

74ALVCF162835

Low Voltage 18-Bit Universal Bus Driver with 3.6V Tolerant Outputs and 26Ω Series Resistors in Outputs

General Description

The 74ALVCF162835 low voltage 18-bit universal bus driver combines D-type latches and D-type flip-flops to allow data flow in transparent, latched and clocked modes.

Data flow is controlled by output-enable (\overline{OE}), latch-enable (LE), and clock (CLK) inputs. The device operates in Transparent Mode when LE is held HIGH. The device operates in clocked mode when LE is LOW and CLK is toggled. Data transfers from the Inputs (I_n) to Outputs (O_n) on a Positive Edge Transition of the Clock. When \overline{OE} is LOW, the output data is enabled. When \overline{OE} is HIGH the output port is in a high impedance state.

The 74ALVCF162835 is designed with 26Ω series resistors in the outputs. This design reduces noise in applications such as memory address drivers, clock drivers, and bus transceivers/transmitters.

The 74ALVCF162835 is designed for low voltage (1.65V to 3.6V) V_{CC} applications with I/O capability up to 3.6V.

The 74ALVCF162835 is fabricated with an advanced CMOS technology to achieve high speed operation while maintaining low CMOS power dissipation.


Features

- Compatible with PC133 DIMM module specifications
- 1.65V-3.6V V_{CC} specifications provided
- 3.6V tolerant outputs
- 26Ω series resistors in outputs
- t_{PD} (CLK to O_n)
 - 3.7 ns max for 3.0V to 3.6V V_{CC}
 - 4.6 ns max for 2.3V to 2.7V V_{CC}
 - 7.4 ns max for 1.65V to 1.95V V_{CC}
- Power-down high impedance outputs
- Latchup conforms to JEDEC JED78
- ESD performance:
 - Human body model > 2000V
 - Machine model >200V

Ordering Code:

Order Number	Package Number	Package Description
74ALVCF162835T	MTD56	56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Connection Diagram**Pin Descriptions**

Pin Names	Description
OE	Output Enable Input (Active LOW)
LE	Latch Enable Input
CLK	Clock Input
I ₁ - I ₁₈	Data Inputs
O ₁ - O ₁₈	3-STATE Outputs

Truth Table

OE	LE	CLK	Inputs		Outputs
			I _n	O _n	
H	X	X	X	Z	
L	H	X	L	L	
L	H	X	H	H	
L	L	↑	L	L	
L	L	↑	H	H	
L	L	H	X	O ₀ (Note 1)	
L	L	L	X	O ₀ (Note 2)	


H = Logic HIGH

L = Logic LOW

X = Don't Care, but not floating

Z = High Impedance

↑ = LOW-to-HIGH Clock Transition

Note 1: Output level before the indicated steady-state input conditions were established provided that CLK was HIGH before LE went LOW.**Note 2:** Output level before the indicated steady-state input conditions were established.**Logic Diagram**

Absolute Maximum Ratings (Note 3)		Recommended Operating Conditions (Note 5)			
Supply Voltage (V_{CC})	-0.5V to +4.6V				
DC Input Voltage (V_I)	-0.5V to 4.6V				
Output Voltage (V_O) (Note 4)	-0.5V to V_{CC} +0.5V				
DC Input Diode Current (I_{IK}) $V_I < 0V$	-50 mA	Power Supply Operating	1.65V to 3.6V		
DC Output Diode Current (I_{OK}) $V_O < 0V$	-50 mA	Input Voltage Output Voltage (V_O)	0V to V_{CC} 0V to V_{CC}		
DC Output Source/Sink Current (I_{OH}/I_{OL})	±50 mA	Free Air Operating Temperature (T_A)	-40°C to +85°C		
DC V_{CC} or GND Current per Supply Pin (I_{CC} or GND)	±100 mA	Minimum Input Edge Rate ($\Delta t/\Delta V$)			
Storage Temperature Range (T_{STG})	-65°C to +150°C	$V_{IN} = 0.8V$ to 2.0V, $V_{CC} = 3.0V$	10 ns/V		
<p>Note 3: The Absolute Maximum Ratings are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the Absolute Maximum Ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.</p> <p>Note 4: I_O Absolute Maximum Rating must be observed.</p> <p>Note 5: Floating or unused control inputs must be held HIGH or LOW.</p>					
DC Electrical Characteristics					
Symbol	Parameter	Conditions	V_{CC} (V)	Min	Max
V_{IH}	HIGH Level Input Voltage		1.65 - 1.95 2.3 - 2.7 2.7 - 3.6	0.65 x V_{CC} 1.7 2.0	
V_{IL}	LOW Level Input Voltage		1.65 - 1.95 2.3 - 2.7 2.7 - 3.6	0.35 x V_{CC} 0.7 0.8	V
V_{OH}	HIGH Level Output Voltage	$I_{OH} = -100 \mu A$	1.65 - 3.6	$V_{CC} - 0.2$	
		$I_{OH} = -2 mA$	1.65	1.2	
		$I_{OH} = -4 mA$	2.3	1.9	
		$I_{OH} = -6 mA$	2.3 3.0	1.7 2.4	V
		$I_{OH} = -8 mA$	2.7	2	
		$I_{OH} = -12 mA$	3.0	2	
V_{OL}	LOW Level Output Voltage	$I_{OL} = 100 \mu A$	1.65 - 3.6		0.2
		$I_{OL} = 2 mA$	1.65		0.45
		$I_{OL} = 4 mA$	2.3		0.4
		$I_{OL} = 6 mA$	2.3 3.0		0.55
		$I_{OL} = 8 mA$	2.7		0.6
		$I_{OL} = 12 mA$	3.0		0.8
I_{OH}	High Level Output Current		1.65 2.3 2.7 3.0		-2 -6 -8 -12
I_{OL}	Low Level Output Current		1.65 2.3 2.7 3.0		2 6 8 12
I_I	Input Leakage Current	$0 \leq V_I \leq 3.6V$	1.65 - 3.6		±5.0
I_{OZ}	3-STATE Output Leakage	$0 \leq V_O \leq 3.6V$, $V_I = V_{IH}$ or V_{IL}	1.65 - 3.6		±10
I_{OFF}	Power Off Leakage Current	$0V \leq (V_I, V_O) \leq 3.6V$	0		10
I_{CC}	Quiescent Supply Current	$V_I = V_{CC}$ or GND, $I_O = 0$	3.6		40
ΔI_{CC}	Increase in I_{CC} per Input	$V_{IH} = V_{CC} - 0.6V$	2.7 - 3.6		750

AC Electrical Characteristics

Symbol	Parameter	$T_A = -40^\circ\text{C to } +85^\circ\text{C}, R_L = 500\Omega$								Units	
		$C_L = 50 \text{ pF}$				$C_L = 30 \text{ pF}$					
		$V_{CC} = 3.3V \pm 0.3V$		$V_{CC} = 2.7V$		$V_{CC} = 2.5 \pm 0.2V$		$V_{CC} = 1.8V \pm 0.15V$			
		Min	Max	Min	Max	Min	Max	Min	Max		
f_{MAX}	Maximum Clock Frequency	250		200		200		100		MHz	
t_{PHL}, t_{PLH}	Propagation Delay Bus-to-Bus	1.1	3.6	1.3	4.5	0.8	4.0	1.5	7.2	ns	
t_{PHL}, t_{PLH}	Propagation Delay Clock to Bus	1.5	3.7	2.0	4.6	1.5	4.1	2.0	7.4	ns	
t_{PHL}, t_{PLH}	Propagation Delay LE to Bus	1.1	4.2	1.3	5.2	0.8	4.7	1.5	8.5	ns	
t_{PZL}, t_{PZH}	Output Enable Time	1.1	4.8	1.3	6.4	0.8	5.9	1.5	9.8	ns	
t_{PZL}, t_{PHZ}	Output Disable Time	1.1	4.7	1.3	5.2	0.8	4.7	1.5	7.9	ns	
t_S	Setup Time	1.5		1.5		1.5		2.5		ns	
t_H	Hold Time	0.7		0.7		0.7		1.0		ns	
t_W	Pulse Width	1.5		1.5		1.5		4.0		ns	

Capacitance

Symbol	Parameter	Conditions		$T_A = +25^\circ\text{C}$		Units	
		V_{CC}	Typical	V_{CC}	Typical		
C_{IN}	Input Capacitance	$V_I = 0V \text{ or } V_{CC}$		3.3	3.5	pF	
C_{OUT}	Output Capacitance	$V_I = 0V \text{ or } V_{CC}$		3.3	5.5	pF	
C_{PD}	Power Dissipation Capacitance	Outputs Enabled	$f = 10 \text{ MHz}, C_L = 0 \text{ pF}$		3.3	13	pF
					2.5	13	


I_{OUT} - V_{OUT} Characteristics

FIGURE 1. Characteristics for Output - Pull Up Drive




FIGURE 2. Characteristics for Output - Pull Down Driver

AC Loading and Waveforms




FIGURE 3. AC Test Circuit

Table 1: Values for Figure 1

TEST	SWITCH
t_{PLH}, t_{PHL}	Open
t_{PZH}, t_{PLZ}	V_L
t_{PZH}, t_{PHZ}	GND

Table 2: Variable Matrix
(Input Characteristics: $f = 1\text{MHz}$; $t_r=t_f=2\text{ns}$; $Z_0=50\Omega$)

Symbol	V_{CC}			
	$3.3V \pm 0.3V$	$2.7V$	$2.5V \pm 0.2V$	$1.8V \pm 0.15V$
V_{mi}	1.5V	1.5V	$V_{CC}/2$	$V_{CC}/2$
V_{mo}	1.5V	1.5V	$V_{CC}/2$	$V_{CC}/2$
V_X	$V_{OL} + 0.3V$	$V_{OL} + 0.3V$	$V_{OL} + 0.15V$	$V_{OL} + 0.15V$
V_Y	$V_{OH} - 0.3V$	$V_{OH} - 0.3V$	$V_{OH} - 0.15V$	$V_{OH} - 0.15V$
V_L	6V	6V	V_{CC}^*2	V_{CC}^*2




FIGURE 4. Waveform for Inverting and Non-inverting Functions




FIGURE 5. 3-STATE Output High Enable and Disable Times for Low Voltage Logic





FIGURE 6. 3-STATE Output Low Enable and Disable Times for Low Voltage Logic

74ALVCF162835 Low Voltage 18-Bit Universal Bus Driver with 3.6V Tolerant Outputs and 26Ω Series Resistors in Outputs

Physical Dimensions inches (millimeters) unless otherwise noted



**56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide
Package Number MTD56**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com