

GALVANISING SPRAY (BRIGHT & MATT)

Product Code: PGB (Bright) & PGM (Matt)

PRODUCT DESCRIPTION

Electrolube Zinc Galvanising Sprays protect surfaces against corrosion. They have good resistance to chemicals (except acids) and to weathering. Due to high metallic zinc content, the electrochemical protection is extremely effective and long lasting. They are very fast drying and have good adhesion to all substrates. Available in gloss and matt finishes to match substrate type.

PRODUCT USE

- * Cold galvanisation paint for metal surfaces
- * Allows depositing of metallic zinc coating which protects against oxidation and corrosion.
- * May constitute a sub-base key for fixing lacquers.
- * Is applied as paint onto iron, steel, galvanised sheet iron, woodwork, roof coverings, piping etc.
- * Contains flammable product. See MSDS for full details.

PREPARATION & APPLICATION

- * First remove dust and degrease the surface to be treated.
- * Removal of well-adhered rust is not essential.
- * Shake the can well before and during use.
- * Clear after application by spraying with the can inverted.
- * Do not apply during very damp weather.

TYPICAL PROPERTIES

Coverage:

Drying time:

(touch dry)

(full cure)

(recoat after)

Maximum Temperature:

PACKAGING

400 ml net aerosol (Bright)

400 ml net aerosol (Matt)

ORDER CODE

PGB400

PGM400

**TECHNICAL
DATA
SHEET**



**Copyright
Electrolube
2003**

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

