




Waterproof 12Vdc Power Supply IP67


- Sealed Unit to IP67
- Resin Potted Unit
- Input 100-240Vac
- Output 12Vdc 1A
- Miniature Size 83 x 37 x 30mm
- 2.1mm Female Jack
- Wall Fixing Lugs
- Supplied with 3.3m lead

Part Number	Description
PSU-12V1AIN-IP	Power Supply Unit 110-230Vac in 12Vdc1A

Mechanical Data



All dimensions are in mm





Waterproof 12Vdc Power Supply IP67

Technical Specification

AC/DC POWER SUPPLY MODULE				
S/N	TEST ITEMS	UNIT	VALUE	TEST CONDITIONS/RECORDS
Input				
01	Nominal Input Voltage	Vac	100 - 240	-
02	Input Voltage Range	Vac	90 - 264	-
03	Input Frequency	Hz	50/60	At any load
04	AC Input Current	Arms	0.40	At full load & any input voltage
Output				
01	Nominal Output Voltage	Vdc	12.0	-
02	Output Voltage Range	Vdc	11.40 – 12.60	At any input voltage & Load
03	Max. Output Current	mA	1000	At any input voltage
04	Line Regulation	%	1% max	At any input voltage & max. load
05	Load Regulation	%	+5%	At any input voltage
06	Ripple and Noise	mVp-p	<50	Any input voltage & any Load
07	Efficiency	%	> 70	At any input and max. load
08	Output Cable	mm	L=1800	Straight Plug : 2.1x5.5x12mm (+)
09	Input Cable	mm	L=1500	BS 1363 Plug
10	Output Short Circuit	-	Hiccup	Self recovering
11	Over Current Protection	A	≤2.0	At any input voltage
Environmental				
01	Operating Temperature	C	0 ~ +40	Full load & natural convection.
02	Storage Temperature	C	-10 ~ +70	-
03	Operating Humidity	%RH	10 ~ 90	-
04	Storage Humidity	%RH	5 ~ 90	Relative humidity, non-condensing
Safety standard & EMI				
01	Withstand Voltage (Hi-Pot)	KVac	I/P to O/P: 3.0 (60Sec.)	Set cut-off current to 10mA
02	Safety Standard	-	EN60065	IP67
03	EMI/RFI Standard	-	EN55022B / FCC	-
Mechanical characteristics				
01	Size	mm	81x37x30mm (LxWxH)	Casing only
02	Weight	g	Approx.	-



Waterproof 12Vdc Power Supply IP67

RF Solutions Ltd RECYCLING NOTICE rfsolutions.co.uk Meets the following EC Directives 
DO NOT Discard with normal waste, please recycle.
ROHS Directive 2002/95/EC Specifies certain limits for hazardous substances.
WEEE Directive 2002/96/EC Waste Electrical & Electronic Equipment. This product must be disposed of through a licensed WEEE collection point. RF Solutions Ltd fulfils its WEEE obligations by membership of an approved compliance scheme. <u>Environment Agency producer registration number WEE/JB0104W/V</u>
Waste Batteries and Accumulators Directive 2006/66/EC Where batteries are fitted, before recycling the product, the batteries must be removed and disposed of at a licensed collection point.

R. F. Solutions Ltd.,

Unit 21, Cliffe Industrial Estate, South Street, Lewes,

E Sussex, BN8 6JL. England

Tel +44 (0)1273 898 000 Fax +44 (0)1273 480 661

Email sales@rfsolutions.co.uk

http://www.rfsolutions.co.uk

Information contained in this document is believed to be accurate, however no representation or warranty is given and R.F. Solutions Ltd. assumes no liability with respect to the accuracy of such information.
Use of R.F.Solutions products as critical components in life support systems is not authorised except with express written approval from R.F. Solutions Ltd.