


Applications

- General Purpose
- For IF applications



Product Features

- Usable bandwidth 2.4 MHz
- Low loss
- High Attenuation
- Single-ended operation
- Ceramic Surface Mount Package (SMP)
- Small Size
- Dimensions: 13.30 x 6.50 x 1.5mm
- Hermetic **RoHS** compliant, **Pb-free**

General Description


The 856980 is a high-performance IF SAW filter with a center frequency of 70 MHz and a usable bandwidth of 2.4 MHz. It is suitable for a wide variety of applications, including wireless data transceivers.

It features low loss with excellent attenuation, and is designed to be used with a single ended input and output.

The device is **RoHS** compliant and **Pb-free**.

Functional Block Diagram

Top view



Pin Configuration

Pin # SE	Description
10	Input
5	Output
1,6	Ground
2,3,4,7,8,9	Case Ground

Ordering Information

Part No.	Description
856980	packaged part
856980-EVB	evaluation board

Standard T/R size = 2000 units/reel.

Specifications

Electrical Specifications ⁽¹⁾

Specified Temperature Range: ⁽²⁾ -55 to +85 °C

Parameter ⁽³⁾	Conditions	Min	Typical ⁽⁴⁾	Max	Units
Center Frequency		-	70	-	MHz
Insertion Loss	at 70 MHz	-	9	10	dB
3 dB Bandwidth ⁽⁷⁾		2.4	2.5	-	MHz
Passband Ripple ⁽⁵⁾	69.3 – 70.7 MHz	-	0.2	0.7	dB p-p
Phase Ripple	69.3 – 70.7 MHz	-	2	5	deg p-p
Absolute Group Delay at 70 MHz		-	1.22	-	μs
Group Delay Variation	69.3 – 70.7 MHz	-	58.4	130	ns
Stopband Attenuation ⁽⁷⁾	5 – 30 MHz 30 – 50 MHz 50 – 63 MHz 77 – 85 MHz 85 – 105 MHz 105 – 130 MHz 130 – 150 MHz 150 – 200 MHz	65 50 40 35 45 55 30 70	72 56 47 43 48 58 33 74	-	dB
Source Impedance (single-ended) ⁽⁸⁾	-	-	50	-	Ω
Load Impedance (single-ended) ⁽⁸⁾	-	-	50	-	Ω

Notes:

1. All specifications are based on the TriQuint schematic for the main reference design shown on page 3
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. Typical values are based on average measurements at room temperature
5. Is defined as the peak to adjacent valley change in amplitude.
6. An external impedance matching network +/- 2% tolerance will be necessary to achieve proposed return loss
7. Relative to 0 dB.
8. This is the optimum impedance in order to achieve the performance shown


Absolute Maximum Ratings

Parameter	Rating
Operating Temperature	-55 to +85 °C
Storage Temperature	-55 to +85 °C

Operation of this device outside the parameter ranges given above may cause permanent damage.

Reference Design – 50Ω SE Input, 50Ω SE Output


Schematic




Notes:

1. Actual matching values may vary due to PCB layout and parasitics

PC Board



Mounting Configuration



Notes:

Top, middle & bottom layers: 1 oz copper
Substrates: FR4 dielectric, .031" thick
Finish plating: Nickel: 3-8µm thick, Gold: .03-.2µm thick
Hole plating: Copper min .0008µm thick







Notes:

1. All dimensions are in millimeters.
2. This footprint represents a recommendation only.

Bill of Material


Reference Desg.	Value	Description	Manufacturer	Part Number
L1	240nH	Coil Wire-wound, 0805, 5%	CoillCraft	0805CS-241XJLC
L2	27nH	Coil Wire-wound, 08053, 5%	CoillCraft	0805CS-270XJLC
L3	150nH	Coil Wire-wound, 0805, 5%	CoillCraft	0805CS-151XJLC
C1	68pF	Chip Capacitor, 0805, 5%	Murata	GRM2165C1H680JZ01
SMA	N/A	SMA connector	Radiall USA Inc.	9602-1111-018
PCB	N/A	3-layer	multiple	960656

Typical Performance (at room temperature)



Mechanical Information

Package Information, Dimensions and Marking



Package Style: SMP-53C
Dimensions: 13.3 x 6.50 x 1.50 mm



Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m, over a 2-6 μ m Ni plating

All dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall length and width
 ± 0.10 mm

The date code consists of: YY =The last two digits of the year (2 Digits), WW = the calendar week of the year (2 Digits)

Tape and Reel Information

Standard T/R size = 2000 units/reel. All dimensions are in millimeters



Product Compliance Information

ESD Information



Caution! ESD-Sensitive Device

ESD Rating: TBD

Value: Passes \geq TBD V min.

Test: Human Body Model (HBM)

Standard: JEDEC Standard JESD22-A114

ESD Rating: TBD

Value: Passes \geq TBD V min.

Test: Machine Model (MM)

Standard: JEDEC Standard JESD22-A115

MSL Rating

Devices are Hermetic, therefore MSL is not applicable.

Solderability

Compatible with the latest version of J-STD-020, lead free solder, 260°C

Refer to [Soldering Profile](#) for recommended guidelines.

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A ($C_{15}H_{12}Br_4O_2$) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.407.886.8860
Fax: +1.407.886.7061

For technical questions and application information:

Email: applications.engineering@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.