



NOTES:

1. TERMINAL TO BE USED IN HOUSING 70066-**** AND 70450-****.
2. REFER TO PRODUCT SPECIFICATION PS-70058.
3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
4. TERMINAL TO BE USED WITH (0.64)/.025 SQUARE PINS.
5. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH (1.63)/.064 MAXIMUM DIAMETER INSULATION.
6. TERMINALS SUPPLIED IN REEL FORM.
7. CRIMP SIZE INDICATOR C=22-24 AWG

PLATING:

.000015 MINIMUM GOLD PLATE IN SELECT AREA,
 .000075 MINIMUM TIN PLATE IN SELECT AREA,
 OVER NICKEL PLATE OVERALL.

REEL UNWIND DIR EC NO: UCP2013-5345 DRWN: RWHIPPLE 2013/06/11 CHKD: DMORGAN 2013/06/11 APPR: SMILLER 2013/07/09	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION		
		▽/0	mm	INCH	MM/IN	10:1	INCH	◎ □		
		▽/0	4 PLACES ± --- ± ---	3 PLACES ± --- ± .005	2 PLACES ± .13 ± .01	1 PLACE ± 0.25 ± ---	0 PLACE ± --- ± ---	DRAWN BY DATE		TITLE
		▽/0	ANGULAR ± 1/2°		DRAFT WHERE APPLICABLE		MATERIAL NO.		DOCUMENT NO.	
MUST REMAIN WITHIN DIMENSIONS			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		DRAWN BY: RWHIPPLE DATE: 2013/06/11 CHECKED BY: JAS DATE: 1988/03/02 APPROVED BY: SMILLER DATE: 2013/07/09		TERMINAL - BOX/CRIMP FOR 22-24 AWG ON A REEL molex		1 OF 1	