2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

KLP42X-60-R/W

Part Number Builder

KLP42X	–	60	R/W
Series		Type	Color Option

RCA PHONO JACKS: KLP42X Series

Stacked RCA Phono Jack PCB Mount

Product Features

Audio Applications for Computers and Multimedia
Gold Plating Available Upon Request
Various Color and Stacking Options Available
CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish
Housing
PBT Thermoplastic, UL94V-0 Rated
Terminals
Brass,Tin Plated
Ground Pin
Brass,Nickel Plated

Electrical Characteristics

Rated Current: 0.3A
Rated Voltage: 16V DC
Contact Resistance
50 milliohms Max.
Insulation Resistance
100 Megohms Min. at 500V DC
Dielectric Withstanding Voltage
500V AC RMS for 1 Minute

Mechanical Characteristics

Insertion Force
0.3kg - 5.0kg
Extraction Force
0.3kg - 5.0kg
Durability
1000 Mating Cycles Min.
Operating Temperature
-20°C to +60°C

Series
KLP42X - Stacked RCA Phono Jack

Type
60 - Single Column, Double Row

Color Option
B/B - Black/Black
R/R - Red/Red
R/W - Red/White
W/B - White/Black
W/R - White/Red
W/W - White/Yellow
W/Y- White/White
Y/Y - Yellow/Yellow

Color Layout - X/Z

Contact Kycon for other options

KLP42X-60
Dimensions in mm