


Thermally-Enhanced High Power RF LDMOS FETs 220 W, 920 – 960 MHz

Description

The PTFA092201E and PTFA092201F are 220-watt, internally-matched LDMOS FETs intended for EDGE and WCDMA applications in the 920 to 960 MHz band. Manufactured with Infineon's advanced LDMOS process, these devices provide excellent thermal performance and superior reliability.

PTFA092201E
Package H-36260-2

PTFA092201F
Package H-37260-2



Features

- Pb-free, RoHS-compliant and thermally-enhanced packages
- Broadband internal matching
- Typical two-carrier WCDMA performance at 960 MHz, 30 V
 - Average output power = 55 W
 - Linear Gain = 18.5 dB
 - Efficiency = 30%
 - Intermodulation distortion = -37 dBc
 - Adjacent channel power = -39 dBc
- Typical CW performance, 960 MHz, 30 V
 - Output power at P-1dB = 250 W
 - Gain = 17.5 dB
 - Efficiency = 59%
- Integrated ESD protection: Human Body Model, Class 2 (minimum)
- Excellent thermal stability, low HCI drift
- Capable of handling 10:1 VSWR @ 30 V, 220 W (CW) output power

RF Characteristics

Two-carrier WCDMA Measurements (not subject to production test—verified by design/characterization in Infineon test fixture)

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $P_{OUT} = 55\text{ W}$ average

$f_1 = 950\text{ MHz}$, $f_2 = 960\text{ MHz}$, 3GPP signal, channel bandwidth = 3.84 MHz, peak/average = 8.1 dB @ 0.01% CCDF

Characteristic	Symbol	Min	Typ	Max	Unit
Intermodulation Distortion	IMD	—	-37	—	dBc
Gain	G_{ps}	—	18.5	—	dB
Drain Efficiency	η_D	—	30	—	%

All published data at $T_{CASE} = 25\text{ °C}$ unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!

RF Characteristics (cont.)

Two-tone Measurements (tested in Infineon test fixture)

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $P_{OUT} = 220\text{ W PEP}$, $f = 960\text{ MHz}$, tone spacing = 1 MHz

Characteristic	Symbol	Min	Typ	Max	Unit
Gain	G_{ps}	17.5	18.5	—	dB
Drain Efficiency	η_D	42	44	—	%
Intermodulation Distortion	IMD	—	—	-28	dBc

DC Characteristics

Characteristic	Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}$, $I_{DS} = 10\text{ mA}$	$V_{(BR)DSS}$	65	—	—	V
Drain Leakage Current	$V_{DS} = 28\text{ V}$, $V_{GS} = 0\text{ V}$	I_{DSS}	—	—	1.0	μA
	$V_{DS} = 63\text{ V}$, $V_{GS} = 0\text{ V}$	I_{DSS}	—	—	10.0	μA
On-State Resistance	$V_{GS} = 10\text{ V}$, $V_{DS} = 0.1\text{ V}$	$R_{DS(on)}$	—	0.04	—	Ω
Operating Gate Voltage	$V_{DS} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$	V_{GS}	2.0	2.5	3.0	V
Gate Leakage Current	$V_{GS} = 10\text{ V}$, $V_{DS} = 0\text{ V}$	I_{GSS}	—	—	1.0	μA

Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	65	V
Gate-Source Voltage	V_{GS}	-0.5 to +12	V
Junction Temperature	T_J	200	$^{\circ}\text{C}$
Total Device Dissipation Above 25 $^{\circ}\text{C}$ derate by	P_D	700	W
		4.0	W/ $^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-40 to +150	$^{\circ}\text{C}$
Thermal Resistance ($T_{CASE} = 70\text{ }^{\circ}\text{C}$, 220 W CW)	$R_{\theta JC}$	0.25	$^{\circ}\text{C/W}$


Ordering Information

Type and Version	Order Code	Package Description	Shipping
PTFA092201E V4 R0	PTFA092201EV4R0XTMA1	H-36260-2, bolt-down	Tape & Reel, 50pcs
PTFA092201E V4 R250	PTFA092201EV4R250XTMA1	H-36260-2, bolt-down	Tape & Reel, 250pcs
PTFA092201F V4 R0	PTFA092201FV4R0XTMA1	H-37260-2, earless flange	Tape & Reel, 50pcs
PTFA092201F V4 R250	PTFA092201FV4R250XTMA1	H-37260-2, earless flange	Tape & Reel, 250pcs

Typical Performance (data taken in a production test fixture)


2-Carrier WCDMA Performance

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $f = 960\text{ MHz}$, 3GPP WCDMA signal, P/A R = 8.1 dB, 10 MHz carrier spacing, 3.84 MHz bandwidth




2-Carrier WCDMA (high gain tune)

$V_{DD} = 30\text{ V}$, $I_{DQ} = 2000\text{ mA}$, $f = 960\text{ MHz}$, 3GPP WCDMA signal, P/A R = 8.1 dB, 10 MHz carrier spacing, 3.84 MHz bandwidth




Two-carrier WCDMA Power Sweep

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1600\text{ mA}$, $f_1 = 889\text{ MHz}$, $f_2 = 894\text{ MHz}$, PAR = 7.1 dB each carrier at 0.01% probability







Gain & Efficiency vs. Output Power

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $f = 960\text{ MHz}$




Typical Performance (cont.)



Typical Performance (cont.)


Intermodulation Distortion vs. Output Power

$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $f_1 = 960$, $f_2 = 959\text{ MHz}$




Intermodulation Distortion vs. Output Power (high gain tune)

$V_{DD} = 30\text{ V}$, $I_{DQ} = 2000\text{ mA}$, $f_1 = 859$, $f_2 = 960\text{ MHz}$




Output Power vs. Supply Voltage

$I_{DQ} = 1850\text{ mA}$, $f = 960\text{ MHz}$




IS-95 CDMA Performance


$V_{DD} = 30\text{ V}$, $I_{DQ} = 1850\text{ mA}$, $f = 960\text{ MHz}$




Typical Performance (cont.)




Broadband Circuit Impedance



Frequency MHz	Z Source Ω		Z Load Ω	
	R	jX	R	jX
900	2.256	-1.363	1.722	-0.413
920	2.250	-1.094	1.653	-0.109
940	2.282	-0.826	1.651	0.186
960	2.239	-0.545	1.562	0.518
980	2.288	-0.307	1.562	0.795



Reference Circuit



Reference circuit block diagram for $f = 960 \text{ MHz}$


Circuit Assembly Information

DUT	PTFA092201E or PTFA092201F	LDMOS Transistor	
PCB	0.76 mm [.030"] thick, $\epsilon_r = 3.48$	Rogers RO4350	1 oz. copper

Microstrip	Electrical Characteristics at 960 MHz ¹	Dimensions: L x W (mm)	Dimensions: L x W (in.)
l_1	0.068 λ , 52.0 Ω	12.78 x 1.60	0.503 x 0.063
l_2	0.041 λ , 38.0 Ω	7.57 x 2.54	0.298 x 0.100
l_3	0.040 λ , 38.0 Ω	7.34 x 2.54	0.289 x 0.100
l_4	0.092 λ , 7.8 Ω	15.95 x 17.83	0.628 x 0.702
l_5	0.025 λ , 7.8 Ω	4.29 x 17.83	0.169 x 0.702
l_6	0.208 λ , 78.3 Ω	40.64 x 0.74	1.600 x 0.029
l_7, l_8	0.200 λ , 60.1 Ω	40.64 x 1.24	1.500 x 0.049
l_9	0.102 λ , 8.4 Ω	17.65 x 16.48	0.695 x 0.649
l_{10} (taper)	0.021 λ , 8.4 Ω / 10.1 Ω	3.56 x 16.48 / 13.36	0.140 x 0.649 / 0.526
l_{11} (taper)	0.094 λ , 10.1 Ω / 37.7 Ω	16.38 x 13.36 / 2.64	0.645 x 0.526 / 0.104
l_{12}	0.022 λ , 37.0 Ω	4.04 x 2.64	0.159 x 0.104
l_{13}	0.035 λ , 52.0 Ω	6.55 x 1.60	0.258 x 0.063

¹Electrical characteristics are rounded.

Reference Circuit (cont.)




Reference circuit assembly diagram (not to scale)*

Component	Description	Suggested Manufacturer	P/N or Comment
C1, C2, C3	Capacitor, 0.001 μ F	Digi-Key	PCC1772CT-ND
C4	Tantalum capacitor, 10 μ F, 35 V	Digi-Key	399-1655-2-ND
C5, C15, C21	Capacitor, 0.1 μ F	Digi-Key	PCC104BCT-ND
C6, C12, C18	Capacitor, 1 μ F	ATC	920C105
C7, C8, C11, C17, C25	Ceramic capacitor, 33 pF	ATC	100B 330
C9	Ceramic capacitor, 3.9 pF	ATC	100B 3R9
C10	Ceramic capacitor, 4.9 pF	ATC	100B 4R9
C13, C16, C19, C22	Tantalum capacitor, 10 μ F, 50 V	Garrett Electronics	TPSE106K050R0400
C14, C20	Electrolytic capacitor, 100 μ F, 50 V	Digi-Key	P5571-ND
C23, C24	Ceramic capacitor, 2.6 pF	ATC	100B 2R6
L1, L2	Ferrite, 8.9 mm	Elna Magnetics	BDS 4.6/3/8.9-4S2
Q1	Transistor	Infineon Technologies	BCP56
QQ1	Voltage regulator	National Semiconductor	LM7805
R1	Chip resistor 1.2 k-ohms	Digi-Key	P1.2KGCT-ND
R2	Chip resistor 1.3 k-ohms	Digi-Key	P1.3KGCT-ND
R3	Chip resistor 2 k-ohms	Digi-Key	P2KECT-ND
R4	Potentiometer 2 k-ohms	Digi-Key	3224W-202ETR-ND
R5, R8	Chip resistor 10 ohms	Digi-Key	P10ECT-ND
R6, R7	Chip resistor 5.1 k-ohms	Digi-Key	P5.1KECT-ND


*Gerber Files for this circuit available on request

Package Outline Specifications



Find the latest and most complete information about products and packaging at the Infineon Internet page
<http://www.infineon.com/rfpower>

Package Outline Specifications (cont.)



Find the latest and most complete information about products and packaging at the Infineon Internet page
<http://www.infineon.com/rfpower>

Revision History: 2016-06-21

Data Sheet

Previous Version: 2009-02-02, Data Sheet Rev. 03.1

Page	Subjects (major changes since last revision)
2	update ordering information.

We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all?

Your feedback will help us to continuously improve the quality of this document.


Please send your proposal (including a reference to this document) to:

highpowerRF@infineon.com

To request other information, contact us at:

+1 877 465 3667 (1-877-GO-LDMOS) USA

or +1 408 776 0600 International



Edition 20. 3*- 3*/ .

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2006 Infineon Technologies AG

All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com/rfpower).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.