


## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/04/270LH SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

### Product image



Similar to illustration

Female plugs with clamping-yoke connection for connecting wires with a right-angle (90° or 270°) outlet direction. The female connectors provide space for labelling and can be coded. Fastened by means of a flange or release latch. They also provide an integrated plus/minus screw, protection against faulty insertion of the wire, and they are delivered with open clamping yokes. HC = High Current.

### General ordering data

|                 |   |
|-----------------|---|
| Delivery status | <b>Discontinued</b>   |
| Available until | 2014-05-20  |
| Type            | BLZP 5.08HC/04/270LH SN OR BX   |
| Order No.       | <a href="#">1947030000</a>  |
| Version         | PCB plug-in connector, female plug, 5.08 mm, Number of poles: 4, 270°, Clamping yoke connection, Clamping range, max.: 4 mm², Box |
| GTIN (EAN)      | 4032248622795   |
| Qty.            | 60 pc(s).   |
| Product data    | IEC: 400 V / 23 A / 0.2 - 4 mm²<br>UL: 300 V / 20 A / AWG 26 - AWG 12   |

Creation date June 5, 2020 9:31:26 PM CEST

**OMNIMATE Signal - series BL/SL 5.08**  
**BLZP 5.08HC/04/270LH SN OR BX**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 30.14   | Width (inches)  | 1.187 inch |
| Height     | 17.7 mm | Height (inches) | 0.697 inch |
| Depth      | 29.5 mm | Depth (inches)  | 1.161 inch |
| Net weight | 10.05 g |                 |            |

**System Parameters**

|  |  |                            |                       |
|--|--|----------------------------|-----------------------|
| Product family                               | OMNIMATE Signal - series BL/SL 5.08    | Type of connection         | Field connection      |
| Wire connection method                       | Clamping yoke connection               | Pitch in mm (P)            | 5.08 mm               |
| Pitch in inches (P)                          | 0.2 inch                               | Conductor outlet direction | 270°                  |
| Number of poles                              | 4                                      | L1 in mm                   | 15.24 mm              |
| L1 in inches                                 | 0.6 inch                               | Number of rows             | 1                     |
| Pin series quantity                          | 1                                      | Rated cross-section        | 4 MΩ                  |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch                 | Volume resistance          | ≤ 5mΩ                 |
| Can be coded                                 | Yes                                    | Stripping length           | 7 mm                  |
| Tightening torque, min.                      | 0.4 Nm                                 | Tightening torque, max.    | 0.5 Nm                |
| Clamping screw                               | M 2.5                                  | Screwdriver blade          | 0.6 x 3.5, PH 1, PZ 1 |
| Screwdriver blade standard                   | DIN 5264, ISO 8764/2-PH, ISO 8764/2-PZ | Plugging cycles            | 25                    |
| Plugging force/pole, max.                    | 10 N                                   | Pulling force/pole, max.   | 9 N                   |

**Material data**

|                                       |  |                                       |  |
|---------------------------------------|--|---------------------------------------|--|
| Insulating material                   | PBT  | Colour                                | orange                                       |
| Colour chart (similar)                | RAL 2000                                     | Insulating material group             | IIIa   |
| Comparative Tracking Index (CTI)      | ≥ 200  | Insulation strength                   | ≥ 10 <sup>8</sup> Ω                          |
| UL 94 flammability rating             | V-0  | GWFI                                  | 960 A / 1 mm + 20 A / 2 mm                   |
| Contact material                      | Copper alloy                                 | Contact surface                       | tinned                                       |
| Layer structure of plug contact       | 4...8 μm Sn hot-dip tinned                   | Storage temperature, min.             | -25 V DC (24,25 V DC +- 50 mV) potenzialfrei |
| Storage temperature, max.             | 50 °C  | Max. relative humidity during storage | 70 %   |
| Operating temperature, min.           | -50 V DC (24,25 V DC +- 50 mV) potenzialfrei | Operating temperature, max.           | 100 V DC (24,25 V DC +- 50 mV) potenzialfrei |
| Temperature range, installation, min. | -25 V DC (24,25 V DC +- 50 mV) potenzialfrei | Temperature range, installation, max. | 100 °C                                       |

## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/04/270LH SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Conductors suitable for connection

|   |                      |   |  |
|---|----------------------|---|--|
| Clamping range, min.                            | 0.13 mm <sup>2</sup> | Clamping range, max.                            | 4 mm <sup>2</sup>  |
| Wire connection cross section AWG, min.         | AWG 30               | Wire connection cross section AWG, max.         | AWG 12   |
| Solid, min. H05(07) V-U                         | 0.2 mm <sup>2</sup>  | Solid, max. H05(07) V-U                         | 4 mm <sup>2</sup>  |
| Flexible, min. H05(07) V-K                      | 0.2 mm <sup>2</sup>  | Flexible, max. H05(07) V-K                      | 4 mm <sup>2</sup>  |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.2 mm <sup>2</sup>  | w. plastic collar ferrule, DIN 46228 pt 4, max. | 2.5 mm <sup>2</sup>  |
| w. wire end ferrule, DIN 46228 pt 1, min.       | 0.2 mm <sup>2</sup>  | w. wire end ferrule, DIN 46228 pt 1, max.       | 4 mm <sup>2</sup>  |
| Plug gauge in accordance with EN 60999 a x b; ø |                      | Reference text                                  | The outside diameter of the plastic collar should not be larger than the pitch (P). Length of ferrules is to be chosen depending on the product and the rated voltage. |
|   | 2.8 mm x 2.4 mm      |   |  |
| Max. clamping range                             | 4 mm <sup>2</sup>    |   |  |

### Rated data acc. to IEC

|   |                        |   |                   |
|---|------------------------|---|-------------------|
| tested acc. to standard   | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C)                         | 23 A              |
| Rated current, max. number of poles (Tu=20°C)                             | 18 A                   | Rated current, min. number of poles (Tu=40°C)                         | 21 A              |
| Rated current, max. number of poles (Tu=40°C)                             | 16 A                   | Rated voltage for surge voltage class / pollution degree II/2         | 400 V             |
| Rated voltage for surge voltage class / pollution degree III/2            | 320 V                  | Rated voltage for surge voltage class / pollution degree III/3        | 250 V             |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 4 kV                   | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 4 kV              |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 4 kV                   | Short-time withstand current resistance                               | 3 x 1s with 120 A |

### Rated data acc. to CSA

|                                   |   |                                   |  |
|-----------------------------------|---|-----------------------------------|--|
| Institute (CSA)                   |  | Certificate No. (CSA)             | 200039-1121690   |
| Rated voltage (Use group B / CSA) | 300 V   | Rated voltage (Use group C / CSA) | 50 V   |
| Rated voltage (Use group D / CSA) | 300 V   | Rated current (Use group B / CSA) | 20 A   |
| Rated current (Use group D / CSA) | 20 A  | Wire cross-section, AWG, min.     | AWG 30   |
| Wire cross-section, AWG, max.     | AWG 12  | Reference to approval values      | Specifications are maximum values, details - see approval certificate. |

## OMNIMATE Signal - series BL/SL 5.08 BLZP 5.08HC/04/270LH SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Rated data acc. to UL 1059

|                                       |   |                                       |        |
|---------------------------------------|---|---------------------------------------|--------|
| Institute (UR)                        |  | Certificate No. (UR)                  | E60693 |
| Institute (cURus)                     |  | Certificate No. (cURus)               | E60693 |
| Rated voltage (Use group B / UL 1059) | 300 V   | Rated voltage (Use group D / UL 1059) | 300 V  |
| Rated current (Use group B / UL 1059) | 20 A  | Rated current (Use group D / UL 1059) | 10 A   |
| Wire cross-section, AWG, min.         | AWG 26  | Wire cross-section, AWG, max.         | AWG 12 |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate.            |                                       |        |

### Packing

|           |     |            |   |
|-----------|-----|------------|---|
| Packaging | Box | VPE length | 0 |
| VPE width | 0   | VPE height | 0 |

### Type tests

|  |                |  |                              |
|--|----------------|--|------------------------------|
| Test: Durability of markings                 | Standard       | DIN EN 61984 section 7.3.2 / 09.02 taking pattern from DIN EN 60068-2-70 / 07.96   |                              |
|  | Test           | mark of origin, rated voltage, rated cross-section, type of material               |                              |
|  | Evaluation     | available  |                              |
|  | Test           | durability   |                              |
|  | Evaluation     | passed   |                              |
| Test: Misengagement (Non-interchangeability) | Standard       | DIN EN 60512-13-5 / 11.06, IEC 60512-13-5 / 02.06                                  |                              |
|  | Test           | 180° turned with coding elements   |                              |
|  | Evaluation     | passed   |                              |
|  | Test           | visual examination   |                              |
|  | Evaluation     | passed   |                              |
| Test: Clampable cross section                | Standard       | DIN EN 60999-1 section 7 and 9.1 / 12.00, DIN EN 60947-1 section 8.2.4.5.1 / 12.02 |                              |
|  | Conductor type | Type of conductor and conductor cross-section                                      | solid 0.2 mm <sup>2</sup>    |
|  |                | Type of conductor and conductor cross-section                                      | stranded 0.2 mm <sup>2</sup> |
|  |                | Type of conductor and conductor cross-section                                      | solid 2.5 mm <sup>2</sup>    |
|  |                | Type of conductor and conductor cross-section                                      | stranded 2.5 mm <sup>2</sup> |
|  |                | Type of conductor and conductor cross-section                                      | AWG 26/1                     |
|  |                | Type of conductor and conductor cross-section                                      | AWG 26/19                    |
|  | Evaluation     | passed   |                              |

**OMNIMATE Signal - series BL/SL 5.08**  
**BLZP 5.08HC/04/270LH SN OR BX**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

|   |                |   |                              |  |
|---|----------------|---|------------------------------|--|
| Test for damage to and accidental loosening of conductors | Standard       | DIN EN 60999-1 section 9.4 / 12.00            |                              |  |
|   | Requirement    | 0.2 kg  |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | AWG 26/1                     |  |
|   |                | Type of conductor and conductor cross-section | AWG 26/19                    |  |
|   | Evaluation     | passed  |                              |  |
|   | Requirement    | 0.3 kg  |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | solid 0.5 mm <sup>2</sup>    |  |
|   |                | Type of conductor and conductor cross-section | stranded 0.5 mm <sup>2</sup> |  |
|   | Evaluation     | passed  |                              |  |
|   | Requirement    | 0.9 kg  |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | AWG 12/1                     |  |
|   |                | Type of conductor and conductor cross-section | AWG 12/19                    |  |
| Evaluation  | passed         |   |                              |  |
| Pull-out test   | Standard       | DIN EN 60999-1 section 9.5 / 12.00            |                              |  |
|   | Requirement    | ≥10 N   |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | AWG 26/1                     |  |
|   |                | Type of conductor and conductor cross-section | AWG 26/19                    |  |
|   | Evaluation     | passed  |                              |  |
|   | Requirement    | ≥20 N   |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | H05V-U0.5                    |  |
|   |                | Type of conductor and conductor cross-section | H05V-K0.5                    |  |
|   | Evaluation     | passed  |                              |  |
|   | Requirement    | ≥60 N   |                              |  |
|   | Conductor type | Type of conductor and conductor cross-section | H07V-U4.0                    |  |
|   |                | Type of conductor and conductor cross-section | H07V-K4.0                    |  |
|   |                | Type of conductor and conductor cross-section | AWG 12/1                     |  |
|   |                | Type of conductor and conductor cross-section | AWG 12/19                    |  |
|   | Evaluation     | passed  |                              |  |

**Classifications**

UNSPSC 30-21-18-01

**Data sheet**

**OMNIMATE Signal - series BL/SL 5.08  
BLZP 5.08HC/04/270LH SN OR BX**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Notes**

- |       |   |
|-------|---|
| Notes | <ul style="list-style-type: none"> <li>• Additional colours on request</li> <br/> <li>• Gold-plated contact surfaces on request</li> <br/> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <br/> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <br/> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <br/> <li>• P on drawing = pitch</li> <br/> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> </ul> |
|-------|---|

|                |  |
|----------------|--|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request. |
|----------------|--|

**Approvals**

Approvals




|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|   |   |
|---|---|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
|---|---|

**OMNIMATE Signal - series BL/SL 5.08  
BLZP 5.08HC/04/270LH SN OR BX**



**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings****Dimensional drawing**


The reproduction, distribution and utilization of this document as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. Weidmüller exclusively reserves the right to file for patents, utility models or designs.

© Weidmüller Interface GmbH & Co. KG


shown:  
BLZP 5.08HC/04/90(LR)/(LH)



conductor




screwdriver




with snap latch = separation latch = LR  
without snap latch = separation lever = LH



shown:  
BLZP 5.08HC/04/270(LR)/(LH)



4.7  
0.185"



screwdriver



conductor

with snap latch = separation latch = LR  
without snap latch = separation lever = LH

P = 5.08 Raster/pitch

n = Polzahl/no of poles#

|    |         |           |
|----|---------|-----------|
| 24 | 116,84  | 4,60      |
| 23 | 111,76  | 4,40      |
| 22 | 106,68  | 4,20      |
| 21 | 101,60  | 4,00      |
| 20 | 96,52   | 3,80      |
| 19 | 91,44   | 3,60      |
| 18 | 86,36   | 3,40      |
| 17 | 81,28   | 3,20      |
| 16 | 76,20   | 3,00      |
| 15 | 71,12   | 2,80      |
| 14 | 66,04   | 2,60      |
| 13 | 60,96   | 2,40      |
| 12 | 55,88   | 2,20      |
| 11 | 50,80   | 2,00      |
| 10 | 45,72   | 1,80      |
| 9  | 40,64   | 1,60      |
| 8  | 35,56   | 1,40      |
| 7  | 30,48   | 1,20      |
| 6  | 25,40   | 1,00      |
| 5  | 20,32   | 0,80      |
| 4  | 15,24   | 0,60      |
| 3  | 10,16   | 0,40      |
| 2  | 5,08    | 0,20      |
| n  | L1 [mm] | L1 [inch] |

For the mounting of PCBs, it should be noted that the rated data given in the catalogue relates only to the connection elements. The necessary creepage and clearance paths must be observed in connection with the respective applicant in accordance to VDE 0110. The current-carrying capacity and pitch tolerance is to be determined according to DIN IEC 326 part 3 very fine.

Weidmüller connectors are tested to the DIN VDE 0627 standard, and are valid for its field of application. Provided that the connectors are used to the intended purpose, all requirements with respect to the occurring of electrical, mechanical, thermic and corrosive stress will be satisfied.

|                                       |            |                                 |  |            |  |
|---------------------------------------|------------|---------------------------------|--|------------|--|
| General tolerance:<br>DIN ISO 2768-mK |            | 89239/5<br>01.08.16 HELIS_MA 02 |  | Cat.no.: . |  |
|                                       |            | Modification                    |  |            |  |
|                                       |            | Drawn                           | Date   | Name       | <b>BLZP 5.08HC/.../.../... ..</b><br>BUCHSENLEISTE<br>SOCKET BLOCK |
| Responsible                           | 08.08.2016 | HERTEL_S                        | Drawing no. <b>3 39786</b> <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">12</span><br>Sheet 03 of 03 sheets |            |  |
| Checked                               | 08.08.2016 | HELIS_MA                        | Product file: BLZP 5.08HC  |            |  |
| Supersedes: .                         | Approved   | LANG_T                          | 7159   |            |  |