It's All About Your Data



SuperTrak® EX SAS and SATA

RAID Controllers

Reliability, Manageability and Performance
Leadership for Today's SAS and SATA
RAID Solutions

Enterprise-Class RAID Reliability

SuperTrak EX SAS and SATA RAID controllers are stable, robust platforms that can be trusted. Built on a leading edge hardware design, supported by a RAID stack developed and refined over more than 15 years, they incorporate a single chip solution for optimized reliability with 512MB data cache on-board, an available 72 hour battery backup module, and a x8 PCI-Express interface to the host.

The SuperTrak EX line of SAS and SATA RAID controllers, with RAID 5 and RAID 6 support, protects your mission-critical data by delivering the data protection features you expect from leadership solutions. Features such as global and dedicated hot spares, RAID level migration, media patrol, read check table, and bad sector remapping offer the most reliable data protection solutions in their class.

Easy Management

The new web-based Promise Array Manager Professional (WebPAM™ PRO) makes SuperTrak RAID Controllers easy to manage for both Windows and Linux environments through the browser-based graphical user interface to create, delete, expand, and convert disk arrays from anywhere in the world.

In the event of a drive or data path failure, WebPAM PRO supports an array of notification options including text and email, as well as an audio alarm located directly on the STEX RAID controller.

SAS RAID Controllers for Performance Hungry Storage

The SuperTrak SAS and SATA RAID controllers are high-performance solutions delivering reliability to demanding data-intensive applications such as tiered storage environments (disk-to-disk or disk-to-disk-to-tape backup), security and surveillance, video editing, and digital content creation.

Support for both SAS and SATA 3Gb/s drives on the same controller maintains configuration optimization for performance based on the characteristics of SAS and SATA drives available today. It's like getting SAS for free.



- :: 3Gb/s SAS/SATA
- :: Hardware-accelerated RAID 6 maximum data protection
- :: Supports RAID levels 0, 1, 1E, 5, 6, 10, 50, 60
- ∴ PerfectRAID[™] technology for robust error handling and recovery
- :: Automatic/manual rebuild of dedicated and global hot spare drive
- :: Online capacity expansion and RAID level migration to add capacity as needed
- :: Optional 72 hour battery backup module
- :: Linux Open Source driver support
- :: Multiple logical drive support
- :: Intel IOP348 Dual XScale I/O processor
- :: PCI Express x8 Host Bus Interface





















Sophisticated Array Management Tools

	ielikiteriprasi					0 - b E-	
MICH	tupa	Hertsette	.	Completions	Contaction Los		e office has been district.
of the control of the control	mit mada beldan						
restanting	Commence of the	nen Constitut					
Day Veragement	C. Day Anna Miles						
	Company seems						
Orten Howard	DENIE		Page 1				
	innered has		Result				
	Committee Court		-				
(FORE)	Sertinetti Sendi		MALINE				
- Carterior	Configuration Control						
	ten Contact a Province						
d bottom							
	100						
	Name of Physicians						
d from 1	NAME OF LAKE POWER						
	Available And Lorente		*******				
Day Inday Streets							
Security Streets	Team.	The same			ter.		Territory Titles
SHIP STANKE STREET AND AND SHIP STANKE STANK						Carally	
DISTRICTEDER	191	ST KERNING			la/w	49/700	in, fysiation
Oncorrect states	15.539	機能を受け			ini	201000	
Oncorrects	151.50E	Meterial In			543	10 core	
Pontage and a series	75.500	(BACK) (S)			SAG		
Contract Contract	10.00	HEKIKALA			LACK .	PERM	24
Busines	THE CO.	27300 Ox3			tar's	mirre	754
Buselted	@ Same Last						
Biometra I							
Minneson 2					100	tion bets	-
13 territori			-	- M		- Total 40	* South # *
22 territor b	SHEET MESS	look	Lane Section	Sansily Desi			
Ligitalinichentry	-0-0434W 200-				TOTAL DE		
Biquities							
B Lipidon 1	40-48 H (M) HHI-					-	
Branchine)	100円月次 2000 100円月次 2000	MR-597-F350, (861	DODA	EQ 141 207	a barrier per	and an experience of	MA NO CONST
	TOTAL A (N) 200-		2000				nation (NATION AND ADDRESS THAT AREA THE
	THE R. P. LEWIS CO., LANSING, MICH.					of the best letter	
	10 TH A 10 PER					no servine feature	

Web-based Promise Array Management (WebPAM PRO) software offers professional management tools in a simple-to-use, straightforward format. Array configurations, management and monitoring features are available via the web-based interface. Moreover, the SuperTrak EX family supports industry standard SNMP and CIM/WBEM so third party management application integration is simplified.

A Leader in SAS and SATA RAID

Promise Technology is the originator of ATA RAID and is a worldwide leader in SAS/SATA RAID with over 15 million controllers shipped. Using SAS and SATA technology to design and manufacture fast, reliable, cost-effective data protection, Promise is the preferred choice for SAS/SATA host bus adapters, RAID controllers and SAS/SATA external storage systems.

Specifications							
Model	STEX8654	STEX8658					
Features							
Controller Configuration	Four internal SAS/SATA ports at 3Gb/s Four external SAS/SATA ports at 3Gb/s One SAS SFF-8088 connector One SAS SFF-8087 connector 1.2Ghz Intel 81348 XScale I/O processor Onboard 512MB ECC DDR II memory	Eight external SAS/SATA ports at 3Gb/s — Two SAS SFF-8088 connectors 1.2Ghz Intel 81348 XScale I/O processor Onboard 512MB ECC DDR II memory					
Hardware Features	 PCI-Express x8 host bus interface Hardware XOR engine to offload parity calculation Hardware RAID 6 accelerator Low-profile MD2 form factor Optional on-board battery backup unit for data retention up to 72 hours 						
Supported RAID Levels	 RAID 0 - Data striped across 1-16 drives for increased performance, but no data protection RAID 1 - Mirrored pair of drives for data protection with increased read performance RAID 1E - Data mirroring extended to maximize balanced performance. Allows odd number drive mirroring RAID 5 - Striped parity on 3-16 drives, ultimate data protection, capacity and performance balance RAID 6 - Double parity for maximum data protection on 4-16 drives; allows double drive failures without downtime or data loss RAID 10 - Mirrored pair of RAID 0 for double drive failure protection; can be split into two RAID 0 sets RAID 50 - Striped multiple RAID 5 sets to improve performance and provide additional data protection RAID 60 - Striped multiple RAID 6 sets to allow multiple drive failures to achieve high-data availability 						
RAID Fault Tolerance and Robustness Features	Multiple logical drive support enables combining different RAID levels on one set of disks Read Check table to avoid data read errors PerfectRAID™ technology for error handling and recovery of fatal, media and disk errors Support hot swap of failed drives and hot spares Automatic/Manual rebuild of hot spare drive Background initialization for instant drive availability Supports bad sector remapping Variable stripe block size support to meet various application requirements Synchronization can be scheduled periodically for RAID data consistency						
Web-based Promise Array Manager	Creates, deletes, expands, and converts disk arrays remotely Media Patrol and Redundancy Check scheduling Monitors drive, array, and enclosure status and provides online event logging Email notification of drive, array, controller or enclosure events (e.g. error or degrade conditions) Remote management based on industry standard CIM/WBEM Interface displays in 10 languages CLI support Remote firmware update						
Operating System Support	 Microsoft Windows Vista, 2000, XP, Windows Server 2003, Windows Server 2008 Red Hat Linux, SuSE Linux, Miracle Linux, Fedora Core, Linux open source driver (32/64-bit) FreeBSD, VMware 3.0.1/3.0.2 						
Platform Support	Intel IA32, EM64T, and AMD64						
SuperBuild™ BIOS	 Array configuration utility at the BIOS level BIOS Boot specification support: boot system from any array Flash-upgradeable BIOS for future upgrades 						
Enclosure Management	 SES-2 SGPIO I²C 						
Cable in Kit	STEX8654 One 0.5-meter cable	STEX8658 (No cables in kit)					
Accessories	Battery Backup Unit PN: STEXBBUIII						
Operating Temperature	0 to 50°C (40°C w/ BBU) Relative humidity: 5%-95% non-condensing						
Physical Dimensions	16.7 cm x 6.8 cm (6.6" x 2.7")						
Agency Certifications	UL, cUL, CE, FCC Class B, BSMI, VCCI, MIC, C-tick						
Limited Warranty	3 Years						

About Promise

With a long history of innovation, Promise Technology develops and manufactures sophisticated RAID solutions recognized worldwide, ranging from a complete line of RAID controller cards to SAS/SATA RAID subsystems. Catering to enterprise, midrange and entry-level data protection needs, Promise products are distinguished by their common RAID code, unified management interface and unparalleled support. Known as the originator of SATA/ATA RAID products, Promise's comprehensive product base includes high available (HA) standalone RAID subsystems with standards-based management interfaces, host-based (internal) RAID controllers, NAS appliances for SOHO, and SATA ASICs integrated into an extensive list of industry-leading motherboards. Headquartered in Milpitas, Calif., Promise has operations throughout Asia and Europe. For more information, visit Promise Technology's website at http://www.promise.com

:: Promise USA

Milpitas, USA
Tel: +1 408 228 1400
E-mail: sales@promise.com

:: Promise EMEA

Son, The Netherlands Tel: +31 0 40 235 2600 E-mail: sales@promise-emea.com

:: Promise Germany

Dortmund, Germany
Tel: +49 0 2 31 56 76 48 0
E-mail: sales-de@promise-emea.cor

:: Promise Italy

Rome, Italy Tel: +39 0 6 367 126 26 E-mail: sales-it@promise-emea.com

:: Promise Ul

Wokingham, United Kingdom
Tel: +44 0 870 112 59 77
E-mail: sales@promise-emea.con

:: Promise Taiwan

Hsin-Chu, Taiwan Tel: +886 3 578 2395 E-mail: sales@promise.com.t

:: Promise China

Beijing, China/Shanghai, China Tel: +86 10 8857 8085/8095 (Beijing) Tel: +86 21 6249 4192/93/99 (Shanghai) E-mail: sales@promisechina.com

:: Promise Japan

Tokyo, Japan Tel: +81 3 5333 3631 E-mail: sales-jp@promise.com.tw