ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: B951024	**Issue: 1**
Page 1 of 2 Pages	**Issue Date: 8/17/2010**
	Effective Date: 10/12/2010

A. Construction — **Diameters (mm)**

1)	Component 1	2 X 1 COND	
a)	Conductor	28 (7/36) AWG TC	0.38
b)	Insulation	0.25 Wall, Nom. PVC, Semi Rigid	0.89
(1)	Color Code	Alpha Wire Color Code E	

Cond	Color	Cond	Color	Cond	Color
1	BLACK	2	BROWN		

2)	Cable Assembly	2 Components Cabled	
a)	Twists:	52.5 Twists/meter (min)	
b)	Core Wrap	Clear Mylar Tape, 25% Overlap, Min.	
3)	Shield:	A/P/A Tape, 25% Overlap, Min.	
a)	Drain Wire	28 (7/36) AWG TC	
b)	Braid	TC,70% Coverage, Min.	
4)	Jacket	0.81 Wall, Nom.,PVC	4.19 (4.44 Max.)
a)	Color(s)	GREY	
b)	Ripcord	1 End 810 Denier Nylon	
c)	Print	ALPHA WIRE-* P/N B951024	
		0.09MM2 (28AWG) (UL) TYPE CM 105C OR AWM 2464	
		VW-1 CE ROHS (SEQ METERS)	
		* = Factory Code	

B. Applicable Specifications

1)	UL		
a)	Component 1	AWM/STYLE 10002	105°C / 300 V_{RMS}
b)	Overall	AWM/STYLE 2464	80°C / 300 V_{RMS}
		CM	105°C
		VW-1	
2)	IEC	EN 60332-1 Flame Behavior	
		EN 60332-2 Flame Behavior	
3)	CE:	LVD 73/23/EEC Amendment 93/68/EEC	

C. Environmental Compliance

1) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

2) REACH Regulation (EC 1907/2006):
This product does not contain any of the substances listed on the European Union REACH Substance of Very High Concern (SVHC) candidate list, dated 30 March 2010, in excess of a concentration of 0.1% weight/weight.

D. Physical & Mechanical Properties

1)	Temperature Range	-30 to 105°C
2)	Bend Radius	10X Cable Diameter
3)	Pull Tension	6.1 Lbs, Maximum
4)	Sunlight Resistance	Yes

E. Electrical Properties (For Engineering purposes only)

1)	Voltage Rating	300 V_{RMS}
2)	Capacitance	88.56 pf/m @1 kHz, Nominal Conductor to Conductor
3)	Ground Capacitance	160.72 pf/m @1 kHz, Nominal
4)	Characteristic Impedance	70 Ω
5)	Inductance	0.7216 µH/m, Nominal
6)	Conductor DCR	216.48 Ω/Km @20°C, Nominal
7)	OA Shield DCR	24.928 Ω/Km @20°C, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711
Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com
www.alphawire.com

F. Other

1) Packaging		Flange x Traverse x Barrel (inches)
	a) 3280 FT	16 x 11 x 8 Continuous length
	b) 1640 FT	12 x 10 x 5 Continuous length
	c) 328 FT	6.5 x 6 x 1.9 Continuous length
	d) 164 FT	6.5 x 4 x 2.5 Continuous length

[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711
Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com
www.alphawire.com