Disposable Hearing Protection

SOUND FIT





- · One size
- Easy to use
- Slow recovery PVC foam for a comfortable fit
- · Dispenser boxes
- · Highly visible for ease identification
- · Flame retardant
- Form a constant and effective noise seal
- · Available in corded and uncorded

Art.nr.	Description	Description				Packaging						
Uncorded	•											
EP07	1 pair in an indivi	dual pl	astic b	ag .	200 pairs/carton							
EP08	1 pair in an indivi	dual po	aper ba	g	200 pairs/carton							
Corded												
EP09	1 pair in an indivi	1 pair in an individual plastic bag					100 pairs/carton					
EP10	1 pair in an indivi	1 pair in an individual paper bag					100 pairs/carton					
Results to	EN352-2: H = 31dB, M	= 25dl	B, L=22	dB, SN	NR = 28	dB						
Frequency (Hz)		63	125	250	500	1000	2000	4000	8000			
Mean Attenuation(dB)		21.1	22.3	26.4	29.3	29.3	34.6	41.3	41.6			
Standard Deviation(dB)			5.7	6.2	6.1	5.4	3.6	5.4	7.1			
Accumod I	120	16.5	20.2	22.1	22.0	21 0	25.0	215				

DECIGUARD AB™







With antimicrobial agents that protect the product against degrading micro organisms. Available only from North.

FEATURES/BENEFITS

- Protects the product against degrading micro organisms. It won't wear out, wash off or rub away. Available only from North
- Re-engineered PVC Formula
- Higher density foam construction, improved, stronger cell structure, excellent wearer protection, better fit in the ear canal, increased comfort
- Quicker recovery, easier to insert in the ear canal, earplugs quickly expand to fit the ear canal leading to increased ease of use
- Foam construction, one size fits most, lightweight, non-toxic and non-irritating, disposable
- · Sealed pouches, maximum cleanliness, assures employees that plugs are unused

Description		Pack	aging								
Uncorded	1 pair per cellopho	ne po	uch	200 pc	airs/car	ton					
Corded	1 pair per cellophane pouch 100 pairs/carton										
Results to EN352-2: H = 31dB, M = 26dB, L = 23dB, SNR = 30dB											
Frequency (Hz)		63	125	250	500	1000	2000	4000	8000		
Mean Attenuat	tion (dB)	24.0	26.1	28.6	30.8	30.9	34.7	43.2	42.9		
Standard Devia	9.8	7.9	7.4	5.4	5.8	4.0	4.6	7.4			
Assumed Prote	ection Value (dB)	14.2	18.2	21.2	25.3	25.1	30.7	38.6	35.6		

DECIDAMPTM



FEATURES/BENEFITS

- Expands to fit ear canal Maximizes wearer protection
- Foam Construction
 One size fits most. Lightweight soft and comfortable. Non-toxic and non-irritating, disposable.
- · Sealed Pouches
- Available in cellophane and degradable paper
- Maximum cleanliness, assures employees that plugs are unused
- · Available in corded and uncorded

Description						Packaging					
Uncorded	1 pair per celloph	1 pair per cellophane pouch				200 pairs/carton					
Corded	1 pair per celloph	1 pair per cellophane pouch 100 pairs/carton									
Results to EN352-2: H = 31dB, M = 26dB, L=23 dB, SNR = 30dB											
Frequency (63	125	250	500	1000	2000	4000	8000			
Mean Attenu	ation(dB)	24.0	26.1	28.6	30.8	30.9	34.7	43.2	42.9		
Standard De	viation(dB)	9.8	7.9	7.4	5.4	5.8	4.0	4.6	7.4		
Assumed Pro	14.2	18.2	21.2	25.3	25.1	30.7	38.6	35.6			

DECI 4200/4240





The new and improved Deci 4200 is now available in a softer Hi Viz orange tapered foam providing more comfort and better fit along with a high SNR rating of 33dB. The improved tapered shape makes it easy for insertion and removal. The Deci4200 is a conic PU earplug. Lightweight and comfortable, the Deci4200 is made of non-toxic and non-irritating soft polyurethane foam. Expands to fit ear canal, maximizes noise protection. Available uncorded or corded.

Description					Packaging						
Uncorded Deci 4200	r cellop	hane p	ouch	200 p	airs/ca	airs/carton					
Corded Deci 4240	ed Deci 4240 1 pair per cellophane pouch 100 pairs/carton										
Results to EN352-2: H=35dB, M=29dB, L=26dB, SNR=33dB											
Frequency (Hz)		63	125	250	500	1000	2000	4000	8000		
Mean Attenuation (dB)		28.6	29.9	31.1	33.1	34.1	37.7	46.0	45		
Standard Deviation (dB)		6	6.6	6.4	7.1	4.9	4.1	3.6	4.3		
Assumed Protection Value (dB)		22.6	23.3	24.7	26	29.2	33.6	42.4	40.7		

