

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [63813-0600](#)
Status: **Active**
Description: Manual Activation and Deactivation Tool

Documents:
[RoHS Certificate of Compliance \(PDF\)](#)


General

Product Family	Application Tooling
Series	T9999
Function	Activation, Deactivation
Geographic Area	Global
Level of Automation	Manual
More Detailed Tech Information	applicationtooling@molex.com
Product Name	N/A
Survey	www.molex.com//review/apptool_survey.html
Tool Type	Handtool
UPC	800753891920

Material Info

Reference - Drawing Numbers

Application Tooling Documents	ATS-638130600, TM-638000029, TM-638000029CN, TM-638000029DE, TM-638000029FR, TM-638000029IT, TM-638000029JP, TM-638000029KR, TM-638000029MY, TM-638000029PL, TM-638000029RU, TM-638000029SK, TM-638000029SP, TM-638000029TH, TM-638000029TW, TM-638000029VN
-------------------------------	---



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
T9999Series

Application Tooling Description	FAQ Product #
Sabre™ Crimp Terminal, Male, 18 AWG, 3.30mm Max. Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact	0431781002
Sabre™ Crimp Terminal, Male, 18 AWG, 3.30mm Max. Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact, Last-Make Wipe Length, complies with the UL1977 finger proof access requirement	0431785002
Sabre™ Crimp Terminal, Male,	0431782002

14-16 AWG or
double 18-20 AWG,
4.57mm Max.
Insulation Diameter,
Reel Packaged, Tin
(Sn) Plated Brass
Contact
Sabre™ Crimp 0431786002
Terminal, Male,
14-18 AWG, 4.57mm
Insulation Diameter,
Reel Packaged,
Tin (Sn) Plated
Brass Contact, Last-
Make Wipe Length,
complies with the
UL1977 finger proof
access requirement
Sabre™ Crimp 0431784002
Terminal, Male,
18-20 AWG, 3.30mm
max. Insulation
Diameter, Reel
Packaged, Tin (Sn)
Plated Brass Contact

This document was generated on 04/30/2013
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION