

## Small Signal Switching Diodes, High Voltage



### FEATURES

- Silicon epitaxial planar diodes
- For general purpose
- AEC-Q101 qualified
- Base P/N-G3 - green, commercial grade
- Material categorization:  
For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### MECHANICAL DATA

**Case:** SOD-123

**Weight:** approx. 9.4 mg

**Packaging codes/options:**

18/10K per 13" reel (8 mm tape), 10K/box

08/3K per 7" reel (8 mm tape), 15K/box

### PARTS TABLE

| PART     | TYPE DIFFERENTIATION | ORDERING CODE                | TYPE MARKING | INTERNAL CONSTRUCTION | REMARKS       |
|----------|----------------------|------------------------------|--------------|-----------------------|---------------|
| BAV19W-G | $V_R = 100\text{ V}$ | BAV19W-G3-08 or BAV19W-G3-18 | AS           | Single diode          | Tape and reel |
| BAV20W-G | $V_R = 150\text{ V}$ | BAV20W-G3-08 or BAV20W-G3-18 | AT           | Single diode          | Tape and reel |
| BAV21W-G | $V_R = 200\text{ V}$ | BAV21W-G3-08 or BAV21W-G3-18 | AU           | Single diode          | Tape and reel |

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                                                                            | TEST CONDITION        | PART     | SYMBOL      | VALUE | UNIT |
|--------------------------------------------------------------------------------------|-----------------------|----------|-------------|-------|------|
| Continuous reverse voltage                                                           |                       | BAV19W-G | $V_R$       | 100   | V    |
|                                                                                      |                       | BAV20W-G | $V_R$       | 150   | V    |
|                                                                                      |                       | BAV21W-G | $V_R$       | 200   | V    |
| Repetitive peak reverse voltage                                                      |                       | BAV19W-G | $V_{RRM}$   | 120   | V    |
|                                                                                      |                       | BAV20W-G | $V_{RRM}$   | 200   | V    |
|                                                                                      |                       | BAV21W-G | $V_{RRM}$   | 250   | V    |
| DC Forward current <sup>(1)</sup>                                                    |                       |          | $I_F$       | 250   | mA   |
| Rectified current (average) half wave rectification with resist. load <sup>(1)</sup> |                       |          | $I_{F(AV)}$ | 200   | mA   |
| Repetitive peak forward current <sup>(1)</sup>                                       | $f \geq 50\text{ Hz}$ |          | $I_{FRM}$   | 625   | mA   |
| Surge forward current                                                                | $t < 1\text{ s}$      |          | $I_{FSM}$   | 1     | A    |
| Power dissipation <sup>(1)</sup>                                                     |                       |          | $P_{tot}$   | 410   | mW   |

### THERMAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                                                 | TEST CONDITION | SYMBOL     | VALUE         | UNIT               |
|-----------------------------------------------------------|----------------|------------|---------------|--------------------|
| Thermal resistance junction to ambient air <sup>(1)</sup> |                | $R_{thJA}$ | 375           | K/W                |
| Junction temperature <sup>(1)</sup>                       |                | $T_J$      | 150           | $^{\circ}\text{C}$ |
| Storage temperature range <sup>(1)</sup>                  |                | $T_{stg}$  | - 65 to + 150 | $^{\circ}\text{C}$ |
| Operating temperature range                               |                | $T_{op}$   | - 55 to + 150 | $^{\circ}\text{C}$ |

#### Note

<sup>(1)</sup> Valid provided that leads are kept at ambient temperature



| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                                           |          |          |      |      |      |               |
|---------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|----------|----------|------|------|------|---------------|
| PARAMETER                                                                                         | TEST CONDITION                                                                            | PART     | SYMBOL   | MIN. | TYP. | MAX. | UNIT          |
| Forward voltage                                                                                   | $I_F = 100\text{ mA}$                                                                     |          | $V_F$    |      |      | 1    | V             |
|                                                                                                   | $I_F = 200\text{ mA}$                                                                     |          | $V_F$    |      |      | 1250 | mV            |
| Leakage current                                                                                   | $V_R = 100\text{ V}$                                                                      | BAV19W-G | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = 100\text{ V}, T_j = 100\text{ }^{\circ}\text{C}$                                   | BAV19W-G | $I_R$    |      |      | 15   | $\mu\text{A}$ |
|                                                                                                   | $V_R = 150\text{ V}$                                                                      | BAV20W-G | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = 150\text{ V}, T_j = 100\text{ }^{\circ}\text{C}$                                   | BAV20W-G | $I_R$    |      |      | 15   | $\mu\text{A}$ |
|                                                                                                   | $V_R = 200\text{ V}$                                                                      | BAV21W-G | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = 200\text{ V}, T_j = 100\text{ }^{\circ}\text{C}$                                   | BAV21W-G | $I_R$    |      |      | 15   | $\mu\text{A}$ |
| Dynamic forward resistance                                                                        | $I_F = 10\text{ mA}$                                                                      |          | $r_f$    |      | 5    |      | $\Omega$      |
| Diode capacitance                                                                                 | $V_R = 0, f = 1\text{ MHz}$                                                               |          | $C_D$    |      | 1.5  |      | pF            |
| Reverse recovery time                                                                             | $I_F = 30\text{ mA}, I_R = 30\text{ mA},$<br>$i_R = 3\text{ mA}, R_L = 100\text{ }\Omega$ |          | $t_{rr}$ |      |      | 50   | ns            |

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Forward Current vs. Forward Voltage




Fig. 3 - Admissible Power Dissipation vs. Ambient Temperature




Fig. 2 - Admissible Forward Current vs. Ambient Temperature




Fig. 4 - Dynamic Forward Resistance vs. Forward Current




Fig. 5 - Leakage Current vs. Junction Temperature








Fig. 6 - Diodes Capacitance vs. Reverse Voltage



Fig. 7 - Non-Repetitive Peak Forward Current vs. Pulse Duration  
Maximum Admissible Values of Square Pulses



## PACKAGE DIMENSIONS in millimeters (inches): SOD-123



Mounting Pad Layout



Rev. 4 - Date: 24. Sep. 2009  
Document no.: S8-V-3910.01-001 (4)  
17432



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**