

HCF1305

High frequency, high current power inductors



Product features

- 12.5 mm x 12.5 mm x 5.0 mm surface mount package
- Ferrite core material
- Inductors designed for higher speed switch mode applications requiring low voltage and high current
- Design utilizes ferrite core with high DC bias resistance and low core loss
- Inductance range from 0.47 μ H to 4.7 μ H
- Current range from 36.0 A to 10.4 A
- Frequency range 100 kHz to 1 MHz

Applications

- Next generation processors
- High current DC-DC converters
- VRM, multi-phase buck regulators
- PC Workstations, Routers, Servers
- Telecom soft switches
- Base stations

Environmental data

- Storage temperature range (component): -40 °C to +125 °C
- Operating temperature range: -40 °C to +125 °C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020 (latest revision) compliant



Product specifications


Part Number	Rated Inductance (μH)	OCL (1) μH ± 20%	I _{rms} (2) Amperes	Isat (3) Amperes	Isat2 (4) Amperes	DCR mΩ@20°C (Typical)	DCR mΩ@20°C (Maximum)	K-factor (5)
HCF1305-R47-R	0.47	0.47	32.0	36.0	30.0	0.83	1.00	21
HCF1305-R56-R	0.56	0.56	32.0	30.0	22.5	0.83	1.00	21
HCF1305-1R0-R	1.00	1.00	22.0	24.0	20.0	1.58	1.90	14
HCF1305-1R2-R	1.20	1.20	22.0	20.0	15.0	1.58	1.90	14
HCF1305-1R8-R	1.80	1.80	16.3	18.0	15.0	2.58	3.10	10
HCF1305-2R2-R	2.20	2.20	16.3	15.0	11.2	2.58	3.10	10
HCF1305-3R0-R	3.00	3.00	13.2	14.4	12.0	4.08	4.90	8.3
HCF1305-3R3-R	3.30	3.30	13.2	12.5	9.0	4.08	4.90	8.3
HCF1305-4R0-R	4.00	4.00	10.9	12.0	10.0	6.0	7.2	6.9
HCF1305-4R7-R	4.70	4.70	10.9	10.4	7.5	6.0	7.2	6.9

- 1) OCL: Open Circuit Inductance test parameters: 100 kHz, 0.1 Vrms, 0.0 Adc. OCL @ -40 °C can be lower than OCL @ +20 °C by 15% max.
- 2) I_{rms}: DC current for an approximate DT of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed +125 °C under worst case operating conditions verified in the end application.
- 3) Isat1: Amperes Peak for approximately 30% rolloff (@ +25 °C)
- 4) Isat2: Amperes Peak for approximately 30% rolloff (@ +125 °C)

- 5) K-factor: Used to determine B p-p for core loss (see graph). $B p-p = K \cdot L \cdot \Delta I$
B p-p: (mT), K: (K factor from table), L: (Inductance in μH), ΔI (Peak to peak ripple current in Amps).


Part number definition:
HCF1305-XXX-R
HCF1305 = Product code and size
XXX = Inductance value in μH.
R = Decimal point. If no R is present, third character = # of zeros -R suffix indicates RoHS compliant

Dimensions- mm




Do not route traces or vias underneath the inductor


Packaging information - mm





Temperature rise vs total loss



Core loss vs Bp-p



Inductance characteristics



Solder Reflow Profile




Table 1 - Standard SnPb Solder (T_p)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_p)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 – 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_c)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_p to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/electronics

© 2017 Eaton
All Rights Reserved
Printed in USA
Publication No. 4133
July 2017