



SERIES: MD-XXSGK | DESCRIPTION: MINI DIN CONNECTOR
FEATURES


- PCB mount
- fully shielded
- right angle
- ground tabs with kinked pins

**PART NUMBER KEY****SPECIFICATIONS**









parameter	conditions/description	min	typ	max	units
rated input voltage		100	12		Vac Vdc
rated input current	at 100 Vac at 12 Vdc		1	2	A A
contact resistance			30		mΩ
insulation resistance	at 250 Vdc	50			MΩ
voltage withstand	for 1 minute		250		Vac
insertion force		1	4.5		kg
withdrawl force		0.8	3		kg
operating temperature		-40	85		°C
life		1,000			cycles



MECHANICAL DRAWINGS

units: mm[inches]

TOLERANCE: $\pm 0.2\text{mm}$ 

	MATERIAL	PLATING
earth terminal	brass	tin
contact terminals (1~8)	phosphor bronze	silver
plastic	PBT	

**MD-30SGK****MD-40SGK****MD-50SGK**

MD-60SGKMD-80SGK**REVISION HISTORY**

rev.	description	date
1.0	initial release	02/23/2006
1.01	new template applied	02/22/2012
1.02	updated pin dimensions	03/07/2012

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.