




DASH NO.	M CODE	MADE FROM
----------	--------	-----------



NOTES:

1. FOR USE WITH RG-55/U CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-1021.
3. INTERFACE PER MIL-STD-348, FIG. 304-2.
4. MATERIALS:
INSULATORS: TEFLON, ASTM-D-4894
GASKET & O-RING: SIL. RUB., ZZ-R-765
LOCKWASER: PHOS. BRONZE, ASTM-B-103
CENTER CONTACT: BER. COP., ASTM-B-196
ALL OTHER PARTS: BRASS, ASTM-B16
5. FINISHES:
CENTER CONTACT: HARD GOLD PLT. PER MIL-G-45204
ALL OTHER METAL PARTS: SILVER PLT. PER QQ-S-365
6. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11GHz



GSD

GSD

KN-19-42 (SHT 1 OF 2)

REVISIONS	
ISSUE	CHANGES
1	CN 37245 C REDRAWN KH 02/26/97
SCALE 4:1	
APPROX SURFACE AREA	
USED ON	
REF:	
JACK, BULKHEAD, N	
DRAWN KH	DATE 02/26/97
DESIGN PB	DATE 02/27/97
APPR.	DATE
KINGS ELECTRONICS CO., INC. TUCKAHOE, NEW YORK 10707	
KN-19-42 (SHT 1 OF 2)	