



Features

- Matched high energy MOV
- Internal thermal disconnects
- Status indicator
- Replaceable modular design
- DIN Rail compatible base
- Remote signalling capability
- Standards compliance: CE, RoHS, UL

- RoHS compliant*

Applications


- DC power systems

1320 Series DC Power Surge Protective Device

General Information

The Bourns® Model 1320 Series is a DC power Surge Protective Device (SPD) designed to protect power systems from damage due to lightning, transients and power surges. The Model 1320 Series is a DIN Rail mountable SPD targeted for systems ranging from 24 to 110 Vdc.

Electrical Diagram



Electrical Characteristics

Characteristic	Model No.			
	1320-S-24	1320-S-48	1320-S-75	1320-S-110
Network Voltage (Un)	24 Vdc	48 Vdc	75 Vdc	110 Vdc
Max. Operating Voltage (Uc)	38 Vdc	65 Vdc	100 Vdc	150 Vdc
Nominal Discharge Current (In)	10 kA	15 kA	20 kA	20 kA
Max. Discharge Current (Imax) 8/20 μ s max.	20 kA	30 kA	40 kA	40 kA
Protection Level @ In (Up)	250 V	300 V	390 V	500 V
Protective Fuses or Circuit Breakers, if applicable	20 A	20 A	50 A	50 A
Thermal Disconnect	Internal			

General Characteristics

Characteristic	Model No.			
	1320-S-24	1320-S-48	1320-S-75	1320-S-110
Connection	By Screw Terminal, Cross-section 1.5-10 mm ² (Active Wire) and 2.5-25 mm ² (Grounding Wire)			
Disconnection Indicator	2 Mechanical Indicators			
Mounting	DIN Rail, 35 mm Symmetrical			
Remote Signal Indicator	DS2xOS-xxDC) by Changeover Contact			
Enclosure Material	Thermoplastic UL 94V0			
Weight	128 g/unit	128 g/unit	128 g/unit	130 g/unit

Environmental Characteristics

Characteristic	Model No.			
	1320-S-24	1320-S-48	1320-S-75	1320-S-110
Operating Temperature	-40 °C to +85 °C			
Environmental Rating	IP 20			

Standards Compliance

UL1449 3rd Edition - USA Type 4, Type 2 Location
 UL1449 3rd Edition - Canada..... Type 4, Type 2 Location
 CSA C22.2 No. 8-M1986..... Class 9091 32, Class 9091 92

IEC61643-1 - InternationalLow Voltage SPD - Test Class II
 NF EN 61643-11 - FranceLow Voltage SPD - Test Class II


*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.
 Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
 Users should verify actual device performance in their specific applications.

1320 Series DC Power Surge Protective Device

BOURNS®

Product Dimensions



How To Order

Series **1320 - S - xxx**
Remote Signalling Code **S** = Remote Signalling
DC Operating Voltage **24 = 24 V**
48 = 48 V
75 = 75 V
110 = 110 V

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116

EMEA: Tel: +36 88 520 390 • Fax: +36 88 520 211

The Americas: Tel: +1-951 781-5500 • Fax: +1-951 781-5700

www.bourns.com

REV. 08/14

Specifications are subject to change without notice.
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.
Users should verify actual device performance in their specific applications.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

[1320-S-75](#) [1320-S-48](#) [1320-S-110](#)