



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	39		J1	REV PER ECO-09-021826	05JAN10	KK	AEG



- 1 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 2 THE TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- 3 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI



RECOMMENDED HOLE LAYOUT

	3.984	3.900	39	80	4-87215-0
OBSOLETE	3.884	3.800	38	78	3-8
	3.784	3.700	37	76	3-8
	3.684	3.600	36	74	3-7
	3.584	3.500	35	72	3-6
	3.484	3.400	34	70	3-5
	3.384	3.300	33	68	3-4
	3.284	3.200	32	66	3-3
	3.184	3.100	31	64	3-2
	3.084	3.000	30	62	3-1
	2.984	2.900	29	60	3-0
OBSOLETE	2.884	2.800	28	58	2-9
	2.784	2.700	27	56	2-8
	2.684	2.600	26	54	2-7
	2.584	2.500	25	52	2-6
	2.484	2.400	24	50	2-5
OBSOLETE	2.384	2.300	23	48	2-4
	2.284	2.200	22	46	2-3
OBSOLETE	2.184	2.100	21	44	2-2
	2.084	2.000	20	42	2-1
	1.984	1.900	19	40	2-0
	1.884	1.800	18	38	1-9
OBSOLETE	1.784	1.700	17	36	1-8
	1.684	1.600	16	34	1-7
OBSOLETE	1.584	1.500	15	32	1-6
	1.484	1.400	14	30	1-5
OBSOLETE	1.384	1.300	13	28	1-4
	1.084	1.000	10	22	1-3
	.284	.200	2	6	1-2
	.184	.100	1	4	1-1
	.084			2	1-0
	1.284	1.200	12	26	-9
	1.184	1.100	11	24	-8
	.984	.900	9	20	-7
	.884	.800	8	18	-6
	.784	.700	7	16	-5
	.684	.600	6	14	-4
	.584	.500	5	12	-3
	.484	.400	4	10	-2
	.384	.300	3	8	87215-1
	C	B	A	NO OF POS	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	3-15-85	tyco Tyco Electronics Corporation Harrisburg, PA 17105-3608	
		CHK	5-21-85		
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME ASSEMBLY, MOD II, HEADER, DOUBLE ROW, .100 X .100 CL. VERTICAL, .025 SQUARE POSTS	
		0 PLC ± -		SIZE A2	
		1 PLC ± -			
		2 PLC ± -		CAGE CODE 00779	
		3 PLC ± .005			
		4 PLC ± -		DRAWING NO C=87215	
		ANGLES ± -			
MATERIAL HOUSING-FLAME RETARDENT THERMOPLASTIC, COLOR-BLACK POSTS-PHOS BRONZE		FINISH POSTS-.000030 GOLD ON THE CONTACT AREA, GOLD FLASH ON SOLDER AREA, ALL OVER .000050 NICKEL		RESTRICTED TO -	
				SCALE -	
				SHEET 1 of 1	
				REV J1	